

FINAL SURVEY NO. 2655. OR SURVEYS.

FEET.

I N S T R U M E N T

This Survey was made with a Buff & Berger "Engineer" Transit; the distances were measured with a 100 ft. steel tape. The meridian was determined by observation of equal altitude of the sun.

S U R F A C E

The surface embraced by this survey is low rolling hills, void of timber and other natural objects for bearings.

NOTE:- The difference between these field notes and the location certificate is due to errors in the latter.

REPORT:- The S.W.Cor. Sec. 33 is marked by a reddish oxidized granite block 8 x 12 inches, 12 inches above a mound of stone, chiseled 4 notches on the East and 2 on the West.

do solemnly swear that we assisted
United States Deputy Mineral Surveyor, in marking the corners and surveying
Alex Bullfrog Mining & Milling Company,
Wathens Lods
in the foregoing field notes as having been surveyed by said deputy mineral surveyor and under his
and that said survey has been in all respects, to the best of our knowledge and belief, faithfully and
and the corner and boundary monuments established according to law and the instructions
by the United States Surveyor General for Nevada.

W.E. Morgan ✓ Chairman
Chairman
Amon
Hagan

Subscribed and sworn to by the above-named persons before me this 23rd
day of June, 1908

Frank A. Boherty
Notary Public in and for
Lincoln County, Nevada