

INSTRUMENT.

This survey was made with a C. L. Berger and Sons' No. 4 Mountain, Mining and Reconnaissance Transit. The courses were deflected from the true meridian as determined by direct observation on Polaris. The distances were measured with 100 ft. and 300 ft. steel tapes.

Note;-- The disagreements between these field notes and the amended certificates of location of the several lodes embraced in this survey are due to errors in said amended certificates of location.

The disagreements between these field notes and the approved field notes of Sur. No. 3304, with regard to the bearings of line 4-1 Head Chief lode, line 6-1 Oregon Fraction lode, and line between sections 13 and 24, Tp. 28 S., R. 63 E., M.D. B. and M., are due to errors in the field notes of Sur. No. 3304.

Report;-- The corner to sections 13, 14, 23 and 24, Tp. 28 S., R. 63 E., M.D. B. and M., as reported in the field notes of Sur. No. 3304, and to which connection is given from the several lodes embraced in this survey, is a granite rock, about 8 ins. by 8 ins., 10 ins. in length, standing upright, its full length above the ground, without any accompanying mound of rock or earth, and showing no notches or other marks upon any of its surfaces. It was identified only by re-running the tie reported in the field notes of Sur. No. 3304, from Cor. No. 1, Head Chief lode. Diligent search throughout a radius of several hundred feet failed to disclose anything else in any way resembling a section corner; nor could the N. E. Cor. to Sec. 24, Tp. 28 S., R. 63 E., M.D. B. and M., be found, although a thorough search was made for it for the purpose of checking the position of the above described corner.

The corner to sections 14, 15, 22 and 23, Tp. 28 S., R. 63 E., M.D. B. and M., to which connection is also given from the several lodes embraced in this survey, is a granite rock 8 ins. by 12 ins., about 10 ins. above the ground, surrounded by a circle of rock, and with three notches chiselled on its south face, and two notches on its east face.

The course and length of line from N. W. to reported N. E. Cor. Sec. 23, Tp. 28 S., R. 63 E., M.D. B. and M., as determined upon the ground, is S.89°15'E. 5402.00 ft.

The 1/4 sec. cor. between sections 13 and 14, the 1/4 sec. cor. between sections 23 and 24, the 1/4 sec. cor. between sections 13