

pective locations on which they are situated.

OTHER IMPROVEMENTS.

A corrugated iron blacksmith shop, the S. E. Cor. of which bears from Cor. No. 3, Elvira lode, N.71°06'W., 203 ft., 12x21 ft., course of long sides N.81°47'W.

A corrugated iron engine house, the S. E. Cor. of which bears from Cor. No. 3, Elvira lode, N.75°14'W. 255.7 ft., 13x18 ft., course of long sides N.81°47'W.

A combination of inclined trestle and gallows frame, continuing track at same angle as shaft, and extending easterly from the mouth of the main incline on the Elvira lode, 80 ft.

A frame house, the N. W. Cor. of which bears from Cor. No. 1, Mesa lode, S.28°06'E. 229.8 ft., main building 22x55 ft., with an addition on east side at south end 18x14 ft. Course of 55 ft. sides N.16°E. Course of south end, S.74°E. 40 ft.

The above improvements belong to the claimant herein.

INSTRUMENT.

This survey was made with a C. L. Berger light mining transit, No. 4270. The courses were deflected from the true meridian as determined by observation on Polaris at eastern elongation. The distances were measured with 100-ft. and 500-ft. steel tapes.

REPORT.

The lode line of each location of this claim was run directly upon the ground, and the several corners established by means of offsets from the lode lines. All tie lines were run either directly upon the ground, or by traverses, run upon the ground and submitted in a separate report herewith.

The N. E. Cor. Sec. 34, T. 28 S., R. 63 E., M.D.M., is a granite rock, 10x12 ins., standing 14 ins. above the ground, without distinguishing marks, but identified as the same rock reported in the approved field notes of Sur. No. 3030, Mondamin lode.

The true N. W. Cor. Sec. 34, and the N. 1/4 Cor. for said section cannot be found.

A granite rock 6x12 ins., 12 ins. above ground and resembling a Sec. Cor., bears N.74°59'10"W. 993.44 ft. from Cor. No. 1, Berdie