

OTHER IMPROVEMENTS. There are no other improvements on this claim.

There are no other improvements on this claim.

There are no other improvements on this claim.

INSTRUMENT.

This survey was made with a C. L. Berger light mining transit, No.

4270. The courses were deflected from the true meridian as deter-

mined by observation on Polaris at eastern elongation. The dis-

tances were measured with 100-ft. and 500-ft. steel tapes.

The courses were deflected from the true meridian as deter-

mined by observation on Polaris at eastern elongation. The dis-

REPORT.

The lode line of each location of this claim was run directly upon the ground, and the several corners established by means of offsets from the lode lines. All tie lines were run either directly upon the ground, or by traverses, run upon the ground and submitted in a separate report herewith.

The N. E. Cor. of Sec. 12, T. 26 S., R. 64 E., M.D.M., is a granite stone, 5x7 ins., standing 12 ins. above a mound of stone, chiseled with one notch on its north edge and five notches on its south edge. This is the nearest standing corner of the public survey that can be found and identified.

Sur. No. 2086, Jubelee lode;

Cors. Nos. 1, 2 and 4 are pine posts, properly set and scribed with the number of the corner and survey. I find the courses of lines 1-2 and 4-1 to be N.8°31'E. and S.81°29'E., respectively, instead of N.8°12'E. and S.81°48'E., respectively, as approved. I also find the course and distance from Cor. No. 1 to the S. E. Cor. of Sec. 1 to be S.87°29'30"E. 1453.93 ft., instead of S.88°26'E. 1452.98 ft., as approved.

Survey No. 3756, Cross lode;

Cor. No. 1 is a pine post, properly set and scribed with the number of the corner and survey.

Midway lode, unsurveyed;

All corners mentioned herein are pine posts, properly set and marked with a description of the corner and the name of the claim.

Note:-- The record showing the second amended certificates of