

monument, Wedge lode, N.51°52'W. 17.8 ft., 14x30 ft. Course of long sides N.63°30'E.

A corrugated iron engine house, the S. E. Cor. of which bears from the discovery monument, O.P.S. lode, S.85°27'W. 95.2 ft., 10x12 ft. Course of long sides N.60°W. Contains a small gasoline hoisting engine.

Heavy gallows frame at the collar of the main working shaft, improvement No. 2, Wedge lode. All these buildings and other improvements belong to claimant herein.

INSTRUMENT.

This survey was made with a C. L. Berger mining transit No. 4270. The courses were deflected from the true meridian as determined by observation on Polaris at western elongation. The distances were measured with 100 ft. and 500 ft. steel tapes.

REPORT.

The lode line of each location of this claim was run directly upon the ground (except that it was necessary to offset around the buildings upon the lode line of the Wedge lode), and the several corners established by means of offsets from the lode lines. All tie lines were run either directly upon the ground or by traverses run upon the ground and submitted in a separate report herewith.

The S. W. Cor. Sec. 7, T. 28 S., R. 64 E., M.D.M., is a granite stone, about 8x10 ins., 15 ins. high, chiseled with six notches on the West face and two notches on the North face. This is the nearest standing corner of the public survey that can be found and identified.

Sur. No. 3755, Ute lode;

Cor. No. 1 is a pine post, properly set and scribed with the number of the corner and survey.

Sur. No. 3788, Clara Belle lode;

Cor. No. 1 is a pine post, properly set and scribed with the number of the corner and survey.

Black Dog, Rabbit and Silo lodes, unsurveyed;

All corners mentioned herein are pine posts, properly set and marked with a description of the corner and the name of the claim.

NOTE:-- All of the discrepancies between these field notes and the