

- No. 1. The discovery shaft of the Gold Fringe lode, which bears from the center of line 3-4 N.66°47'W. 117.3 ft., 4x6 ft., 10 ft. deep.
Value, \$100.00
- No. 2. A shaft which bears from Cor. No. 5, Gold Fringe lode, N.61°47'E. 196.2 ft., 4x8 ft., 240 ft. deep, timbered for 233 ft. with 6x6 ins. timber and 2 ins. plank lagging. 7 ft. of water in bottom.
Value, \$3600.00

OTHER IMPROVEMENTS.

A corrugated iron engine house, the N. W. Cor. of which bears from a point on line 4-1, Gilt Edge lode, 494.25 ft. from Cor. No. 1, N.46°43'E. 276.9 ft., 20x24 ft. Course of long sides S.73°E.

A frame house, the N. E. Cor. of which bears from the Discovery post, Gold Fringe lode, N.84°16'W. 217.1 ft., 12x24 ft. Course of long sides S.11°W. Both belong to claimants herein.

INSTRUMENT.

This survey was made with a C. L. Berger mining transit No. 4270. The courses were deflected from the true meridian as determined by observation on Polaris at western elongation. The distances were measured with 100-ft. and 500-ft. steel tapes.

REPORT.

The lode line of each location of this claim was run directly upon the ground, and the several corners established by means of offsets from the lode lines. All tie lines were run directly upon the ground.

The N. W. Cor. Sec. 27, T. 28 S., R. 63 E., M.D.M., is a black rock, showing 12x12x8 ins. above a mound of stone, chiseled 3 notches on E. and 2 notches on N.

The N. E. Cor. Sec. 27, T. 28 S., R. 63 E., M.D.M., is a pine post 4 ins. square, showing 2 ft. above a mound of stone and earth, scribed T. 28, S. 23 on its N. E. face; R. 63 E., S. 26 on its S. E. face; S. 27 on its S. W. face; and S. 22 on its N. W. face. These are the nearest standing corners of the public survey that can be found and identified.

Sur. No. 2798, Little Nellie and Dora Fraction lodes;--

All corners mentioned herein are pine posts, properly set and scribed with the number of the corner and survey, except that the