

INSTRUMENT.

This survey was made with a C. L. Berger light mining transit No. 4270. The courses were deflected from the true meridian as determined by observation on Polaris at eastern elongation. The distances were measured with 100-ft. and 500-ft. steel tapes.

REPORT.

The lode line of each location of this claim was run directly upon the ground, and the several corners established by means of offsets from the lode lines. All tie lines were run either directly upon the ground or by traverses, run upon the ground and submitted in a separate report herewith.

The N. E. Cor. Sec. 27, T.28 S., R. 63 E., M.D.M., is a pine post 4 ins. square, showing 2 ft. above a mound of stone and earth, scribed T. 28, S.23 on its N. E. face; R.63 E., S.26 on its S. E. face; S.27 on its S. W. face; and S.22 on its N. W. face. This is the nearest standing corner of the public survey that can be found and identified.

I find the E. boundary Sec. 27 to be N.0°39'20"W. 5246.6 ft., instead of North 5280 ft., as given in the field notes and plat of the public land survey.

Survey No. 2834, Victory lode;--

Cor. No. 4 is a pine post, properly set and scribed with the number of the corner and survey. I find all courses and distances to be correct as approved.

Survey No. 3683, Annette lode;--

Cor. No. 4 is a pine post, properly set and scribed with the number of the corner and survey. I find all courses and distances to be correct as approved.

Princess and Germaine lodes, unsurveyed;--

All corners mentioned herein are pine posts, properly set and marked with the name of the claim and a description of the corner.

NOTE; The discrepancies between these field notes and the amended certificates of location are due to errors in the latter.