

Mineral Survey No. 4916 A

FEET	Mineral Survey No. 4916 A
	<p style="text-align: center;">MILL LODE</p> <p>At. Cor. No. 1 of the Mill lode.</p> <p>Set a solid iron post, 24 ins. long, 1 in. diam., 18 ins, in the ground, surrounded by a mound of stone, with 3 in. aluminum cap marked Mill-1-MS4916A; from which</p> <p style="padding-left: 40px;">The corner common to Sections 19-20-29-30, T. 28 S., R. 61 E., M.D.B. & M: A stone 8"x12"x18", 2 notches on South and 5 notches on East - Also - 3' long natural limb (species unknown) adze trimmed to nominal 1½"x1½" - - profuse, illegible scribing on at least 3 sides, bears S. 62°21' W., 1,495.6 feet distant.</p> <p style="padding-left: 40px;">No local bearing objects available.</p> <p style="padding-left: 80px;">Thence N. 68°09' E.</p>
130.0	High voltage power transmission lines overhead bear N. 48°30' E., and S. 48°30' W.
461.0	Center of 12 foot wide truck trail, which bears Northerly and Southerly.
1,500.0	<p>Cor. No. 2.</p> <p>Set a solid iron post, 24 ins. long, 1 in. diam., 18 ins. in the ground, surrounded by a mound of stone, with 3 in. aluminum cap marked Mill-2-MS4916A.</p> <p style="padding-left: 40px;">No local bearing objects available.</p> <p style="padding-left: 80px;">Thence S. 21°51' E.</p>
62.0	Center of 12 foot wide truck trail, which bears Northeasterly and Southwesterly.
300.0	Lode line, discovery point bears S. 68°09' W., 750.0 feet distant.
504.0	Center of 40 foot wide dry watercourse, drains Southwesterly.
600.0	<p>Cor. No. 3.</p> <p>Set a solid iron post, 24 ins. long, 1 in. diam., 18 ins. in the ground, surrounded by a mound of stone, with 3 in. aluminum cap marked Mill-3-MS4916A.</p> <p style="padding-left: 40px;">No local bearing objects available.</p> <p style="padding-left: 80px;">Thence S. 68°09' W.</p>
138.0	Center of 40 foot wide dry watercourse, drains Southeasterly.

(This form bound on left side)