

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

THE SECOND STANDARD PARALLEL NORTH,
THROUGH PORTIONS OF RANGES 21 AND 22 EAST,

A PORTION OF THE EAST BOUNDARY

AND

A PORTION OF THE SUBDIVISIONAL LINES

AND

THE SUBDIVISION OF CERTAIN SECTIONS,

TOWNSHIP 10 NORTH, RANGE 22 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

EXECUTED BY

Don R. Aschenbach, Cadastral Surveyor

Under Special Instructions dated September 4, 2003,
and approved September 4, 2003,
which provided for the surveys included under Group No. 816,
and Assignment Instructions dated September 4, 2003.

Survey commenced September 11, 2003

Survey completed June 27, 2007

INDEX DIAGRAM

TOWNSHIP 10 NORTH, RANGE 22 EAST, MOUNT DIABLO MERIDIAN, NEVADA

6	5	5	4	4	3	2
14 6	14 5	12 4	12 4	10 3	9 2	7 1 8 7
7 12	8 13	9 11	10	11	12	
18	17	10 16	15	14	13	
19	20	21	22	23	24	
30	29	28	27	26	25	
31	32	33	34	35	36	

Subdivision of Section 1 pp. 15 - 18.
 Subdivision of Section 3 p. 18.
 Subdivision of Section 4 p. 19.
 Subdivision of Section 6 pp. 19 - 21.
 Subdivision of Section 7 pp. 21 - 24.
 Subdivision of Section 8 pp. 24 - 26.
 Subdivision of Section 17 pp. 26 - 28.

TOWNSHIP 10 NORTH, RANGE 22 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The following field notes are those of dependent resurvey of the Second Standard Parallel North, through portions of Ranges 21 and 22 East, a portion of the east boundary and a portion of the subdivisional lines, and the subdivision of certain sections in Township 10 North, Range 22 East, Mount Diablo Meridian, Nevada.

The north boundary, (Second Standard Parallel North) was surveyed by U.S. Deputy Surveyor B. Ives in 1861 under Contract "A". The east boundary was surveyed by U.S. Deputy Surveyor A. Lash, Jr. in 1868 under Contract No. 8. The fractional south and west boundaries and the subdivisional lines were surveyed by U.S. Deputy Surveyor D.H. Barker in 1877 under Contract No. 75. Connections were determined by Barker with the former state line (Von Schmidt). The former California-Nevada state line (Von Schmidt) from 238 mile cor. to 241 mile cor., the present California-Nevada state line (Coast and Geodetic) from Monument 23 to Monument 25, the north boundary (Second Standard Parallel North), the fractional south and west boundaries, the east boundary and the subdivisional lines were retraced or resurveyed, and Tracts 37 and 38 were surveyed by metes-and-bounds by Cadastral Engineer C.S. Swanholm and Associate Cadastral Engineer R.F. Wilson in 1940-45 under Group No. 280, California, and Group No. 246, Nevada. Certain closing corners were determined at points of intersections with the former state line (Von Schmidt), and new closing corners established at points of intersections with the present state line (Coast and Geodetic).

Before restoring the corners, the lines of the original surveys were retraced and a diligent search made for any evidence of the original corners and other calls of the original field note record.

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 816, dated September 4, 2003.

Measurements were made with Trimble 5800 Global Positioning System (GPS) receivers using the real-time kinematic (RTK) method and refer to the true meridian based on geodetic methods. The mean bearings of the lines and horizontal equivalents of ground distances only are entered in the field notes.

The NAD 83 geographic position of the 1/4 section corner of sections 1 and 6, on the east boundary of the township, determined from Global Positioning System (GPS) static observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) LNC1 LINCOLN 1 CORS ARP, UPSA UPSAL HOGBACK CORS ARP and GABB GABBS CORS ARP, in 2006, is as follows:

Latitude: 38°45'33.219" N. Longitude: 119°27'36.784" W.

The 1986 mean magnetic declination is 15°30' E., as shown on U.S.G.S. 7 1/2 minute quadrangle map "OREANA PEAK, NEVADA", provisional edition dated 1986.

DEPENDENT RESURVEY OF THE SECOND STANDARD PARALLEL NORTH,
THROUGH A PORTION OF RANGE 22 EAST,
MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Reestablishment of a Portion of the Survey Executed by B. Ives, U.S. Deputy Surveyor, in 1861, and a Portion of the Dependent Resurvey Executed by C.S. Swanholm, Cadastral Engineer, in 1940-45</p> <hr/> <p>Beginning at the standard cor. of Tps. 11 N., Rs. 22 and 23 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 18 ins. above the ground, supported in a mound of stone, 4 ft. base, to top, with brass cap mkd. as described in the field notes of the dependent resurvey of the Second Standard Parallel North through Range 22 East, executed under Group No. 246. During the course of this survey, this monument was removed by person(s) unknown.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 4 ft. base, to top, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SC T11N R22E R23E S36 S31</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">2007</p> <p>Cor. is located 20 lks. W. of a jeep trail, 20 lks wide, extending SE. and NW.</p> <p>S. 89°56'30" W., on the S. bdy. of sec. 36.</p> <p>Over low hills covered with sagebrush and scattered pinon pines.</p>
12.684	The closing cor. of Tps. 10 N., Rs. 22 and 23 E., hereinafter described.
32.311	Point for the E 1/16 sec. cor. of sec. 1 only, T. 10 N., R. 22 E., hereinafter described.
40.065	<p>The standard 1/4 sec. cor. of sec. 36, monumented with an iron post, 2 ins. diam., firmly set, projecting 18 ins. above the ground, supported in a mound of stone, 4 ft. base, to top, with brass cap mkd. as described in the field notes of the dependent resurvey of the Second Standard Parallel North through Range 22 East, executed under Group No. 246, from which the 1940-45 bearing trees</p> <p style="padding-left: 40px;">A pinon pine, 25 ins. diam., bears N. 9° E., 65.0 lks. dist., with the marks S1/4 BT visible.</p> <p style="padding-left: 40px;">A pinon pine, 20 ins. diam., bears N. 43 3/4° W., 90.0 lks. dist., with the marks 1/4 SC BT visible.</p> <hr style="width: 20%; margin: auto;"/>

DEPENDENT RESURVEY OF THE SECOND STANDARD PARALLEL NORTH,
THROUGH A PORTION OF RANGE 22 EAST,
MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	S. 89°51'00" W., beginning new measurement.
11.873	Point for the 1/4 sec. cor. of sec. 1 only, T. 10 N., R. 22 E., hereinafter described.
31.500	Point for the W 1/16 sec. cor. of sec. 1 only, T. 10 N., R. 22 E., hereinafter described.
39.653	The standard cor. of secs. 35 and 36, monumented with an iron post, 2 ins. diam., firmly set, projecting 26 ins. above the ground, supported in a mound of stone, 4 ft. base, 2 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of the Second Standard Parallel North through Range 22 East, executed under Group No. 246, from which the remains of an original bearing tree A pinon pine stump, 11 ins. diam., bears N. 35°19' W., 25.0 lks. dist., mkd. with a chaining notch, with the base of bearing tree alongside, faintly scribed BT visible. (Record: N. 32° W., 24 lks.) from which the remaining 1940-45 bearing tree A pinon pine, 16 ins. diam., bears N. 13° E., 67.1 lks. dist., mkd. SC T11N R22E S36 BT. (1940-45 record: N. 14 1/2° E., 68 lks.) from which a new bearing object A granite boulder, 5x2 1/2x2 ft. above ground, bears N. 63°04' W., 53.5 lks. dist., mkd. X B0.
	N. 89°59'50" W., on the S. bdy. of sec. 35. Over rough mountainous land through medium timber and dense undergrowth.
1.30	Spur, bears SE.
5.20	Jeep trail, 20 lks. wide, bears N. and S.
11.474	The closing cor. of secs. 1 and 2, T. 10 N., R. 22 E., hereinafter described.
39.603	The standard 1/4 sec. cor. of sec. 35, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the Second Standard Parallel North through Range 22 East, executed under Group No. 246, from which the remaining 1940-45 bearing tree A pinon pine, 12 ins. diam., bears N. 66° W., 89.3 lks. dist., mkd. SC 1/4 S35 BT. (Record: 90 lks.)

DEPENDENT RESURVEY OF THE SECOND STANDARD PARALLEL NORTH,
THROUGH A PORTION OF RANGE 22 EAST,
MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From the standard cor. of secs. 34 and 35, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the Second Standard Parallel North through Range 22 East, executed under Group No. 246, from which the remaining original bearing tree</p> <p style="padding-left: 40px;">A pinon pine, 20 ins. diam., bears N. 41 3/4° W., 62.2 lks. dist., with healed blaze. (1940-45 record: 60 lks.)</p> <p>from which the 1940-45 bearing tree</p> <p style="padding-left: 40px;">A pinon pine, 20 ins. diam., bears N. 45°25' E., 139.3 lks. dist., with the marks T11N R22E BT visible. (Record: N. 44 3/4° E., 140 lks.)</p> <p>N. 89°56'30" W., on the S. bdy. of sec. 34.</p> <p>Over rough mountainous land, through medium timber and dense undergrowth.</p>
11.292	Point for the closing cor. of secs. 2 and 3, T. 10 N., R. 22 E., hereinafter described.
39.918	<p>The standard 1/4 sec. cor. of sec. 34, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above the ground, supported in a mound of stone, 4 ft. base, 1 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of the Second Standard Parallel North through Range 22 East, executed under Group No. 246, from which the remaining 1940-45 bearing tree</p> <p style="padding-left: 40px;">A pinon pine, 14 ins. diam., bears N. 72°20' W., 82 lks. dist., with the marks BT visible. (Record: N. 74° W.)</p> <hr style="width: 30%; margin-left: auto; margin-right: auto;"/> <p>S. 89°54'40" W., beginning new measurement.</p>
11.350	Point for the 1/4 sec. cor. of sec. 3 only, T. 10 N., R. 22 E., hereinafter described.
39.745	<p>The standard cor. of secs. 33 and 34, monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the Second Standard Parallel North through Range 22 East, executed under Group No. 246.</p> <p>Cor. is located 2 lks S. of the corner of fences extending N. and E.</p> <hr style="width: 30%; margin-left: auto; margin-right: auto;"/> <p>S. 89°57'20" W., on the S. bdy. of sec. 33.</p> <p>Over rolling land, through scattered small timber and medium dense low undergrowth.</p>
11.581	The closing cor. of secs. 3 and 4, T. 10 N., R. 22 E., hereinafter described.

DEPENDENT RESURVEY OF THE SECOND STANDARD PARALLEL NORTH,
THROUGH A PORTION OF RANGE 22 EAST,
MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.979	<p>The standard 1/4 sec. cor. of sec. 33, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above the ground, supported in a mound of stone, 4 ft. base, 1 ft. high, as described in the field notes of the dependent resurvey of the Second Standard Parallel North through Range 22 East, executed under Group No. 246.</p>
	<hr/> <p>N. 89°59'50" W., beginning new measurement.</p>
11.618	<p>Point for the 1/4 sec. cor. of sec. 4 only, T. 10 N., R. 22 E., hereinafter described.</p>
39.931	<p>The standard cor. of secs. 32 and 33, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the Second Standard Parallel North through Range 22 East, executed under Group No. 246.</p>
	<hr/> <p>N. 89°56'10" W., on the S. bdy. of sec. 32.</p> <p>Over steep hills covered with native grasses and sagebrush.</p>
11.703	<p>The closing cor. of secs. 4 and 5, T. 10 N., R. 22 E., hereinafter described.</p>
39.863	<p>The standard 1/4 sec. cor. of sec. 32, monumented with an iron post, 1 in. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the Second Standard Parallel North through Range 22 East, executed under Group No. 246, from which the remains of a 1940-45 bearing tree</p> <p style="padding-left: 40px;">A pinon pine stump, 10 ins. diam., bears N. 32 1/2° W., 126.1 lks. dist., no mks. visible. (Record: 128 lks.)</p> <p>Cor. is located 20 lks. S. of a jeep trail, 20 lks. wide, extending SE. and NW.</p>
	<hr/> <p>From the standard cor. of secs. 31 and 32, monumented with an iron post, 2 ins. diam., firmly set, projecting 15 ins. above the ground, supported in a mound of stone, 4 ft. base, to top, with brass cap mkd. as described in the field notes of the dependent resurvey of the Second Standard Parallel North through Range 22 East, executed under Group No. 246.</p> <p>S. 89°55'00" W., on the S. bdy. of sec. 31.</p> <p>Over rough mountains covered with native grasses and scattered timber.</p>
11.461	<p>The closing cor. of secs. 5 and 6, T. 10 N., R. 22 E., hereinafter described.</p>

DEPENDENT RESURVEY OF THE SECOND STANDARD PARALLEL NORTH,
THROUGH A PORTION OF RANGE 22 EAST,
MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
31.353	Point for the E 1/16 sec. cor. of sec. 6 only, T. 10 N., R. 22 E., hereinafter described.
39.922	The standard 1/4 sec. cor. of sec. 31, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the Second Standard Parallel North through Range 22 East, executed under Group No. 246.
<hr/> <p>S. 89°53'30" W., beginning new measurement.</p>	
11.323	Point for the 1/4 sec. cor. of sec. 6 only, T. 10 N., R. 22 E., hereinafter described.
39.748	The standard cor. of Tps. 11 N., Rs. 21 and 22 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 10 ins. above the ground, with a pine post, 15x4x4, faintly scribed set alongside, supported in a mound of stone, 4 ft. base, to top, with brass cap mkd. as described in the field notes of the dependent resurvey of the Second Standard Parallel North through Range 22 East, executed under Group No. 246.
<hr/> <p>DEPENDENT RESURVEY OF THE SECOND STANDARD PARALLEL NORTH, THROUGH A PORTION OF RANGE 21 EAST, MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>	
<p>Reestablishment of a Portion of the Survey Executed by B. Ives, U.S. Deputy Surveyor, in 1861 and a Portion of the Dependent Resurvey Executed by C.S. Swanholm, Cadastral Engineer, in 1940-45</p> <hr/>	
<p>From the standard cor. of Tps. 11 N., Rs. 21 and 22 E., hereinbefore described.</p>	
<p>N. 89°59'30" W., on the S. bdy. of sec. 36.</p>	
<p>Over low hills covered with sagebrush and scattered pinon pines.</p>	
10.769	The closing cor. of Tps. 10 N., Rs. 21 and 22 E., monumented with an iron post, 2 ins. diam., firmly set, projecting 18 ins. above the ground, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 10 N., R. 21 E., executed under Group No. 246.
39.454	The standard 1/4 sec. cor. of sec. 36, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above the ground, supported in a mound of stone, 4 ft. base, to top, with brass cap mkd. as described in the field notes of the dependent resurvey of the Second Standard Parallel North, through Range 21 East, executed under Group No. 246.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 10 N., R. 22 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 38.469</p>	<p>Intersect the Second Standard Parallel North.</p> <p>The closing cor. of secs. 1 and 2, monumented with an iron post, 2 ins. diam., firmly set, projecting 20 ins. above the ground, supported in a mound of stone, 4 1/2 ft. base, to top, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 10 N., R. 22 E., executed under Group No. 246, from which the remaining 1940-45 bearing tree</p> <p style="text-align: center;">A pinon pine, 12 ins. diam., dead and leaning, bears S. 43 1/4° E., 97.0 lks. dist., with the marks CC BT visible. (Record: 102 lks.)</p> <p>From this cor., the standard cor. of secs. 35 and 36, T. 11 N., R. 22 E., bears S. 89°59'50" E., 11.474 chs. dist., hereinbefore described.</p> <hr/> <p>The point for the 1/4 sec. cor. of sec. 1 only, T. 10 N., R. 22 E., is at midpoint on the N. bdy. of sec. 1.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, encircled in a collar of stone, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;"> <hr style="width: 10%; margin: 0 auto;"/> 1/4 S 1 T10N R22E 2004 </p> <p>From this cor., the standard 1/4 sec. cor. of sec. 36, T. 11 N., R. 22 E., bears N. 89°51'00" E., 11.873 chs. dist., hereinbefore described.</p> <hr/> <p>The point for the E 1/16 sec. cor. of sec. 1 only, T. 10 N., R. 22 E., is at midpoint between the closing cor. of Tps. 10 N., Rs. 22 and 23 E. and the 1/4 sec. cor. of sec. 1 only, on the N. bdy. of sec. 1.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled in a collar of stone, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;"> <hr style="width: 10%; margin: 0 auto;"/> E 1/16 S 1 2004 </p> <p>Set a steel sign post alongside the stainless steel post.</p> <p>From this cor., the standard 1/4 sec. cor. of sec. 36, T. 11 N., R. 22 E., bears S. 89°56'30" W., 7.754 chs. dist., hereinbefore described.</p> <hr/>
--------------------------	---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 10 N., R. 22 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p> <p>38.653</p> <p>38.684</p>	<p>The point for the W 1/16 sec. cor. of sec. 1 only, T. 10 N., R. 22 E., is at midpoint between the closing cor. of secs. 1 and 2, and the 1/4 sec. cor. of sec. 1 only, on the N. bdy. of sec. 1.</p> <p>POINT NOT MONUMENTED.</p> <p>From this point, the standard cor. of secs. 35 and 36, T. 11 N., R. 22 E., bears S. 89°51'00" W., 8.153 chs. dist., hereinbefore described.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 2 and 3, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 10 N., R. 22 E., executed under Group No. 246, from which the remaining 1940-45 accessories</p> <p style="padding-left: 40px;">A pinon pine stump, 10 ins. diam., bears S. 40 1/2° E., 134 lks. dist., with the marks 1/4 BT visible.</p> <p style="padding-left: 40px;">A granite boulder, 4x3x2 ft. above ground, bears S. 1°39' W., 42 lks. dist., mkd. with an "X". (Record: S. 0° 56' W.)</p> <p>N. 0°57'40" E., bet. secs. 2 and 3.</p> <p>Over rough mountains land covered with sagebrush and scattered timber.</p> <p>The 1940-45 closing cor. of secs. 2 and 3, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. as described in the dependent resurvey of T. 10 N., R. 22 E., executed under Group No. 246, from which the remaining 1940-45 bearing tree</p> <p style="padding-left: 40px;">A pinon pine, 14 ins. diam., bears S. 63°23' E., 148 lks. dist., mkd. T10N R22E BT. (Record: S. 63° E., 147 lks. dist.)</p> <p>Add the marks AM to the brass cap and bury the iron post in place, 3 ins. below the surface of the ground.</p> <p>Intersect the Second Standard Parallel North.</p> <p>Point for the closing cor. of secs. 2 and 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, encircled in a collar of stone, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T11N R22E S34 ----- S 3 S 2 T10N R22E CC</p> <p>2007</p> </div> <p>Raise a mound of stone, 4 ft. base, 2 ft. high, S. of cor.</p>
---	--

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 10 N., R. 22 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From this point, the standard cor. of secs. 34 and 35, T. 11 N., R. 22 E., bears S. 89°56'30" E., 11.292 chs. dist., hereinbefore described.</p>
	<hr/> <p>From the 1/4 sec. cor. of secs. 3 and 4, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, encircled in a collar of stone, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 10 N., R. 22 E., executed under Group No. 246.</p> <p>N. 0°40'20" E., bet. secs. 3 and 4.</p> <p>Over rolling flats covered with sagebrush and scattered timber.</p>
40.020	<p>Intersect the Second Standard Parallel North.</p> <p>The closing cor. of secs. 3 and 4, monumented with an iron post, 2 ins. diam., firmly set, projecting 7 ins. above the ground, encircled in a collar of stone, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 10 N., R. 22 E., executed under Group No. 246, and a sign post 2 ft. S.</p> <p>From this cor., the standard cor. of secs. 33 and 34, T. 11 N., R. 22 E., bears N. 89°57'20" E., 11.581 chs. dist., hereinbefore described.</p>
	<hr/> <p>The point for the 1/4 sec. cor. of sec. 3 only, T. 10 N., R. 22 E., is at midpoint on the N. bdy. of sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, encircled in a collar of stone, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;"> <hr style="width: 10%; margin: 0 auto;"/> 1/4 S 3 T10N R22E 2004 </p>
19.367	<p>From this point, the standard 1/4 sec. cor. of sec. 34, T. 11 N., R. 22 E., bears N. 89°54'40" E., 11.350 chs. dist., hereinbefore described.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 16 and 17, monumented with an iron post, 1 in. diam., firmly set, projecting 11 ins. above the ground, encircled in a collar of stone, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 10 N., R. 22 E., executed under Group No. 246.</p> <p>N. 1°22'20" E., bet. secs. 16 and 17.</p> <p>Over rolling land covered with sagebrush and scattered timber.</p> <p>Point for the N 1/16 sec. cor. of secs. 16 and 17.</p> <p>Set a copper-coated steel stake, 24 ins. long, 1/2 in. diam., 6 ins. in drill hole of bedrock, supported in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 10 N., R. 22 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">N 1/16 S17 S16</p> <p style="text-align: center;">2004</p> <p>A rebar of unknown origin, 18 ins. long, 5/8 in. diam., was found laying loose nearby, with the position undeterminable. Deposit rebar alongside the copper-coated steel stake.</p> <p>38.734 The cor. of secs. 8, 9, 16 and 17, monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. above the ground, encircled in a collar of stone, 2 ft. base, to top, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 10 N., R. 22 E., executed under Group No. 246.</p> <p>Cor. is located 2 lks. W. of cor. of fences extending E. and N.</p> <hr/> <p>N. 0°15'10" W., bet. secs. 8 and 9.</p> <p>Over rolling hills covered with scattered timber and sagebrush.</p> <p>19.668 The S 1/16 sec. cor. of secs. 8 and 9, determined by person(s) unknown, monumented with a rebar, 18 ins. long, 1/2 in. diam., firmly set, projecting 3 ins. above the ground. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled in a collar of stone, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S 8 S 9</p> <p style="text-align: center;">2004</p> <p>Deposit rebar inside the stainless steel post and set a steel sign post alongside.</p> <hr/> <p>N. 0°15'10" W., beginning new measurement.</p> <p>Continue over rolling hills covered with scattered timber and sagebrush.</p> <p>19.669 The 1/4 sec. cor. of secs. 8 and 9, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 10 N., R. 22 E., executed under Group No. 246.</p> <p>Cor. falls at cor. of fences extending N., S., E. and W.</p> <hr/>
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 10 N., R. 22 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p> <p>39.670</p>	<p>From the 1/4 sec. cor. of secs. 4 and 5, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above the ground, supported in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 10 N., R. 22 E., executed under Group No. 246, from which the remaining 1940-45 bearing tree</p> <p style="text-align: center;">A pinon pine stump, 6 ins. diam., bears S. 81 1/2° E., 103 lks. dist.</p> <p>N. 0°08'40" W., bet. secs. 4 and 5.</p> <p>Over gentle rolling land covered with native grasses and sparse timber.</p> <p>Intersect the Second Standard Parallel North.</p> <p>The closing cor. of secs. 4 and 5, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 10 N., R. 22 E., executed under Group No. 246.</p> <p>From this cor., the standard cor. of secs. 32 and 33, T. 11 N., R. 22 E., bears S. 89°56'10" E., 11.703 chs. dist., hereinbefore described.</p> <hr/> <p>The point for the 1/4 sec. cor. of sec. 4 only, T. 10 N., R. 22 E., is at midpoint on the N. bdy. of sec. 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to solid bedrock, supported in a mound of stone, 4 ft. base, to top, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <hr style="width: 10%; margin: 0 auto;"/> <p>1/4 S 4 T10N R22E</p> <p>2004</p> </div> <p>From this point, the standard 1/4 sec. cor. of sec. 33, T. 11 N., R. 22 E., bears S. 89°59'50" E., 11.618 chs. dist., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 7, 8, 17 and 18, monumented with an iron post, 2 ins. diam., firmly set, projecting 16 ins. above the ground, supported in mound of stone, 4 ft. base, to top, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 10 N., R. 22 E., executed under Group No. 246.</p> <p>S. 89°31'20" W., bet. secs. 7 and 18.</p> <p>Over rolling hills covered with native grasses, sagebrush and scattered timber.</p>
-----------------------------	--

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 10 N., R. 22 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
19.642	<p>The E 1/16 sec. cor. of secs. 7 and 18, determined by Paul Higginbotham, Nevada Professional Land Surveyor No. 6200, monumented with a rebar, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with plastic cap mkd. HIGG N RLS 62 and the rest illegible, and a steel fence post alongside. This position is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, encircled in a collar of stone, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{r} S\ 7 \\ E\ 1/16 \quad \frac{\quad}{S18} \end{array}$ <p>2005</p> </div> <p>Deposit the rebar, 18 ins. long, alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°31'20" W., beginning new measurement.</p> <p>Continue over rolling hills covered with native grasses, sagebrush and scattered timber.</p>
19.642	<p>The 1/4 sec. cor. of secs. 7 and 18, monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above the ground, supported in mound of stone, 6 ft. base, 1 1/2 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 10 N., R. 22 E., executed under Group No. 246, from which the 1940-45 bearing trees</p> <p style="padding-left: 40px;">A pinon pine, 18 ins. diam., bears S. 13 1/4° E., 164.4 lks. dist., with healed blaze. (Record: 165 lks.)</p> <p style="padding-left: 40px;">A dead pinon pine, 12 ins. diam., bears N. 26 1/2° W., 83.3 lks. dist., with healed blaze. (Record: 82 lks.)</p> <hr style="width: 60%; margin: 10px auto;"/>
	<p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 0°35'50" E., bet. secs. 7 and 8.</p> <p>Over broken mountains with native grasses and scattered timber.</p>
19.445	<p>Point for the S 1/16 sec. cor. of secs. 7 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{r} S\ 1/16 \\ S\ 7 \quad \quad S\ 8 \end{array}$ <p>2004</p> </div>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 10 N., R. 22 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
38.890	<p>The 1/4 sec. cor. of secs. 7 and 8, determined by person(s) unknown, monumented with a rebar, 18 ins. long, 3/8 in. diam., firmly set, projecting 3 ins. above the ground. This position has been adopted by various professional land surveyors and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T10N R22E 1/4 S 7 S 8</p> <p style="text-align: center;">2004</p> <p>Deposit the rebar inside the stainless steel post and set a steel sign post alongside.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 5 and 6, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 10 N., R. 22 E., executed under Group No. 246.</p> <p>N. 0°20'00" E., bet. secs. 5 and 6.</p> <p>Over mountainous land covered with native grasses, sagebrush and scattered timber.</p>
19.936	<p>Point for the N 1/16 sec. cor. of secs. 5 and 6.</p> <p>POINT NOT MONUMENTED.</p>
39.314	<p>Intersect the Second Standard Parallel North.</p> <p>The closing cor. of secs. 5 and 6, monumented with an iron post, 3 ins. diam. (Record: 2 ins.), firmly set, projecting 18 ins. above the ground, supported in a mound of stone, 4 ft. base, to top, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 10 N., R. 22 E., executed under Group No. 246.</p> <p>From this cor., the standard cor. of secs. 31 and 32, T. 11 N., R. 22 E. bears N. 89°55'00" E., 11.461 chs. dist., hereinbefore described.</p> <hr/> <p>The point for the 1/4 sec. cor. of sec. 6 only, T. 10 N., R. 22 E., is at proportionate distance on the N. bdy. of sec. 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, encircled in a collar of stone, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 10 N., R. 22 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">1/4 S 6 T10N R22E</p> <p style="text-align: center;">2005</p> <p>Set a steel sign post alongside the stainless steel post.</p> <p>From this point, the standard 1/4 sec. cor. of sec. 31, T. 11 N., R. 22 E., bears N. 89°53'30" E., 11.323 chs. dist., hereinbefore described.</p> <hr/> <p>The point for the E 1/16 sec. cor. of sec. 6 only, T. 10 N., R. 22 E., is at midpoint between the closing cor. of secs. 5 and 6, and the 1/4 sec. cor. of sec. 6 only, on the N. bdy. of sec. 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">E 1/16 S 6</p> <p style="text-align: center;">2005</p> <p>Set a steel sign post alongside the stainless steel post.</p> <p>From this point, the standard 1/4 sec. cor. of sec. 31, T. 11 N., R. 22 E., bears S. 89°55'00" W., 8.569 chs. dist., hereinbefore described.</p> <hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 1, T. 10 N., R. 22 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 1 and 12, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 10 N., R. 22 E., executed under Group No. 246, and a mound of stone, 3 ft. base, 1 ft. high, N. of cor.</p> <p>N. 0°09'20" E., on the N-S center line of sec. 1.</p> <p>Over rough mountains covered with sagebrush and scattered timber.</p> <p>39.856 Point for the center 1/4 sec. cor. of sec. 1, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled in a collar of stone, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T10N R22E C 1/4 S 1</p> <p style="text-align: center;">2004</p>
--------	--

SUBDIVISION OF SECTION 1,
T. 10 N., R. 22 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Set a steel sign post alongside the stainless steel post.
59.737	Point for the C-N 1/16 sec. cor. of sec. 1.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, encircled in a collar of stone, over a plastic-encased magnet, with brass cap mkd.
	$\begin{array}{c} C \\ N\ 1/16 \mid S\ 1 \\ C \end{array}$
	2004
77.038	The 1/4 sec. cor. of sec. 1 only, on the N. bdy. of sec. 1.
	From the 1/4 sec. cor. of secs. 1 and 6, on the E. bdy. of the Tp.
	S. 88°02'20" W., on the E-W center line of sec. 1.
	Over rough mountains covered with sagebrush and scattered timber.
19.693	Point for the C-E 1/16 sec. cor. of sec. 1.
	POINT NOT MONUMENTED.
31.00	Jeep trail, 20 lks. wide, bears NE. and SW.
36.50	Jeep trail, 20 lks. wide, bears SE. and NW.
39.386	The center 1/4 sec. cor. of sec. 1.
40.10	Jeep trail, 20 lks. wide, bears NE. and SW.
48.50	Ridge, bears SE. and NW.
59.121	Point for the C-W 1/16 sec. cor. of sec. 1.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	$\begin{array}{c} W\ 1/16 \\ C \text{---} C \\ S\ 1 \end{array}$
	2001
	Set a steel sign post alongside the stainless steel post.
78.856	The 1/4 sec. cor. of secs. 1 and 2.
	From the point for the C-E 1/16 sec. cor. of sec. 1.
	N. 0°04'30" E., on the N-S center line of the NE1/4 of sec. 1.
	Over rough mountains covered with sagebrush and scattered timber.

SUBDIVISION OF SECTION 1,
T. 10 N., R. 22 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
19.927	<p>Point for the NE 1/16 sec. cor. of sec. 1, at intersection with the E-W center line of the NE1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled in a collar of stone, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S 1 2004</p>
24.20	Draw, drains SE.
36.547	<p>The E 1/16 sec. cor. of sec. 1 only, on the N. bdy. of sec. 1.</p> <hr/> <p>From the point for the N 1/16 sec. cor. of secs. 1 and 6, on the E. bdy. of the Tp.</p> <p>S. 87°55'00" W., on E-W center line of the NE1/4 of sec. 1.</p> <p>Over rough mountains covered with sagebrush and scattered timber.</p>
19.665	The NE 1/16 sec. cor. of sec. 1.
39.331	<p>The C-N 1/16 sec. cor. of sec. 1.</p> <hr/> <p>From the C-W 1/16 sec. cor. of sec. 1.</p> <p>N. 0°17'50" E., on the N-S center line of the NW1/4 of sec. 1.</p> <p>Over rough mountains covered with sagebrush and scattered timber.</p>
6.60	Ridge, bears SE. and NW.
10.70	Draw, drains SE.
13.80	Draw, drains SE.
16.70	Jeep trail, 20 lks. wide, bears E. and W.
19.845	<p>Point for the NW 1/16 sec. cor. of sec. 1, at intersection with the E-W center line of the NW1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S 1 2004</p>
37.806	<p>The point for the W 1/16 sec. cor. of sec. 1 only, on the N. bdy. of sec. 1.</p> <hr/>

SUBDIVISION OF SECTION 1,
T. 10 N., R. 22 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the C-N 1/16 sec. cor. of sec. 1.</p> <p>S. 87°55'00" W., on the E-W center line of the NW1/4 of sec. 1.</p> <p>Over rough mountains covered with sagebrush and scattered timber.</p>
3.60	Ridge, bears SE. and NW.
12.30	Jeep trail, 20 lks. wide, bears NE. and SW.
19.686	The NW 1/16 sec. cor. of sec. 1.
39.374	The point for the N 1/16 sec. cor. of secs. 1 and 2.
<hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 3, T. 10 N., R. 22 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>	
	<p>From the 1/4 sec. cor. of secs. 3 and 10, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 10 N., R. 22 E., executed under Group No. 246, and a mound of stone, 3 ft. base, 2 ft. high, S. of the cor.</p> <p>Cor. is located 1 lk. S. of a fence extending E. and W.</p> <p>N. 0°47'30" E., on the N-S center line of sec. 3.</p> <p>Over gradual accent covered with sagebrush and scattered timber.</p>
40.015	<p>Point for the center 1/4 sec. cor. of sec. 3, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled in a collar of stone, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T10N R22E C 1/4 S 3 2004</p>
79.396	<p>Set a steel sign post alongside the stainless steel post.</p> <p>The 1/4 sec. cor. of sec. 3 only, on the N. bdy. of sec. 3.</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 2 and 3.</p> <p>S. 89°00'40" W., on the E-W center line of sec. 3.</p> <p>Over hills covered with sagebrush and scattered timber.</p>
39.879	The center 1/4 sec. cor. of sec. 3.
79.791	The 1/4 sec. cor. of secs. 3 and 4.

SUBDIVISION OF SECTION 4,
T. 10 N., R. 22 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the 1/4 sec. cor. of secs. 4 and 9, monumented with an iron post, 1 in. diam., firmly set, projecting 19 ins. above the ground, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 10 N., R. 22 E., executed under Group No. 246.</p> <p>N. 0°14'20" E., on the N-S center line of sec. 4.</p> <p>Over gradual accent covered with sagebrush and scattered timber.</p>
40.309	<p>Point for the center 1/4 sec. cor. of sec. 4, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, encircled in a collar of stone, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T10N R22E C 1/4 S 4 2004</p>
80.131	<p>Set a steel sign post alongside the stainless steel post.</p> <p>The 1/4 sec. cor. of sec. 4 only, on the N. bdy. of sec. 4.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 3 and 4.</p> <p>N. 89°45'20" W., on the E-W center line of sec. 4.</p> <p>Over flats covered with sagebrush and scattered timber.</p>
39.715	<p>The center 1/4 sec. cor. of sec. 4.</p>
79.469	<p>The 1/4 sec. cor. of secs. 4 and 5.</p> <hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 6, T. 10 N., R. 22 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 6 and 7, monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above the ground, supported in a mound of stone, 4 ft. base, 1 1/2 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 10 N., R. 22 E., executed under Group No. 246.</p> <p>N. 0°04'30" W., on the N-S center line of sec. 6.</p> <p>Over rough hills covered with native grasses, sagebrush and scattered timber.</p>
7.10	<p>Draw, drains NW.</p>
39.229	<p>Point for the center 1/4 sec. cor. of sec. 6, at intersection with the E-W center line.</p>

SUBDIVISION OF SECTION 6,
T. 10 N., R. 22 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, encircled in a collar of stone, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T10N R22E C 1/4 S 6</p> <p style="text-align: center;">2005</p> <p>Set a steel sign post alongside the stainless steel post.</p>
59.181	<p>Point for the C-N 1/16 sec. cor. of sec. 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, encircled in a collar of stone, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">C N 1/16 S 6 C</p> <p style="text-align: center;">2005</p> <p>Set a steel sign post alongside the stainless steel post.</p>
75.00	Ridge, bears E. and W.
78.404	The 1/4 sec. cor. of sec. 6 only, on the N. bdy. of sec. 6.
	<hr/> <p>From the 1/4 sec. cor. of secs. 5 and 6.</p> <p>N. 89°53'50" W., on the E-W center line of sec. 6.</p> <p>Over rough hills covered with native grasses, sagebrush and scattered timber.</p>
2.90	Draw, drains S.
14.60	Ridge, bears N. and S.
19.754	Point for the C-E 1/16 sec. cor. of sec. 6.
	POINT NOT MONUMENTED.
39.508	The center 1/4 sec. cor. of sec 6.
77.869	<p>The 1/4 sec. cor. of secs. 1 and 6, on the W. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. the above the ground, supported in a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 10 N., R. 22 E., executed under Group No. 246.</p> <hr/> <p>From the point for the C-E 1/16 sec. cor. of sec. 6.</p> <p>N. 0°07'50" E., on the N-S center line of the NE1/4 of sec. 6.</p> <p>Over rough hills covered with native grasses, sagebrush and scattered timber.</p>

SUBDIVISION OF SECTION 6,
T. 10 N., R. 22 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
19.940	<p>Point for the NE 1/16 sec. cor. of sec. 6, at intersection with the E-W center line of the NE1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, encircled in a collar of stone, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S 6 2004</p> <p>Set a steel sign post alongside the stainless steel post.</p>
39.243	<p>The E 1/16 sec. cor. of sec 6 only, on the N. bdy. of sec. 6.</p> <hr/> <p>From the point for the N 1/16 sec. cor. of secs. 5 and 6. N. 89°52'20" W., on the E-W center line of the NE1/4 of sec. 6.</p> <p>Over rough hills covered with native grasses, sagebrush and scattered timber.</p>
19.822	<p>The NE 1/16 sec. cor. of sec. 6.</p>
39.645	<p>The C-N 1/16 sec. cor. of sec. 6.</p> <hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 7, T. 10 N., R. 22 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 7 and 18. N. 0°15'20" E., on the N-S center line of sec. 7.</p> <p>Over rolling hills covered with sagebrush and timber.</p>
12.10	<p>Center of asphalt of U.S. Highway No. 395, 60 lks. wide, bears S. 30° E. and N. 30° W.</p>
38.516	<p>The center 1/4 sec. cor. of sec. 7, determined by William L. Higginbotham, Nevada Professional Land Surveyor No. 6200, monumented with a rebar, 18 ins. long, 5/8 in. diam., firmly set, projecting 3 ins. above the ground at cor. of fences extending N. and W., with aluminum cap mkd. HIGG N SONS C1/4 S7 RLS 6200, with a rebar of unknown origin, 18 ins. long, 1/2 in. diam., laying alongside. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

SUBDIVISION OF SECTION 7,
T. 10 N., R. 22 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T10N R22E C 1/4 S 7 2004
	Deposit rebars inside the stainless steel post and set a steel sign post alongside.
	<hr/> N. 0°14'40" E., beginning new measurement.
	Over rolling hills covered with sagebrush and timber, along fence.
20.018	Point for the C-N 1/16 sec. cor. of sec. 7. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, encircled in a collar of stone, over a plastic-encased magnet, with brass cap mkd.
	$\begin{array}{c} C \\ N\ 1/16\ \ S\ 7 \\ C \end{array}$ 2004
	From this point, a rebar of unknown origin, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, bears N. 2°34' E., 0.413 chs. dist. This position is not harmoniously related to surrounding corners, cannot be reconciled with proper procedures and is not utilized during the course of this survey.
20.40	Leave fence line, continue over rolling hills.
40.036	The 1/4 sec. cor. of secs. 6 and 7.
	<hr/> From the 1/4 sec. cor. of secs. 7 and 8.
	S. 88°59'10" W., on the E-W center line of sec. 7.
	Over rolling hills covered with grass, sagebrush and scattered timber.
0.60	Mine road, 20 lks. wide bears NE. and SW.
4.30	Mine road, 20 lks. wide, bears SE. and NW.
5.40	Mine road, 20 lks. wide, bears NE. and SW.
18.70	Mine road, 20 lks. wide, bears NE. and SW.
19.20	Wash, 10 lks. wide, drains SW.
19.762	The C-E 1/16 sec. cor. of sec. 7, determined by person(s) unknown, monumented with a rebar, 18 ins. long, 5/8 in. diam., firmly set, projecting 6 ins. above the ground, with remains of plastic cap illegible. This is accepted as a careful and faithful determination of the position of the corner.

SUBDIVISION OF SECTION 7,
T. 10 N., R. 22 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, encircled in a collar of stone, over a plastic-encased magnet, with brass cap mkd.</p> $\begin{array}{c} \text{E } 1/16 \\ \text{C} \text{-----} \text{C} \\ \text{S } 7 \end{array}$ <p style="text-align: center;">2004</p> <p>Deposit rebar inside the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 88°59'20" W., beginning new measurement.</p> <p>Over rolling hills covered with native grasses, sagebrush and scattered timber.</p> <p>19.751 The center 1/4 sec. cor. of sec. 7.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 88°58'50" W., beginning new measurement.</p> <p>1.50 Dry creek, 20 lks. wide, course SE.</p> <p>13.757 A position determined by William L. Higginbotham, Nevada Professional Land Surveyor No. 6200, monumented with a rebar, 5/8 in. diam., firmly set, projecting 4 ins. above the ground at cor. of fences extending SE. and NW., with aluminum cap mkd. HIGG N SONS RLS 6200.</p> <p>15.47 Center of asphalt surface of U.S. Highway No. 395, 60 lks. wide, bears SE. and NW.</p> <p>17.179 A position determined by Bennett J. Vasey, Nevada Professional Land Surveyor No. 1586, monumented with a rebar, 5/8 in. diam., firmly set, projecting 4 ins. above the ground at cor. of fences extending SE. and NW., with aluminum cap mkd. RLS 1586.</p> <p>20.281 The C-W 1/16 sec. cor. of sec. 7, determined by Bennett J. Vasey, Nevada Professional Land Surveyor No. 1586, monumented with a rebar, 18 ins. long, 5/8 in. diam., firmly set, projecting 4 ins. above the ground at cor. of fences extending E., S. and W., with aluminum cap mkd. RLS 1586. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, encircled in a collar of stone, 3 ft. base, to top, over a plastic-encased magnet, with brass cap mkd.</p> $\begin{array}{c} \text{W } 1/16 \\ \text{C} \text{-----} \text{C} \\ \text{S } 7 \end{array}$ <p style="text-align: center;">2004</p> <p>Deposit rebar inside stainless steel post.</p> <hr style="width: 20%; margin: auto;"/>
--------	--

SUBDIVISION OF SECTION 7,
T. 10 N., R. 22 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	S. 88°58'50" W., beginning new measurement.
17.247	The 1/4 sec. cor. of secs. 7 and 12, on the W. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 10 N., R. 22 E., executed under Group No. 246.
<hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 8, T. 10 N., R. 22 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>	
	From the 1/4 sec. cor. of secs. 8 and 17, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, encircled in a collar of stone, 4 ft. base, to top, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 10 N., R. 22 E., executed under Group No. 246.
	N. 0°06'30" W., on the N-S center line of sec. 8.
	Over rough hills covered with native grasses, sagebrush and scattered timber.
2.20	Ridge, bears SE. and NW.
4.90	Draw, drains SE.
15.00	Ridge bears SE. and NW.
19.098	Point for the C-S 1/16 sec. cor. of sec. 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, encircled in a collar of stone, over a plastic-encased magnet, with brass cap mkd.
	$\begin{array}{c} C \\ S \ 1/16 \ \ S \ 8 \\ C \end{array}$ <p style="text-align: center;">2004</p>
33.80	Draw, drains E.
38.196	Point for the center 1/4 sec. cor. of sec. 8, at intersection with the E-W center line. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<p style="text-align: center;">T10N R22E C 1/4 S 8</p> <p style="text-align: center;">2004</p>
38.60	Ridge, bears E. and W.
43.80	Draw, drains NE.
47.00	Ridge, bears E. and W.

SUBDIVISION OF SECTION 8,
T. 10 N., R. 22 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
52.30	Draw, drains SE.
59.00	Ridge, bears E. and W.
77.161	The 1/4 sec. cor. of secs. 5 and 8, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 10 N., R. 22 E., executed under Group No. 246.
	<hr/> <p>From the 1/4 sec. cor. of secs. 8 and 9.</p> <p>N. 88°44'20" W., on the E-W center line of sec. 8.</p> <p>Over rough hills covered with native grasses, sagebrush and scattered timber, along fence.</p>
9.10	Leave fence, continue over rough hills.
10.30	Center of asphalt road, 40 lks. wide, bears N. and S.
19.772	The C-E 1/16 sec. cor. of sec. 8, determined by person(s) unknown, monumented with a rebar, 18 ins. long, 1/2 in. diam., firmly set, projecting 4 ins. above the ground. This is accepted as a careful and faithful determination of the position of the corner.
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \text{E } 1/16 \\ \text{C} \text{-----} \text{C} \\ \text{S } 8 \end{array}$ <p>2004</p> </div> <p>Deposit rebar inside the stainless steel post.</p> <hr/> <p>N. 88°44'20" W., beginning new measurement.</p> <p>Continue over rough hills covered with native grasses, sagebrush and scattered timber.</p>
19.772	The center 1/4 sec. cor. of sec. 8.
42.75	Ridge, bears N. and S.
51.25	Mine road, bears NE. and SW.
59.222	The 1/4 sec. cor. of secs. 7 and 8.
	<hr/>

SUBDIVISION OF SECTION 8,
T. 10 N., R. 22 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the S 1/16 sec. cor. of secs. 8 and 9.</p> <p>N. 87°54'50" W., on the E-W center line of the SE1/4 of sec. 8.</p> <p>Over rough hills covered with native grasses, sagebrush and scattered timber.</p>
33.20	Spur, slopes NE.
39.612	The C-S 1/16 sec. cor. of sec. 8.
<hr/>	
	<p>N. 89°14'40" W., on the E-W center line of the SW1/4 of sec. 8.</p> <p>Over rough hills covered with native grasses, sagebrush and scattered timber.</p>
8.70	Ridge, bears SE. and NW.
18.10	Draw, drains S.
25.60	Ridge, bears NE. and SW.
39.683	The S 1/16 sec. cor. of secs. 7 and 8.
<hr/>	
<p>SUBDIVISION OF SECTION 17, T. 10 N., R. 22 E., MOUNT DIABLO MERIDIAN, NEVADA</p>	
<hr/>	
	<p>From the 1/4 sec. cor. of secs. 17 and 20, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above the ground, supported in a mound of stone, 4 ft. base, to top, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 10 N., R. 22 E., executed under Group No. 246.</p> <p>N. 0°08'40" E., on the N-S center line of sec. 17.</p> <p>Over flats covered with sagebrush and scattered timber.</p>
7.80	Dry wash, 20 lks. wide, drains NE.
24.30	Dry wash, 20 lks. wide, drains NE.
26.00	Right-of-way fence, bears SE. and NW.
27.19	Center of asphalt surface of State Route 208, 60 lks. wide, bears SE. and NW.
28.36	Right-of-way fence, bears SE. and NW.
28.73	Center of asphalt surfaced road, 40 lks. wide, bears SE. and NW.
39.964	<p>The center 1/4 sec. cor. of sec. 17, determined by William J. Wilson, Nevada Professional Land Surveyor No. 1710, monumented with a rebar, 18 ins. long, 5/8 in. diam., firmly set, projecting 5 ins. above the ground, with aluminum cap mkd. CEN SEC 17, as shown on the Record of Survey for Topaz Ranch Estates, filed as Document No. 32578 in the Office of the County Recorder, Douglas County, Nevada. This is accepted as a careful and faithful determination of the position of the corner.</p>

SUBDIVISION OF SECTION 17,
T. 10 N., R. 22 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, encircled in a collar of stone, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T10N R22E C 1/4 S17</p> <p style="text-align: center;">2004</p> <p>Deposit rebar inside the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°08'40" E., beginning new measurement.</p> <p>Continue over rough hills covered with native grasses, sagebrush and scattered timber, along fence.</p>
19.00	Ridge, bears SE. and NW.
20.024	<p>The C-N 1/16 sec. cor. of sec. 17, determined by William J. Wilson, Nevada Professional Land Surveyor No. 1710, monumented with a rebar, 18 ins. long, 5/8 in. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. NE SE 1/4 NW 1/4 NW SW 1/4 NE 1/4, as shown on the Record of Survey for Topaz Ranch Estates, filed as Document No. 32578 in the Office of the County Recorder, Douglas County, Nevada. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, encircled in a collar of stone, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">C N 1/16 S17 C</p> <p style="text-align: center;">2004</p> <p>Deposit rebar inside the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°09'00" E., beginning new measurement.</p>
3.00	Draw, drains NE.
12.50	Draw, drains SE.
20.002	<p>The 1/4 sec. cor. of secs. 8 and 17.</p> <hr style="width: 20%; margin: auto;"/> <p>From the 1/4 sec. cor. of secs. 16 and 17.</p> <p>N. 88°57'00" W., on the E-W center line of sec. 17.</p>

SUBDIVISION OF SECTION 17,
T. 10 N., R. 22 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Over rough hills covered with native grasses, sagebrush and scattered timber.
5.40	Jeep trail, 20 lks. wide, bears NE. and SW.
23.60	Spur, slopes SE.
38.824	The center 1/4 sec. cor. of sec. 17.

	N. 88°57'40" W., beginning new measurement.
19.843	The C-W 1/16 sec. cor. of sec. 17, determined by Wyatt J. Owens, Nevada Professional Land Surveyor No. 3090, monumented with a rebar, 5/8 in. diam., firmly set, projecting 4 ins. above the ground, with plastic cap mkd. OWENS ENG. PLS 3090, as shown on the Record of Survey for Walker River Enterprises, filed as Document No. 359709 in the Office of the County Recorder, Douglas County, Nevada. This is accepted as a careful and faithful determination of the position of the corner.
	From this cor., a rebar, of unknown origin, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with aluminum cap mkd. SW COR SE1/4 NW1/4 S17, bears S. 54° E., 0.010 chs. dist. This position cannot be reconciled with proper procedures and is not utilized during the course of this survey.

	N. 88°57'40" W., beginning new measurement.
9.15	Dry wash, 30 lks. wide, drains SE.
14.46	Center of asphalt surfaced road, 40 lks. wide, bears SE. and NW.
19.843	The 1/4 sec. cor. of secs. 17 and 18, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above the ground, supported in a mound of stone, 3 1/2 ft. base, 1/2 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 10 N., R. 22 E., executed under Group No. 246.

	From the N 1/16 sec. cor. of secs. 16 and 17.
	N. 87°59'50" W., on the E-W center line of the NE1/4 of sec. 17.
	Over rough hills covered with native grasses, sagebrush and scattered timber.
2.80	Draw, drains SE.
13.30	Jeep trail, 20 lks. wide, bears N. and S.
15.00	Draw, drains SE.
39.254	The C-N 1/16 sec. cor. of sec. 17.

TOWNSHIP 10 NORTH, RANGE 22 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	GENERAL DESCRIPTION
	<p data-bbox="451 369 1477 583">The soil in the hilly part of this township is mostly coarse, thin clay loam and rocks over hardpan and bedrock, generally 3rd rate. The main vegetation is sagebrush, pinon pine and juniper trees. The mean elevation is approximately 5500 feet above sea level. U.S. Highway No. 395, State Route 208, numerous asphalt and dirt surfaced roads and jeep trails provide access to the area. There is no evidence of any successful mineral activity.</p> <hr data-bbox="451 604 1477 609"/>

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Kane M. Hellebust	Student Trainee (Land Survey)
Steven E. Dagitz	Surveying Technician
Joseph J. Johnson	Surveying Technician
Jeremiah J. Lee	Surveying Technician
Clay W. Morrow	Surveying Technician
Mark G. Petrosine	Surveying Technician

CERTIFICATE OF SURVEY

I, Don R. Aschenbach, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 4th day of September, 2003, I have dependently resurveyed the Second Standard Parallel North, through portions of Ranges 21 and 22 East, a portion of the east boundary and a portion of the subdivisional lines, and subdivided certain sections, Township 10 North, Range 22 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

August 16, 2007
(Date)

Don R. Aschenbach
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of the dependent resurvey of the Second Standard Parallel North, through portions of Ranges 21 and 22 East, a portion of the east boundary and a portion of the subdivisional lines, and the subdivision of certain sections, Township 10 North, Range 22 East, Mount Diablo Meridian, executed by Don R. Aschenbach, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

August 23, 2007
(Date)

David W. Yorlan
(Chief Cadastral Surveyor, Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above described surveys in T. 10 N., R. 22 E., Mount Diablo Meridian, is a true copy of the original field notes.~~

~~_____
(Date)~~

~~_____
(Chief Cadastral Surveyor, Nevada)~~