

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

A PORTION OF THE WEST BOUNDARY

AND A PORTION OF THE SUBDIVISIONAL LINES,

AND

A METES-AND-BOUNDS SURVEY OF A PORTION OF U.S. HIGHWAY NO. 93,

TOWNSHIP 11 SOUTH, RANGE 63 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

EXECUTED BY

David J. Passmore, Professional Land Surveyor (VTN, Inc.)

Craig L. Wanless, Cadastral Surveyor (BLM)

Under Special Instructions dated February 1, 2005,
and approved February 1, 2005,
which provided for the surveys included under Group No. 824,
and Assignment Instructions dated February 2, 2005.

Survey commenced February 7, 2005

Survey completed September 26, 2006

INDEX DIAGRAM

TOWNSHIP 11 SOUTH, RANGE 63 EAST, MOUNT DIABLO MERIDIAN, NEVADA

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
4 19 7	20	21	22	23	24
3 30 6	6 29	28	27	26	25
2 31	5 32	33	34	35	36

Metes-and-Bounds Survey of a Portion of U.S. Highway No. 93. pp. 8 - 10.

TOWNSHIP 11 SOUTH, RANGE 63 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The following field notes are those of the dependent resurvey of a portion of the west boundary and a portion of the subdivisional lines, and a metes-and-bounds survey of a portion of U.S. Highway No. 93, in Township 11 South, Range 63 East, Mount Diablo Meridian, Nevada.

The exterior boundaries were surveyed by U.S. Deputy Surveyor C.F. Putnam in 1881, under Contract No. 125. The subdivisional lines were surveyed by U.S. Deputy Surveyors C.F. Putnam and W.F. Benson in 1881, under Contract No. 125. A portion of the south boundary was dependently resurveyed concurrently under this same Group.

Before restoring the corners, the lines of the original surveys were retraced and a diligent search made for any evidence of the original corners and other calls of the original field note record.

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 824, dated February 1, 2005.

The direction and distances of the lines of this survey were obtained by Trimble 4700 Global Positioning System (GPS) receivers using real-time kinematic method and refer to the true meridian, based on geodetic methods.

The mean bearings of the lines and horizontal equivalents of ground distances only are entered in the field notes.

The geographic position, NAD 1983, of the corner of sections 5, 6, 31 and 32, on the south boundary of the township as determined by survey grade global positioning system receivers, in 2005, is as follows:

Latitude: 36°56'26.914" N. Longitude: 114°57'37.581" W.

The mean magnetic declination is 15 1/2° E., as shown on U.S.G.S. quadrangle map "WILDCAT WASH NW, NEV.", dated 1969.

116

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 11 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Reestablishment of a Portion of the Survey Executed by C.F. Putnam in 1881
	<p>Beginning at the cor. of Tps. 11 and 12 S., Rs. 62 and 63 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set in a mound of stone, 4 ft. diam., 6 ins. high, mkd. as described in the field notes of the dependent resurvey of the west boundary of T. 12 S., R. 63 E., executed concurrently under this same Group.</p> <p>N. 0°35'40" W., bet. secs. 31 and 36.</p> <p>Over nearly level land.</p>
39.987	<p>The 1/4 sec. cor. of secs. 31 and 36, monumented with a granite stone, 18x10x7 ins., firmly set in a mound of stone, 4 ft. diam., 2 ft. high, mkd. 1/4 on W. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T11S 1/4 R62E R63E S36 S31</p> <p>2005</p> </div> <p>Deposit the original stone alongside the stainless steel post.</p>
34.80	<p>N. 0°16'40" E., beginning new measurement.</p> <p>Spur, slopes W.</p>
35.60	<p>Gulch, 75 lks. wide, drains N. 80° E.</p>
40.009	<p>The cor. of secs. 25, 30, 31 and 36, perpetuated by Jerry Barnson, Nevada Professional Land Surveyor No. 4046, not recorded, monumented with a rebar, 5/8 in. diam., with aluminum cap mkd. VTN ENGR CO RLS 4046, firmly set, and in a mound of stone, 3 ft. diam., 1 ft. high, alongside of which is a cement stone, 18x8x6 ins., mkd. with 5 grooves on one face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T11S R62E R63E S25 S30 ----- S36 S31</p> <p>2005</p> </div>

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 11 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	Deposit the original stone alongside and the rebar inside stainless steel post.
	<hr/>
	N. 0°08'20" W., bet. secs. 25 and 30. Over nearly level land.
4.30	Dirt road, 15 lks. wide, bears N. 30° W. and S. 30° E.
12.70	Gulch, 75 lks. wide, drains E.
34.60	Pahranagat Wash, 2 chs. wide, drains SE.
40.232	The 1/4 sec. cor. of secs. 25 and 30, perpetuated by Jerry Barnson, Nevada Professional Land Surveyor No. 4046, not recorded, monumented with a rebar, 5/8 in. diam., with aluminum cap mkd. VTN ENGR CO PLS 4046, firmly set, and in a mound of stone, 3 ft. diam., 1 ft. high, alongside of which is a cement stone, 14x11x6 ins., mkd. 1/4 on one face. At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<p style="text-align: center;">T11S 1/4 R62E R63E S25 S30 2005</p>
	Deposit the original stone alongside and the rebar inside the stainless steel post. <hr/>
	N. 0°06'20" E., beginning new measurement.
39.930	The cor. of secs. 19, 24, 25 and 30, perpetuated from original evidence no longer in existence by Boyd R. Urie, Nevada Professional Land Surveyor No. 8614, in 1997, as recorded in Lincoln County Record of Survey Plat B, Page 19A. The monument set by Urie is no longer in existence, therefore the cor. is determined at Urie's record distance from the 1/4 sec. cor. of secs. 19 and 24, hereinafter described, and on a bearing projected from the cor. of secs. 13, 18, 19, 24, hereinafter described, through the 1/4 sec. cor. of secs. 19 and 24. This position is substantiated by a bearing and distance tie made by the Nevada Department of Transportation from U.S. Highway No. 93 to the original corner as shown on the State of Nevada right-of-way application Nev-061281, dated August 7, 1963. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

118

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 11 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T11S</td></tr> <tr><td style="text-align: center;">R62E</td><td style="text-align: center;">R63E</td></tr> <tr><td style="text-align: center;">S24</td><td style="text-align: center;">S19</td></tr> <tr><td style="text-align: center;">S25</td><td style="text-align: center;">S30</td></tr> <tr><td colspan="2" style="text-align: center;">2005</td></tr> </table>	T11S		R62E	R63E	S24	S19	S25	S30	2005	
T11S											
R62E	R63E										
S24	S19										
S25	S30										
2005											
	<hr/> <p>N. 0°03'00" W., bet. secs. 19 and 24.</p> <p>Over nearly level land.</p> <p>40.242 The 1/4 sec. cor. of secs. 19 and 24, reestablished at proportionate position by Boyd R. Urie, Nevada Professional Land Surveyor No. 8614, in 1997, as recorded in Lincoln County Record of Survey Plat B, Page 19A; monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, with aluminum cap mkd. PLS 8614, there is no remaining evidence of the original cor. This is accepted as a careful and faithful reestablishment of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <table border="1" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T11S</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">R62E</td><td style="text-align: center;">R63E</td></tr> <tr><td style="text-align: center;">S24</td><td style="text-align: center;">S19</td></tr> <tr><td colspan="2" style="text-align: center;">2005</td></tr> </table> <p>Deposit the rebar inside the stainless steel post.</p> <hr/>	T11S		1/4		R62E	R63E	S24	S19	2005	
T11S											
1/4											
R62E	R63E										
S24	S19										
2005											
	<p>N. 0°03'00" W., beginning new measurement.</p> <p>40.242 The cor. of secs. 13, 18, 19 and 24, perpetuated from original evidence no longer in existence by Dennis H. Wise, Nevada Professional Land Surveyor No. 2379 and accepted by Boyd R. Urie, Nevada Professional Land Surveyor No. 8614, in 1997, monumented with a rebar, 5/8 in. diam., firmly set, with an aluminum cap mkd. PLS 2379, as recorded in Lincoln County Record of Survey Plat B, Page 19A. The position of this cor. is substantiated by a bearing and distance tie made by the Nevada Department of Transportation from U.S. Highway No. 93 to the corner as shown on the State of Nevada right-of-way application Nev-061281 dated August 7, 1963. This is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p>										

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 11 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS									
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T11S</td></tr> <tr><td style="text-align: center;">R62E</td><td style="text-align: center;">R63E</td></tr> <tr><td style="text-align: center;">S13</td><td style="text-align: center;">S18</td></tr> <tr><td style="text-align: center;">S24</td><td style="text-align: center;">S19</td></tr> </table> <p style="text-align: center;">2005</p>	T11S		R62E	R63E	S13	S18	S24	S19
T11S									
R62E	R63E								
S13	S18								
S24	S19								
	<p>Deposit the rebar inside the stainless steel post.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 11 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of a Portion of the Survey Executed by C.F. Putnam and W.F. Benson in 1881</p> <hr/> <p>From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set in a mound of stone, 3 ft. diam., 6 ins. high, as described in the field notes of the dependent resurvey of the north boundary of T. 12 S., R. 63 E., executed concurrently under this same Group.</p> <p>N. 1°27'30" W., bet. secs. 31 and 32.</p> <p>Over rolling hills.</p>								
14.00	Gulch, drains W.								
39.880	Point for the 1/4 sec. cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original cor.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.								
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T11S R63E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">S31</td><td style="text-align: center;">S32</td></tr> </table> <p style="text-align: center;">2005</p>	T11S R63E		1/4		S31	S32		
T11S R63E									
1/4									
S31	S32								
59.00	Gulch, 5 lks. wide, drains W.								
62.30	Wash, drains S. 80° W.								
79.760	The cor. of secs. 29, 30, 31 and 32, monumented with an unmarked lava stone, 14x12x9 ins., firmly set in a mound of stone, 2 ft. diam., 2 ft. high.								
	At the corner point								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.								

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 11 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T11S R63E S30 S29 ----- S31 S32</p> <p style="text-align: center;">2005</p> <p>Deposit the original stone alongside the stainless steel post.</p> <hr/> <p>S. 89°51'20" W., bet. secs. 30 and 31.</p> <p>Over rolling hills.</p>
39.080	<p>The 1/4 sec. cor. of secs. 30 and 31, monumented with a lava stone, 19x16x9 ins., firmly set in a mound of stone, 2 ft. base, 1 ft. high, mkd. 1/4 on N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T11S R63E S30 1/4 ----- S31</p> <p style="text-align: center;">2005</p> <p>Deposit the original stone alongside the stainless steel post.</p> <p>The corner is located on N. slope.</p> <hr/> <p>N. 88°35'40" W., beginning new measurement.</p> <p>Bottom of descent; continue over nearly level land.</p>
18.739	<p>Point for a witness point and intersection with the centerline of U.S. Highway No. 93, hereinafter described.</p>
39.411	<p>The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0°10'10" W., bet. secs. 29 and 30.</p> <p>Over rolling hills.</p>
8.00	<p>Spur, slopes W.</p>
39.609	<p>The 1/4 sec. cor. of secs. 29 and 30, monumented with an unmarked lava stone, 16x14x8 ins., firmly set in a mound of stone, 3 ft. diam., 1 ft. high.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 11 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T11S R63E 1/4 S30 S29</p> <p style="text-align: center;">2005</p> <p>Deposit the original stone alongside the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°16'30" E., beginning new measurement.</p>
29.802	<p>Point for the N-N 1/64 sec. cor. of secs. 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">N-N 1/64 S30 S29</p> <p style="text-align: center;">2005</p>
35.30	<p>Graveled road, 40 lks. wide, bears N. 60° E. and S. 60° W.</p>
39.736	<p>The cor. of secs. 19, 20, 29 and 30, monumented with an unmarked lava stone, 16x14x12 ins., firmly set in a mound of stone, 3 ft. diam., 1 ft. high.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T11S R63E S19 S20 S30 S29</p> <p style="text-align: center;">2005</p> <p>Deposit the original stone alongside the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 88°40'10" W., bet. secs. 19 and 30.</p> <p>Over rolling hills.</p>
38.492	<p>The 1/4 sec. cor. of secs. 19 and 30, monumented with an unmarked granite stone, 16x10x9 ins., firmly set in a mound of stone, 3 ft. diam., 1 ft. high.</p>

122

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 11 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T11S R63E S19 1/4 <u> </u> S30</p> <p style="text-align: center;">2005</p> <p>Deposit the original stone alongside the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 88°52'10" W., beginning new measurement.</p> <p>22.50 Gulch, drains S.</p> <p>30.733 Point for a witness point and intersection with the centerline of U.S. Highway No. 93, hereinafter described.</p> <p>40.089 The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p style="text-align: center;">METES-AND-BOUNDS SURVEY OF A PORTION OF U.S. HIGHWAY NO. 93, T. 11 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">MEMORANDUM</p> <p>The survey of lands for patent conveyance to Coyote Springs Investment, L.L.C., was executed in accordance with the described land in the document titled.</p> <p>The centerline of the right-of-way for U.S. Highway No. 93 was determined utilizing monuments set by the Nevada Department of Transportation and the description in State of Nevada right-of-way application Nev-061281. Some monuments were found to be not at their geometric position. In those instances, direct bearing and distance ties are reported from a point on the centerline to the Nevada Department of Transportation stations.</p> <p>Witness points were established at intersection with the centerline of the right-of-way and section lines.</p> <hr/> <p>From the witness point at intersection with the lines, bet. secs. 6 and 31, on the S. bdy. of the Tp., monumented with a PK nail and washer, flush with asphalt surface, with washer mkd. as described in the field notes of the dependent resurvey of the north boundary of T. 12 S., R. 63 E., executed concurrently under this same Group.</p> <p>N. 8°00'50" W., on the centerline of U.S. Highway No. 93, in sec. 31.</p> <p>38.006 Point on Tangent. Not monumented.</p>
--------	--

METES-AND-BOUNDS SURVEY OF A PORTION OF U.S. HIGHWAY NO. 93,
T. 11 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p>	<p>From this point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA A 346+48.06 POT DIST 75.09 bears N. 80°27'40" E., 1.138 chs. dist.</p> <p>From this same point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA A 346+48.06 POT DIST 74.82 bears S. 80°27'40" W., 1.134 chs. dist.</p> <p>81.150 Point for a witness point, at intersection with the line bet. secs. 30 and 31.</p> <p>Set a PK nail and washer flush with the asphalt surface, with washer mkd. WP S30 S31 HWY93.</p> <hr/> <p>N. 8°01'00" W., on the centerline of U.S. Highway No. 93, in sec. 30.</p> <p>14.017 Point on Tangent. Not monumented.</p> <p>From this point, a Nevada Department of Transportation highway station, monumented with a standard Nevada Department of Transportation wood post, 4x4 ins. square, bears N. 81°59'00" E., 3.035 chs. dist.</p> <p>From this same point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA A 384+20.99 POT DIST 75.00 bears S. 81°59'00" W., 1.136 chs. dist.</p> <p>81.075 Point of Curvature. Not monumented.</p> <p>From this point, a Nevada Department of Transportation highway station utilized to determine alignment only of the centerline of the right-of-way, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA A 428+46.84 PC DIST 74.92 bears N. 82°40'20" E., 1.135 chs. dist.</p> <p>From this same point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way, monumented with a standard Nevada Department of Transportation wood post, 4x4 ins. square, bears N. 82°40'20" E., 3.022 chs. dist.</p> <p>From this same point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way, monumented with a standard Nevada Department of Transportation wood post, 4x4 ins. square, bears S. 82°40'20" W., 3.034 chs. dist.</p> <p>Thence along the arc of a circular curve to the right, having a radius of 20,000.00 ft.; the cord of said arc bears N. 7°59'50" W., 0.204 chs. dist.</p>
---------------	---

METES-AND-BOUNDS SURVEY OF A PORTION OF U.S. HIGHWAY NO. 93,
T. 11 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p> <p>0.204</p>	<p>Point for a witness point, at intersection with the line bet. secs. 19 and 30.</p> <p>Set a PK nail and washer flush with the asphalt surface, with washer mkd. WP S19 S30 HWY93.</p> <p>From this point, a Nevada Department of Transportation highway station, monumented with a standard Nevada Department of Transportation wood post, 4x4 ins. square, bears N. 5°13'20" E., 14.781 chs. dist.</p> <p>From this same point, a Nevada Department of Transportation highway station, monumented with a standard Nevada Department of Transportation wood post, 4x4 ins. square, bears N. 18°17'50" W., 14.930 chs. dist.</p> <p>From this same point, a Nevada Department of Transportation highway station, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA 428+30.25 PT DIST 75.00 bears N. 11°04'10" W., 14.616 chs. dist.</p> <p>From this same point, a Nevada Department of Transportation highway station, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA 428+30.25 PT DIST 75.00 bears N. 2°08'30" W., 14.560 chs. dist.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The lands included in this survey are located in Lincoln County, Nevada, about 30 miles southeast of the community of Alamo, Nevada. Access is gained by way of U.S. Highway No. 93.</p> <p>Kane Springs Wash drains southwesterly through the township. Coyote Springs Valley runs northerly and southerly through the area surveyed. The average elevation of the area surveyed is approximately 2500 feet above sea level.</p> <p>No apparent mineral activity was noted in the area during this survey.</p> <hr/>
----------------------------	---

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS PROVIDED THROUGH PRE-TRANSFER AGREEMENT

Kenneth S. Burns	Field Technician (VTN, Inc.)
Kevin A. Campbell	Field Technician (VTN, Inc.)
Matthew R. Matecki	Field Technician (VTN, Inc.)
Jake A. Pavelka	Field Technician (VTN, Inc.)

126

CERTIFICATE OF SURVEY

We, David J. Passmore, Professional Land Surveyor (VTN, Inc.) and Craig L. Wanless, Cadastral Surveyor (BLM), HEREBY CERTIFY upon honor, that in pursuance of Special Instructions bearing date of the 1st day of February, 2005, We have dependently resurveyed a portion of the west boundary and a portion of the subdivisional lines, and executed a metes-and-bounds survey of a portion of U.S. Highway No. 93, Township 11 South, Range 63 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

September 26, 2006

(Date)

David J. Passmore

(Professional Land Surveyor)

November 28, 2006

(Date)

David D. Moran

/For Craig L. Wanless

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of the dependent resurvey of a portion of the west boundary and a portion of the subdivisional lines, and a metes-and-bounds survey of a portion of U.S. Highway No. 93, Township 11 South, Range 63 East, Mount Diablo Meridian, Nevada, executed by David J. Passmore, Professional Land Surveyor (VTN, Inc.) and Craig L. Wanless, Cadastral Surveyor (BLM), having been critically examined and found correct, are hereby approved.

November 28, 2006

(Date)

David D. Moran

(Chief Cadastral Surveyor, Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 11 S., R. 63 E., M.D.M., Nevada, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor, Nevada)~~