

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

A PORTION OF THE WEST BOUNDARY,
A PORTION OF THE SUBDIVISIONAL LINES
AND A PORTION OF THE SUBDIVISION-OF-SECTION LINES OF SECTIONS 6 AND 8,
THE SUBDIVISION OF SECTIONS 7, 16, 17 AND 18,
THE FURTHER SUBDIVISION OF SECTIONS 5, 6, 8 AND 9,
AND METES-AND-BOUNDS SURVEYS IN SECTIONS 6, 7 AND 18,
TOWNSHIP 12 NORTH, RANGE 29 EAST,
OF THE MOUNT DIABLO MERIDIAN,
IN THE STATE OF NEVADA

EXECUTED BY

Don R. Aschenbach, Cadastral Surveyor
Mark G. Petrosine, Surveying Technician

Under Special Instructions dated April 15, 2005,
and approved April 15, 2005,
which provided for the surveys included under Group No. 827,
and Assignment Instructions dated June 13, 2005.

Survey commenced June 13, 2005
Survey completed February 5, 2007

INDEX DIAGRAM

TOWNSHIP 12 NORTH, RANGE 29 EAST, MOUNT DIABLO MERIDIAN, NEVADA

5 18	6 17	5 19 17	4	3	2	1
3	7	17 8	9	10	11	12
2	14 18	13 17	8 16	5 15	14	13
11 19	9 20	7 21	22	23	24	
30	29	28	27	26	25	
31	32	33	34	35	36	

Dependent Resurvey of a Portion of the
 Subdivision-of-Section Lines of Section 6 pp. 20 - 21.

Dependent Resurvey of a Portion of the
 Subdivision-of-Section Lines of Section 8 pp. 21 - 24.

Subdivision of Section 7 pp. 24 - 35.

Subdivision of Section 16 pp. 36 - 42.

Subdivision of Section 17 pp. 43 - 54.

Subdivision of Section 18 pp. 55 - 66.

Further Subdivision of Section 5 pp. 66 - 67.

Further Subdivision of Section 6 pp. 67 - 71.

Further Subdivision of Section 8 pp. 72 - 82.

Further Subdivision of Section 9 pp. 83 - 85.

Metes-and-Bounds Section 6 p. 86.

Metes-and-Bounds Section 7 pp. 86 - 87.

Metes-and-Bounds Section 18 pp. 87 - 88.

TOWNSHIP 12 NORTH, RANGE 29 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The following field notes are those of the dependent resurvey of a portion of the west boundary, a portion of the subdivisional lines and a portion of the subdivision-of-section lines of sections 6 and 8, the subdivision of sections 7, 16, 17 and 18, the further subdivision of sections 5, 6, 8 and 9, and metes-and-bounds surveys in sections 6, 7 and 18, Township 12 North, Range 29 East, Mount Diablo Meridian, Nevada.

The south and west boundaries, portions of the north and east boundaries, a portion of the subdivisional lines and the meanders of Walker Lake were surveyed by U.S. Deputy Surveyors H.E. Franks and J.S. Mullen in 1904 under Contract No. 237. The west three miles of the north boundary were retraced and the east three miles of the north boundary were surveyed by U.S. Cadastral Engineer E. Voigt in 1920 under Group No. 66. Portions of the east and north boundaries and a portion of the subdivisional lines were dependently resurveyed and a portion of the east boundary and a portion of the subdivisional lines were surveyed by U.S. Cadastral Engineer C.S. Swanholm and U.S. Transitsmen R.F. Guinn and H. Westfall in 1936 under Group No. 181. Portions of the south and west boundaries, a portion of the subdivisional lines and meanders of Walker Lake were dependently resurveyed, and portions of the south boundary, Tracts 38, 39 and 40, and the thalweg of the Walker River were surveyed Cadastral Surveyor D.R. Bauer in 1973 under Group No. 497. The north one mile of the west boundary, the west two miles of the north boundary, and a portion of the subdivisional lines were dependently resurveyed and portions of the subdivision lines of sections 5, 6, 8 and 9 were surveyed by Cadastral Surveyor J.A. Mack in 1986-87 under Group No. 635. Portions of the subdivisional lines of fractional sections 22, 23 and 26 were dependently resurveyed and the subdivision of section 26 was surveyed by Cadastral Surveyor R.A. Pratt in 1989 under Group No. 670.

Before restoring the corners, the lines of the original surveys were retraced and a diligent search made for any evidence of the original corners and other calls of the original field note record.

Identified corners were accepted in their original positions, some were remonumented. Lost corners were reestablished at positions based on the record or by using the rules of proportionate measurement, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 827 dated April 15, 2005.

Measurements were made with Trimble 4700, 5700 and 5800 Global Positioning Satellite(GPS) receivers, utilizing Real Time Kinematic(RTK) and static methods and refer to the true meridian based on geodetic methods. The mean bearings of the lines and horizontal equivalents of ground distances only are entered in the field notes.

TOWNSHIP 12 NORTH, RANGE 29 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>The NAD 83 geographic position of the corner of sections 15, 16, 21 and 22, determined from Global Positioning System(GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service(OPUS), utilizing Continuously Operating Reference Stations(CORS): "DYER CORS ARP", "FALLON CORS ARP", "GABBS CORS ARP", "MINERET SUMMIT CORS ARP", and "UPSAL CORS ARP", in 2005 and carried forward by Real Time Kinematic(RTK) observations is as follows:</p> <p>Latitude: 38°53'43.703" N. Longitude: 118°44'12.370" W.</p> <p>The 1988 mean magnetic declination is 15°30' East, as shown on U.S.G.S. 7 1/2 minute quadrangle map, "Schurz, Nevada", provisional edition dated 1988.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY, T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of a Portion of the Survey Executed by H.E. Franks and J.S. Mullen in 1904, a Portion of the Dependent Resurvey Executed by D.R. Bauer in 1973 and a Portion of the Dependent Resurvey Executed by J.A. Mack in 1986-87</p> <hr/> <p>Beginning at the cor. of secs. 13, 18, 19 and 24, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the E. bdy. of T. 12 N., R. 28 E., executed under Group No. 497.</p> <p>Cor. is located 24 lks. N. of a barbwire fence, bears E. and W. N. 0°03'00" E., bet. secs. 13 and 18.</p> <p>Over nearly level land, covered with scattered sagebrush and grasses.</p> <p>0.40 Graded dirt road, 15 lks. wide, bears E. and W.</p> <p>20.004 Point for the S 1/16 sec. cor. of secs. 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S13 S18</p> <p style="text-align: center;">2005</p> <p>40.008 The 1/4 sec. cor. of secs. 13 and 18, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the E. bdy. of T. 12 N., R. 28 E., executed under Group No. 497.</p>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From this cor., a granite stone, of unknown origin, 16x7x5 ins., firmly set, projecting 10 ins. above the ground, no marks visible, bears S. 3° W., 0.61 chs. dist., with a wood post, 6x8 ins., firmly set, projecting 6 ft. above the ground, alongside, on the S. side. This stone was not noted or recognized in the 1973 dependent resurvey executed by D.R. Bauer and is not utilized in the course of this survey.</p>
	<hr/> <p>N. 0°01'10" E., beginning new measurement.</p>
	<p>Continue across nearly level land, covered with sagebrush and grasses.</p>
19.996	<p>Point for the N 1/16 sec. cor. of secs. 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S13 S18</p> <p style="text-align: center;">2005</p>
39.992	<p>From this cor., a wood post, 6x8 ins., firmly set, projecting 4 ft. above the ground, bears N. 58° E., 0.10 chs. dist.</p> <p>The cor. of secs. 7, 12, 13 and 18, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the E. bdy. of T. 12 N., R. 28 E., executed under Group No. 497.</p>
	<hr/> <p>N. 0°04'30" E., bet. secs. 7 and 12.</p> <p>Over nearly level land, covered with scattered sagebrush and grasses.</p>
19.849	<p>Point for the S 1/16 sec. cor. of secs. 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S12 S7</p> <p style="text-align: center;">2005</p>
39.698	<p>The 1/4 sec. cor. of secs. 7 and 12, monumented with the weathered remains of a wood post, 1x2 ins., 12 ins. long, firmly set, projecting 2 ins. above the ground, no marks visible, with a second wood post, 2x4 ins., 17 ins. long, loosely set, projecting 15 ins. above the ground, alongside, and is accepted as the best available evidence of the position of the original corner.</p>

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T12N 1/4 R28E R29E S12 S 7</p> <p style="text-align: center;">2005</p> <p>Deposit the wood post remains, and the second wood post, alongside the stainless steel post and below the surface of the ground.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°12'00" E., beginning new measurement.</p> <p>Continue across nearly level land, covered with scattered sagebrush and grasses.</p> <p>10.039 Point for the S-N 1/64 sec. cor. of secs. 7 and 12, identical with Angle Point No. 6, sec. 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S-N 1/64 S12 S 7</p> <p style="text-align: center;">2005</p> <p>20.078 Point for the N 1/16 sec. cor. of secs. 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S12 S 7</p> <p style="text-align: center;">2005</p> <p>From this cor., a weathered redwood post, 2x3x24 ins. long, with ground point, no marks visible, was found lying loose nearby, original position indeterminate, not utilized in the course of this survey.</p> <p>40.156 The cor. of secs. 1, 6, 7 and 12, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635.</p> <p>Raise a mound of stone around the aluminum post, 3 ft. base, to top.</p> <hr style="width: 20%; margin: 10px auto;"/>
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the 1/4 sec. cor. of secs. 1 and 6, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635.</p> <p>N.0°12'00"E., bet. secs. 1 and 6.</p> <p>0.90 Descend into river cut, bears NW. and SE.</p> <p>4.00 Right bank of the Walker River, bears NW. and SE., thence across river, course SE.</p> <p>9.995 True point for the S-N 1/64 sec. cor. of secs. 1 and 6, at proportionate dist., falls on the left bank of the Walker River where it is impractical to set a permanent monument.</p> <p>10.50 Leave river cut, bears NW. and SE.</p> <p>10.658 The witness S-N 1/64 sec. cor. of secs. 1 and 6, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of a Portion of the Survey Executed by H.E. Franks and J.S. Mullen in 1904, a Portion of the Dependent Resurvey Executed by D.R. Bauer in 1973, a Portion of the Dependent Resurvey Executed by J.A. Mack in 1986-87, and a Portion of the Dependent Resurvey Executed by R.A. Pratt in 1989</p> <hr/> <p>From the point for the cor. of secs. 15, 16, 21 and 22, determined at record bearing and distance from the 1/4 sec. cor. of secs. 15 and 22, there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. below the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center; margin-top: 20px;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T12N</td> <td style="padding: 0 5px;">R29E</td> </tr> <tr> <td style="padding: 0 5px; border-right: 1px solid black;">S16</td> <td style="padding: 0 5px;">S15</td> </tr> <tr> <td style="padding: 0 5px; border-right: 1px solid black;">S21</td> <td style="padding: 0 5px;">S22</td> </tr> </table> <p style="margin-top: 10px;">2005</p> </div>	T12N	R29E	S16	S15	S21	S22
T12N	R29E						
S16	S15						
S21	S22						

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	from which
	<p>A "mag" nail, 1 in. long, 1/4 in. diam., bears S. 23°03' W., 263.1 lks. dist., set in a drill hole, 1/4 in. diam., at the center of a chiseled X on a concrete pad, 12 ft. square, 1.1 lks. from N. edge and 2.9 lks. from E. edge.</p> <p>From this cor., the 1/4 sec. cor. of secs. 15 and 22, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 670, bears S. 89°51'00" E., 40.390 chs. dist., with a weathered wood post, 3x4 ins., projecting 12 ins. above the ground, alongside of the cor.</p> <p>From this same cor., a rebar, of unknown origin, 1/2 in. diam., set 2 ins. below the surface of the ground, no marks visible, bears N. 73°01' E., 0.194 chs. dist., not utilized in the course of this survey.</p> <p>N. 0°51'30" E., bet. secs. 15 and 16.</p> <p>Across open bladed field.</p>
39.25	Concrete lined ditch, 12 lks. wide, 3 ft. deep, bears E. and W.
39.70	Barbwire fence, bears E. and W.
	Continue across nearly level land, covered with sagebrush and grasses.
40.062	Point for the 1/4 sec. cor. of secs. 15 and 16, at proportionate dist., there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<p>T12N R29E 1/4 S16 S15 2005</p>
60.093	Point for the N 1/16 sec. cor. of secs. 15 and 16.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<p>N 1/16 S16 S15 2005</p>
61.20	Graded dirt road, 30 lks. wide, bears NW. and SE.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
80.124	<p>The cor. of secs. 9, 10, 15 and 16, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 16 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635, with the original wood post, 4 ins. square, firmly set, projecting 18 ins. above the ground with illegible scribe marks visible, alongside, N. of the cor.; a wood post, 2x4 ins., firmly set, projecting 22 ins. above the ground, alongside, E. of the cor.; an iron pipe, 2 ins. diam., no marks visible, lying loose nearby; and a wood post, 4 ins. square, firmly set, projecting 8 ins. above the ground, alongside, NW. of the cor.</p>
	<p>From the cor. of secs. 15, 16, 21 and 22. N. 89°56'30" W., bet. secs. 16 and 21. Across level bladed field.</p>
24.40	Graded dirt road, 15 lks. wide, bears N. and S.
39.724	<p>Point for the 1/4 sec. cor. of secs. 16 and 21, at proportionate dist., in bladed alfalfa field, there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. below the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T12N R29E S16 1/4 $\frac{\quad}{\quad}$ S21</p> <p>2005</p> </div>
79.10	Concrete lined irrigation ditch, 15 lks. wide, 3 ft. deep, drains S.
79.30	Graded dirt road, 15 lks. wide, bears N. and S.
79.448	<p>The cor. of secs. 16, 17, 20 and 21, monumented with the rusted remains of a concrete filled iron post, 2 1/2 ins. diam., set 7 ins. below the surface of the ground, with brass cap mkd. US INDIAN IRRIGATION SERVICE BM S16 S17 S20 S21, on the N. side of and butted against a railroad tie fence cor. post, with barbwire fences extending N., S. and W. No record was discovered for this monument and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T12N R29E S17 S16 S20 S21</p> <p>2006</p> </div>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Deposit rusted remains and brass cap alongside stainless steel post.</p> <p>From this cor., a rebar, of unknown origin, 1/2 in. diam., firmly set, projecting 5 ins. above the ground, bears N. 71°14' E., 0.499 chs. dist., not utilized in the course of this survey.</p>
	<p>N. 0°23'30" E., bet. secs. 16 and 17.</p> <p>Along W. side of a graded dirt road, 15 lks. wide, bears N. and S., and paralleling concrete lined ditch to the E.</p>
19.971	<p>Point for the S 1/16 sec. cor. of secs. 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S17 S16 2005</p>
39.942	<p>Cor. is located N. 73° W., 55 lks. dist., from intersection of concrete lined ditches, 15 lks. wide, extending N., E. and SSE. and at the projected intersection of fallen barbwire fences, extending N., E. and S.</p> <p>Point for the 1/4 sec. cor. of secs. 16 and 17, at proportionate dist., there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 2 ins. below the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T12N R29E 1/4 S17 S16 2005</p> <p>from which</p> <p style="padding-left: 40px;">A well casing, 6 ins. diam., projecting 2 ft. above the ground, bears S. 78°11' W., 84.6 lks. dist.</p> <p style="padding-left: 40px;">A steel fence cor. post, 6 ins. diam., set in concrete, projecting 6 ft. above the ground, bears N. 7° W., 3.2 lks. dist., from which steel gates bear E. and S. and a barbwire fence extending W.</p>
40.40	<p>Graded dirt road, 10 lks. wide, bears E. and W.</p>
50.05	<p>Dirt road, bears NW. and SE.</p>
52.50	<p>Dirt road, bears NW. and SE.</p>
59.913	<p>Point for the N 1/16 sec. cor. of secs. 16 and 17.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S17 S16</p> <p style="text-align: center;">2005</p>
79.884	<p>The cor. of secs. 8, 9, 16 and 17, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above ground, in a mound of stone, 6 ft. base, to top, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635.</p> <p>Cor. is located on the N. side of intersection of graded dirt roads, each 15 lks. wide, extending N., E., S., W. and NW., and 47 lks. W. of an irrigation ditch, 15 lks. wide, 3 ft. deep, drains S.</p>
	<p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>N. 89°55'20" W., bet. secs. 17 and 20.</p> <p>Over nearly level land covered with scattered sagebrush and grasses, and along N. side of barbwire fence.</p>
9.990	<p>Point for the E-E 1/64 sec. cor. of secs. 17 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S17 -E-E 1/64- S20</p> <p style="text-align: center;">2005</p>
10.03	<p>Barbwire fence, bears N. and S. for 20 lks. to a railroad tie fence cor. post, thence extending E.</p>
19.980	<p>Point for the E 1/16 sec. cor. of secs. 17 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S17 E 1/16 — S20</p> <p style="text-align: center;">2005</p>
29.970	<p>Point for the W-E 1/64 sec. cor. of secs. 17 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, 2 ft. diam., over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">S17 -W-E 1/64- S20</p> <p style="text-align: center;">2005</p>
39.960	<p>Point for the 1/4 sec. cor. of secs. 17 and 20, at proportionate dist., there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T12N R29E S17 1/4 $\frac{\quad}{\quad}$ S20</p> <p style="text-align: center;">2005</p> <p>Cor. falls on E. shoulder of graded dirt road, bears N. and S.</p>
40.70	<p>Powerline, extending N. and W.</p> <p>Continue along N. side of powerline.</p>
49.950	<p>Point for the E-W 1/64 sec. cor. of secs. 17 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S17 -E-W 1/64- S20</p> <p style="text-align: center;">2005</p>
59.940	<p>The W 1/16 sec. cor. of secs. 17 and 20, determined by person(s) unknown, monumented with a weathered redwood post, 2 1/2 ins. square, 28 ins. long, firmly set, projecting 1 in. above the ground, no marks visible and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">W 1/16 $\frac{\quad}{\quad}$ S17 S20</p> <p style="text-align: center;">2005</p> <p>Deposit the redwood post, with ground point, alongside the stainless steel post and below the surface of the ground.</p> <hr style="width: 20%; margin: 10px auto;"/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 89°54'40" W., beginning new measurement. Continue over nearly level land, covered with scattered sagebrush and grasses, and along N. side of powerline extending E. and W.
9.982	Point for the W-W 1/64 sec. cor. of secs. 17 and 20. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. S17 -W-W 1/64- S20 2005
19.964	The cor. of secs. 17, 18, 19 and 20, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 497. <hr/> N. 89°48'00" W., bet. secs. 18 and 19. Over nearly level land, covered with scattered sagebrush and grasses, and along N. side of powerline, extending E. and W.
9.993	Point for the E-E 1/64 sec. cor. of secs. 18 and 19. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. S18 -E-E 1/64- S19 2005
19.986	Point for the E 1/16 sec. cor. of secs. 18 and 19. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. E 1/16 $\frac{S18}{S19}$ 2005
29.979	Point for the W-E 1/64 sec. cor. of secs. 18 and 19. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">S18 -W-E 1/64- S19</p> <p style="text-align: center;">2005</p>
32.20	Descend into river cut, bears NW. and SE.
39.972	<p>Point for the 1/4 sec. cor. of secs. 18 and 19, at proportionate dist., there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T12N R29E S18 1/4 $\frac{\quad}{\quad}$ S19</p> <p style="text-align: center;">2005</p>
42.20	Left bank of the Walker River bears N. and S., thence across river, course S.
43.60	<p>Right bank of the Walker River, bears N. and S.</p> <p>Continue along N. side of powerline, extending E. and W., and along S. side of a graded dirt road, 15 lks. wide, parallels powerline.</p>
49.965	<p>Point for the E-W 1/64 sec. cor. of secs. 18 and 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S18 -E-W 1/64- S19</p> <p style="text-align: center;">2005</p> <p>From this cor., a rebar, 5/8 in. diam., firmly set, projecting 6 ins. above the ground, bears S. 31°51' E., 0.517 chs. dist., as shown on the parcel map created by Geosurveys in 1976, on file with the Nature Conservancy of Nevada. Established on a line diverging from the section line, not utilized in the course of this survey.</p>
54.80	Leave river cut, continue across nearly level ground, through scattered sagebrush and grasses.
59.958	<p>Point for the W 1/16 sec. cor. of secs. 18 and 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. below the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;"> $\begin{array}{r} S18 \\ W\ 1/16 \quad \frac{\quad}{S19} \\ \hline 2005 \end{array}$ </p>
69.516	<p>Point for Angle Point No. 1, sec. 18, established at midpoint bet. the cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., and the W 1/16 sec. cor. of secs. 18 and 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;"> $\begin{array}{r} T12N\ R29E \\ S\ \ 18 \\ AP\ \ 1 \\ \hline S19 \\ 2005 \end{array}$ </p>
78.40	<p>Abandoned irrigation ditch, 15 lks. wide, 1 ft. deep, drains S.</p>
79.00	<p>From this point, a powerpole bears South, 12 lks. dist., with powerlines extending E. and S.</p>
79.074	<p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 0°02'00" E., bet. secs. 17 and 18.</p> <p>Over nearly level land, covered with sagebrush and grasses.</p>
20.004	<p>Point for the S 1/16 sec. cor. of secs. 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;"> $\begin{array}{r} S1/16 \\ S18\ \ S17 \\ \hline 2005 \end{array}$ </p>
40.008	<p>The 1/4 sec. cor. of secs. 17 and 18, monumented with the rotted remains of a wood post, 3 ins. square, set 6 ins. below the surface of the ground and extending 12 ins. down and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">T12N R29E 1/4 S18 S17 2005</p> <hr/>
19.994	<p>N. 0°02'30" E., beginning new measurement.</p> <p>Continue over nearly level land, covered with scattered sagebrush and grasses.</p> <p>Point for the N 1/16 sec. cor. of secs. 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
39.988	<p style="text-align: center;">N 1/16 S18 S17 2005</p> <p>Cor. is located on the SE. side of a fence cor. post, with barbwire fences extending N. and E.</p> <p>From this cor., a rotted redwood post, of unknown origin, 3 ins. square, 24 ins. long, no marks visible, was found lying loose nearby, original position indeterminate, not utilized in the course of this survey.</p> <p>Continue along barbwire fence.</p> <p>The cor. of secs. 7, 8, 17 and 18, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635, with a mound of stone, 1 ft. base, 1 ft. high, W. of the cor.</p> <p>Cor. is located on the SE. side of a fence cor., with barbwire fences extending E. and S.</p>
10.004	<hr/> <p>N. 89°47'30" W., bet. secs. 7 and 18.</p> <p>Over nearly level land, covered with scattered sagebrush and grasses.</p> <p>Point for the E-E 1/64 sec. cor. of secs. 7 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">S 7 -E-E 1/64- S18 2005</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	From this cor., a rotted redwood post, of unknown origin, 3 ins. square, 24 ins. long, no marks visible, was found lying loose nearby, original position indeterminate, not utilized in the course of this survey.
20.008	Point for the E 1/16 sec. cor. of secs. 7 and 18. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;"> $E \frac{1}{16} \frac{S \ 7}{S18}$ 2005 </div>
30.012	Point for the W-E 1/64 sec. cor. of secs. 7 and 18. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;"> $\begin{array}{c} S \ 7 \\ -W-E \ 1/64- \\ S18 \end{array}$ 2005 </div>
31.75	Descend into river cut, bears NE. and SW.
32.00	Left bank of the Walker River, bears NE. and SW., thence across river, course SW.
40.016	True point for the 1/4 sec. cor. of secs. 7 and 18, at proportionate dist., there is no remaining evidence of the original witness cor., falls in river where it is impractical to set a permanent monument.
45.50	Right bank of the Walker River bears NE. and S., continue through scattered cottonwoods, willows and tamarisk.
45.60	Leave river cut, bears NE. and S., continue across nearly level land, covered with scattered sagebrush and grasses.
46.552	Point selected for the witness 1/4 sec. cor. of secs. 7 and 18. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;"> $\begin{array}{c} WC \\ T12N \ R29E \\ S \ 7 \\ 1/4 \longrightarrow \\ S18 \end{array}$ 2005 </div>
50.020	Point for the E-W 1/64 sec. cor. of secs. 7 and 18.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p>	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 7 -E-W 1/64- S18</p> <p style="text-align: center;">2005</p>
<p>60.024</p>	<p>Point for the W 1/16 sec. cor. of secs. 7 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">W 1/16 $\frac{S 7}{S18}$</p> <p style="text-align: center;">2005</p>
<p>60.40</p>	<p>Cor. is located on E. bank of abandoned irrigation ditch, 15 lks. wide, 4 ft. deep, drains S.</p> <p>Dirt road, 10 lks. wide, parallels ditch.</p>
<p>69.568</p>	<p>Angle Point No. 5, sec. 18, identical with Angle Point No. 1, sec. 7, monumented with a weathered redwood post, of unknown origin, 2x2 1/2 ins., 21 ins. long, firmly set, projecting 14 ins. above the ground, with illegible scribe marks visible on E. face and is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T12N R29E S 7 AP 1 ----- AP 5 S 18</p> <p style="text-align: center;">2005</p> <p>Deposit the redwood post alongside the stainless steel post and below the surface of the ground.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89°49'50" W., beginning new measurement.</p> <p>Continue through scattered sagebrush and grasses.</p>
<p>9.493</p>	<p>The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., hereinbefore described.</p> <hr style="width: 80%; margin: auto;"/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the N 1/16 sec. cor. of secs. 7 and 8, monumented with an aluminum post, 2 1/2 ins. diam., projecting 4 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635.</p> <p>From this cor., a fence cor., bears S. 8° E., 0.29 chs. dist., with barbwire fences extending N., E. and S.</p> <p>N. 0°00'30" E., bet. secs. 7 and 8.</p> <p>Along barbwire fence through willows and scattered cottonwood trees.</p>						
8.90	<p>Left bank of the Walker River, bears E. and NW., thence across river, course E.</p>						
10.001	<p>True point for the N-N 1/64 sec. cor. of secs. 7 and 8, at proportionate distance, falls in river where it is impractical to set a permanent monument.</p>						
10.10	<p>Right bank of the Walker River, bears E. and NW.</p> <p>Continue along barbwire fence and ascend.</p>						
12.591	<p>The witness N-N 1/64 sec. cor. of secs. 7 and 8, monumented with an aluminum post, 2 1/2 ins. diam., projecting 5 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°00'40" W., beginning new measurement.</p> <p>Continue through scattered cottonwoods.</p>						
7.10	<p>Concrete lined irrigation ditch, 15 lks. wide, 3 1/2 ft. deep, bears E. and W.</p>						
7.414	<p>Point for the cor. of secs. 5, 6, 7 and 8, at proportionate dist., on N. embankment of concrete lined irrigation ditch, there is no remaining evidence of the original cor. or the monument set by J.A. Mack in 1986-87.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2">T12N R29E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 6</td> <td style="padding: 0 5px;">S 5</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 7</td> <td style="padding: 0 5px;">S 8</td> </tr> </table> <p>2005</p> </div> <hr style="width: 20%; margin: 10px auto;"/> <p>From the W 1/16 sec. cor. of secs. 5 and 8, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635, with a mound of stone, 1 ft. base, 1 ft. high, N. of the cor.</p>	T12N R29E		S 6	S 5	S 7	S 8
T12N R29E							
S 6	S 5						
S 7	S 8						

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	Cor. is located on the E. side of a graded dirt road, 15 lks. wide, bears N. and S.
	N. 89°55'40" W., bet. secs. 5 and 8.
4.10	From this point, a 90° bend in a concrete lined irrigation ditch, 15 lks. wide, bears South, 25 lks. dist., drains S.
	Continue along the N. embankment of a concrete lined irrigation ditch.
10.082	Point for the W-W 1/64 sec. cor. of secs. 5 and 8, at proportionate distance, there is no evidence remaining of the monument set by J.A. Mack in 1986-87.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.
	<p style="text-align: center;">S 5 -W-W 1/64- S 8 2005</p>
	Cor. is located 23 lks. N. of concrete lined irrigation ditch, 15 lks. wide, 3 ft. deep, bears E. and W.
20.164	The cor. of secs. 5, 6, 7 and 8.
	N. 89°45'40" W., bet. secs. 6 and 7.
0.45	Concrete lined irrigation ditch, 15 lks. wide, 3 ft. deep, bears N. and S.
0.75	Graded dirt road, 15 lks. wide, bears N. and S.
	Continue across nearly level land, covered with sagebrush and grasses.
3.00	Descend into river cut, bears N. and S.
3.50	Left bank of the Walker River, bears N. and S., thence across river, course S.
4.00	Right bank of the Walker River, bears N. and S., continue across rolling land, through scattered cottonwoods, willows and tamarisk.
9.932	The E-E 1/64 sec. cor. of secs. 6 and 7, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635, with a mound of stone, 2 ft. base, 1 ft. high, N. of the cor.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS											
	<p>From the W 1/16 sec. cor. of secs. 6 and 7, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635, with a mound of stone, 2 1/2 ft. base, 1/2 ft. high, N. of the cor.</p> <p>S. 89°55'50" W., bet. secs. 6 and 7.</p> <p>Across rolling land, covered with sagebrush and grasses.</p>										
9.525	<p>Point for Angle Point No. 1, sec. 6, established at midpoint bet. the cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp. and the W 1/16 sec. cor. of secs. 6 and 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td>T12N</td> <td>R29E</td> </tr> <tr> <td>S</td> <td>6</td> </tr> <tr> <td>AP</td> <td>1</td> </tr> <tr> <td colspan="2"><hr/></td> </tr> <tr> <td>S</td> <td>7</td> </tr> </table> <p>2006</p> </div>	T12N	R29E	S	6	AP	1	<hr/>		S	7
T12N	R29E										
S	6										
AP	1										
<hr/>											
S	7										
10.053	<p>From this cor., a weathered redwood post, 2x3 ins., firmly set, projecting 6 ins. above the ground, no marks visible, bears S. 82° E., 0.23 chs. dist., not utilized in the course of this survey.</p> <p>The W-W-1/64 sec. cor. of secs. 6 and 7, monumented with an aluminum post, 2 1/2 ins. diam., projecting 4 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635.</p> <hr/> <p>S. 89°55'50" W., beginning new measurement.</p>										
8.997	<p>The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>Across nearly level land, covered with sagebrush and grasses.</p> <p>N. 0°06'20" E., bet. secs. 5 and 6.</p>										
20.010	<p>The S 1/16 sec. cor. of secs. 5 and 6, monumented with an aluminum post, 2 1/2 ins. diam., projecting 6 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635.</p> <p>Raise a mound of stone around the aluminum post, 3 ft. base, to top.</p> <hr/>										

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISION-OF-SECTION LINES OF SECTION 6,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Reestablishment of a Portion of the Subdivision of Section 6, Executed by J.A. Mack in 1986-87</p> <hr/>
	<p>From the E 1/16 sec. cor. of secs. 6 and 7, monumented with an aluminum post, 2 1/2 ins. diam., projecting 5 ins. above the ground with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635, with a mound of stone, 2 1/2 ft. base, 1 ft. high, N. of the cor.</p>
	<p>N. 0°03'30" W., on the N-S center line of the SE1/4 of sec. 6.</p>
	<p>Across rolling land, through scattered cottonwoods, willows and tamarisk.</p>
9.90	<p>Descend into river cut, bears NW. and SE.</p>
19.00	<p>Right bank of the Walker River, bears NW. and SE., thence across river course SE.</p>
19.972	<p>True point for the SE 1/16 sec. cor. of sec. 6, at intersection with the E-W center line of the SE1/4, falls in the Walker River where it is impractical to set a permanent monument.</p>
20.50	<p>Left bank of the Walker River, bears SE. and NW.</p>
20.60	<p>Leave river cut, bears NW. and SE., continue across nearly level land, covered with scattered sagebrush and grasses.</p>
21.995	<p>Point selected for the witness SE 1/16 sec. cor. of sec. 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">WC SE 1/16 S 6 2006 ↓</p>
22.436	<p>Record distance for the 1986-87 witness SE 1/16 sec. cor. of sec. 6, there is no evidence remaining of the monument set in 1986-87.</p>
39.946	<p>The C-E 1/16 sec. cor. of sec. 6, monumented with an aluminum post, 2 1/2 ins. diam., 12 ins. below the surface of the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635.</p> <hr/> <p>From the C-E-SE 1/64 sec. cor. of sec. 6, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635.</p>

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISION-OF-SECTION LINES OF SECTION 6,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>N. 89°55'00" W., on the E-W center line of the SE1/4, sec. 6. Across nearly level land, covered with sagebrush and grasses.</p> <p>8.00 Descend into river cut, bears NW. and SE.</p> <p>9.20 Left bank of the Walker River, bears NW. and SE., thence across river, course SE.</p> <p>9.964 True point for the SE 1/16 sec. cor. of sec. 6.</p> <p>14.40 Right bank of the Walker River, bears NW. and SE.</p> <p>14.90 Leave river cut, bears NW. and SE., continue across nearly level land, covered with scattered sagebrush and grasses.</p> <p>19.910 The C-W-SE 1/64 sec. cor. of sec. 6, monumented with an aluminum post, 2 1/2 ins. diam., 7 ins. below the surface of a graded dirt road, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635.</p> <p>Cor. is located at the intersection of graded dirt roads, 15 lks. wide, extending N., E. and S.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISION-OF-SECTION LINES OF SECTION 8, T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of a Portion of the Subdivision of Section 8, Executed by J.A. Mack in 1986-87</p> <hr/> <p>From the center 1/4 sec. cor. of sec. 8, determined at record distances from the 1986-87 reference monuments:</p> <p style="padding-left: 40px;">An aluminum post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, bears N. 50° E., 69.7 lks. dist., with aluminum cap, mkd. RM T12N R29E 46 FT C 1/4 S8 1986 and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">An aluminum post, 2 1/2 ins. diam., firmly set, flush with the surface of the ground, bears S. 45 3/4° E., 81.8 lks. dist., with aluminum cap, mkd. XRM T12N R29E 54 FT C 1/4 S8 1986 and an arrow pointing to the cor.</p> <p>At the corner point</p> <p>Set a copper coated steel stake, 1/2 in. diam., 24 ins. long, 12 ins. below the surface of the ground, with brass cap, 1 1/4 ins. diam., mkd.</p> <p style="text-align: center;">BLM T12N R29E C 1/4 S 8</p> <p style="text-align: center;">2006</p>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE
 SUBDIVISION-OF-SECTION LINES OF SECTION 8,
 T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From this cor., a rebar, 1/2 in. diam., set 3 ins. below the surface of the ground, with damaged plastic cap, the marks RLS 38 remaining, bears S. 65° E., 0.010 chs. dist., no record was recovered for this monument and is not utilized in the course of this survey.</p> <p>N. 0°07'20" E., on the N-S center line of sec. 8.</p> <p>Along the E. side of a graded dirt road, 35 lks. wide, bears N. and S.</p>
10.009	<p>Point for the C-S-N 1/64 sec. cor. of sec. 8, at proportionate dist., there is no remaining evidence of the cor. determined in the 1986-87 dependent resurvey.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;"> $\begin{array}{c} C \\ S-N \ 1/64 \ \ S \ 8 \\ C \end{array}$ 2005 </p>
20.018	<p>The C-N 1/16 sec. cor. of sec. 8, monumented with the sheared bottom end of an aluminum post, 2 1/2 ins. diam., still in an upright position, 20 ins. below the surface of the ground.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;"> $\begin{array}{c} C \\ N \ 1/16 \ \ S \ 8 \\ C \end{array}$ 2005 </p> <p>Deposit the remains of the aluminum post alongside the stainless steel post and below the surface of the ground.</p>
	<p>From the C-E 1/16 sec. cor. of sec. 8, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635.</p> <p>From this cor., a railroad tie fence cor. post, bears N. 72° W., 12 lks. dist., with barbwire fences extending N., E. and W.</p> <p>N. 0°10'00" E., on the N-S center line of the NE1/4 of sec. 8.</p> <p>Across level bladed field and along E. side of barbwire fence.</p>

DEPENDENT RESURVEY OF A PORTION OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 8,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.031	True point for the NE 1/16 sec. cor. of sec. 8, at intersection with E-W center line of the NE1/4, there is no remaining evidence of the position of the cor. determined by J.A. Mack in the 1986-87 dependent resurvey. The aluminum monument set in the 1986-87 dependent resurvey was found lying loose nearby. Cor. falls under a barbwire fence, with fences extending E. and W. and at the intersection of irrigation ditches, where it is impractical to set a permanent monument.
27.60	Leave bladed fields.
28.20	Barbwire fence, parallels a dirt road.
28.70	Graded dirt road, 25 lks. wide, bears NW. and SE.
29.00	Barbwire fence, parallels a dirt road.
31.748	Intersect Southern Pacific Railroad right-of-way, bears N. 59°21.3' W. and S. 59°21.3' E.
33.00	Irrigation ditch, 10 lks. wide, drains SE.
33.506	Centerline Southern Pacific Railroad tracks, parallels right-of-way.
35.264	Intersect Southern Pacific Railroad right-of-way, bears N. 59°21.3' W. and S. 59°21.3' E.
40.055	<p>The E 1/16 sec. cor. of secs. 5 and 8, determined at record distances from the 1986-87 reference monuments:</p> <p>An aluminum post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, bears S. 49 3/4° W., 21.2 lks. dist., with aluminum cap, mkd. RM E 1/16 14 FT S8 1986 and an arrow pointing to the cor.</p> <p>An aluminum post, 2 1/2 ins. diam., set 12 ins. below the surface of the ground, and bent 14 ins. below cap, bears N. 50 1/2° W., 21.2 lks. dist. to upright portion of base, with aluminum cap, mkd. RM S5 14 FT E1/16 1986 and an arrow pointing to the cor.</p> <p>At the corner point</p> <p>Set a PK nail, 1/4 in. diam., 1 in. long, in a 1/4 in. hole drilled in concrete lining of irrigation ditch.</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 51°39' E., 56.0 lks. dist., with brass cap, mkd. RM E 1/16 S5 37.0 FT TO COR 2006 and an arrow pointing to the cor.</p> <hr/>

DEPENDENT RESURVEY OF A PORTION OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 8,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	From the C-E-NE 1/64 sec. cor. of sec. 8, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635.
	N. 89°51'50" W., on the E-W center line of the NE1/4 of sec. 8.
1.00	Cor. of barbwire fences, with fences extending S. and W.
	Across level bladed field, along barbwire fence and irrigation ditch, drains E.
9.678	Point selected for the witness NE 1/16 sec. cor. of sec. 8, Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	WC ←—NE 1/16 S 8 2006
10.072	True point for the NE 1/16 sec. cor. of sec. 8.
10.30	Cor. of barbwire fences, with fences extending E., S. and W.
19.90	Cor. of barbwire fences, with fences extending N. and E.
20.131	The C-W-NE 1/64 sec. cor. of sec. 8, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed by J.A. Mack under Group No. 635. Cor. is located 15 lks. S. of irrigation ditch, 15 lks. wide, 3 ft. deep, drains E.
SUBDIVISION OF SECTION 7, T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA	
	From the true point for the 1/4 sec. cor. of secs. 7 and 18. N. 0°13'30" E., on the N-S center line of sec. 7 and across the Walker River.
1.10	Right bank of the Walker River bears NE. and SW.
3.20	Leave river cut, bears NW. and SE., continue across nearly level land, covered with scattered sagebrush and grasses.
19.930	Point for the C-S 1/16 sec. cor. of sec. 7. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

SUBDIVISION OF SECTION 7,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">C S 1/16 S 7 C</p> <p style="text-align: center;">2005</p> <p>From this cor., a redwood post, of unknown origin, 2 ins. square, firmly set, projecting 2 ins. above the ground, no marks visible, bears S. 84°45' W., 0.108 chs. dist., established on a line diverging from the N-S center line, not utilized in the course of this survey.</p>
39.860	<p>Point for the center 1/4 sec. cor. of sec. 7, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T12N R29E C 1/4 S 7</p> <p style="text-align: center;">2005</p> <p>From this cor., a redwood post, of unknown origin, 1 1/2 ins. square, firmly set, projecting 4 ins. above the ground, with illegible scribe marks visible on N. side, bears N. 89°55' W., 0.268 chs. dist., established on a line diverging from the N-S center line, not utilized in the course of this survey.</p>
59.948	<p>Point for the C-N 1/16 sec. cor. of sec. 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">C N 1/16 S 7 C</p> <p style="text-align: center;">2005</p> <p>From this cor., the remains of a redwood post, of unknown origin, no marks visible, was found lying loose nearby, original position indeterminate, not utilized in the course of this survey.</p>
80.036	<p>The 1/4 sec. cor. of secs. 6 and 7, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635, with the original redwood post, 2 ins. square, firmly set, projecting 4 ins. above the ground, with the marks 1/4 on the S. face, and 6 on the E. face, E. of the cor.; and with a railroad tie, 6x8 ins., firmly set, projecting 5 ft. above ground, N. of the cor.</p>
	<p>From the 1/4 sec. cor. of secs. 7 and 8, monumented with an aluminum post, 2 1/2 ins. diam., set flush with the surface of the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635.</p>

SUBDIVISION OF SECTION 7,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Cor. is located on E. side of fence post, 4x6 ins., with barbwire fence extending E., 12 lks. dist. to steel gate and W. for 3 lks. dist. to a fence cor. with barbwire fences extending N. and S.</p> <p>S. 89°58'00" W., on the E-W center line of sec. 7.</p> <p>Across rolling land, covered with sagebrush and scattered cottonwood trees.</p>
9.969	<p>Point for the C-E-E 1/64 sec. cor. of sec. 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> $\begin{array}{c} \text{E-E } 1/64 \\ \text{C} \text{-----} \text{C} \\ \text{S } 7 \end{array}$ <p style="text-align: center;">2005</p>
18.30	<p>Left bank of the Walker River, bears NW. and SE., thence across river, course SE.</p>
19.938	<p>True point for the C-E 1/16 sec. cor. of sec. 7, falls in river where it is impractical to set a permanent monument.</p>
21.70	<p>Right bank of the Walker River, bears NW. and SE.</p>
21.90	<p>Leave river cut, bears NW. and SE., continue across nearly level land, covered with scattered sagebrush and grasses.</p>
22.212	<p>Point selected for the witness C-E 1/16 sec. cor. of sec. 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> $\begin{array}{c} \text{WC} \\ \text{E } 1/16 \\ \text{C} \text{-----} \text{C} \rightarrow \\ \text{S } 7 \end{array}$ <p style="text-align: center;">2005</p>
29.907	<p>Point for the C-W-E 1/64 sec. cor. of sec. 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> $\begin{array}{c} \text{W-E } 1/64 \\ \text{C} \text{-----} \text{C} \\ \text{S } 7 \end{array}$ <p style="text-align: center;">2005</p> <p>From this cor., a redwood post, of unknown origin, 2 ins. square, firmly set, projecting 2 ins. above the ground, no marks visible, bears S. 9°42' E., 0.131 chs. dist., not utilized in the course of this survey.</p>

SUBDIVISION OF SECTION 7,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.876	The center 1/4 sec. cor. of sec. 7.
49.909	<p>Point for the C-E-W 1/64 sec. cor. of sec. 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> $\begin{array}{c} \text{E-W } 1/64 \\ \text{C} \text{-----} \text{C} \\ \text{S } 7 \end{array}$ <p style="text-align: center;">2005</p> <p>From this cor., a redwood post, of unknown origin, 2x3 ins., firmly set, projecting 10 ins. above the ground, no marks visible, bears S. 77°56' W., 0.146 chs. dist., not utilized in the course of this survey.</p>
54.45	Abandoned irrigation ditch, 15 lks. wide, 3 ft. deep, drains SSW.
54.80	Dirt road, 10 lks. wide, parallels ditch.
59.942	<p>Point for the C-W 1/16 sec. cor. of sec. 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> $\begin{array}{c} \text{W } 1/16 \\ \text{C} \text{-----} \text{C} \\ \text{S } 7 \end{array}$ <p style="text-align: center;">2005</p>
69.481	<p>Point for Angle Point No. 3, sec. 7, established at midpoint bet. the 1/4 sec. cor. of secs. 7 and 12, on the W. bdy. of the Tp. and the C-W 1/16 sec. cor. of sec. 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> $\begin{array}{c} \text{T12N R29E} \\ \text{AP} 3 \\ \text{C} \text{-----} \text{C} \\ \text{S} 7 \end{array}$ <p style="text-align: center;">2005</p> <p>From this cor., the remains of a redwood post, of unknown origin, 2x3x24 ins. long, the marks 24 visible, was found lying loose nearby, original position indeterminate, not utilized in the course of this survey.</p>
79.020	The 1/4 sec. cor. of secs. 7 and 12, on the W. bdy. of the Tp.

SUBDIVISION OF SECTION 7,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the true point for the C-E 1/16 sec. cor. of sec. 7.</p> <p>N. 0°07'00" E., on the N-S center line of the NE1/4 of sec. 7, and across the Walker River.</p>
6.90	Right bank of the Walker River, bears NE. and SW., leave river.
7.00	Leave river cut, bears NE. and SW., continue across nearly level land, covered with sagebrush and grasses.
20.050	<p>Point for the NE 1/16 sec. cor. of sec. 7, at intersection with the E-W center line of the NE1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S 7</p> <p style="text-align: center;">2005</p> <p>From this cor., the remains of a redwood post, of unknown origin, 2x3x22 ins. long, with ground point, with illegible scribe marks visible, was found lying loose nearby, original position indeterminate, not utilized in the course of this survey.</p>
40.100	<p>The E 1/16 sec. cor. of secs. 6 and 7.</p> <hr/> <p>From the N 1/16 sec. cor. of secs. 7 and 8.</p> <p>N. 89°55'20" W., on the E-W center line of the NE1/4 of sec. 7.</p> <p>Across nearly level land, covered with sagebrush and grasses.</p>
9.951	<p>Point for the C-E-NE 1/64 sec. cor. of sec. 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 7 C-E-NE 1/64</p> <p style="text-align: center;">2005</p> <p>From this cor., a weathered redwood post, of unknown origin, 2x3x22 ins. long, with ground point, illegible scribe marks visible, was found lying loose nearby, original position indeterminate, not utilized in the course of this survey.</p>
19.902	The NE 1/16 sec. cor. of sec. 7.
29.852	<p>Point for the C-W-NE 1/64 sec. cor. of sec. 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

SUBDIVISION OF SECTION 7,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	S 7 C-W-NE 1/64 2005
39.802	<p>The C-N 1/16 sec. cor. of sec. 7.</p> <hr/> <p>From the C-E-NE 1/64 sec. cor. of sec. 7.</p> <p>N. 0°03'10" E., on the N-S center line of the NE1/4NE1/4 of sec. 7.</p> <p>Across nearly level land, covered with scattered sagebrush and grasses.</p>
20.033	<p>The E-E 1/64 sec. cor. of secs. 6 and 7.</p> <hr/> <p>From the C-E-E 1/64 sec. cor. of sec. 7.</p> <p>N. 0°04'10" E., on the N-S center line of the SE1/4NE1/4 of sec. 7.</p> <p>Across nearly level land, covered with sagebrush and scattered cottonwood trees.</p>
1.30	Descend into river cut, bears NE. and SW.
1.40	Left bank of the Walker River, bears NE. and SW., thence across river, course SW.
6.50	Right bank of the Walker River, bears NE. and SW., continue through willows, scattered cottonwoods and tamarisk.
16.70	Leave river cut, bears NE. and SW., continue across nearly level land, covered with scattered sagebrush and grasses.
20.031	<p>The C-E-NE 1/64 sec. cor. of sec. 7.</p> <hr/> <p>From the C-W-E 1/64 sec. cor. of sec. 7.</p> <p>N. 0°10'20" E., on the N-S center line of the SW1/4NE1/4 of sec. 7.</p> <p>Across nearly level land, covered with sagebrush and grasses.</p>
20.069	<p>The C-W-NE 1/64 sec. cor. of sec. 7.</p> <hr/> <p>N. 0°10'00" E., on the N-S center line of the NW1/4NE1/4 of sec. 7.</p> <p>Across nearly level land, covered with scattered sagebrush and grasses.</p>

SUBDIVISION OF SECTION 7,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.066	<p>The W-E 1/64 sec. cor. of secs. 6 and 7, monumented with an aluminum post, 2 1/2 ins., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635, with a mound of stone, 2 ft. base, 1 ft. high, N. of the cor.</p>
	<hr/> <p>From the E 1/16 sec. cor. of secs. 7 and 18. N. 0°07'30" E., on the N-S center line of the SE1/4 of sec. 7. Across nearly level land, covered with sagebrush and grasses.</p>
5.70	<p>Descend into river cut, bears NE. and SW., continue across river cut, through willows and scattered cottonwood trees.</p>
7.05	<p>Left bank of the Walker River, bears NE. and SW., thence across river, course W.</p>
14.75	<p>Right bank of the Walker River, bears E. and SW.</p>
14.90	<p>Leave river cut, bears NE. and SW., continue across nearly level land, covered with scattered sagebrush and grasses.</p>
19.966	<p>Point for the SE 1/16 sec. cor. of sec. 7, at intersection with the E-W center line of the SE1/4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">SE 1/16 S 7 2005</p>
	<p>From this cor., a weathered redwood post, of unknown origin, 2x3x24 ins. long, no marks visible, was found lying loose nearby, original position indeterminate, not utilized in the course of this survey.</p>
39.945	<p>The true point for the C-E 1/16 sec. cor. of sec. 7.</p>
	<hr/> <p>From the S 1/16 sec. cor. of secs. 7 and 8, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 11 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635. Cor. is located 4 lks. N. of a barbwire fence extending E. and W. N. 89°53'30" W., on the E-W center line of the SE1/4 of sec. 7. Across oxbow cutoff bend of the Walker River through scattered cottonwood trees, willows and tamarisk and along barbwire fence.</p>
5.30	<p>Left bank of the Walker River, bears N. and S., thence across river, course S.</p>

SUBDIVISION OF SECTION 7,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
8.00	Right bank of the Walker River, bears N. and S.
8.10	Leave river cut, bears N. and S., continue across nearly level land, covered with scattered sagebrush and grasses.
9.995	Point for the C-E-SE 1/64 sec. cor. of sec. 7. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. S 7 C-E-SE 1/64 2005 From this cor., a weathered redwood post, 2x4x24 ins. long, with the marks 2, 0, 19 and 9 visible, was found lying loose nearby, original position indeterminate, not utilized in the course of this survey.
19.990	The SE 1/16 sec. cor. of sec. 7.
29.977	Point for the C-W-SE 1/64 sec. cor. of sec. 7. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. S 7 C-W-SE 1/64 2005
39.964	The C-S 1/16 sec. cor. of sec. 7. <hr/> From the C-E-SE 1/64 sec. cor. of sec. 7. N. 0°03'00" E., on the N-S center line of the NE1/4SE1/4 of sec. 7. Across nearly level land, covered with sagebrush and grasses.
6.30	Descend into river cut, bears NW. and SE., continue through scattered cottonwood trees, willows and tamarisk.
10.00	Right bank of the Walker River, bears NW. and SE., thence across river, course SE.
14.50	Left bank of the Walker River, bears NW. and SE.
17.25	Leave river cut, bears NW. and SE., continue across nearly level land, covered with scattered sagebrush and grasses.
20.002	The C-E-E 1/64 sec. cor. of sec. 7. <hr/>

SUBDIVISION OF SECTION 7,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the E-E 1/64 sec. cor. of secs. 7 and 18.</p> <p>N. 0°05'40" E., on the N-S center line of the SE1/4SE1/4 of sec. 7.</p> <p>Across nearly level land, covered with sagebrush and grasses.</p>
6.30	Descend into river cut, bears NW. and SE., continue through scattered cottonwoods, willows and tamarisk.
11.80	Left bank of the Walker River, bears NE. and SW., thence across river, course W.
14.75	Right bank of the Walker River, bears NE. and W.
16.70	Leave river cut, bears NE. and SW., continue across nearly level land, covered with scattered sagebrush and grasses.
19.982	The C-E-SE 1/64 sec. cor. of sec. 7.
	<hr/>
	<p>From the W-E 1/64 sec. cor. of secs. 7 and 18.</p> <p>N. 0°09'40" E., on the N-S center line of the SW1/4SE1/4 of sec. 7.</p> <p>Across nearly level land, covered with sagebrush and grasses.</p>
3.60	Descend into river cut, bears NE. and SW., continue through scattered cottonwoods, willows and tamarisk.
7.45	Left bank of the Walker River, bears E. and SW., thence across river, course SW.
12.00	Right bank of the Walker River, bears NE. and SW.
12.10	Leave river cut, bears NE. and SW., continue across nearly level land, covered with scattered sagebrush and grasses.
19.948	The C-W-SE 1/64 sec. cor. of sec. 7.
	<hr/>
	<p>N. 0°09'40" E., on the N-S center line of the NW1/4SE1/4 of sec. 7.</p> <p>Across nearly level land, covered with sagebrush and grasses.</p>
19.954	The C-W-E 1/64 sec. cor. of sec. 7.
	<hr/>
	<p>From the W 1/16 sec. cor. of secs. 7 and 18.</p> <p>N. 0°08'20" E., on the N-S center line of the SW1/4 of sec. 7.</p> <p>Across nearly level land, covered with sagebrush and grasses, and along E. side abandoned irrigation ditch, 15 lks. wide, 4 ft. deep, drains S.</p>

SUBDIVISION OF SECTION 7,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
7.70	Leave irrigation ditch, curves NE. and bears S., and continue across nearly level land, covered with sagebrush and grasses.
19.886	Point for the SW 1/16 sec. cor. of sec. 7, at intersection with the E-W center line of the SW1/4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, 2 ft. diam., with brass cap mkd. SW 1/16 S 7 2006
39.774	The C-W 1/16 sec. cor. of sec. 7. <hr/> From the C-S 1/16 sec. cor. of sec. 7. N. 89°55'10" W., on the E-W center line of the SW1/4 of sec. 7. Across nearly level land, covered with sagebrush and grasses.
10.019	Point for the C-E-SW 1/64 sec. cor. of sec. 7. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. S 7 C-E-SW 1/64 2005
15.60	Abandoned irrigation ditch, 15 lks. wide, 3 ft. deep, drains S.
16.30	Dirt road, 10 lks. wide, parallels ditch.
20.038	The SW 1/16 sec. cor. of sec. 7.
29.567	Point for Angle Point No. 2, sec. 7, established at midpoint bet. the S 1/16 sec. cor. of secs. 7 and 12, on the W. bdy. of the Tp. and the SW 1/16 sec. cor. of sec. 7. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T12N R29E AP 2 S ——— S 7 2005 From this cor., a weathered redwood post, 2x3x30 ins. long, with illegible scribe marks visible, was found lying loose nearby, original position indeterminate, not utilized in the course of this survey.

SUBDIVISION OF SECTION 7,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.096	<p>The S 1/16 sec. cor. of secs. 7 and 12, on the W. bdy. of the Tp.</p> <hr/> <p>From the C-E-SW 1/64 sec. cor. of sec. 7.</p> <p>N. 0°10'50" E., on the N-S center line of the NE1/4SW1/4 of sec. 7.</p> <p>Across nearly level land, covered with sagebrush and grasses.</p>
19.909	<p>The C-E-W 1/64 sec. cor. of sec. 7.</p> <hr/> <p>From the E-W 1/64 sec. cor. of secs. 7 and 18.</p> <p>N. 0°10'50" E., on the N-S center line of the SE1/4SW1/4 of sec. 7.</p> <p>Across nearly level land, covered with sagebrush and grasses.</p>
19.908	<p>The C-E-SW 1/64 sec. cor. of sec. 7.</p> <hr/> <p>From the C-W 1/16 sec. cor. of sec. 7.</p> <p>N. 0°09'40" E., on the N-S center line of the NW1/4 of sec. 7.</p> <p>Across nearly level land, covered with sagebrush and grasses.</p>
20.082	<p>Point for the NW 1/16 sec. cor. of sec. 7, at intersection with the E-W center line of the NW1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S 7</p> <p style="text-align: center;">2005</p> <p>From this cor., a weathered redwood post, of unknown origin, 2x3x30 ins. long, no marks visible, was found lying loose nearby, original position indeterminate, not utilized in the course of this survey.</p>
40.164	<p>The W 1/16 sec. cor. of secs. 6 and 7.</p> <hr/> <p>From the C-N 1/16 sec. cor. of sec. 7.</p> <p>S. 89°56'50" W., on the E-W center line of the NW1/4 of sec. 7.</p> <p>Across nearly level land, covered with sagebrush and grasses.</p>
9.50	<p>Abandoned irrigation ditch, 15 lks. wide, 5 ft. deep, drains SW.</p>

SUBDIVISION OF SECTION 7,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
9.90	Dirt road, 10 lks. wide, parallels ditch.
10.044	<p>Point for the C-E-NW 1/64 sec. cor. of sec. 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S 7 C-E-NW 1/64 2005</p>
20.088	The NW 1/16 sec. cor. of sec. 7.
29.620	<p>Point for Angle Point No. 4, sec. 7, established at midpoint bet. the N 1/16 sec. cor. of secs. 7 and 12, on the W. bdy. of the Tp. and the NW 1/16 sec. cor. of sec. 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T12N R29E AP 4 N ——— N 7 S</p> <p style="text-align: center;">2005</p> <p>From this cor., a weathered redwood post, 2x3x30 ins. long, no marks visible, was found lying loose nearby, original position indeterminate, not utilized in the course of this survey.</p>
39.152	<p>The N 1/16 sec. cor. of secs. 7 and 12, on the W. bdy. of the Tp.</p> <hr/> <p>From the C-E-NW 1/64 sec. cor. of sec. 7.</p> <p>N. 0°11'40" E., on the N-S center line of the NE1/4NW1/4 of sec. 7.</p> <p>Across nearly level land, covered with sagebrush and grasses.</p>
20.085	<p>The E-W 1/64 sec. cor. of secs. 6 and 7, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635, with a mound of stone, 2 1/2 ft. base, 1 ft. high, N. of the cor..</p> <hr/> <p>From the C-E-W 1/64 sec. cor. of sec. 7.</p> <p>N. 0°11'30" E., on the N-S center line of the SE1/4NW1/4 of sec. 7.</p>

SUBDIVISION OF SECTION 7,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Across nearly level land, covered with sagebrush and grasses.</p>
18.40	<p>Abandoned irrigation ditch, 15 lks. wide, drains SW.</p>
19.70	<p>Dirt road, 10 lks. wide, parallels ditch.</p>
20.085	<p>The C-E-NW 1/64 sec. cor. of sec. 7.</p> <hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 16, T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 16 and 21.</p> <p>N. 0°37'50" E., on the N-S center line of sec. 16.</p> <p>Across level alfalfa field.</p>
19.70	<p>Concrete lined irrigation ditch, 10 lks. wide, 3 ft. deep, course E.</p>
39.30	<p>Concrete lined irrigation ditch, 10 lks. wide, 3 ft. deep, course E.</p>
39.55	<p>Graded dirt road, 15 lks. wide, parallels ditch.</p>
39.75	<p>Powerline and barbwire fence, parallels ditch.</p> <p>Enter scattered cottonwood trees.</p>
40.003	<p>Point for the center 1/4 sec. cor. of sec. 16, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. below the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T12N R29E C 1/4 S16</p> <p style="text-align: center;">2005</p> <p>Cor. is located in a dirt road, 10 lks. wide, bears E. and W.</p> <p>Continue across nearly level land, covered with sagebrush and grasses, and scattered cottonwood trees.</p>
42.00	<p>Leave cottonwood trees.</p>
60.003	<p>Point for the C-N 1/16 sec. cor. of sec. 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">C N 1/16 S16 C</p> <p style="text-align: center;">2005</p>

SUBDIVISION OF SECTION 16,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
80.003	<p>The 1/4 sec. cor. of secs. 9 and 16, monumented with an aluminum post, 2 1/2 ins. diam., projecting 8 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 15 and 16.</p> <p>S. 89°58'30" W., on the E-W center line of sec. 16.</p> <p>Across nearly level land, covered with sagebrush and grasses.</p>
19.940	<p>Point for the C-E 1/16 sec. cor. of sec. 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \text{E } 1/16 \\ \text{C} \text{-----} \text{C} \\ \text{S16} \end{array}$ <p>2005</p> </div> <p>Cor. is located 83 lks. N. of concrete lined ditch, 12 lks. wide, 3 ft. deep, bears E. and W. and 33 lks. N. of a barbwire fence, parallels ditch.</p>
28.20	<p>Graded dirt road, 20 lks. wide, bears NE. and W., continue along the dirt road through scattered cottonwood trees.</p>
39.880	<p>The center 1/4 sec. cor. of sec. 16.</p>
49.852	<p>Point for the C-E-W 1/64 sec. cor. of sec. 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \text{E-W } 1/64 \\ \text{C} \text{-----} \text{C} \\ \text{S16} \end{array}$ <p>2005</p> </div> <p>Cor. is located 67 lks. N. of concrete lined ditch, 12 lks. wide, 3 ft. deep, bears E. and W.; 40 lks. N. of a graded dirt road, 20 lks. wide, parallels ditch; 18 lks. N. of a barbwire fence, parallels ditch; and 33 lks. S. of a graded dirt road, 10 lks. wide, bears E. and W.</p>
50.25	<p>Intersection of graded dirt roads, 15 lks. wide, extending E., SW. and NW.</p> <p>Continue across nearly level land, covered with sagebrush and grasses, through scattered cottonwood trees.</p>
59.824	<p>Point for the C-W 1/16 sec. cor. of sec. 16.</p>

SUBDIVISION OF SECTION 16,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> $\begin{array}{c} W\ 1/16 \\ C\ \hline S16 \\ C \end{array}$ <p style="text-align: center;">2005</p> <p>Cor. is located 63 lks. N. of concrete lined ditch, 12 lks. wide, 3 ft. deep, bears E. and W.; 35 lks. N. of a graded dirt road, 20 lks. wide, parallels ditch; and 17 lks. N. of a barbwire fence, also parallels ditch.</p> <p>Leave scattered cottonwood trees, continue across nearly level land, covered with sagebrush and grasses.</p>
69.796	<p>Point for the C-W-W 1/64 sec. cor. of sec. 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> $\begin{array}{c} W-W\ 1/16 \\ C\ \hline S16 \\ C \end{array}$ <p style="text-align: center;">2005</p> <p>Cor. is located 58 lks. N. of concrete lined ditch, 12 lks. wide, 3 ft. deep, bears E. and W.; 30 lks. N. of a graded dirt road, 20 lks. wide, parallels ditch; and 10 lks. N. of a barbwire fence, parallels ditch.</p>
78.42	<p>Cor. of barbwire fences, with fences extending W. and S. for 6 lks. thence E., continue along barbwire fence.</p>
79.10	<p>Irrigation ditch, 12 lks. wide, drains S.</p>
79.65	<p>Graded dirt road, 15 lks. wide, bears N. and S.</p>
79.768	<p>The 1/4 sec. cor. of secs. 16 and 17.</p> <hr/> <p>From the C-E 1/16 sec. cor. of sec. 16.</p> <p>N. 0°44'30" E., on the N-S center line of the NE1/4 of sec. 16.</p> <p>Across nearly level land, covered with sagebrush and grasses.</p>
7.55	<p>Graded dirt road, 20 lks. wide, bears NE. and SW.</p>
20.015	<p>Point for the NE 1/16 sec. cor. of sec. 16, at intersection with the E-W center line of the NE1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

SUBDIVISION OF SECTION 16,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	NE 1/16 S16 2005
34.00	Graded dirt road, 30 lks. wide, bears NW. and SE.
40.030	The E 1/16 sec. cor. of secs. 9 and 16, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635, with a wood post, 4 ins square, firmly set, projecting 12 ins. above the ground, N. of the cor.
	From the N 1/16 sec. cor. of secs. 15 and 16. S. 89°56'10" W., on the E-W center line of the NE1/4 of sec. 16.
8.20	Graded dirt road, 20 lks. wide, bears NE. and SW.
9.990	Point for the C-E-NE 1/16 sec. cor. of sec. 16. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	S16 C-E-NE 1/64 2005
19.980	The NE 1/16 sec. cor. of sec. 16.
29.969	Point for the C-W-NE 1/64 sec. cor. of sec. 16. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	S16 C-W-NE 1/64 2005
	From this cor., a weathered redwood post, 2 ins. square, 28 ins. long, with ground point, no marks visible, was found lying loose nearby, original position indeterminate, not utilized in the course of this survey.
39.958	The C-N 1/16 sec. cor. of sec. 16.
	From the C-E-NE 1/64 sec. cor. of sec. 16. N. 0°48'10" E., on the N-S center line of the NE1/4NE1/4 of sec. 16.

SUBDIVISION OF SECTION 16,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Across nearly level land, covered with sagebrush and grasses.</p>
7.40	<p>Graded dirt road, 30 lks. wide, bears NW. and SE.</p>
20.020	<p>The E-E 1/64 sec. cor. of secs. 9 and 16, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635, with a wood post, 4 ins. square, firmly set, projecting 12 ins. above the ground, N. of the cor.</p> <hr/> <p>From the C-W-NE 1/64 sec. cor. of sec. 16.</p> <p>N. 0°40'10" E., on the N-S center line of the NW1/4NE1/4 of sec. 16.</p> <p>Across nearly level land, covered with sagebrush and grasses.</p>
20.004	<p>The W-E 1/64 sec. cor. of secs. 9 and 16, monumented with the sheared bottom end of an aluminum post, 2 1/2 ins. diam., still in an upright position, 12 ins. below the surface of a graded dirt road, 30 lks. wide, bears NW. and SE.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. below the surface of the graded dirt road, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 9 -W-E 1/64- S16</p> <p style="text-align: center;">2005</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, in a mound of stone, 3 ft. base, to top, over a plastic-encased magnet, for a reference monument, bears N. 52°37' E., 76.4 lks. dist., with brass cap, mkd. RM-W-E 1/64-50.4 FT TO COR S9 2005 and an arrow pointing to the cor.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, in a mound of stone, 3 ft. base, to top, over a plastic-encased magnet, for a reference monument, bears S. 25°06' E., 75.8 lks. dist., with brass cap, mkd. RM-W-E 1/64-50 FT TO COR S16 2005 and an arrow pointing to the cor.</p> <p>Deposit aluminum post remains alongside the stainless steel post and below the brass cap.</p> <hr/>

SUBDIVISION OF SECTION 16,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the C-W 1/16 sec. cor. of sec. 16.</p> <p>N. 0°31'50" E., on the N-S center line of the NW1/4 of sec. 16.</p> <p>Across nearly level land, covered with sagebrush and grasses.</p>
19.986	<p>Point for the NW 1/16 sec. cor. of sec. 16, at intersection with the E-W center line of the NW1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S16 2005</p>
39.949	<p>From this cor., the S. end of a barbwire fence, with fence extending N., bears N. 89° E., 0.90 chs. dist.</p> <p>The W 1/16 sec. cor. of secs. 9 and 16, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635.</p> <p>Cor. is located at cor. of barbwire fences, with fences extending N. and W., and S. 88° W., 90 lks. dist., from the N. end of a barbwire fence, extending S., and on the N. side of a dirt road, 10 lks. wide, bears NE. and W.</p> <hr/>
9.989	<p>From the C-N 1/16 sec. cor. of sec. 16.</p> <p>S. 89°56'00" W., on the E-W center line of the NW1/4 of sec. 16.</p> <p>Across nearly level land, covered with sagebrush and grasses.</p> <p>Point for the C-E-NW 1/64 sec. cor. of sec. 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S16 C-E-NW 1/64 2005</p>
15.85	<p>Graded dirt road, 20 lks. wide, bears NE. and SW.</p>
19.978	<p>The NW 1/16 sec. cor. of sec. 16.</p>
29.973	<p>Point for the C-W-NW 1/64 sec. cor. of sec. 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

SUBDIVISION OF SECTION 16,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	S16 C-W-NW 1/64 2005
	Cor. is located on the N. bank of an abandoned irrigation ditch, drains ESE.
	Continue along abandoned irrigation ditch.
39.35	Irrigation ditch, 12 lks. wide, 3 ft. deep, drains S.
39.60	Graded dirt road, 15 lks. wide, bears N. and S.
39.968	The N 1/16 sec. cor. of secs. 16 and 17.
	From the C-E-NW 1/64 sec. cor. of sec. 16.
	N. 0°32'50" E., on the N-S center line of the NE1/4NW1/4 of sec. 16.
	Across nearly level land, covered with sagebrush and grasses.
19.992	The E-W 1/64 sec. cor. of secs. 9 and 16, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635.
	From the C-E-W 1/64 sec. cor. of sec. 16.
	N. 0°34'50" E., on the N-S center line of the SE1/4NW1/4 of sec. 16.
	Across nearly level land, covered with sagebrush and grasses.
0.30	Graded dirt road, 20 lks. wide, bears E. and W.
19.993	The C-E-NW 1/64 sec. cor. of sec. 16.
	N. 0°27'40" E., on the N-S center line of the SW1/4NW1/4 of sec. 16.
	Across nearly level land, covered with sagebrush and grasses, and along W. side of a fallen barbwire fence.
19.978	The C-W-NW 1/64 sec. cor. of sec. 16.
	N. 0°29'10" E., on the N-S center line of the NW1/4NW1/4 of sec. 16.
	Across nearly level land, covered with sagebrush and grasses.

SUBDIVISION OF SECTION 16,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
19.991	<p>The W-W 1/64 sec. cor. of secs. 9 and 16, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635.</p> <p>Cor. is located under a barbwire fence, with fences extending E. and W., and on the N. side of a dirt road, 10 lks. wide, parallels fence.</p> <hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 17, T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 17 and 20.</p> <p>N. 0°13'30" E., on the N-S center line of sec. 17.</p> <p>Along the E. shoulder of a graded dirt road.</p>
19.989	<p>Point for the C-S 1/16 sec. cor. of sec. 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, in a collar of stone, 2 ft. diam., over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} C \\ S\ 1/16\ \ S17 \\ C \end{array}$ <p>2005</p> </div> <p>Cor. is located on the E. shoulder of a graded dirt road, 40 lks. wide, bears N. and S.</p>
34.85	<p>Graded dirt road 10 lks. wide, bears NE. from a graded dirt road, 40 lks. wide.</p>
39.978	<p>Point for the center 1/4 sec. cor. of sec. 17, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, in a collar of stone, 2 1/2 ft. diam., with brass cap mkd.</p> <div style="text-align: center;"> <p>T12N R29E C 1/4 S17</p> <p>2005</p> </div> <p>Cor. is located on the E. shoulder of a graded dirt road, 40 lks. wide, bears N. and S. and N. 60° W., 16 lks. dist. from a railroad tie fence cor. post, 6x8 ins., with barbwire fences extending N. and E.</p> <p>Continue along E. side of a graded dirt road, and along W. side of fence.</p>

SUBDIVISION OF SECTION 17,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
59.959	<p>Point for the C-N 1/16 sec. cor. of sec. 17.</p> <p>Set a copper coated steel rod, 1/2 in. diam., 24 ins. long, 8 ins. below the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} C \\ N\ 1/16\ \ S17 \\ C \end{array}$ <p>2005</p> </div> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, over a plastic-encased magnet, for a reference monument, bears S. 45°12' W., 66.1 lks. dist., with brass cap, mkd. RM CN 1/16 43.6 FT TO COR S17 2005 and an arrow pointing to the cor.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, in a collar of stone, 2 ft. diam., over a plastic-encased magnet, for a reference monument, bears N. 45°18' W., 63.8 lks. dist., with brass cap, mkd. RM CN 1/16 42.1 FT TO COR S17 2005 and an arrow pointing to the cor.</p> <p>Cor. is located on the E. edge of a graded dirt road, and N. 60° W., 27 lks. dist., from a railroad tie fence cor. post, 7x9 ins., with barbwire fences extending E. and S.</p>
79.940	<p>The 1/4 sec. cor. of secs. 8 and 17, perpetuated by person(s) unknown, monumented with a rebar, 1/2 in. diam., firmly set 3 ins. below the surface of a graded dirt road, 40 lks. wide, bears N. and S. and 25 lks. from E. edge, no marks visible and is accepted as a careful and faithful perpetuation of the position of the cor.</p> <p>from which the 1986 reference monuments</p> <p>An aluminum post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, bears S. 57° E., 47.0 lks. dist., with aluminum cap, mkd. RM 1/4 31 FT S17 1986 and an arrow pointing to the cor.</p> <p>An aluminum post, 2 1/2 ins. diam., firmly set, projecting 3 above the ground, bears N. 59 1/4° W., 59.1 lks. dist., with aluminum cap, mkd. RM 1/4 39 FT S8 1986 and an arrow pointing to the cor.</p> <p>and a new bearing object</p> <p>The marks BX0, 1/4 in. in height, bears S. 52°22' W., 34.9 lks. dist. stamped on the top bolt of a fire hydrant with the marks 1999 on the W. side.</p>

SUBDIVISION OF SECTION 17,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From the 1/4 sec. cor. of secs. 16 and 17.</p> <p>N. 89°52'20" W., on the E-W center line of sec. 17.</p> <p>Along powerline extending E. and W., along barbwire fence parallels powerline, and along the S. side of a graded dirt road, 10 lks. wide, parallels powerline.</p>
9.990	<p>Point for the C-E-E 1/64 sec. cor. of sec. 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \text{E-E } 1/64 \\ \text{C} \text{-----} \text{C} \\ \text{S } 17 \end{array}$ <p>2005</p> </div> <p>Cor. is located on the S. side of barbwire fence.</p>
19.980	<p>The C-E 1/16 sec. cor. of sec. 17, monumented with a weathered redwood post, of unknown origin, 3 ins. square, 30 ins. long, firmly set, projecting 19 ins. above the ground, with illegible scribe marks visible, 2 lks. S. of a wood fence cor. post, 7x8 ins., with barbwire fences extending E. and S. and is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \text{E } 1/16 \\ \text{C} \text{-----} \text{C} \\ \text{S } 17 \end{array}$ <p>2005</p> </div> <p>Deposit the redwood post alongside the stainless steel post and below the surface of the ground.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°52'20" W., beginning new measurement.</p> <p>Leave E-W barbwire fence.</p>
10.046	<p>Point for the C-W-E 1/64 sec. cor. of sec. 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \text{W-E } 1/64 \\ \text{C} \text{-----} \text{C} \\ \text{S } 17 \end{array}$ <p>2005</p> </div> <p>Cor. is located on the S. side of a dirt road, 10 lks. wide, bears E. and curves SW.</p>

SUBDIVISION OF SECTION 17,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
10.50	Dirt road, bears E. and SW. Continue through scattered sagebrush and grasses.
20.092	The center 1/4 sec. cor. of sec. 17.
20.35	Graded dirt road, 40 lks. wide, bears N. and S.
20.75	Powerline, extending N. and S.
30.111	Point for the C-E-W 1/64 sec. cor. of sec. 17. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. $\begin{array}{c} \text{E-W } 1/64 \\ \text{C} \text{-----} \text{C} \\ \text{S } 17 \end{array}$ <p style="text-align: center;">2005</p>
40.130	Point for the C-W 1/16 sec. cor. of sec. 17. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. $\begin{array}{c} \text{W } 1/16 \\ \text{C} \text{-----} \text{C} \\ \text{S } 17 \end{array}$ <p style="text-align: center;">2005</p>
50.149	Point for the C-W-W 1/64 sec. cor. of sec. 17. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. $\begin{array}{c} \text{W-W } 1/64 \\ \text{C} \text{-----} \text{C} \\ \text{S } 17 \end{array}$ <p style="text-align: center;">2005</p>
60.168	The 1/4 sec. cor. of secs. 17 and 18. <hr/> From the C-E 1/16 sec. cor. of sec. 17. N. 0°13'20" E., on the N-S center line of the NE1/4 of sec. 17. Across nearly level land, covered with scattered sagebrush and grasses.
19.85	Graded dirt road, 10 lks. wide, bears E. and W.
19.977	Point for the NE 1/16 sec. cor. of sec. 17, at intersection with the E-W center line of the NE1/4.

SUBDIVISION OF SECTION 17,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S17</p> <p style="text-align: center;">2005</p>
28.80	Graded dirt road, 20 lks. wide, bears N. 50° W. and S. 50° E.
39.957	<p>The E 1/16 sec. cor. of secs. 8 and 17, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635.</p> <hr/> <p>From the N 1/16 sec. cor. of secs. 16 and 17.</p> <p>N. 89°51'20" W., on the E-W center line of the NE1/4 of sec. 17.</p> <p>Across nearly level land, covered with scattered sagebrush and grasses, and along the S. side of a graded dirt road, 10 lks. wide, bears W.</p>
9.05	Graded dirt road, 20 lks. wide, bears NW. and SE.
10.019	<p>Point for the C-E-NE 1/64 sec. cor. of sec. 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S17 C-E-NE 1/64 2005</p>
20.038	The NE 1/16 sec. cor. of sec. 17.
30.083	<p>Point for the C-W-NE 1/64 sec. cor. of sec. 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S17 C-W-NE 1/64 2005</p> <p>From this cor., a weathered redwood post, 2 ins. square, 20 ins. long, no marks visible, was found lying loose nearby, original position indeterminate, not utilized in the course of this survey.</p>
40.128	The C-N 1/16 sec. cor. of sec. 17.

SUBDIVISION OF SECTION 17,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the C-E-NE 1/64 sec. cor. of sec. 17.</p> <p>N. 0°18'00" E., on the N-S center line of the NE1/4NE1/4 of sec. 17.</p> <p>Across nearly level land, covered with scattered sagebrush and grasses.</p>
0.15	Graded dirt road, 10 lks. wide, bears W. and E. for 75 lks. to a graded dirt road, 20 lks. wide, bears N. 50° W. and S. 50° E.
0.75	Graded dirt road, 20 lks. wide, bears N. 50° W. and S. 50° E.
19.976	The E-E 1/64 sec. cor. of secs. 8 and 17, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635.
<hr/>	
	<p>From the C-E-E 1/64 sec. cor. of sec. 17.</p> <p>N. 0°18'20" E., on the N-S center line of the SE1/4NE1/4 of sec. 17.</p> <p>Across nearly level land, covered with scattered sagebrush and grasses.</p>
0.05	Barbwire fence, bears E. and W.
0.30	Graded dirt road, 10 lks. wide, parallels barbwire fence.
19.974	The C-E-NE 1/64 sec. cor. of sec. 17.
<hr/>	
	<p>From the C-W-E 1/64 sec. cor. of sec. 17.</p> <p>N. 0°13'20" E., on the N-S center line of the SW1/4NE1/4 of sec. 17.</p> <p>Across nearly level land, covered with scattered sagebrush and grasses.</p>
19.979	The C-W-NE 1/64 sec. cor. of sec. 17.
<hr/>	
	<p>N. 0°14'10" E., on the N-S center line of the NW1/4NE1/4 of sec. 17.</p>
17.20	Graded dirt road, 20 lks. wide, bears NW. and SE.
19.979	The W-E 1/64 sec. cor. of secs. 8 and 17, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635.
<hr/>	
	<p>From the E 1/16 sec. cor. of secs. 17 and 20.</p> <p>N. 0°23'20" E., on the N-S center line of the SE1/4 of sec. 17.</p>

SUBDIVISION OF SECTION 17,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
19.82	Barbwire fence, bears E. and W. for 17 lks., thence N.
19.980	Point for the SE 1/16 sec. cor. of sec. 17, at intersection with the E-W center line of the SE1/4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. SE 1/16 S 17 2005 From this cor., a railroad tie fence cor. post, 6x7 ins., bears S. 45° W., 0.22 chs. dist., with barbwire fences extending N. and E. A weathered redwood post, 2 ins. square, 33 ins. long, ground to a point, with illegible scribe marks visible, was found lying loose on the N. side. Continue along E. side of barbwire fence.
39.958	The C-E 1/16 sec. cor. of sec. 17. <hr/>
9.990	From the S 1/16 sec. cor. of secs. 16 and 17. N. 89°53'40" W., on the E-W center line of the SE1/4 of sec. 17. Point for the C-E-SE 1/64 sec. cor. of sec. 17. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. S17 C-E-SE 1/64 2005 From this cor., a railroad tie fence cor. post, 7x8 ins., bears S. 32° W., 0.08 chs. dist., with barbwire fences extending S. and W. A weathered redwood post, 2 ins. square, 33 ins. long, ground to a point, with illegible scribe marks visible, was found lying loose on the SW. side. Continue along barbwire fence.
19.980	The SE 1/16 sec. cor. of sec. 17.
20.14	Barbwire fence, bears N. and S. for 16 lks. to fence cor. post thence E.
29.999	Point for C-W-SE 1/64 sec. cor. of sec. 17. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

SUBDIVISION OF SECTION 17,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	S17 C-W-SE 1/64 2005
40.018	<p>The C-S 1/16 sec. cor. of sec. 17.</p> <hr/> <p>From the C-E-SE 1/64 sec. cor. of sec. 17.</p> <p>N. 0°23'20" E., on the N-S center line of the NE1/4SE1/4 of sec. 17.</p> <p>Across nearly level land, covered with scattered sagebrush and grasses.</p>
19.975	<p>The C-E-E 1/64 sec. cor. of sec. 17.</p> <hr/> <p>From the E-E 1/64 sec. cor. of secs. 17 and 20.</p> <p>N. 0°23'20" E., on the N-S center line of the SE1/4SE1/4 of sec. 17.</p> <p>Across nearly level land, covered with scattered sagebrush and grasses.</p>
19.976	<p>The C-E-SE 1/64 sec. cor. of sec. 17.</p> <hr/> <p>From the W-E 1/64 sec. cor. of secs. 17 and 20.</p> <p>N. 0°18'20" E., on the N-S center line of the SW1/4SE1/4 of sec. 17.</p> <p>Across nearly level land, covered with scattered sagebrush and grasses.</p>
19.984	<p>The C-W-SE 1/64 sec. cor. of sec. 17.</p> <hr/> <p>N. 0°18'20" E., on the N-S center line of the NW1/4SE1/4 of sec. 17.</p> <p>Across nearly level land, covered with scattered sagebrush and grasses.</p>
19.983	<p>The C-W-E 1/64 sec. cor. of sec. 17.</p> <hr/> <p>From the W 1/16 sec. cor. of secs. 17 and 20.</p> <p>N. 0°08'20" E., on the N-S center line of the SW1/4 of sec. 17.</p>
19.998	<p>Point for the SW 1/16 sec. cor. of sec. 17, at intersection with the E-W center line of the SW1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

SUBDIVISION OF SECTION 17,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	SW 1/16 S17
	2005
39.994	The C-W 1/16 sec. cor. of sec. 17.
	From the C-S 1/16 sec. cor. of sec. 17.
	N. 89°53'40" W., on the E-W center line of the SW1/4 of sec. 17.
0.25	Graded dirt road, 40 lks. wide, N. and S.
0.70	Powerline, extending N. and S.
	Continue across nearly level land, covered with scattered sagebrush and grasses.
10.004	Point for the C-E-SW 1/64 sec. cor. of sec. 17.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	S17 C-E-SW 1/64
	2005
20.008	The SW 1/16 sec. cor. of sec. 17.
30.008	Point for the C-W-SW 1/64 sec. cor. of sec. 17.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	S17 C-W-SW 1/64
	2005
	From this cor., a weathered redwood post, 2x3x31 ins. long, no marks visible, was found lying loose nearby, original position indeterminate, not utilized in the course of this survey.
40.008	The S 1/16 sec. cor. of secs. 17 and 18.
	From the C-E-SW 1/64 sec. cor. of sec. 17.
	N. 0°10'50" E., on the N-S center line of the NE1/4SW1/4 of sec. 17.
	Across nearly level land, covered with scattered sagebrush and grasses.
19.992	The C-E-W 1/64 sec. cor. of sec. 17.

SUBDIVISION OF SECTION 17,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
19.994	<p>From the E-W 1/64 sec. cor. of secs. 17 and 20.</p> <p>N. 0°10'50" E., on the N-S center line of the SE1/4SW1/4 of sec. 17.</p> <p>Across nearly level land, covered with scattered sagebrush and grasses.</p> <p>The C-E-SW 1/64 sec. cor. of sec. 17.</p>
20.001	<p>From the W-W 1/64 sec. cor. of secs. 17 and 20.</p> <p>N. 0°05'10" E., on the N-S center line of the SW1/4SW1/4 of sec. 17.</p> <p>Across nearly level land, covered with scattered sagebrush and grasses.</p> <p>The C-W-SW 1/64 sec. cor. of sec. 17.</p>
20.000	<p>N. 0°05'10" E., on the N-S center line of the NW1/4SW1/4 of sec. 17.</p> <p>Across nearly level land, covered with scattered sagebrush and grasses.</p> <p>The C-W-W 1/64 sec. cor. of sec. 17.</p>
19.988	<p>From the C-W 1/16 sec. cor. of sec. 17.</p> <p>N. 0°08'40" E., on the N-S center line of the NW1/4 of sec. 17.</p> <p>Across nearly level land, covered with scattered sagebrush and grasses.</p> <p>Point for the NW 1/16 sec. cor. of sec. 17, at intersection with the E-W center line of the NW1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S17</p> <p style="text-align: center;">2005</p>
39.972	<p>The W 1/16 sec. cor. of secs. 8 and 17, monumented with a railroad spike, set flush with the surface, from which the 1986-87 reference monuments</p> <p>An aluminum post, 2 1/2 ins. diam., firmly set, projecting 11 ins. above the ground, bears N. 33°27' E., 37.9 lks. dist., with aluminum cap, mkd. RM 25 FT W 1/16 S8 1986 and an arrow pointing to the cor. (Record: N. 34 1/2° E.)</p>

SUBDIVISION OF SECTION 17,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>An aluminum post, 2 1/2 ins. diam., firmly set flush with the surface of the ground, bears S. 24°42' E., 37.2 lks. dist., with aluminum cap, mkd. RM W 1/16 25 FT S17 1986 and an arrow pointing to the cor. (Record: S. 25 1/4° E., 37.9 lks.)</p> <p>Drive the railroad spike 6 ins. below the surface of the dirt road.</p> <p>Cor. falls in the center of a graded dirt road, 10 lks. wide, bears E. and W.</p> <hr/> <p>From the C-N 1/16 sec. cor. of sec. 17.</p> <p>N. 89°51'20" W., on the E-W center line of the NW1/4 of sec. 17.</p>
0.15	<p>Graded dirt road, 40 lks. wide, bears N. and S.</p> <p>Across nearly level land, covered with scattered sagebrush and grasses.</p>
0.65	<p>Powerline, bears N. and S.</p>
10.032	<p>Point for the C-E-NW 1/64 sec. cor. of sec. 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S17 C-E-NW 1/64 2005</p>
20.064	<p>The NW 1/16 sec. cor. of sec. 17.</p>
30.100	<p>Point for the C-W-NW 1/64 sec. cor. of sec. 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S17 C-W-NW 1/64 2005</p>
40.136	<p>From this cor., a steel fence cor. post, 2 3/4 in. diam., bears N. 48° W., 0.03 chs. dist., with wire fences extending N. and W. Set on top of the fence post is a weathered redwood post, 2x3x30 ins. long, with illegible scribe marks visible.</p> <p>The N 1/16 sec. cor. of secs. 17 and 18.</p> <hr/> <p>From the C-E-NW 1/64 sec. cor. of sec. 17.</p> <p>N. 0°11'10" E., on the N-S center line of the NE1/4NW1/4 of sec. 17.</p>

SUBDIVISION OF SECTION 17,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
19.982	<p>Across nearly level land, covered with scattered sagebrush and grasses.</p> <p>The E-W 1/64 sec. cor. of secs. 8 and 17, monumented with a railroad spike, set flush with the surface, from which the 1986-87 reference monuments</p> <p style="padding-left: 40px;">An aluminum post, 2 1/2 ins. diam., firmly set, projecting 21 ins. above the ground, bears N. 38°29' E., 27.3 lks. dist., with aluminum cap, mkd. RM S8 18 FT E-W 1/64 1986 and an arrow pointing to the cor. (Record: N. 39 3/4° E.)</p> <p style="padding-left: 40px;">An aluminum post, 2 1/2 ins. diam., firmly set flush with the surface of the ground, bears S. 41 3/4° E., 27.3 lks. dist., with aluminum cap, mkd. RM S17 18 FT E-W 1/64 1986 and an arrow pointing to the cor.</p> <p>Drive the railroad spike 4 ins. below the surface of the dirt road.</p> <p>Cor. falls in the center of a graded dirt road, 10 lks. wide, bears E. and W.</p> <hr/> <p>From the C-E-W 1/64 sec. cor. of sec. 17.</p> <p>N. 0°11'00" E., on the N-S center line of the SE1/4NW1/4 of sec. 17.</p> <p>Across nearly level land, covered with scattered sagebrush and grasses.</p>
19.984	<p>The C-E-NW 1/64 sec. cor. of sec. 17.</p> <hr/> <p>From the C-W-W 1/64 sec. cor. of sec. 17.</p> <p>N. 0°05'40" E., on the N-S center line of the SW1/4NW1/4 of sec. 17.</p>
19.991	<p>The C-W-NW 1/64 sec. cor. of sec. 17.</p> <hr/> <p>N. 0°06'00" E., on the N-S center line of the NW1/4NW1/4 of sec. 17.</p> <p>Across nearly level land, covered with scattered sagebrush and grasses.</p>
19.992	<p>The W-W 1/64 sec. cor. of secs. 8 and 17, determined at record distances from the 1986-87 reference monuments:</p> <p style="padding-left: 40px;">An aluminum post, 2 1/2 ins. diam., set flush with the surface of the ground, bears N. 32 3/4° E., 37.9 lks. dist., with aluminum cap, mkd. RM S8 25 FT W-W 1/64 1986 and an arrow pointing to the cor., with a mound of stone, 1 ft. base, 1/2 ft. high, W.</p>

SUBDIVISION OF SECTION 17,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>An aluminum post, 2 1/2 ins. diam., projecting 5 ins. above the ground, bears S. 46 3/4° E., 37.9 lks. dist., with aluminum cap, mkd. RM W-W 1/64 25 FT S17 1986 and an arrow pointing to the cor., with a mound of stone, 1 1/2 ft. base, 1/2 ft. high. W.</p> <p>At the corner point</p> <p>Set a copper coated steel rod, 1/2 in. diam., 24 ins. long, 2 ins. below the surface of the ground, with brass cap, 1 1/2 ins. diam., mkd.</p> <p style="text-align: center;">BLM S 8 -W-W 1/64- S17 2006</p>
	<hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 18, T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 18 and 19.</p> <p>North, on the N-S center line of sec. 18.</p> <p>Through river cut, scattered cottonwoods, willows and tamarisk.</p>
5.30	<p>Leave river cut, bears NW. and SE., continue across nearly level land, covered with scattered sagebrush and grasses.</p>
18.20	<p>Descend into river cut, bears NE. and SW., continue through scattered cottonwoods, willows and tamarisk.</p>
20.005	<p>Point for the C-S 1/16 sec. cor. of sec. 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">C S 1/16 S18 C 2005</p>
32.90	<p>Left bank of the Walker River, bears NE. and SW., thence across river, course SW.</p>
37.10	<p>Right bank of the Walker River, bears NE. and SW.</p>
40.010	<p>Point for the center 1/4 sec. cor. of sec. 18, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

SUBDIVISION OF SECTION 18,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T12N R29E C 1/4 S18 2005
	Cor. is located at the base of a steep sandy SE. slope.
40.60	Leave river cut, bears NE. and SW., continue across nearly level land, covered with scattered sagebrush and grasses.
52.50	Descend into river cut, bears NE. and SW.
52.80	Right bank of the Walker River, bears NE. and SW., thence across river, course E.
58.10	Left bank of the Walker River, bears E. and W., continue through scattered cottonwoods, willows and tamarisk.
60.006	Point for the C-N 1/16 sec. cor. of sec. 18. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	$\begin{array}{c} C \\ N\ 1/16 \mid S18 \\ C \end{array}$ 2005
	Cor. is located within oxbow bend of the Walker River.
61.55	Left bank of the Walker River, bears NE. and SW., thence across bend in river.
70.70	Left bank of the Walker River, bears NE. and SW., continue through scattered cottonwoods, willows and tamarisk.
77.40	Left bank of the Walker River, bears NE. and SW., thence across river course SW.
80.002	True point for the 1/4 sec. cor. of secs. 7 and 18.
	<hr/> From the 1/4 sec. cor. of secs. 17 and 18. N. 89°48'00" W., on the E-W center line of sec. 18. Over nearly level land, covered with scattered sagebrush and grasses.
9.998	Point for the C-E-E 1/64 sec. cor. of sec. 18. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	$\begin{array}{c} E-E\ 1/64 \\ C \text{ --- } C \\ S18 \end{array}$ 2005

SUBDIVISION OF SECTION 18,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
12.20	Descend into river cut, bears NE. and SW., continue through scattered willows and tamarisk.
18.474	<p>Point selected for the witness C-E 1/16 sec. cor. of sec. 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \text{WC} \\ \text{E } 1/16 \\ \leftarrow \text{C} \text{-----} \text{C} \\ \text{S18} \end{array}$ <p>2005</p> </div> <p>Continue through willows, scattered cottonwoods and tamarisk.</p>
19.40	Left bank of the Walker River, bears NE. and SW., thence across river, course SW.
19.996	True point for the C-E 1/16 sec. cor. of sec. 18, falls in river where it is impractical to set a permanent monument.
23.40	Right bank of the Walker River, bears NE. and SW.
29.994	<p>Point for the C-W-E 1/64 sec. cor. of sec. 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \text{W-E } 1/64 \\ \text{C} \text{-----} \text{C} \\ \text{S18} \end{array}$ <p>2006</p> </div>
36.10	Right bank of the Walker River, bears SE. and SW.
39.992	The center 1/4 sec. cor. of sec. 18.
42.00	Leave river cut, bears NE. and SW., continue across nearly level land, covered with scattered sagebrush and grasses.
49.982	<p>Point for the C-E-W 1/64 sec. cor. of sec. 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \text{E-W } 1/64 \\ \text{C} \text{-----} \text{C} \\ \text{S18} \end{array}$ <p>2005</p> </div>
59.972	Point for the C-W 1/16 sec. cor. of sec. 18.

SUBDIVISION OF SECTION 18,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;"> $\begin{array}{c} \text{W } 1/16 \\ \text{C} \text{-----} \text{C} \\ \text{S } 18 \end{array}$ </p> <p style="text-align: center;">2005</p> <p>From this cor., a weathered redwood post, 2x3x24 ins. long, no marks visible, was found lying loose nearby, original position indeterminate, not utilized in the course of this survey.</p>
69.515	<p>Point for Angle Point No. 3, sec. 18, established at midpoint bet. the 1/4 sec. cor. of secs. 13 and 18 on the W. bdy. of the Tp. and the C-W 1/16 sec. cor. of sec. 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;"> $\begin{array}{c} \text{T12N R29E} \\ \text{AP } 3 \\ \text{C} \text{-----} \text{C} \\ \text{S } 18 \end{array}$ </p> <p style="text-align: center;">2005</p> <p>From this cor., a weathered redwood post, 2 ins. square, 31 ins. long, ground to a point, the marks 78 visible, was found lying loose nearby, original position indeterminate, not utilized in the course of this survey.</p>
79.058	<p>The 1/4 sec. cor. of sec. 13 and 18, on the W. bdy. of the Tp.</p> <hr/> <p>From the true point for the C-E 1/16 sec. cor. of sec. 18.</p> <p>N. 0°01'20" E., on the N-S center line of the NE1/4 of sec. 18.</p> <p>Across the Walker River course SW.</p>
0.30	<p>Right bank of the Walker River, bears NE. and SW., continue through willows and tamarisk.</p>
8.80	<p>Right bank of the Walker River, bears NW. and SE., thence across river, course SE.</p>
15.30	<p>Left bank of the Walker River, bears NW. and SE.</p>
17.00	<p>Leave river cut, bears NW. and SE., continue across nearly level land, covered with scattered sagebrush and grasses.</p>
19.995	<p>Point for the NE 1/16 sec. cor. of sec. 18, at intersection with the E-W center line of the NE1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

SUBDIVISION OF SECTION 18,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	NE 1/16 S18
	2005
39.989	The E 1/16 sec. cor. of secs. 7 and 18.
	<hr/> <p>From the N 1/16 sec. cor. of secs. 17 and 18. N. 89°47'40" W., on the E-W center line of the NE1/4 of sec. 18. Over nearly level land, covered with scattered sagebrush and grasses.</p>
10.001	Point for the C-E-NE 1/64 sec. cor. of sec. 18.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S18 C-E-NE 1/64</p> <p style="text-align: center;">2005</p>
	<p>From this cor., a rotted redwood post, 3 ins. square, 24 ins. long, no marks visible, was found lying loose nearby, original position indeterminate, not utilized in the course of this survey.</p>
20.002	The NE 1/16 sec. cor. of sec. 18.
27.068	Point selected for the witness C-W-NE 1/64 sec. cor. of sec. 18.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">WC S18 ←C-W-NE 1/64</p> <p style="text-align: center;">2007</p>
29.30	Descend into river cut, bears NW. and SE.
30.003	True point for the C-W-NE 1/64 sec. cor. of sec. 18, falls on left bank of the Walker River, bears SE. and SW., where it is impractical to set a permanent monument.
	Continue through willows, scattered cottonwoods and tamarisk.
40.004	The C-N 1/16 sec. cor. of sec. 18.
	<hr/> <p>From the C-E-NE 1/64 sec. cor. of sec. 18. N. 0°02'00" E., on the N-S center line of the NE1/4NE1/4 of sec. 18.</p>

SUBDIVISION OF SECTION 18,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Over nearly level land, covered with scattered sagebrush and grasses.
19.994	The E-E 1/64 sec. cor. of secs. 7 and 18. <hr/>
	From the C-E-E 1/64 sec. cor. of sec. 18. N. 0°02'00" E., on the N-S center line of the SE1/4NE1/4 of sec. 18. Over nearly level land, covered with scattered sagebrush and grasses.
19.994	The C-E-NE 1/64 sec. cor. of sec. 18. <hr/>
	From the C-W-E 1/64 sec. cor. of sec. 18. N. 0°00'40" E., on the N-S center line of the SW1/4NE1/4 of sec. 18.
3.50	Leave river cut, bears NE. and SW., continue across nearly level land, covered with scattered sagebrush and grasses.
10.40	Descend into river cut, bears NW. and SE., continue through scattered cottonwoods, willows and tamarisk.
18.40	Right bank of the Walker River, bears NW. and SE., thence across the Walker River course SE.
19.995	True point for the C-W-NE 1/64 sec. cor. of sec. 18. <hr/>
	N. 0°00'40" E., on the N-S center line of the NW1/4NE1/4 of sec. 18. Ascend steep sandy cutbank of the Walker River.
0.50	Leave river cut, bears NW. and SE., continue across nearly level land, covered with scattered sagebrush and grasses.
19.995	The W-E 1/64 sec. cor. of secs. 7 and 18. <hr/>
	From the E 1/16 sec. cor. of secs. 18 and 19. N. 0°01'00" E., on the N-S center line of the SE1/4 of sec. 18. Over nearly level land, covered with scattered sagebrush and grasses.
20.005	Point for the SE 1/16 sec. cor. of sec. 18, at intersection with the E-W center line of the SE1/4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

SUBDIVISION OF SECTION 18,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	SE 1/16 S18 2005
35.60	Descend into river cut, bears E. and W. Continue through scattered cottonwoods, willows and tamarisk.
39.90	Left bank of the Walker River, bears NE. and SW., thence across river, course SW.
40.009	True point for the C-E 1/16 sec. cor. of sec. 18.
<hr/>	
	From the S 1/16 sec. cor. of secs. 17 and 18. N. 89°48'00" W., on the E-W center line of the SE1/4 of sec. 18. Over nearly level land, covered with scattered sagebrush and grasses.
9.996	Point for the C-E-SE 1/64 sec. cor. of sec. 18. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. S18 C-E-SE 1/64 2005
19.992	The SE 1/16 sec. cor. of sec. 18.
29.988	Point for the C-W-SE 1/64 sec. cor. of sec. 18. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. S18 C-W-SE 1/64 2005
37.80	From this cor., a rebar, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, no marks visible, bears S. 19°31' W., 0.069 chs. dist., as shown on an unrecorded parcel map created by Geosurveys in 1976, on file with the Nature Conservancy of Nevada. Established by improper methods, not utilized in the course of this survey.
39.984	Descend into river cut, bears NE. and SW. The C-S 1/16 sec. cor. of sec. 18.
<hr/>	

SUBDIVISION OF SECTION 18,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	From the C-E-SE 1/64 sec. cor. of sec. 18. N. 0°01'30" E., on the N-S center line of the NE1/4SE1/4 of sec. 18. Over nearly level land, covered with scattered sagebrush and grasses.
20.004	The C-E-E 1/64 sec. cor. of sec. 18. <hr/>
	From the E-E 1/64 sec. cor. of secs. 18 and 19. N. 0°01'30" E., on the N-S center line of the SE1/4SE1/4 of sec. 18. Over nearly level land, covered with scattered sagebrush and grasses.
20.004	The C-E-SE 1/64 sec. cor. of sec. 18. <hr/>
	From the W-E 1/64 sec. cor. of secs. 18 and 19. N. 0°00'30" E., on the N-S center line of the SW1/4SE1/4 of sec. 18. Over nearly level land, covered with scattered sagebrush and grasses.
20.005	The C-W-SE 1/64 sec. cor. of sec. 18. <hr/>
	N. 0°00'30" E., on the N-S center line of the NW1/4SE1/4 of sec. 18. Over nearly level land, covered with scattered sagebrush and grasses.
13.80	Descend into river cut, bears NE. and SW.
18.00	Left bank of the Walker River, bears NE. and SW., thence across the Walker River, course SW.
19.00	Right bank of the Walker River, bears NE. and SW.
20.004	The C-W-E 1/64 sec. cor. of sec. 18. <hr/>
	From the W 1/16 sec. cor. of secs. 18 and 19. N. 0°00'30" E., on the N-S center line of the SW1/4 of sec. 18.
0.15	N. edge of a graded dirt road, 10 lks. wide, bears E. and W. Continue over nearly level land, covered with scattered sagebrush and grasses.
20.005	Point for the SW 1/16 sec. cor. of sec. 18, at intersection with the E-W center line of the SW1/4.

SUBDIVISION OF SECTION 18,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p> <p>40.009</p>	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SW 1/16 S18</p> <p style="text-align: center;">2005</p>
	<p>The C-W 1/16 sec. cor. of sec. 18.</p> <hr/>
	<p>From the C-S 1/16 sec. cor. of sec. 18.</p> <p>N. 89°48'10" W., on the E-W center line of the SW1/4 of sec. 18.</p> <p>Through river cut, scattered cottonwoods and willows.</p>
<p>8.80</p>	<p>Left bank of the Walker River, bears NW. and SE., thence across river, course SE.</p>
<p>9.991</p>	<p>True point for the C-E-SW 1/64 sec. cor. of sec. 18, falls in river where it is impractical to set a permanent monument.</p>
<p>12.10</p>	<p>Right bank of the Walker River, bears NW. and SE.</p>
<p>12.897</p>	<p>Point selected for the witness C-E-SW 1/64 sec. cor. of sec. 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">WC S18 C-E-W→ 1/64</p> <p style="text-align: center;">2005</p>
<p>14.20</p>	<p>Leave river cut, bears N. and S., continue across nearly level land, covered with scattered sagebrush and grasses.</p>
<p>19.982</p>	<p>The SW 1/16 sec. cor. of sec. 18.</p>
<p>29.533</p>	<p>Point for Angle Point No. 2, sec. 18, established at midpoint bet. the S 1/16 sec. cor. of secs. 13 and 18 on the W. bdy. of the Tp., and the SW 1/16 sec. cor. of sec. 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T12N R29E AP 2 S ——— S 18</p> <p style="text-align: center;">2005</p>
<p>39.084</p>	<p>The S 1/16 sec. cor. of secs. 13 and 18, on the W. bdy. of the Tp.</p> <hr/>

SUBDIVISION OF SECTION 18,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From the true point for the C-E-SW 1/64 sec. cor. of sec. 18.</p> <p>N. 0°00'10" E., on the N-S center line of the NE1/4SW1/4 of sec. 18.</p> <p>Across the Walker River, course SE.</p>
0.70	Left bank of the Walker River, bears NW. and SE., continue through scattered cottonwoods, willows and tamarisk.
5.70	Left bank of the Walker River, bears NE. and SW. thence across river, course SW.
7.60	Right bank of the Walker River, bears NE. and SW.
14.30	Leave river cut, bears NW. and SE., continue across nearly level land, covered with scattered sagebrush and grasses.
20.004	The C-E-W 1/64 sec. cor. of sec. 18.
<hr/>	
	<p>From the E-W 1/64 sec. cor. of secs. 18 and 19.</p> <p>N. 0°00'10" E., on the N-S center line of the SE1/4SW1/4 of sec. 18.</p>
0.15	N. edge of a graded dirt road, 10 lks. wide, bears E. and W. Continue through willows, scattered cottonwoods and tamarisk.
7.30	Right bank of the Walker River, bears NW. and SE., thence across river, course SE.
9.30	Left bank of the Walker River, bears NW. and SE., continue through willows, scattered cottonwoods and tamarisk.
13.50	Left bank of the Walker River, bears NE. and SW., thence across river, course SW.
20.005	True point for the C-E-SW 1/64 sec. cor. of sec. 18.
<hr/>	
	<p>From the C-W 1/16 sec. cor. of sec. 18.</p> <p>N. 0°02'50" W., on the N-S center line of the NW1/4 of sec. 18.</p> <p>Over nearly level land, covered with scattered sagebrush and grasses.</p>
19.996	<p>Point for the NW 1/16 sec. cor. of sec. 18, at intersection with the E-W center line of the NW1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	NW 1/16 S18
	2005

SUBDIVISION OF SECTION 18,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From this cor., a weathered redwood post, 2x3x23 ins. long, no marks visible, was found lying loose nearby, original position indeterminate, not utilized in the course of this survey.</p>
38.35	<p>Abandoned irrigation ditch, 15 lks. wide, 4 ft. deep, bears N., and drains SW.</p> <p>Continue along irrigation ditch.</p>
39.995	<p>The W 1/16 sec. cor. of secs. 7 and 18.</p> <hr/> <p>From the C-N 1/16 sec. cor. of sec. 18.</p> <p>N. 89°48'10" W., on the E-W center line of the NW1/4 of sec. 18.</p>
2.90	<p>Left bank of the Walker River, bears NW. and SE., thence across river, course SE.</p>
6.60	<p>Right bank of the Walker River, bears NW. and SE., continue through willows and scattered tamarisk.</p>
9.997	<p>Point for the C-E-NW 1/64 sec. cor. of sec. 18, on steep cutbank of the Walker River.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a T-bar fence post, 5 ft. long, driven completely in the ground, with brass cap mkd.</p> <p style="text-align: center;">S18 C-E-NW 1/64</p> <p style="text-align: center;">2006</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, at the top of cutbank, over a plastic-encased magnet, for a reference monument, bears S. 44°54' W., 172.3 lks. dist., with brass cap, mkd. RM C-E-NW 1/64 S18 113.7 FT TO COR 2005 and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, at the top of cutbank, over a plastic-encased magnet, for a reference monument, bears N. 43°04' W., 98.4 lks. dist., with brass cap, mkd. RM C-E-NW 1/64 S18 64.9 FT TO COR 2005 and an arrow pointing to the cor.</p>
10.20	<p>Leave river cut, bears NE. and SW., continue across nearly level land, covered with scattered sagebrush and grasses.</p>
19.994	<p>The NW 1/16 sec. cor. of sec. 18.</p>
29.524	<p>Point for Angle Point No. 4, sec. 18, established at midpoint bet. the N 1/16 sec. cor. of secs. 13 and 18, on the W. bdy. of the Tp. and the NW 1/16 sec. cor. of sec. 18.</p>

SUBDIVISION OF SECTION 18,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p>	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T12N R29E AP 4 N ——— ——— N S 18</p> <p>2005</p> </div> <p>39.054 The N 1/16 sec. cor. of secs. 13 and 18, on the W. bdy. of the Tp.</p> <hr/> <p>From the C-E-NW 1/64 sec. cor. of sec. 18.</p> <p>N. 0°01'20" W., on the N-S center line of the NE1/4NW1/4 of sec. 18.</p> <p>Ascend steep cutbank.</p> <p>0.60 Leave river cut, bears NE. and SW., continue across nearly level land, covered with scattered sagebrush and grasses.</p> <p>19.997 The E-W 1/64 sec. cor. of secs. 7 and 18.</p> <hr/> <p>From the C-E-W 1/64 sec. cor. of sec. 18.</p> <p>N. 0°01'20" W., on the N-S center line of the SE1/4NW1/4 of sec. 18.</p> <p>Across nearly level land, covered with scattered sagebrush and grasses.</p> <p>17.80 Descend into river cut, bears NW. and SE.</p> <p>19.996 The C-E-NW 1/64 sec. cor. of sec. 18.</p> <hr/> <div style="text-align: center;"> <p>FURTHER SUBDIVISION OF SECTION 5, T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA</p> </div> <hr/> <p>From the E-E 1/64 sec. cor. of secs. 5 and 8, monumented with an aluminum post, 2 1/2 ins. diam., set flush with the surface of the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635, with an embedded mound of stone, 1 ft. base, N. of the cor.</p> <p>Cor. is located under a barbwire fence, extending E. and W.</p> <p>N. 0°20'50" W., on the N-S center line of the SE1/4SE1/4 of sec. 5.</p> <p>Across rolling land, covered with sagebrush and grasses.</p>
---------------	---

FURTHER SUBDIVISION OF SECTION 5,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.052	<p>The C-E-SE 1/64 sec. cor. of sec. 5, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635, with a mound of stone, 1 ft. base, 1 ft. high, W. of the cor.</p> <hr/> <p>From the C-W-SE 1/64 sec. cor. of sec. 5, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 9 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635.</p> <p>N. 0°15'40" W., on the N-S center line of the NW1/4SE1/4 of sec. 5.</p> <p>Across nearly level land, covered with sagebrush and grasses.</p>
20.033	<p>The C-W-E 1/64 sec. cor. of sec. 5, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635, with a mound of stone, 1 ft. base, 1 ft. high, W. of the cor..</p> <hr/> <p>From the C-E-SW 1/64 sec. cor. of sec. 5, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635, with a mound of stone, 2 ft. base, 1 ft. high, W. of the cor.</p> <p>N. 0°07'10" W., on the N-S center line of NE1/4SW1/4 of sec. 5.</p> <p>Across nearly level land, covered with sagebrush and grasses.</p>
20.022	<p>The C-E-W 1/64 sec. cor. of sec. 5, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635, with a mound of stone, 1 ft. base, 1/2 ft. high, W. of the cor.</p> <p>Cor. is located on S. shoulder of graded dirt road, 30 lks. wide, bears E. and W.</p> <hr/> <p style="text-align: center;">FURTHER SUBDIVISION OF SECTION 6, T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the E-E 1/64 sec. cor. of secs. 6 and 7.</p> <p>N. 0°03'00" E., on the N-S center line of the SE1/4SE1/4 of sec. 6.</p>

FURTHER SUBDIVISION OF SECTION 6,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Across nearly level land, covered with sagebrush and scattered cottonwood trees.
5.50	Descend into river cut, bears NW. and SE. Continue through scattered cottonwood trees.
10.00	Right bank of the Walker River, bears SE. and NW., thence across river course SE.
10.30	Left bank of the Walker River, bears SE. and NW.
12.00	Leave river cut, bears NW. and SE., continue across nearly level land, covered with scattered sagebrush and grasses. Continue across nearly level land, covered with sagebrush and grasses.
19.988	The C-E-SE 1/64 sec. cor. of sec. 6. <hr/> From the W-E 1/64 sec. cor. of secs. 6 and 7. N. 0°06'00" W., on the N-S center line of SW1/4SE1/4 of sec. 6. Across nearly level land, covered with sagebrush and grasses.
6.35	Dirt road, bears NW. and SE.
6.50	Descend into river cut, bears SE. and NW., continue through scattered cottonwood trees, willows and tamarisk.
14.50	Right bank of the Walker River, bears SE. and NW., thence across river course SE.
15.00	Left bank of the Walker River, bears NW. and SE.
15.30	Leave river cut, bears NW. and SE., continue across nearly level land, covered with scattered sagebrush and grasses.
19.956	The C-W-SE 1/64 sec. cor. of sec. 6. <hr/> N. 0°10'10" W., on the N-S center line of NW1/4SE1/4 of sec. 6. Across nearly level land, covered with scattered sagebrush and grasses.
19.954	The C-W-E 1/64 sec. cor. of sec. 6, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635, with a wood post, 4x6 ins., firmly set, projecting 6 ft. above the ground, E. of the cor. <hr/> From the W 1/16 sec. cor. of secs. 6 and 7. N. 0°12'40" W., on the N-S center line of the SW1/4 of sec. 6.

FURTHER SUBDIVISION OF SECTION 6,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Across nearly level land, covered with sagebrush and grasses.
0.35	Abandoned irrigation ditch, 15 lks. wide, 4 ft. deep, bears E. and curves NW.
	Continue across nearly level land, covered with sagebrush and grasses.
9.969	<p>Point for the C-S-SW 1/64 sec. cor. of sec. 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 6 C-S-SW 1/64 2005</p>
19.938	<p>Point for the SW 1/16 sec. cor. of sec. 6, at intersection with the E-W center line of the SW1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SW 1/16 S 6 2005</p>
29.909	<p>Cor. is located on the S. shoulder of a graded dirt road, 10 lks. wide, bears E-W, 5 lks. from S. edge.</p> <p>Continue across rolling lands, through sagebrush and scattered cottonwood trees.</p> <p>Point for the C-N-SW 1/64 sec. cor. of sec. 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 6 C-N-SW 1/64 2005</p> <p>Continue through scattered cottonwood trees.</p>
30.40	Descend into river cut, bears NW. and SE.
30.70	Right bank of the Walker River, bears NW. and SE., thence across river course SE.
31.20	Left bank of the Walker River, bears NW. and SE.

FURTHER SUBDIVISION OF SECTION 6,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
31.30	Leave river cut, bears NW. and SE.
39.880	<p>The C-W 1/16 sec. cor. of sec. 6, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635.</p> <hr/> <p>From the C-S 1/16 sec. cor. of sec. 6, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground and in a collar of stone, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635, with an iron pipe, 2 1/2 ins. diam., firmly set, projecting 4 ft. above the ground, S. of the cor.</p> <p>S. 89°56'50" W., on the E-W center line of the SW1/4 of sec. 6.</p> <p>Across rolling land, through sagebrush and scattered cottonwood trees.</p>
6.00	<p>Graded dirt road, 15 lks. wide, curves SE. and bears W.</p> <p>Continue across nearly level land, covered with sagebrush and grasses, and along S. shoulder of graded dirt road.</p>
20.104	The SW 1/16 sec. cor. of sec. 6.
29.613	<p>Point for Angle Point No. 2, sec. 6, established at midpoint bet. the S 1/16 sec. cor. of secs. 1 and 6, on the W. bdy. of the Tp. and the SW 1/16 sec. cor. of sec. 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T12N R29E AP2 ----- S 6 ----- 2007</p> </div>
29.78	S. end of a culvert, 6 lks. diam., running along with an irrigation ditch, 15 lks. wide, 3 ft. deep, bears NW. and SE.
39.122	<p>The S 1/16 sec. cor. of secs. 1 and 6, on the W. bdy. of the Tp., monumented with an aluminum post, 2 1/2 ins. diam., projecting 6 ins. above and bent at the surface of the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635, with a mound of stone, 2 ft. base, 1 ft. high, and a splintered redwood post, 2x3 ins. diam., firmly set, projecting 2 ins. above the ground, W. of the cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

FURTHER SUBDIVISION OF SECTION 6,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">S 1/16 S 1 S 6</p> <p style="text-align: center;">2007</p> <p>Deposit aluminum post alongside and below the surface of the ground.</p> <hr/> <p>From the C-N-S 1/64 sec. cor. of sec. 6, monumented with an aluminum post, 2 1/2 ins., firmly set, projecting 6 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635, with a mound of stone, 1 1/2 ft. base, 1 ft. high, W. of the cor.</p> <p>S. 89°55'20" W., on the E-W center line of the NE1/4SW1/4 of sec. 6.</p> <p>Across rolling land, through scattered cottonwood trees, willows and tamarisk.</p> <p>8.70 Descend into river cut, bears NW. and SE.</p> <p>9.30 Right bank of the Walker River, bears NE. and SW., thence across river, course NE.</p> <p>11.60 Left bank of the Walker River, bears NE. and SW.</p> <p>17.90 Left bank of the Walker River, bears NW. and SE., thence across river, course SE.</p> <p>18.40 Right bank of the Walker River, bears NW. and SE.</p> <p>19.40 Leave river cut, bears NW. and SE.</p> <p>20.101 The C-N-SW 1/64 sec. cor. of sec. 6.</p> <hr/> <p>From the C-S-S 1/64 sec. cor. of sec. 6, monumented with an aluminum post, 2 1/2 ins., firmly set, projecting 6 ins. above the ground, in a collar of stone, 2 ft. diam., with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635.</p> <p>S. 89°55'50" W., on the E-W center line of the SE1/4SW1/4 of sec. 6.</p> <p>Across rolling land, through scattered cottonwoods and sagebrush.</p> <p>20.106 The C-S-SW 1/64 sec. cor. of sec. 6.</p> <hr/> <p>From the C-N-SW 1/64 sec. cor. of sec. 6</p> <p>S. 89°57'40" W., on the E-W center line of the NW1/4SW1/4 of sec. 6.</p>
--------	--

FURTHER SUBDIVISION OF SECTION 6,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Across nearly level land, through scattered cottonwoods and sagebrush.
19.012	<p>The N-S 1/64 sec. cor. of secs. 1 and 6, on the W. bdy. of the Tp., monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635, with a mound of stone, 2 ft. base, 1 ft. high, W. of the cor.</p> <hr/> <p>From the C-S-NW 1/64 sec. cor. of sec. 6, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635.</p> <p>Cor. is located 6 lks. W. of a barbwire fence, extending N. and S.</p> <p>N. 89°56'30" W., on the E-W center line of the SW1/4NW1/4 of sec. 6.</p> <p>Across nearly level land, through scattered cottonwood trees and sagebrush, and along the S. side of pasture.</p>
18.80	Descend into river cut, bears NW. and SE.
18.957	True point for the S-N 1/64 sec. cor. of secs. 1 and 6, on the W. bdy. of the Tp.
<p>FURTHER SUBDIVISION OF SECTION 8, T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>	
<p>From the C-W-E 1/64 sec. cor. of sec. 8, determined at record bearing and distance from the 1986-87 record tie to a rebar. The 1986-87 aluminum post, 30 ins. long, 2 1/2 ins. diam., was found lying loose nearby, original position indeterminate, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635.</p>	
from which	
<p style="padding-left: 40px;">A rebar, 5/8 ins. diam., firmly set, projecting 1 in. above the ground, with aluminum cap, 1 1/2 ins. diam., no marks visible, bears N. 73°15' W., 3.5 lks. dist., under a barbwire fence, extending E. and W.</p>	
At the corner point	
Reset the aluminum post, 24 ins. in the ground over a plastic-encased magnet, and add the marks 2005.	
N. 0°08'50" E., on the N-S center line of the SW1/4NE1/4 of sec. 8.	

FURTHER SUBDIVISION OF SECTION 8,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Across level bladed field.
20.038	<p>The C-W-NE 1/64 sec. cor. of sec. 8.</p> <hr/> <p>From the E 1/16 sec. cor. of secs. 8 and 17.</p> <p>N. 0°08'10" E., on the N-S center line of the SE1/4 of sec. 8.</p> <p>Across nearly level land, covered with sagebrush and grasses.</p>
20.024	<p>The SE 1/16 sec. cor. of sec. 8, monumented with a weathered redwood post, of unknown origin, 2 ins. square, 30 ins. long, firmly set, projecting 14 ins. above the ground, with illegible scribe marks, and on the SE. side of a fence cor., with barbwire fences extending N., E. and W. and is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S 8</p> <p style="text-align: center;">2005</p> <p>Deposit redwood post, with ground point, alongside stainless steel post.</p> <hr/>
20.032	<p>N. 0°12'50" E., beginning new measurement.</p> <p>Continue across nearly level land, covered with sagebrush and grasses, and along barbwire fence.</p> <p>The C-E 1/16 sec. cor. of sec. 8.</p> <hr/> <p>From the S 1/16 sec. cor. of secs. 8 and 9, monumented with a railroad spike, set 6 ins. below the surface, from which the 1986-87 reference monuments</p> <p style="padding-left: 40px;">An aluminum post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, bears S. 65°33' W., 14.9 lks. dist., with aluminum cap, mkd. S 1/16 S8 10 FT 1986 and an arrow pointing to the cor., with a mound of stone, 1 ft. base, 1/2 ft. high, N. (Record: S. 62 1/2° W., 15.2 lks.)</p> <p style="padding-left: 40px;">An aluminum post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above the ground, bears S. 75°34' E., 21.2 lks. dist., with aluminum cap, mkd. S 1/16 S9 14 FT RM 1986 and an arrow pointing to the cor. (Record: S. 72 3/4° E.)</p> <p>Cor. falls in a graded dirt road, 15 lks. wide, bears N. and S.</p>

FURTHER SUBDIVISION OF SECTION 8,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>N. 89°52'30" W., on the E-W center line of SE1/4 of sec. 8. Across alfalfa field and along N. side of barbwire fence.</p>
9.88	<p>Cor. of barbwire fences, with fences extending N., E., S. and W. Continue across nearly level land covered with sagebrush and grasses, and along N. side of barbwire fence.</p>
10.062	<p>Point for the C-E-SE 1/64 sec. cor. of sec. 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 8 C-E-SE 1/64 2005</p>
20.124	<p>The SE 1/16 sec. cor. of sec. 8.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 89°46'20" W., beginning new measurement. Continue across nearly level land covered with sagebrush and grasses, and along barbwire fence.</p>
9.961	<p>The C-W-SE 1/64 sec. cor. of sec. 8, monumented with a weathered redwood post, of unknown origin, 2 ins. square, 30 ins. long, firmly set, projecting 5 ins. above the ground, with illegible scribe marks and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 8 C-W-SE 1/64 2005</p> <p>Deposit the redwood post, with ground point, alongside stainless steel post and below the surface of the ground.</p> <p>From this cor., a rebar, of unknown origin, 1/2 in. diam., set flush with the top of a concrete post, 4x6 ins., firmly set, projecting 19 ins. above the ground, bears S. 79°34" W., 0.026 chs. dist., not utilized in the course of this survey.</p> <hr style="width: 30%; margin: 10px auto;"/>

FURTHER SUBDIVISION OF SECTION 8,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p> <p>9.36</p> <p>9.63</p> <p>10.137</p> <p>20.038</p>	<p>N. 89°55'20" W., beginning new measurement.</p> <p>Continue across nearly level land covered with sagebrush and grasses, and along barbwire fence.</p> <p>Fence cor., with barbwire fences extending N., E. and W.</p> <p>Fence cor., with barbwire fences extending E. and S.</p> <p>The C-S 1/16 sec. cor. of sec. 8, determined at record bearing and distance from the remaining 1986-87 reference monument:</p> <p style="padding-left: 40px;">An aluminum post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, bears N. 69 1/4° E., 50.0 lks. dist., with aluminum cap, mkd. RM C-S 1/16 S8 33 FT 1986 and an arrow pointing to the cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 5 ins. below the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} C \\ S\ 1/16\ S\ 8 \\ C \end{array}$ <p>2005</p> </div> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 21°19' E., 52.9 lks. dist., with brass cap, mkd. C-S 1/16 S8 39.1 FT 2006 and an arrow pointing to the cor.</p> <hr/> <p>From the C-E-SE 1/64 sec. cor. of sec. 8.</p> <p>N. 0°13'20" E., on the N-S center line of the NE1/4SE1/4 of sec. 8.</p> <p>Along barbwire fence and W. side of level alfalfa field.</p> <p>The C-E-E 1/64 sec. cor. of sec. 8, monumented with an aluminum post, 2 1/2 ins. diam., set flush with the surface of the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635.</p> <p>Cor. is located S. 80° E., 23 lks. dist. from a fence cor., with barbwire fences extending N., E., S. and W.,</p> <hr/> <p>From the E-E 1/64 sec. cor. of secs. 8 and 17.</p> <p>N. 0°11'10" E., on the N-S center line of the SE1/4SE1/4 of sec. 8.</p>
---	---

FURTHER SUBDIVISION OF SECTION 8,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Across nearly level land, covered with scattered sagebrush and grasses.
7.25	From this point, a fence cor. bears East, 30 lks. dist., with barbwire fences extending N. and E.
20.026	Continue along W. side of barbwire fence and alfalfa field. The C-E-SE 1/64 sec. cor. of sec. 8.
20.039	From the W-E 1/64 sec. cor. of secs. 8 and 17. N. 0°21'40" E., on the N-S center line of the SW1/4SE1/4 of sec. 8. Across nearly level land, covered with scattered sagebrush and grasses. The C-W-SE 1/64 sec. cor. of sec. 8.
19.60	N. 0°03'00" W., on the N-S center line of the NW1/4SE1/4 of sec. 8. Across level alfalfa field.
19.90	Irrigation ditch, 10 lks. wide, 3 ft. deep, bears E. and W.
20.010	Dirt road, 10 lks. wide, parallels ditch. The C-W-E 1/64 sec. cor. of sec. 8.
10.008	From the W 1/16 sec. cor. of secs. 8 and 17. N. 0°03'30" E., on the N-S center line of the SW1/4 of sec. 8. Across nearly level land, covered with sagebrush and grasses. Point for the C-S-SW 1/64 sec. cor. of sec. 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
20.016	<p style="text-align: center;">S 8 C-S-SW 1/64 2005</p> Point for the SW 1/16 sec. cor. of sec. 8, at intersection with the E-W center line of the SW1/4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

FURTHER SUBDIVISION OF SECTION 8,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	SW 1/16 S 8
	2005
	Cor. falls under a barbwire fence, bears E. and W.
30.00	Barbwire fence, bears E. and W.
	Continue across level alfalfa field.
30.027	Point for the C-N-SW 1/16 sec. cor. of sec. 8.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. below the surface of the ground, over a plastic-encased magnet, with brass cap mkd.
	S 8 C-N-SW 1/64
	2005
	Cor. falls in alfalfa field.
40.00	Barbwire fence, bears E. and W.
40.038	The C-W 1/16 sec. cor. of sec. 8, monumented with an aluminum post, 2 1/2 ins. diam., set 10 ins. below the surface of the ground, in a clay cylinder, 10 ins. diam., with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635.
	From the C-S 1/16 sec. cor. of sec. 8.
	N. 89°52'30" W., on the E-W center line of the SW1/4 of sec. 8.
0.20	Paved road, 40 lks. wide, bears N. and S.
0.55	Powerline, parallels road.
0.60	From this point, a fence cor. bears North, 2 lks. dist., with barbwire fences extending N. and W.
	Continue across nearly level land, covered with sagebrush and grasses, and along S. side of barbwire fence.
20.108	The SW 1/16 sec. cor. of sec. 8.
	Continue along barbwire fence.
32.90	Fence cor., with barbwire fences extending N., E. and W.
34.00	Descend into river cut, bears N. and S., and continue through scattered cottonwood trees, willows and tamarisk.
40.207	The S 1/16 sec. cor. of secs. 7 and 8.

FURTHER SUBDIVISION OF SECTION 8,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the C-N-S 1/64 sec. cor. of sec. 8, monumented with the sheared bottom end of an aluminum post, 2 1/2 ins. diam., still in upright position, 12 ins. below the surface of the ground.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 5 ins. below the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;"> $\begin{array}{c} \text{C} \\ \text{N-S } 1/64 \text{ S } 8 \\ \text{C} \end{array}$ 2005 </p> <p>Deposit aluminum post remains alongside the stainless steel post and below the brass cap.</p> <p>N. 89°52'10" W., on the E-W center line of the NE1/4SW1/4 of sec. 8.</p> <p>0.30 Paved road, 40 lks. wide, bears N. and S.</p> <p>0.60 Powerline, bears N. and S.</p> <p>Continue across level alfalfa field.</p> <p>20.120 The C-N-SW 1/64 sec. cor. of sec. 8.</p> <hr/> <p>From the C-S-S 1/64 sec. cor. of sec. 8, determined at record bearing and distance from the remaining 1986-87 reference monument:</p> <p style="padding-left: 40px;">An aluminum post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, bears S. 41 1/2° W., 71.2 lks. dist., with aluminum cap, mkd. X RM and an arrow pointing to the cor. Add the marks C-S-S 1/64 47 FT TO COR S8 2005 and build a collar of stone around monument, 1 1/2 ft. diam. (Record: 47 FT XRM 1986 and an arrow pointing to the cor.)</p> <p>At the corner point</p> <p>Set a copper coated steel stake, 1/2 in. diam., 24 ins. long, 4 ins. below the surface of the ground, with brass cap, 1 1/2 ins. diam., mkd.</p> <p style="text-align: center;"> $\begin{array}{c} \text{BLM} \\ \text{C} \\ \text{S-S } 1/64 \text{ S } 8 \\ \text{C} \end{array}$ 2005 </p>
--------	---

FURTHER SUBDIVISION OF SECTION 8,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground and in a mound of stone, 3 ft. base, to top, for a reference monument, bears N. 43°55' W., 65.3 lks. dist., with brass cap mkd. C-S 1/64 S8 43.1 FT TO COR 2005 and an arrow pointing to the cor.</p> <p>Cor. is located in a graded dirt road, 40 lks. wide, bears N. and S., 15 lks. dist. from E. edge.</p> <p>N. 89°52'10" W., on the E-W center line of the SE1/4SW1/4 of sec. 8.</p> <p>Across nearly level land, covered with sagebrush and grasses.</p>
20.098	<p>The C-S-SW 1/64 sec. cor. of sec. 8.</p> <hr/>
20.107	<p>N. 89°50'50" W., on the E-W center line of the SW1/4SW1/4 of sec. 8.</p> <p>Across nearly level land, covered with sagebrush and grasses.</p> <p>The S-S 1/64 sec. cor. of secs. 7 and 8, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635.</p> <hr/>
14.95	<p>From the C-N-SW 1/64 sec. cor. of sec. 8.</p> <p>N. 89°51'50" W., on the E-W center line of the NW1/4SW1/4 of sec. 8.</p> <p>Across level alfalfa field.</p>
15.55	<p>Barbwire fence, bears N. and S.</p>
19.90	<p>Irrigation ditch, 15 lks. wide, 3 ft. deep bears NW. and SE.</p>
20.120	<p>Descend into river cut, bears NW. and SE.</p> <p>The N-S 1/64 sec. cor. of secs. 7 and 8, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635.</p> <hr/>
	<p>From the C-W 1/16 sec. cor. of sec. 8.</p> <p>N. 0°04'50" E., on the N-S center line of the NW1/4 of sec. 8.</p> <p>Across level alfalfa field.</p>

FURTHER SUBDIVISION OF SECTION 8,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
10.009	<p>The C-S-NW 1/64 sec. cor. of sec. 8, monumented with a rebar, of unknown origin, 5/8 in. diam., 24 ins. long, set flush with the surface of the ground, with a corroded aluminum cap, 1 1/2 ins. diam., no marks visible, no record was recovered for this monument and is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 8 C-S-NW 1/64 2005</p> <p>Deposit rebar inside stainless post.</p> <p>Cor. is located under a barbwire fence, bears E. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°03'40" E., beginning new measurement.</p> <p>Continue across level alfalfa field.</p>
10.008	<p>True point for the NW 1/16 sec. cor. of sec. 8, at intersection with the E-W center line of the NW1/4, falls in flooded irrigation ditch under a barbwire fence, bears E. and W., where it is impractical to set a permanent monument.</p>
10.309	<p>Point selected for the witness NW 1/16 sec. cor. of sec. 8, on dirt embankment, 10 lks. wide, bears N. and S.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">WC NW 1/16 S 8 ↓ 2005</p> <p>Continue along E. side of barbwire fence.</p>
20.00	<p>Barbwire fence, bears E. and W.</p>
20.018	<p>Point for the C-N-NW 1/64 sec. cor. of sec. 8, on the top E. wall of a concrete irrigation ditch, 8 lks. wide, 2 ft. deep, bears NNW and SSE.</p> <p>Set a PK nail, 1 in. long, 1/4 in. diam., in a 1/4 in. drill hole.</p>

FURTHER SUBDIVISION OF SECTION 8,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 37°33' W., 3.5 lks. dist., with brass cap, mkd. RM C-N-NW 1/64 2.3 FT TO COR S8 2005 and an arrow pointing to the cor.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 65°57' W., 5.5 lks. dist., with brass cap, mkd. RM C-N-NW 1/64 3.6 FT TO COR S8 2005 and an arrow pointing to the cor.</p>
30.028	<p>The W 1/16 sec. cor. of secs. 5 and 8.</p>
	<hr/> <p>From the C-N 1/16 sec. cor. of sec. 8.</p> <p>N. 89°53'00" W., on the E-W center line of the NW1/4 of sec. 8.</p>
0.55	<p>Paved road, 35 lks. wide, bears N. and S.</p>
0.85	<p>Powerline, parallels road.</p>
0.95	<p>Barbwire fence, bears N. and S.</p>
	<p>Continue across level alfalfa field and along the N. side of a barbwire fence.</p>
20.142	<p>True point for the NW 1/16 sec. cor. of sec. 8.</p>
	<p>Continue along the N. side of barbwire fence.</p>
24.75	<p>Concrete lined irrigation ditch, 15 lks. wide, 3 ft. deep, drains SW.</p>
	<p>Continue across rolling land, covered with sagebrush and scattered cottonwood trees.</p>
29.80	<p>Left bank of the Walker River, bears NE. and SW., thence across river, course SW.</p>
32.40	<p>Right bank of the Walker River, bears NE. and SW.</p>
39.20	<p>Top right cutbank of the Walker River, bears NE. and SW.</p>
	<p>Continue across nearly level land, covered with sagebrush and grasses.</p>
40.25	<p>Barbwire fence, extending N. and S.</p>
40.286	<p>The N 1/16 sec. cor. of secs. 7 and 8.</p>
	<hr/> <p>From the C-N-N 1/64 sec. cor. of sec. 8, monumented with the sheared bottom end of an aluminum post, 2 1/2 ins. diam., still in an upright position, 4 ins. below the surface of the ground.</p>

FURTHER SUBDIVISION OF SECTION 8,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;"> $\begin{array}{c} C \\ N-N \ 1/64 \ \ S \ 8 \\ C \end{array}$ </p> <p style="text-align: center;">2005</p> <p>Deposit remains of aluminum post alongside stainless steel post and below surface of the ground.</p> <p>N. 89°53'40" W., on the E-W center line of the NE1/4NW1/4 of sec. 8.</p>
0.65	Paved road, 36 lks. wide, bears N. and S.
0.90	Powerline, parallels road.
1.00	Barbwire fence, bears N. and S. for 5 lks. to a fence cor. from which fences extend S. and W.
	Continue across level alfalfa field, and along N. side of barbwire fence.
13.90	Concrete lined irrigation ditch, 15 lks. wide, 3 ft. deep, drains SW.
20.153	The C-N-NW 1/64 sec. cor. of sec. 8.
	<hr/> <p>From the C-S-N 1/64 sec. cor. of sec. 8.</p> <p>N. 89°52'40" W., on the E-W center line of the SE1/4NW1/4 of sec. 8.</p>
0.50	Paved road, 36 lks. wide, bears N. and S.
0.75	Powerline, parallels road.
0.85	Barbwire fence, bears S. and N. for 5 lks. to a fence cor. from which fences extend N. and W.
	Continue across level alfalfa field, and along S. side of barbwire fence.
20.132	The C-S-NW 1/64 sec. cor. of sec. 8.
	<hr/> <p>N. 89°52'50" W., on the E-W center line of the SW1/4NW1/4 of sec. 8.</p> <p>Across level alfalfa field.</p>
13.90	Concrete lined irrigation ditch, 15 lks. wide, 3 ft. deep, drains SW.

FURTHER SUBDIVISION OF SECTION 8,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.02	Fence cor., with barbwire fences extending N., E. and W.
20.137	<p>The S-N 1/64 sec. cor. of secs. 7 and 8, monumented with an aluminum post, 2 1/2 ins. diam., projecting 4 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635.</p> <p>Cor. is located on the E. side of a railroad tie fence corner post, from which barbwire fences extend E. and S.</p>
<hr/>	
From the C-N-NW 1/64 sec. cor. of sec. 8.	
N. 89°54'30" W., on the E-W center line of the NW1/4NW1/4 of sec. 8.	
0.04	Concrete lined irrigation ditch, 8 lks. wide, drains SE.
4.04	<p>Concrete lined irrigation ditch, 15 lks. wide, drains SW.</p> <p>Continue across nearly level land, covered with sagebrush and grasses.</p>
4.70	Descend into river cut, bears NW. and S.
10.00	Left bank of the Walker River, bears SE. and NW., thence across river, course SE.
20.153	True point for the N-N 1/64 sec. cor. of secs. 7 and 8.
<hr/>	
<p>FURTHER SUBDIVISION OF SECTION 9, T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA</p>	
<hr/>	
<p>From the C-E 1/16 sec. cor. of sec. 9, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635.</p>	
N. 0°01'30" E., on the N-S center line of the NE1/4 of sec. 9.	
Across nearly level land, covered with sagebrush and grasses.	
14.95	Barbwire fence, bears NW. and SE.
20.017	<p>Point for the NW 1/16 sec. cor. of sec. 9, at intersection with the E-W center line of the NE1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
NE 1/16 S 9	
2005	

FURTHER SUBDIVISION OF SECTION 9,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From this cor., a weathered redwood post, 2x3x34 ins. long, with ground point, no marks visible, was found lying loose nearby, original position indeterminate, not utilized in the course of this survey.</p>
40.033	<p>The E 1/16 sec. cor. of secs. 4 and 9, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635, with a weathered redwood post, firmly set, projecting 15 ins. above the ground, no marks visible, W. and alongside cor.</p>
	<p>From the N 1/16 sec. cor. of secs. 9 and 10, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635.</p> <p>From this cor., a weathered redwood post, 2x2 1/2x31 ins. long, no marks visible, was found lying loose nearby, original position indeterminate, not utilized in the course of this survey.</p> <p>S. 89°59'50" W., on the E-W center line of the NE1/4 of sec. 9.</p> <p>Across nearly level land, covered with sagebrush and grasses.</p>
19.904	<p>The NE 1/16 sec. cor. of sec. 9.</p>
26.66	<p>Barbwire fence, bears NW. and SE.</p>
29.846	<p>Point for the C-W-NE 1/64 sec. cor. of sec. 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 9 C-W-NE 1/64</p> <p style="text-align: center;">2005</p>
39.788	<p>From this cor., a weathered redwood post, 2x3x31 ins. long, the marks 345 visible, was found lying loose nearby, original position indeterminate, not utilized in the course of this survey.</p> <p>The C-N 1/16 sec. cor. of sec. 9, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635.</p> <p>From this cor., a weathered redwood post, 2x3x22 ins. long, no marks visible, was found lying loose nearby, original position indeterminate, not utilized in the course of this survey.</p>

FURTHER SUBDIVISION OF SECTION 9,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p> <p>20.027</p>	<p>From the C-W-E 1/64 sec. cor. of sec. 9, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635.</p> <p>From this cor., a weathered redwood post, 2 ins. square, 31 ins. long, with ground point, no marks visible, was found lying loose nearby, original position indeterminate, not utilized in the course of this survey.</p> <p>N. 0°05'20" E., on the N-S center line of the SW1/4NE1/4 of sec. 9.</p> <p>The C-W-NE 1/64 sec. cor. of sec. 9.</p>
<p>20.023</p>	<p>From the E-W 1/64 sec. cor. of secs. 9 and 16.</p> <p>N. 0°10'10" E., on the N-S center line of the SE1/4SW1/4 of sec. 9.</p> <p>Across nearly level land, covered with sagebrush and grasses.</p> <p>The C-E-SW 1/64 sec. cor. of sec. 9, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635.</p> <p>From this cor., the SW 1/16 sec. cor. of sec. 9, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, the top half bent at a 90 degree angle to the base, bears S. 89°54'20" W., 10.005 chs. dist., with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SW 1/16 S 9</p> <p style="text-align: center;">2006</p> <p>Deposit aluminum post alongside stainless steel post and below the surface of the ground.</p>
	<p>From the W-W 1/64 sec. cor. of secs. 9 and 16.</p> <p>N. 0°10'20" E., on the N-S center line of the SW1/4SW1/4 of sec. 9.</p> <p>Across nearly level land, covered with sagebrush and grasses.</p>

FURTHER SUBDIVISION OF SECTION 9,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.019	<p>The C-W-SW 1/64 sec. cor. of sec. 9, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635.</p> <p>Cor. is located under a barbwire fence, extending E. and W.</p> <hr/> <p>N. 0°12'10" E., on the N-S center line of the NW1/4SW1/4 of sec. 9.</p> <p>Across nearly level land, covered with sagebrush and grasses.</p>
20.028	<p>The C-W-W 1/64 sec. cor. of sec. 9, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635.</p> <p>From this cor., a cor. of barbwire fences bears N. 70° W., 0.09 chs. dist., with fences extending N., S. and W.</p> <hr/> <p style="text-align: center;">METES-AND-BOUNDS SURVEY IN SECTION 6, T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From Angle Point No. 1, sec. 6, hereinbefore described.</p> <p>N. 0°10'10" W., on line 1-2.</p> <p>Over nearly level land, covered with scattered sagebrush and grasses.</p>
19.941	<p>Angle Point No. 2, sec. 6, on the E-W center line of the SW1/4 of sec. 7, hereinbefore described.</p> <hr/> <p style="text-align: center;">METES-AND-BOUNDS SURVEY IN SECTION 7, T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From Angle Point No. 1, sec. 7, identical with Angle Point No. 5, sec. 18, on the line bet. secs. 7 and 18, hereinbefore described.</p> <p>N. 0°10'50" E., on line 1-2.</p> <p>Over nearly level land, covered with scattered sagebrush and grasses.</p>
19.864	<p>Angle Point No. 2, sec. 7, on the E-W center line of the SW1/4 of sec. 7, hereinbefore described.</p> <hr/> <p>N. 0°06'20" E., on line 2-3.</p>

METES-AND-BOUNDS SURVEY IN SECTION 7,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Over nearly level land, covered with scattered sagebrush and grasses.
19.869	Angle Point No. 3, sec. 7, on the E-W center line of sec. 7, hereinbefore described. <hr/>
	N. 0°10'50" E., on line 3-4.
	Over nearly level land, covered with scattered sagebrush and grasses.
10.040	Point for Angle Point No. 5, sec. 7, established at midpoint bet. Angle Point No. 3, sec. 7, and Angle Point No. 4, sec. 7. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<p style="text-align: center;">T12N R29E AP 5 — S 7 2005</p>
	From this cor., a weathered redwood post, 2x3x28 ins. long, with illegible scribe marks visible, was found lying loose nearby, original position indeterminate, not utilized in the course of this survey.
20.080	Angle Point No. 4, sec. 7, on the E-W center line of the NW1/4 of sec. 7, hereinbefore described. <hr/>
	From Angle Point No. 5, sec. 7.
	S. 89°57'10" W., on line 5-6.
	Over nearly level land, covered with scattered sagebrush and grasses.
9.536	Angle Point No. 6, sec. 7, identical with the S-N 1/64 sec. cor. of secs. 7 and 12, on the W. bdy. of the Tp., hereinbefore described. <hr/>
	<p style="text-align: center;">METES-AND-BOUNDS SURVEY IN SECTION 18, T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>
	From Angle Point No. 1, sec. 18, on the line bet. secs. 18 and 19, hereinbefore described.
	N. 0°01'40" E., on line 1-2.
	Over nearly level land, covered with scattered sagebrush and grasses.
20.004	Angle Point No. 2, sec. 18, on the E-W center line of the SW1/4 of sec. 18, hereinbefore described. <hr/>

METES-AND-BOUNDS SURVEY IN SECTION 18,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p> <p>20.004</p> <p>19.996</p> <p>12.55</p> <p>12.85</p> <p>20.001</p>	<p>N. 0°01'40" E., on line 2-3.</p> <p>Over nearly level land, covered with scattered sagebrush and grasses.</p> <p>Angle Point No. 3, sec. 18, on the E-W center line of sec. 18, hereinbefore described.</p> <hr/> <p>N. 0°00'50" W., on line 3-4.</p> <p>Over nearly level land, covered with scattered sagebrush and grasses.</p> <p>Angle Point No. 4, sec. 18, on the E-W center line of the NW1/4 of sec. 18, hereinbefore described.</p> <hr/> <p>N. 0°05'10" W., on line 4-5.</p> <p>Over nearly level land, covered with scattered sagebrush and grasses.</p> <p>Abandoned irrigation ditch, 15 lks. wide, 4 ft. deep, bears NE. and SW.</p> <p>Dirt road, 10 lks. wide, parallels ditch.</p> <p>Angle Point No. 5, sec. 18, identical with Angle Point No. 1, sec. 7, on the line bet. secs. 7 and 18, hereinbefore described.</p>
<p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The lands contained within the scope of this survey are generally level sandy river deposits at an average elevation of about 4100 ft. above sea level. The vegetation generally is sagebrush, grasses and low vegetation where the land is undeveloped, except where the Walker River meanders within its own cut. Within this cut, running generally through section 6, section 7, the W1/2 of section 8, and section 18, and about 30 to 40 ft. deep, large cottonwood trees, willows and invasive tamarisk is found. On the developed lands found in section 5, section 6, section 8, and section 16, alfalfa is grown.</p> <p>The area is southeast of Schurz, Nevada, about 1 mile with access to the lands east of the river being gained via a paved road running southeast from the post office at Schurz. Access to the lands west of the river are gained via dirt roads running from the store and gas station on Highway No. 95 south of Schurz. Several irrigation ditches are found with a few being abandoned along with developed fields, testimony to the limited resources of the Walker River with increased activity upstream in Mason and Smith Valleys.</p> <hr/>	

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Lance A. Barney	Cadastral Surveyor
Steven E. Dagitz	Surveying Technician
Richard A. Harrison	Surveying Technician
Kane M. Hellebust	Surveying Technician
Edward Thayer	Surveying Technician
Michelle E. Martin	Supervisory Range Technician
Derrick J. Rader	Supervisory Range Technician
Antwan R. Dickson	Survey Aid
Quentaous Jones	Survey Aid

CERTIFICATE OF SURVEY

We, Don R. Aschenbach, Cadastral Surveyor, and Mark G. Petrosine, Surveying Technician, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 15th day of April, 2005, we have dependently resurveyed a portion of the west boundary, a portion of the subdivisional lines and a portion of the subdivision-of-section lines of sections 6 and 8, subdivided sections 7, 16, 17 and 18, further subdivided sections 5, 6, 8 and 9, and executed metes-and-bounds surveys in sections 6, 7 and 18, Township 12 North, Range 29 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

August 20, 2007

(Date)

Don R Aschenbach

(Cadastral Surveyor)

August 20, 2007

(Date)

Mark G Petrosine

(Surveying Technician)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of the dependent resurvey of a portion of the west boundary, a portion of the subdivisional lines and a portion of the subdivision-of-section lines of sections 6 and 8, the subdivision of sections 7, 16, 17 and 18, the further subdivision of sections 5, 6, 8 and 9, and metes-and-bounds surveys in sections 6, 7 and 18, Township 12 North, Range 29 East, of the Mount Diablo Meridian, in the State of Nevada, executed by Don R. Aschenbach, Cadastral Surveyor, and Mark G. Petrosine, Surveying Technician, having been critically examined and found correct, are hereby approved.

August 28, 2007

(Date)

David P. Moran

(Chief Cadastral Surveyor, Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 12 N., R. 29 E., Mount Diablo Meridian, Nevada, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor, Nevada)~~