

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF

A PORTION OF THE SOUTH BOUNDARY OF  
TOWNSHIP 14 NORTH, RANGE 25 EAST;

A PORTION OF THE SUBDIVISIONAL LINES AND  
PORTIONS OF MINERAL SURVEY NOS. 4499, 4531, AND 4778,

AND THE

SUBDIVISION OF CERTAIN SECTIONS,  
TOWNSHIP 13 NORTH, RANGE 25 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

EXECUTED BY

Don R. Aschenbach, Cadastral Surveyor

Under Special Instructions dated March 28, 2002,  
and approved March 28, 2002,  
which provided for the surveys included under Group No. 806,  
and Assignment Instructions dated April 19, 2002.

Survey commenced April 22, 2002

Survey completed November 30, 2004

INDEX DIAGRAM

TOWNSHIP 13 NORTH, RANGE 25 EAST, MOUNT DIABLO MERIDIAN, NEVADA

	6	4	2			
6	32 5	23 4	11 3	2	1	
	31	21				
7	30 8	19 9	10 10	11	12	
	28	17				
18	27 17	15 16	8 15	14	13	
	26	15				
19	25 20	14 21	6 22	23	24	
	24	13				
30	29	28	27	26	25	
31	32	33	34	35	36	

- Dependent Resurvey of a Portion of Mineral Survey No. 4499 . pgs 34 - 36
- Dependent Resurvey of a Portion of Mineral Survey No. 4531 . pgs 37 - 48
- Dependent Resurvey of a Portion of Mineral Survey No. 4778 . pgs 49 - 51
- Subdivision of Section 4 .....pgs 52 - 54
- Subdivision of Section 5 .....pgs 54 - 57
- Subdivision of Section 8 .....pgs 57 - 60
- Subdivision of Section 9 .....pgs 60 - 65
- Subdivision of Section 16 .....pgs 65 - 70
- Subdivision of Section 17 .....pgs 70 - 82
- Subdivision of Section 20 .....pgs 82 - 88
- Subdivision of Section 21 .....pgs 88 - 91

## TOWNSHIP 13 NORTH, RANGE 25 EAST, MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

The following field notes are those of the dependent resurvey of a portion of the south boundary of Township 14 North, Range 25 East; a portion of the subdivisional lines and portions of Mineral Survey Nos. 4499, 4531, and 4778, and the subdivision of certain sections, Township 13 North, Range 25 East, Mount Diablo Meridian, Nevada.

The north, south, east, and west boundaries were surveyed by U.S. Deputy Surveyors R.A. Chase and A. Lash, Jr., in 1868 under Contract No. 8.

The east four tiers of the subdivisional lines were surveyed by U.S. Deputy Surveyor A. Lash, Jr., in 1868 under Contract No. 20.

A portion of the south boundary was dependently and independently resurveyed, the west boundary, portions of the north boundary and the fourth meridional line of the subdivisional lines were dependently resurveyed, and the west two tiers of the subdivisional lines were surveyed by U.S. Cadastral Engineer E. Voigt and U.S. Transitman W.H. Good in 1921 under Group No. 85.

Mineral Survey No. 4499 was surveyed by U.S. Mineral Surveyor G.W. Malone in 1921.

Mineral Survey No. 4531 was surveyed by U.S. Mineral Surveyor G.W. Lloyd in 1922.

Mineral Survey No. 4778 was surveyed by U.S. Mineral Surveyor C.V. Taylor in 1944.

Before restoring the corners, the lines of the original surveys were retraced and diligent search made for any evidence of the original corners and other calls of the original field note record.

The mineral surveys pertinent to this resurvey are located mostly in Yerington Mine open pit; only one mineral survey corner was recovered. The lost corners required for the resurvey of the mineral surveys were reestablished at record bearing and distance from Corner No. 4, Mineral Survey No. 4778, No. 38 lode.

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 806 dated March 28, 2002.

Measurements were made with Trimble 4700 GPS receivers. The mean bearings of the lines and horizontal equivalents of ground distances only are entered in the field notes.

095

## TOWNSHIP 13 NORTH, RANGE 25 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>The geographic position (NAD 1983) of the 1/4 section corner of section 31 only, T. 14 N., R. 25 E., as determined by survey grade global positioning system receivers, in 2002, from National Geodetic Survey control (formerly U.S. Coast and Geodetic Survey triangulation) station "CARSON HILL", in section 24, T. 14 N., R. 24 E., is as follows:</p> <p>Latitude: 39°01'33.766" N. Longitude: 119°13'39.902" W.</p> <p>The mean magnetic declination is 15°30' East, as shown on the U.S. Geological Survey quadrangle map "YERINGTON, NEV." provisional edition dated 1986.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY, T. 14 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of the Survey Executed by R.A. Chase and A. Lash, Jr., in 1868, and the Resurvey Executed by E. Voigt and W.H. Good, in 1921</p> <hr/> <p>Beginning at the cor. of secs. 3, 4, 33 and 34, determined by Nevada Department of Highways, in 1934, as shown on Right-of-Way Map Route 2B-A, Sec. A, and was adopted by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1981, as recorded in Lyon County Survey File No. 67452, monumented with a rebar, 5/8 in. diam., with remains of aluminum cap, firmly set, 2 ft. below the surface of the ground. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T14N</td> <td>R25E</td> </tr> <tr> <td>S33</td> <td>S34</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td>S 4</td> <td>S 3</td> </tr> <tr> <td colspan="2" style="text-align: center;">T13N</td> </tr> <tr> <td colspan="2" style="text-align: center;">2004</td> </tr> </table> <p>Deposit the rebar inside of the stainless steel post.</p> <p>The corner is located on E. side of U.S. Highway No. 95A.</p> <p>S. 89°39'30" W., bet. secs. 4 and 33.</p> <p>Over U.S. Highway No. 95A.</p> <p>0.60 Enter Luzier Lane, extending W.</p>	T14N	R25E	S33	S34	-----		S 4	S 3	T13N		2004	
T14N	R25E												
S33	S34												
-----													
S 4	S 3												
T13N													
2004													

096

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 14 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

40.041

The 1/4 sec. cor. of secs. 4 and 33, determined by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1981, monumented with a rebar, 5/8 in. diam., and remains of an aluminum cap, firmly set, flush with the asphalt surface of Luzier Lane, as recorded in Lyon County Survey File No. 67452. This is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a copper-coated steel stake, 24 ins. long, 1/2 in. diam., 26 ins. in the ground, the top is 2 ins. below the asphalt surface of Luzier Lane, with brass cap mkd.

T14N R25E  
S33  
1/4 —  
S 4  
T13N

2002

from which

A PK nail with shiner, 1 ft. above base of a railroad tie projecting 4 ft. above ground, bears N. 42°25'00" E., 0.365 chs. dist.

A PK nail with shiner, in a concrete retaining wall, bears S. 25°21'00" E., 0.580 chs. dist.

Remove and dispose of the rebar.

\_\_\_\_\_

S. 89°39'40" W., beginning new measurement.

39.896

The cor. of secs. 4, 5, 32 and 33, determined by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1981, monumented with a rebar, 5/8 in. diam., firmly set, flush with the asphalt surface of Luzier Lane, as recorded in Lyon County Survey File No. 67452. This is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 31 ins. in the ground, the top is 3 ins. below the asphalt surface of Luzier Lane, over a plastic-encased magnet, with brass cap mkd.

T14N R25E  
S32 | S33  
— | —  
S 5 | S 4  
T13N

2002

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 14 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p>	<p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 22°34'00" E., 0.474 chs. dist., with brass cap mkd. T13N R25E S4 RM 31.3 FT 2002, and an arrow pointing to the cor.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 28°11'00" W., 0.497 chs. dist., with brass cap mkd. T13N R25E S5 RM 32.8 FT 2002, and an arrow pointing to the cor.</p> <p>Deposit the rebar inside the stainless steel post.</p> <hr/> <p>S. 89°38'30" W., on the S. bdy. of sec. 32.</p> <p>Along Luzier Lane.</p> <p>16.00 Remains of railroad grade, bears N. and S.</p> <p>39.691 The 1/4 sec. cor. of sec. 32 only, determined by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1985, monumented with a rebar, 5/8 in. diam., set flush with the asphalt surface of Luzier Lane, with a plastic cap with illegible marks, as recorded in Lyon County Survey File No. 95548. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a copper-coated steel stake, 24 ins. long, 1/2 in. diam., 26 ins. in the ground, the top is 2 ins. below the asphalt surface of Luzier Lane, with brass cap mkd.</p> <p style="text-align: center;">T14N R25E 1/4 S32 <hr/>2003</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 40°33'00" E., 0.896 chs. dist., with brass cap mkd. RM 59.2 FT 2002, and an arrow pointing to the cor.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 54°11'00" W., 1.176 chs. dist., with brass cap mkd. RM 77.6 FT 2002, and an arrow pointing to the cor.</p> <p>Remove and dispose of the rebar.</p> <hr/>
---------------	--

098

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 14 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS					
1.834	<p>S. 89°38'00" W., beginning new measurement.</p> <p>The 1/4 sec. cor. of sec. 5 only, T. 13 N., R. 25 E., at proportionate dist.; there is no remaining evidence of the original corner.</p> <p>Set a copper-coated steel stake, 24 ins. long, 1/2 in. diam., 2 ins. below the asphalt surface of Luzier Lane, with brass cap mkd.</p> <div style="text-align: center;"> <hr style="width: 10%; margin: 0 auto;"/> <p>1/4 S 5 T13N R25E</p> <p>2002</p> </div> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 33°23'10" W., 0.835 chs. dist., with brass cap mkd. T13N R25E S5 RM 55.1 FT 2002, and an arrow pointing to the cor.</p>				
21.770	<p>Point for the W 1/16 sec. cor. of sec. 5 only, T. 13 N., R. 25 E., hereinafter described.</p>				
39.714	<p>The cor. of secs. 31 and 32 only, determined by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1988, monumented with a rebar, 5/8 in. diam., firmly set, 6 ins. below the asphalt surface of Luzier Lane, as recorded in Lyon County Survey File No. 117811. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a copper-coated steel stake, 24 ins. long, 1/2 in. diam., 30 ins. in the ground, the top is 6 ins. below the asphalt surface of Luzier Lane, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1" style="margin: 0 auto;"> <tr> <td style="padding: 2px;">T14N</td> <td style="padding: 2px;">R25E</td> </tr> <tr> <td style="padding: 2px;">S31</td> <td style="padding: 2px;">S32</td> </tr> </table> <p>S 5 T13N</p> <p>2003</p> </div> <p>from which</p> <p>A PK nail with shiner, driven into a power pole, 1 ft. above ground, bears S. 31°11' E., 1.002 chs. dist.</p> <p>A PK nail with shiner, driven into a wood fence post, 1 ft. above ground, bears S. 4°33' W., 0.947 chs. dist.</p> <p>A PK nail with shiner, driven into a power pole, 1 ft. above ground, bears S. 53°17' W., 0.702 chs. dist.</p>	T14N	R25E	S31	S32
T14N	R25E				
S31	S32				

099

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 14 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Remove and dispose of the rebar.</p> <hr/> <p>S. 89°39'40" W., on the S. bdy. of sec. 31.</p> <p>Continue along Luzier Lane.</p> <p>0.50 Power line, bears N. and S.</p> <p>1.992 The closing cor. of secs. 5 and 6, T. 13 N., R. 25 E., hereinafter described.</p> <p>39.849 The 1/4 sec. cor. of sec. 31 only, monumented with the remains of the iron post, 1 in. diam., firmly set, top is 12 ins. below ground. The brass cap is missing.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T14N R25E 1/4 S31 <hr/>2002</p> <p>Deposit the remains of the original iron post alongside the stainless steel post.</p> <p>The corner is located on N. side of Luzier Lane.</p> <p>From this corner, National Geodetic Survey control (formerly U.S. Coast and Geodetic Survey triangulation) station "CARSON HILL", monumented with a standard brass disk, cemented in rock outcropping, with top mkd. CARSON HILL, bears N. 13°07'30" W., 183.906 chs. dist.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of the Survey Executed by A. Lash, Jr., in 1868, and the Resurvey by E. Voigt and W.H. Good in 1921</p> <hr/> <p>From the cor. of secs. 21, 22, 27 and 28, determined by R.C. Downer, Nevada Registered Engineer No. 446, in 1964, as recorded in Lyon County Survey File No. 88796, and re-determined by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1989, as recorded in Lyon County Survey File No. 121728, monumented with a rebar, 5/8 in. diam., firmly set in concrete and flush with the surface of the ground, with aluminum cap mkd. T13N R25E 21 22 27 28 1988 RLS 4045. This is accepted as the best available evidence of the position of the original corner.</p>
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>The cor. is located 2 lks. E. of the intersection of fences, extending N. and W.</p> <p>N. 0°22'20" E., bet. secs. 21 and 22.</p> <p>Over nearly level pasture lands.</p> <p>8.50 Right bank of Walker River, course E.</p> <p>10.20 Left bank of Walker River, course E.</p> <p>18.20 Left bank of Walker River, course N. 60° W.</p> <p>19.911 Point for the S 1/16 sec. cor. of secs. 21 and 22. Not monumented.</p> <p>20.10 Right bank of Walker River, course N. 60° W.</p> <p>31.00 Right bank of Walker River, course N. 25° E.</p> <p>38.10 Right bank of the Walker River, course N. 50° W.</p> <p>39.822 The 1/4 sec. cor. of secs. 21 and 22, reestablished by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1989, monumented with a rebar, 5/8 in. diam., firmly set, 4 ins. below the surface of the ground, with aluminum cap mkd. T13N R25E S21 S22 1988 RLS 4045, as recorded in Lyon County Survey File No. 121728. This is accepted as a careful and faithful reestablishment of the position of the original corner.</p> <hr/> <p>N. 0°21'40" E., beginning new measurement.</p> <p>19.908 The N 1/16 sec. cor. of secs. 21 and 22, determined by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1993, monumented with a rebar, 5/8 in. diam., firmly set 12 ins. below the surface of the ground, with aluminum cap mkd. PLS 10576 DIRECT SURV CO, as recorded in Lyon County Survey File No. 160786. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>From this corner, a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA E1-39+65.42 PC DIST 43.75 ANGLE 90, bears N. 89°37'00" W., 9.481 chs. dist.</p> <p>From this same corner, a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA E1-39+65.42 PC DIST 45.22 ANGLE 90, bears N. 86°39'30" W., 10.757 chs. dist.</p> <hr/> <p>N. 0°21'40" E., beginning new measurement.</p> <p>19.908 The cor. of secs. 15, 16, 21 and 22, determined by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1981, monumented with a rebar, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, as recorded in Lyon County Survey File No. 67451. This is accepted as the best available evidence of the position of the original corner.</p>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS													
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T13N</td> <td>R25E</td> </tr> <tr> <td>S16</td> <td>S15</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td>S21</td> <td>S22</td> </tr> </table> <p style="text-align: center;">2002</p> <p>Deposit the rebar inside and set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <p>From this corner, a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA E1-46+10.43 PT DIST 43.83 ANGLE 90, bears S. 34°39'50" W., 12.434 chs. dist.</p> <p>From this corner, a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA E1-46+10.43 PT DIST 46.71 ANGLE 90, bears S. 39°54'20" W., 13.152 chs. dist.</p> <hr/> <p>N. 0°09'20" E., bet. secs. 15 and 16.</p> <p>Over nearly level land.</p> <p>0.50 Road, asphalt surface, 60 lks. wide, bears E. and W.</p> <p>5.00 Right bank of Walker River, course N. 50° E.</p> <p>8.00 Left bank of Walker River, course N. 50° E.</p> <p>20.032 The S 1/16 sec. cor. of secs. 15 and 16, determined by Walter G. Reid, Nevada Professional Land Surveyor No. 235, in 1966, as recorded in Lyon county Survey File No. 97641, and adopted by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1984, monumented with a rebar, 5/8 in. diam., 5 ins. below the surface of the ground, with a plastic cap mkd. PLS 4045, as recorded in Lyon County Survey File No. 85452. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic encased-encased magnet, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>S 1/16</td> <td></td> </tr> <tr> <td>S16</td> <td>S15</td> </tr> </table> <p style="text-align: center;">2002</p> <p>Deposit the rebar inside and set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <hr/>	T13N	R25E	S16	S15			S21	S22	S 1/16		S16	S15
T13N	R25E												
S16	S15												
S21	S22												
S 1/16													
S16	S15												

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°07'50" E., beginning new measurement.
20.076	<p>The 1/4 sec. cor. of secs. 15 and 16, determined by the Nevada Department of Highways, monumented with a rebar, 5/8 in. diam., firmly set in a standard concrete highway monument. This position has been adopted and recorded by various professional land surveyors, as indicated on land survey records in Lyon County, and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13N R25E 1/4 S16 S15</p> <p>2002</p> </div> <p>Deposit the rebar inside the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/>
	N. 0°17'00" E., beginning new measurement.
32.20	U.S. Highway No. 95A, 60 lks. wide, asphalt surface, bears N. 5° E. and S. 5° W.
40.226	<p>The cor. of secs. 9, 10, 15 and 16, determined by person(s) unknown, monumented with a rebar, 1/2 in. diam., 12 ins. below the surface of the ground. This position has been adopted by various professional land surveyors as indicated on land survey records in Lyon County, and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 34 ins. in the ground, 6 ins. below the asphalt surface of driveway, bears E. and W., over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13N R25E S 9   S10 <hr style="width: 10%; margin: auto;"/>S16   S15</p> <p>2002</p> </div> <p>from which</p> <p style="padding-left: 40px;">A PK nail with shiner, in a concrete pad, 3x3 ft. square, bears S. 0°18'00" W., 1.279 chs. dist.</p> <p style="padding-left: 40px;">An X chiseled on a metal fence corner post, 1 ft. above ground, fences extending S. and W., bears S. 80°11'00" W., 1.588 chs. dist.</p> <p>Deposit the rebar inside the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>N. 0°12'40" E., bet. secs. 9 and 10.</p>
	<p>Over nearly level land.</p>
7.00	<p>U.S. Highway No. 95A, 60 lks. wide, asphalt surface, bears N. 5° W. and S. 5° E.</p>
40.315	<p>The 1/4 sec. cor. of secs. 9 and 10, determined by person(s) unknown, adopted by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1986, monumented with an iron pipe, 1/2 in. diam., as recorded in Lyon County Survey File No. 100056. This is accepted as the best available evidence of the position of the original corner.</p>
	<p>At the corner point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p>T13N R25E 1/4 S 9   S10</p>
	<p>2002</p>
	<p>Deposit the iron pipe and set a carsonite post, 5 ft. long, alongside the stainless steel post.</p>
	<p>The corner is located at the intersection of fence lines, extending N., S. and E.</p>
	<p>N. 0°14'20" E., beginning new measurement.</p>
6.70	<p>Graveled road, bears E. and W.</p>
19.956	<p>The N 1/16 sec. cor. of secs. 9 and 10, determined by person(s) unknown, monumented with an iron pipe, 1/2 in. diam., projecting 12 ins. above the ground. This is accepted as a careful and faithful determination of the position of the corner.</p>
	<p>At the corner point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p>N 1/16 S 9   S10</p>
	<p>2002</p>
	<p>Deposit the iron pipe alongside the stainless steel post.</p>
	<p>From this corner, a copper rod, 3/16 in. diam., set in a standard Nevada Department of Transportation concrete monument, bears S. 36°37'40" W., 3.409 chs. dist.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p> <p>2.25</p> <p>19.956</p> <p>4.50</p> <p>15.50</p> <p>19.996</p>	<p>From this same corner, a copper rod, 3/16 in. diam., set in a standard Nevada Department of Transportation concrete monument, bears S. 77°25'50" W., 8.212 chs. dist.</p> <hr/> <p>N. 0°14'20" E., beginning new measurement.</p> <p>Unimproved dirt road, bears N. 45° E. and S. 30° W.</p> <p>The cor. of secs. 3, 4, 9 and 10, determined by person(s) unknown, adopted by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1981, as recorded in Lyon County Survey File No. 67452, also adopted by Corey L. Rice, Nevada Professional Land Surveyor No. 12468, in 1998, as recorded in Lyon County Survey File No. 221481, monumented with an iron pipe, 1/2 in. diam., firmly set, flush with the surface of the ground. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T13N</td> <td>R25E</td> </tr> <tr> <td>S 4</td> <td>S 3</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td>S 9</td> <td>S10</td> </tr> </table> <p style="text-align: center;">2002</p> <p>Deposit the rebar inside and set a carsonite post, 5 ft. long, alongside of the stainless steel post.</p> <p>From this corner, a copper rod, 3/16 in. diam., set in a standard Nevada Department of Transportation concrete monument, bears S. 18°47'10" W., 7.146 chs. dist.</p> <p>From this same corner, a copper rod, 3/16 in. diam., set in a standard Nevada Department of Transportation concrete monument, bears S. 53°16'30" W., 10.399 chs. dist.</p> <hr/> <p>N. 0°24'50" E., bet. secs. 3 and 4.</p> <p>Over nearly level land.</p> <p>Unimproved dirt road, bears N. 80° E. and S. 80° W.</p> <p>Unimproved dirt road, bears N. 40° E. and S. 30° W.</p> <p>The S 1/16 sec. cor. of secs. 3 and 4, determined by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1986, monumented with a rebar, 5/8 in. diam., with an aluminum cap mkd. T13N R25E S1/16 S3 S4 1986 RLS 4045, as recorded in Lyon County Survey File No. 102305. This is accepted as a careful and faithful determination of the position of the corner.</p>	T13N	R25E	S 4	S 3			S 9	S10
T13N	R25E								
S 4	S 3								
S 9	S10								

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S 4   S 3</p> <p style="text-align: center;">2002</p> <p>Deposit the rebar inside and set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <hr/> <p>N. 0°23'50" E., beginning new measurement.</p>
19.986	<p>The 1/4 sec. cor. of secs. 3 and 4, perpetuated by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1981, monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, with a plastic cap mkd. RLS 4045 DENSON, alongside of which is a trapstone, 22x12x8 ins., (Record, 14x8x6 ins.) laying loosely on the ground, mkd. 1/4 on one face, as recorded in Lyon County Survey File No. 67452.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T13N R25E 1/4 S 4   S 3</p> <p style="text-align: center;">2002</p> <p>Deposit the original stone, the rebar, and set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <hr/> <p>N. 0°26'10" E., beginning new measurement.</p>
19.521	<p>From this point, a rebar, 5/8 in. diam., firmly set, determined by Corey L. Rice, Nevada Professional Land Surveyor No. 12468, in 1998, with aluminum cap mkd. COREY L RICE PLS 12468, as recorded in Lyon County Survey File No. 221481, bears West, 0.010 chs. dist. This position is not utilized in this survey.</p>
38.133	<p>The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., hereinbefore described.</p> <hr/>

## 106

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	From the cor. of secs. 21, 22, 27 and 28. N. 89°44'30" W., bet. secs. 21 and 28. Over nearly level land.
13.40	Fence, bears E.
14.00	Right bank of Walker River, course N. 10° W.
15.50	Left bank of Walker River, course N. 10° W.
19.588	Point for the E 1/16 sec. cor. of secs. 21 and 28. Not monumented.
24.485	Point for the E-W-E 1/256 sec. cor. of secs. 21 and 28.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. the ground, over a plastic-encased magnet, with brass cap mkd.  S21 E-W-E 1/256 S28  2002  Set a carsonite post, 5 ft. long, alongside the stainless steel post.
24.90	Nevada State Route No. 339, asphalt surface, 60 lks. wide, bears N. 17° E. and S. 17° W.
29.382	Point for the W-E 1/64 sec. cor. of secs. 21 and 28. Not monumented.
29.80	Enter mine tailings, edge bears N. 25° E. and S. 25° W.
39.176	Point for the 1/4 sec. cor. of secs. 21 and 28, at proportionate dist.; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet with brass cap mkd.  T13N R25E S21 1/4 — S28  2002  Set a carsonite post, 5 ft. long, alongside the stainless steel post.
55.40	Leave mine tailings, edge bears N. 30° W. and S. 30° E.
67.90	Asphalt road, 50 lks. wide, bears N. 65° W. and S. 65° E.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
78.352	<p>The cor. of secs. 21 and 28 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. as described in the field notes of T. 13 N., R. 25 E., executed under Group No. 85.</p>
	<p>N. 0°38'20" W., on the W. bdy. of sec. 21.</p> <p>Over nearly level land.</p>
1.665	<p>The closing cor. of secs. 20 and 29, hereinafter described.</p>
14.70	<p>Enter mine tailings, edge bears N. 30° W. and S. 45° E.</p>
39.669	<p>Point for the 1/4 sec. cor. of sec. 21 only, at proportionate dist.; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T13N R25E   1/4   S21</p> <p style="text-align: center;">2002</p>
	<p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <p>Over mine tailings.</p>
41.393	<p>Point for the 1/4 sec. cor. of sec. 20 only, at proportionate dist.; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T13N R25E 1/4   S20  </p> <p style="text-align: center;">2002</p>
	<p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <p>From this corner, Anaconda Control Station UU, monumented with an iron pipe, 2 ins. diam., firmly set in concrete, bears N. 60°33'10" W., 43.980 chs. dist.</p>
61.390	<p>Point for the N 1/16 sec. cor. of sec. 20 only. Not monumented.</p>
67.659	<p>Intersect line 2-3, Black Horse lode, at a point from which Cor. No. 2, Black Horse lode, identical with Cor. No. 4, West Starlight lode, both of Mineral Survey No. 4531, hereinafter described, bears S. 82°51'00" E., 10.283 chs. dist.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
67.90	Enter open pit, edge bears N. 60° W. and S. 65° E.
74.728	Point selected for the witness cor. to the cor. of secs. 16 and 21 only.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<div style="text-align: center;"> <p>WC T13N R25E ↑ S16 S20 ———   S21</p> <p>2004</p> </div>
79.338	<p>The true point for the cor. of secs. 16 and 21 only, determined utilizing coordinates from the survey data record "Triangulation Stations Yerington Mines", by M. Smith, dated January 9, 1951, obtained from the SRK Consulting office, Yerington, Nevada, which represents information observed prior to ground surface disturbance, and is corroborated by additional Anaconda coordinate records dated 1993. This is accepted as the best available evidence of the position of the original corner. Cor. is located in open pit where it is impracticable to establish a permanent monument.</p> <hr/> <p>From the cor. of secs. 15, 16, 21 and 22. N. 89°57'50" W., bet. secs. 16 and 21. Over nearly level land.</p>
15.20	Enter open pit, edge bears N. 60° W. and S. 30° E.
19.933	Point for the E 1/16 sec. cor. of secs. 16 and 21. Not monumented.
39.866	Point for the 1/4 sec. cor. of secs. 16 and 21, at proportionate dist.; there is no remaining evidence of the original corner. Cor. is located in open pit where it is impracticable to establish a permanent monument.
79.732	<p>The true point for the cor. of secs. 16 and 21 only.</p> <hr/> <p>N. 0°04'40" E., on the W. bdy. of sec. 16. Over open pit.</p>
2.049	The point for the closing cor. of secs. 17 and 20, hereinafter described.
22.035	Point for the S 1/16 sec. cor. of sec. 17 only. Not monumented.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
34.143	Intersect line 1-2, No. Twenty Four lode, at a point from which the true point for Cor. No. 1, No. Twenty Four lode, identical with Cor. No. 2, No. 38 lode and Cor. No. 1, No. Twenty Five lode, all of Mineral Survey No. 4778, hereinafter described, bears N. 82°54'00" W., 6.648 chs. dist.
35.10	Leave open pit, edge bears N. 80° W. and S. 65° E.
39.00	Graveled road, 60 lks. wide, bears N. 40° W. and S. 40° E.
40.721	<p>The 1/4 sec. cor. of sec. 16 only, determined utilizing coordinates from the survey data record "Triangulation Stations Yerington Mines", by M. Smith, dated January 9, 1951, obtained from the SRK Consulting office, Yerington, Nevada, which represents information observed prior to ground surface disturbance, and is identical to the position determined by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1987, monumented with a rebar, 5/8 in. diam., firmly set, as recorded in Lyon County Survey File No. 111528. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T13N R25E   1/4   S16</p> <p style="text-align: center;">2002</p> <p>Deposit the rebar inside and set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°01'40" E., beginning new measurement.</p>
1.300	<p>Point for the 1/4 sec. cor. of sec. 17 only, at proportionate dist.; there is no remaining evidence of original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T13N R25E 1/4   S17  </p> <p style="text-align: center;">2002</p> <p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p>
12.50	Asphalt road, 45 lks. wide, bears N. 40° E. and S. 40° W.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
17.20	Graveled road, 60 lks. wide, bears N. 40° E. and S. 40° W.
20.377	Point for the N 1/16 sec. cor. of sec. 16 only.
	Set a stainless steel post, 28 ins. long. 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	$\begin{array}{ c} \text{N } 1/16 \\ \hline \text{S } 16 \end{array}$
	2002
	from which
	<p>The SW cor. of a metal building, 30x40 ft. bears N. 4°35'00" E., 6.956 chs. dist., the long side bears N. 50° W. and S. 50° E.</p>
	Set a carsonite post, 5 ft. long, alongside the stainless steel post.
21.302	Point for the N 1/16 sec. cor. of sec. 17 only. Not monumented.
23.135	Intersect the S. side of a metal frame building, 235x60 ft., the SE cor. bears S. 50° E., 0.56 chs. dist., the long side bears N. 50° W. and S. 50° E.
40.754	The cor. of secs. 9 and 16 only, monumented with an iron post, 2 ins. diam., firmly set, 2 ft. below the surface of the ground, with brass cap mkd. as described in the field notes of T. 13 N., R. 25 E., executed under Group No. 85.
	From the cor. of secs. 9, 10, 15 and 16.
	N. 89°13'00" W., bet. secs. 9 and 16.
	Over rolling hills.
6.061	A property cor. determined by Walter G. Reid, Nevada Registered Professional Engineer No. 235, in 1964, monumented with a rebar, 1/2 in. diam., as recorded in Lyon County Survey File No. 97464.
	The cor. falls 0.01 chs. dist., S., of fence line, bears E. and W.
14.924	From this point, a property cor. determined by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1987, monumented with a rebar, 5/8 in. diam., with a metal tag mkd. 4045, set in a fence line, bears E. and W., as recorded in Lyon County Survey File No. 111531, bears South, 0.006 chs. dist.
	From this same point, a property cor. determined by Lawrence A. Bagdon, Nevada Professional Land Surveyor No. 2344, in 1967, monumented with a rebar, 1/2 in. diam., as recorded in Lyon County Survey File No. 99942, bears S. 53°20'00" W., 0.010 chs. dist.

## 111

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
16.819	From this point, a property cor. determined by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1987, monumented with a rebar, 5/8 in. diam., set in a fence line, bears E. and W., as recorded in Lyon County Survey File No. 111531, bears South, 0.006 chs. dist.
20.023	<p>Point for the E 1/16 sec. cor. of secs. 9 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 9 E 1/16 — S16 2002</p> <p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <p>The corner is located at the intersection of fence lines, extending S., E. and W.</p>
40.046	<p>The 1/4 sec. cor. of secs. 9 and 16, determined by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1987, monumented with a rebar, 5/8 in. diam., firmly set, with an aluminum cap mkd. T13N R25E 1/4 S9 S16 1983 RLS 4045, as recorded in Lyon County Survey File No. 82467. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T25N R13E S 9 1/4 — S16 2002</p> <p>Deposit the rebar and set a carsonite post, 5 ft. long, alongside the stainless steel post.</p>
	<p style="text-align: center;">N. 89°04'40" W., beginning new measurement.</p>
12.40	Asphalt road, 45 lks. wide., bears N. 35° E. and S. 35° W.
15.90	Enter mine tailings, edge bears NE and SW.
19.950	Point for the W 1/16 sec. cor. of secs. 9 and 16. Not monumented.

## 112

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.40	Leave mine tailings, edge bears NW and SE.
39.900	The cor. of secs. 9 and 16 only.
	N. 0°19'30" E., on the W. bdy. of sec. 9.
	Over nearly level land.
0.20	Enter mine tailings, edge bears NW and SE.
0.550	The closing cor. of secs. 8 and 17, hereinafter described.
19.979	Point for the S 1/16 sec. cor. of sec. 9 only.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
	23 ins. in the ground, over a plastic-encased magnet, with
	brass cap mkd.
	<div style="text-align: center;">             S 1/16              S 9         </div>
	2002
	Set a carsonite post, 5 ft. long, alongside the stainless steel
	post.
	From this corner, a point determined as the S 1/16 sec. cor.
	of sec. 9 only, by George H. Denson, Nevada Professional Land
	Surveyor No. 4045, in 1986, monumented with a rebar, 5/8 in.
	diam., projecting 4 ins. above the ground, with an aluminum cap
	mkd. 1/16 8 1986 LS 4045, as recorded in Lyon County Survey
	File No. 10056, bears N. 76°52'00" W., 0.096 chs. dist. This
	point was determined using improper control and is not utilized
	in this survey.
20.564	From this point, a point determined as the S 1/16 sec. cor.
	of sec. 8 only, by George H. Denson, Nevada Professional Land
	Surveyor No. 4045, in 1986, monumented with a rebar, 5/8 in.
	diam., projecting 4 ins. above the ground, with an aluminum cap
	mkd. S 1/16 S8 S9 1986 LS 4045, as recorded in Lyon County
	Survey File No. 100056, bears West, 0.096 chs. dist. This
	point was determined using improper control and is not utilized
	in this survey.
39.958	Point for the 1/4 sec. cor. of sec. 9 only, determined
	utilizing coordinates from the survey data record
	"Triangulation Stations Yerington Mines", by M. Smith, dated
	January 9, 1951, obtained from the SRK Consulting office,
	Yerington, Nevada, which represents information observed prior
	to ground surface disturbance, and is corroborated by
	additional Anaconda coordinate records dated 1993. This is
	accepted as the best available evidence of the position of the
	original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
	22 ins. in the ground, over a plastic-encased magnet, with
	brass cap mkd.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T13N R25E   1/4   S 9</p> <p style="text-align: center;">2002</p> <p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <hr style="width: 30%; margin: auto;"/>
0.580	<p>N. 0°03'30" W., beginning new measurement.</p> <p>Point for the 1/4 sec. cor. of sec. 8 only, determined at proportionate dist.; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T13N R25E 1/4   S 8  </p> <p style="text-align: center;">2002</p> <p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p>
19.876	<p>Point for the N 1/16 sec. cor. of sec. 9 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">  N 1/16   S 9</p> <p style="text-align: center;">2002</p> <p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <p>From this corner, a point established as the N 1/16 sec. cor. of sec. 9 only, by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1986, monumented with a rebar, 5/8 in. diam., projecting 5 ins. above the ground, with an aluminum cap mkd. T13N R25E N 1/16 S9 1986 LS 4045, as recorded in Lyon County Survey File No. 100056, bears N. 58°31'00" E., 0.037 chs. dist. This point was determined using improper control and is not utilized in this survey.</p>
20.596	<p>Point for the N 1/16 sec. cor. of sec. 8 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">N 1/16   S 8  </p> <p style="text-align: center;">2002</p> <p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <p>From this corner, a point established as the N 1/16 sec. cor. of sec. 8 only, by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1986, monumented with a rebar, 5/8 in. diam., projecting 2 ins. above the ground, with an aluminum cap mkd. T13N R25E N 1/16 S8 1986 LS 4045, as recorded in Lyon County Survey File No. 100056, bears N. 65°48'00" E., 0.049 chs. dist. This point was determined using improper control and is not utilized in this survey.</p>
39.752	<p>Point for the cor. of secs. 4 and 9 only, determined utilizing coordinates from the survey data record "Triangulation Stations Yerington Mines", by M. Smith, dated January 9, 1951, obtained from the SRK Consulting office, Yerington, Nevada, which represents information observed prior to ground surface disturbance, and is corroborated by additional Anaconda coordinate records dated 1993. This is accepted as the best available evidence of the position of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T13N R25E S 8   S 4         S 9</p> <p style="text-align: center;">2002</p> <p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <p>From this corner, a point determined as the cor. of secs. 4 and 9 only, by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1986, monumented with a rebar, 5/8 in. diam., projecting 3 ins. above the ground, with an aluminum cap mkd. T13N R25E 4 9 1986 LS 4045, bears S. 88°56'00" E., 0.250 chs. dist., as described in Lyon County Survey File No. 100056. Positions computed during the course of this survey from coordinates of the 1951 and 1993 data records and the 1921 Voigt and Good resurvey record are closely related, but they show a large discrepancy with Denson's monumented position; therefore the Denson position is not utilized in this survey.</p> <hr/> <p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>N. 89°31'10" W., bet. secs. 4 and 9.</p> <p>Over rolling hills.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
4.95	U.S. Highway No. 95A, 60 lks. wide, asphalt surface, bears N. 10° E. and S. 10° W.
10.006	Point for the E-E 1/64 sec. cor. of secs. 4 and 9.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	$\begin{array}{r} S\ 4 \\ E-E\ 1/64\ \frac{\quad}{\quad} \\ S\ 9 \\ 2002 \end{array}$
	Set a carsonite post, 5 ft. long, alongside the stainless steel post.
11.65	Enter mine tailings, edge bears N. and SE.
20.012	Point for the E 1/16 sec. cor. of secs. 4 and 9.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	$\begin{array}{r} S\ 4 \\ E\ 1/16\ \frac{\quad}{\quad} \\ S\ 9 \\ 2002 \end{array}$
	Set a carsonite post, 5 ft. long, alongside the stainless steel post.
	From this corner, a point determined as the E 1/16 sec. cor. of secs. 4 and 9, by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1986, monumented with a rebar, 5/8 in. diam., projecting 4 ins. above the ground, with an aluminum cap mkd. T13N R25E SE 1/16 S4 1986 LS 4045, as recorded in Lyon County Survey File No. 1023035, bears N. 86°38'00" E., 0.034 chs. dist. This point was determined using improper control and is not utilized in this survey.
40.024	Point for the 1/4 sec. cor. of secs. 4 and 9, at proportionate dist.; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	$\begin{array}{r} T13N\ R25E \\ S\ 4 \\ 1/4\ \frac{\quad}{\quad} \\ S\ 9 \\ 2002 \end{array}$

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p>
	<p>From this corner, a point established as the 1/4 sec. cor. of secs. 4 and 9, by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1987, monumented with a rebar, 5/8 in. diam., projecting 4 ins. above the ground, with an aluminum cap mkd. T13N R25E 1/4 4 9 1986 LS 4045, as recorded in Lyon County Survey File Nos. 100056 and 102305, bears N. 76°53'00" E., 0.075 chs. dist. The Denson surveys indicate the corner position was placed on a straight line between the cor. of secs. 3, 4, 9 and 10 and the Denson cor. of secs. 4 and 9 only, thereby using improper control and therefore is not utilized in this survey.</p>
60.036	<p>Point for the W 1/16 sec. cor. of secs. 4 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 4 W 1/16 ——— S 9</p> <p>2002</p> </div>
	<p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <p>From this corner, a point established as the W 1/16 sec. cor. of secs. 4 and 9, by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1987, monumented with a rebar, 5/8 in. diam., projecting 3 ins. above the ground, with an aluminum cap mkd. W 1/16 4 9 1986 LS 4045, as recorded in Lyon County Survey File No. 100056, bears N. 87°09'00" E., 0.162 chs. dist. This point was determined using improper control and is not utilized in this survey.</p>
80.048	<p>The cor. of secs. 4 and 9 only.</p> <hr/> <p>N. 0°30'00" E., on the W. bdy. of sec. 4.</p> <p>Over mine tailings.</p>
0.860	<p>The closing cor. of secs. 5 and 8, hereinafter described.</p>
19.798	<p>Point for the S 1/16 sec. cor. of sec. 4 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>  S 1/16   S 4</p> <p>2002</p> </div>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Set a carsonite post, 5 ft. long, alongside the stainless steel post.
27.10	Leave mine tailings, edge bears E. and W.
39.596	Point for the 1/4 sec. cor. of sec. 4 only, at proportionate dist.; there is no remaining evidence of the original cor. Cor. is located in chemical pond. Not monumented.
40.877	Point for the 1/4 sec. cor. of sec. 5 only, at proportionate dist.; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T13N R25E 1/4   S 5    2002
	Set a carsonite post, 5 ft. long, alongside the stainless steel post.  From this corner, a point determined as the 1/4 sec. cor. of sec. 5 only, by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1987, monumented with a rebar, 5/8 in. diam., firmly set and leaning, as recorded in Lyon County Survey File No. 100056, bears S. 75°13'00" E., 0.145 chs. dist. The position of this monument indicates it was placed on a straight line between the Denson cor. of secs. 4 and 9 only, and the cor. of secs. 4, 5, 32 and 33 on the N. bdy. of the Tp., hereinbefore described, thereby using improper control and therefore is not utilized in this survey.
46.50	Ditch, 30 lks. wide, bears N. 30° W. and S. 30° E.
76.50	Fence, bears E. and W.
76.965	The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., hereinbefore described.
	<hr/> From the cor. of secs. 19, 20, 29 and 30, monumented with an iron pipe, 2 ins. diam., firmly set, projecting 12 ins. above the ground, in a collar of stone, with a brass cap mkd. as described in the field notes of T. 13 N., R. 25 E., executed under Group No. 85.  N. 89°57'50" E., bet. secs. 20 and 29.  Descend over E. slope.
40.038	The 1/4 sec. cor. of secs. 20 and 29, determined by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1987, monumented with a rebar, 5/8 in. diam., firmly set, projecting 4 ins. above the ground, in a mound of stone, 2 ft. diam., 1 ft. high, as recorded in Lyon County Survey File No. 111657. This is accepted as the best available evidence of the position of the original corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T13N R25E S20 1/4 — S29</p> <p style="text-align: center;">2002</p> <p>Deposit the rebar inside and set a carsonite post alongside the stainless steel post.</p> <hr/>
41.285	<p>S. 89°59'20" E., beginning new measurement.</p> <p>The closing cor. of secs. 20 and 29, on the W. bdy. of sec. 21, monumented with an iron post, 2 ins. diam., firmly set, flush with the surface of the ground, with a brass cap mkd. as described in the field notes of the survey of T. 13 N., R. 25 E., executed under Group No. 85.</p> <p>From this corner, the cor. of secs. 21 and 28 only, bears S. 0°38'20" E., 1.665 chs. dist.</p> <hr/>
	<p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0°07'20" W., bet. secs. 19 and 20.</p> <p>Over rolling hills.</p>
39.911	<p>The 1/4 sec. cor. of secs. 19 and 20, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with a brass cap mkd. as described in the field notes of the survey of T. 13 N., R. 25 E., executed under Group No. 85.</p> <hr/> <p>N. 0°06'10" E., beginning new measurement.</p>
17.55	<p>Dry wash, 10 lks. wide, course E.</p>
18.30	<p>Unimproved dirt road, bears N. 50° E. and S. 50° W.</p>
19.948	<p>Point for the N 1/16 sec. cor. of secs. 19 and 20. Not monumented.</p>
39.896	<p>The cor. of secs. 17, 18, 19 and 20, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 13 N., R. 25 E., executed under Group No. 85.</p> <hr/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	S. 89°59'10" E., bet. secs. 17 and 20.
	Over rolling hills.
20.000	Point for the W 1/16 sec. cor. of secs. 17 and 20. Not monumented.
30.000	Point for the E-W 1/64 sec. cor. of secs. 17 and 20. Not monumented.
35.000	The E-E-W 1/256 sec. cor. of secs. 17 and 20, determined by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1987, monumented with a rebar, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with a plastic cap mkd. RLS 4045, as recorded in Lyon County Survey File No. 111528. This is accepted as a careful and faithful determination of the position of the corner.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	S17 E-E-W 1/256 S20
	2002
	Deposit the rebar inside and set a carsonite post, 5 ft. long, alongside the stainless steel post.
	_____
	S. 89°58'20" E., beginning new measurement.
4.997	The 1/4 sec. cor. of secs. 17 and 20, determined by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1987, monumented with a rebar, 5/8 in. diam., firmly set, flush with the asphalt surface of the road, with an aluminum cap mkd. T13N R25E 1/4 S17 S20 1987, as recorded in Lyon County Survey File No. 111528. This is accepted as the best available evidence of the position of the original corner.
	_____
	S. 89°55'20" E., beginning new measurement.
10.002	Point for the W-E 1/64 sec. cor. of secs. 17 and 20. Not monumented.
15.003	Point for the E-W-E 1/256 sec. cor. of secs. 17 and 20.  Set a copper-coated steel stake, 24 ins. long, 1/2 in. diam., 2 ins. below the surface of the road, with brass cap mkd.
	S17 E-W-E 1/256 S20
	2002

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
15.25	Asphalt road, 45 lks. wide, bears N. 10° W. and S. 10° E.
20.004	Point for the E 1/16 sec. cor. of secs. 17 and 20. Not monumented.
23.50	Enter open pit, edge bears N. 25° E. and S. 25° W.
29.763	Intersect line 1-4, Mineral Survey No. 4531, Katy-didn't lode, at a point from which Cor. No. 4, Katy-didn't lode, identical with Cor. No. 4, Black Horse lode, both of Mineral Survey No. 4531, hereinafter described, bears S. 7°09'00" W., 3.197 chs. dist.
40.459	<p>Intersect the W. bdy. of sec. 16.</p> <p>Point for the closing cor. of secs. 17 and 20, at proportionate dist.; there is no remaining evidence of the original corner. This position is harmoniously related to Anaconda Control Station UU, as shown on the survey by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1987, Lyon County Survey File No. 111657. Not monumented.</p> <p>From this point, the true point for the cor. of secs. 16 and 21 only, bears S. 0°04'40" W., 2.049 chs. dist.</p> <p>From this same point, Anaconda Control Station UU, monumented with an iron pipe, 2 ins. diam., firmly set in concrete, bears S. 64°09'20" W., 42.085 chs. dist.</p>
	From the cor. of secs. 17, 18, 19 and 20.
	N. 0°01'20" W., bet. secs. 17 and 18.
	Over rolling hills.
19.953	Point for the S 1/16 sec. cor. of secs. 17 and 18. Not monumented.
39.906	<p>The 1/4 sec. cor. of secs. 17 and 18, perpetuated by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1987, from evidence of the original corner no longer in existence, monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, with a plastic cap mkd. RLS 4045, as recorded in Lyon County Survey File No. 111528. This is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	T13N R25E
	1/4
	S18 S17
	2002

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Deposit the rebar and set a carsonite post alongside the stainless steel post.</p> <p>From this corner, Anaconda Control Station M, monumented with an iron pipe, 2 ins. diam., firmly set in concrete, 10 ins. diam., with a threaded metal cap mkd. M, bears S. 29°53'00" E., 16.142 chs. dist.</p> <hr/> <p>N. 0°01'10" W., beginning new measurement.</p> <p>Over rolling hills.</p> <p>19.988 Point for the N 1/16 sec. cor. of secs. 17 and 18. Not monumented.</p> <p>39.976 The cor. of secs. 7, 8, 17 and 18, monumented with an iron post, 2 ins. diam., firmly set, projecting 15 ins. above the ground, and in a mound of stone, 2 1/2 ft. diam., 1 ft. high, with brass cap mkd. as described in the field notes of the survey of T. 13 N., R. 25 E., executed under Group No. 85.</p> <hr/> <p>N. 89°56'50" E., bet. secs. 8 and 17.</p> <p>Over rolling hills.</p> <p>2.00 Graveled road, 60 lks. wide, bears N. 25° W. and S. 25° E.</p> <p>3.00 Power transmission line, bears N. 55° W. and S. 55° E.</p> <p>3.75 Power transmission line, bears N. 55° W. and S. 55° E.</p> <p>16.25 Enter mine tailings, edge bears N. 15° W. and S. 15° E.</p> <p>19.990 Point for the W 1/16 sec. cor. of secs. 8 and 17.</p> <p>Set a stainless steel post, 28 ins. diam., 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 8</p> <p>W 1/16 <u>        </u></p> <p>S17</p> <p>2002</p> </div> <p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <p>39.980 The 1/4 sec. cor. of secs. 8 and 17, determined by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1986, monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, with a plastic cap mkd. RLS 4045, as recorded in Lyon County Survey File No. 100056. This is accepted as the best available evidence of the position of the original corner.</p>
--------	---

## 122

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T13N R25E S 8 1/4 — S17 2002</p> <p>Deposit the rebar and set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>S. 89°59'20" E., beginning new measurement.</p>
9.50	Enter mine tailings, edge bears N. and S.
11.60	Graveled road, 50 lks. wide, bears N. 20° E. and S. 10° E.
17.11	Graveled road, 75 lks. wide, bears N. 50° W. and S. 50° E.
20.021	<p>Point for the E 1/16 sec. cor. of secs. 8 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 8 E 1/16 — S17 2004</p> <p>A rebar, 5/8 in. diam., laying loosely on the ground nearby, was deposited alongside the stainless steel post.</p> <p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p>
20.50	Graveled road, 50 lks. wide, bears N. 20° E. and S. 20° W.
38.50	Leave mine tailings, edge bears NW and SE.
40.562	Intersect the W. bdy. of sec. 9.
	<p>Point for the closing cor. of secs. 8 and 17, determined at proportionate dist.; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T13N R25E S 8   CC ——— S 9 S17  </p> <p style="text-align: center;">2002</p>
	<p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p>
	<p>From this corner, a point determined as the closing cor. of secs. 8 and 17, by George H. Denson, Nevada Professional Land Surveyor No. 4045, monumented with a rebar, 5/8 in. diam., projecting 4 ins. above the ground, with an aluminum cap mkd. T13N R25E S8 S17 1986 LS 4045, as recorded in Lyon County Survey File No. 100056. bears N. 45°27'00" W., 0.012 chs. dist. This point is not utilized in this survey.</p>
	<p>From this same corner, the cor. of secs. 9 and 16 only, bears S. 0°19'30" W., 0.550 chs. dist.</p> <hr/>
	<p>From the cor. of secs. 7, 8, 17 and 18. N. 0°03'10" W., bet. secs. 7 and 8.</p>
	<p>Over nearly level land.</p>
1.50	<p>Power transmission line, bears N. 55° W. and S. 55° E.</p>
2.00	<p>Power transmission line, bears N. 55° W. and S. 55° E.</p>
20.008	<p>The S 1/16 sec. cor. of secs. 7 and 8, determined by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1986, monumented with a rebar, 5/8 in. diam., projecting 3 ins. above the ground, with a plastic cap mkd. PLS 4045, as recorded in Lyon County Survey File No. 100056. This is accepted as a careful and faithful determination of the position of the corner.</p>
	<p>At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">S 1/16 S 8   S 7</p> <p style="text-align: center;">2002</p>
	<p>Deposit the rebar and set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <hr/>
	<p>N. 0°03'10" W., beginning new measurement.</p>
6.95	<p>Graveled road, 80 lks. wide, bears N. 30° W. and S. 30° E.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.008	<p>The 1/4 sec. cor. of secs. 7 and 8, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, with a brass cap mkd. as described in the field notes of the survey of T. 13 N., R. 25 E., executed under Group No. 85.</p> <hr/> <p>N. 0°00'10" E., beginning new measurement.</p>
39.958	<p>The cor. of secs. 5, 6, 7 and 8, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above ground, with a brass cap mkd. as described in the field notes of the survey of T. 13 N., R. 25 E., executed under Group No. 85.</p> <hr/> <p>N. 89°57'00" E., bet. secs. 5 and 8.</p> <p>Over nearly level land.</p>
27.45	<p>Enter mine tailings, edge bears N. 45° W. and S. 20° E.</p>
34.285	<p>Point selected for the witness cor. to the 1/4 sec. cor. of secs. 5 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC T13N R25E S 5 1/4 → S 8</p> <p>2004</p> </div>
40.030	<p>True point for the 1/4 sec. cor. of secs. 5 and 8, at proportionate dist.; there is no remaining evidence of the original corner. Cor. is located in tailings pond where it is impracticable to establish a permanent monument.</p>
53.50	<p>Graveled road, 50 lks. wide, bears N. 30° W. and S. 30° E.</p>
60.045	<p>Point for the E 1/16 sec. cor. of secs. 5 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 5 E 1/16 — S 8</p> <p>2002</p> </div> <p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From this corner, a point determined as the E 1/16 sec. cor. of secs. 5 and 8, by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1986, monumented with a rebar, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with an aluminum cap, mkd. E 1/16 S5 S8 1986 LS 4045, as recorded in Lyon County Survey File No. 100056, bears S. 83°02'00" E., 0.217 chs. dist. This point was determined using improper control and is not utilized in this survey.</p> <p>68.25 Graveled road, 50 lks. wide, bears N. 33° E. and S. 33° W.</p> <p>80.750 Intersect the W. bdy. of sec. 4.</p> <p>Point for the closing cor. of secs. 5 and 8, at proportionate dist.; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <math display="block">\begin{array}{r} \text{T13N R25E} \\ \text{S 5} \\ \text{CC} \frac{\quad}{\quad} \text{S 4} \\ \text{S 8} \end{array}</math> <p>2002</p> </div> <p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <p>From this corner, a point determined as the closing cor. of secs. 5 and 8, by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1986, monumented with a rebar, 5/8 in. diam., projecting 2 ins. above the ground, with an aluminum cap mkd. T13N R25E CC S5 S8 1986 LS 4045, as recorded in Lyon County Survey File No. 100056, bears S. 88°20'00" E., 0.249 chs. dist. This point was determined using improper control and is not utilized in this survey.</p> <hr/> <p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>North, bet. secs. 5 and 6.</p> <p>Over nearly level land.</p> <p>40.014 The 1/4 sec. cor. of secs. 5 and 6, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above the ground, with a brass cap mkd. as described in the field notes of the survey of T. 13 N., R. 25 E., executed under Group No. 85.</p> <hr/> <p>N. 0°00'10" E., beginning new measurement.</p> <p>2.967 An iron pipe, 1/2 in. diam., firmly set, projecting 3 ins. above the ground, set by person(s) unknown.</p>
--------	--

## 126

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
5.879	An iron pipe, 1/2 in. diam., firmly set, projecting 4 ins. above the ground, set by person(s) unknown.
12.245	An iron pipe, 1/2 in. diam., firmly set, projecting 6 ins. above the ground, set by person(s) unknown.
19.959	Point for the N 1/16 sec. cor. of secs. 5 and 6. Not monumented.
21.787	An iron pipe, 1/2 in. diam., firmly set, projecting 4 ins. above ground, set by person(s) unknown.
28.728	From this point, a rebar, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, set by person(s) unknown, bears East, 0.018 chs. dist.
31.998	From this point, a property cor. determined by Fred L. Peterson, Nevada Professional Land Surveyor No. 2371, in 1982, monumented with a rebar, 5/8 in. diam., firmly set, projecting 4 ins. above the ground, with an aluminum cap mkd. RLS and other illegible marks, as recorded in Lyon County Survey File No. 66338, bears East, 0.006 chs. dist.
35.648	Intersect the S. bdy. of T. 14 N., R. 25 E.  Point for the closing cor. of secs. 5 and 6.  Set a copper-coated steel stake, 24 ins. long, 1/2 in. diam., the top is 2 ins. below the surface of the road, with brass cap mkd.
	<div style="text-align: center;"> <p>T14N R25E</p> <p>S31</p> <hr style="width: 50%; margin: auto;"/> <p>S 6   S 5</p> <p>CC</p> <p>T13N</p> <p>2002</p> </div>
	<p>from which</p> <p style="padding-left: 40px;">A PK nail with shiner, driven into a power pole, 1 ft. above the ground, bears S. 73°34'00" E., 1.491 chs. dist.</p>
	<p style="padding-left: 40px;">A PK nail with shiner, driven into a power pole, 1 ft. above ground, bears S. 79°17'00" W., 2.196 chs. dist.</p>
	<p style="padding-left: 40px;">A wooden post, bears N. 12°43'00" W., 0.536 chs. dist., with a sign attached mkd. LUZIER LANE MASON PASS ROAD.</p>
	<p>From this corner, the original closing cor. of secs. 5 and 6, monumented with an iron pipe, 2 ins. diam., firmly set, 4 ins. below the surface of Luzier Lane, with brass cap mkd. as described in the field notes of the survey of T. 13 N., R. 25 E., executed under Group No. 85, bears N. 0°00'10" E., 0.009 chs. dist. Add the marks AM to the brass cap.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

From this same corner, the cor. of secs. 31 and 32, T. 14 N., R. 25 E., hereinbefore described, bears N. 89°39'40" E., 1.992 chs. dist.

The point for the W 1/16 sec. cor. of sec. 5 only, is at midpoint in departure bet. the closing cor. of secs. 5 and 6, and the 1/4 sec. cor. of sec. 5 only, on the N. bdy. of sec. 5.

Set a copper-coated steel stake, 24 ins. long, 1/2 in. diam., 2 ins. below the surface of the road, with brass cap mkd.

W 1/16 S 5

2002

from which

An iron pipe, 3 ins. diam., firmly set in concrete, projecting 4 ft. above the ground, bears N. 75°41'00" E., 1.969 chs. dist., and chisel marks X on SW face, 1 ft. above ground.

An iron pipe, 3 ins. diam., firmly set in concrete, projecting 4 ft. above the ground, bears N. 8°10'00" W., 0.492 chs. dist., and chisel marks X on SE face, 1 ft. above ground.

From this corner, the cor. of secs. 31 and 32 only, T. 14 N., R. 25 E., hereinbefore described, bears S. 89°38'00" W., 17.944 chs. dist.

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4499,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by  
G.W. Malone in 1921

Portions of Wild Rose No. 2, Wild Rose No. 1 and  
Wild Rose lodes

From the point for Cor. No. 1, Mineral Survey No. 4499, Wild Rose No. 2 lode, determined at record bearing and distance utilizing Mineral Survey Nos. 4499, 4531 and 4778 and the record ties between these mineral surveys; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

MS 4531 BS

COR 1  
WR 2  
MS 4499



2003

## 128



DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4499,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	Set a carsonite post, 5 ft. long, alongside the stainless steel post.
	From this corner, Cor. No. 4, Mineral Survey No. 4778, No. 38 lode, bears N. 44°20'30" W., 87.521 chs. dist., monumented with an iron pipe, 2 1/2 ins. diam., firmly set, 1 in. below the ground, with illegible marks on brass cap.
	S. 7°07'00" W., on line 1-2, Mineral Survey No. 4499, Wild Rose No. 2 lode.
0.032	Intersect line 3-4, Mineral Survey No. 4531, Blue Star lode, at a point from which Cor. No. 4, hereinafter described, bears N. 82°57'00" W., 0.300 chs. dist.
22.727	Point for the Cor. No. 2, Mineral Survey No. 4499, Wild Rose No. 2 lode, determined at record bearing and distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, in a collar of stone, 2 ft. base, with brass cap mkd.
	 <p style="text-align: center;">T13N R25E 2003</p>
	Set a carsonite post, 5 ft. long, alongside the stainless steel post.
	<hr/> <p>Thence S. 82°53'00" E., on line 2-3, Mineral Survey No. 4499, Wild Rose No. 2 lode.</p>
9.091	Point for Cor. No. 3, Wild Rose No. 2 lode, identical with Cor. No. 2, Wild Rose No. 1 lode, both of Mineral Survey No. 4499, determined at record bearing and distance; there is no remaining evidence of the original corner. Not monumented.
	<hr/> <p>Thence, S. 82°53'00" E. on line 2-3, Mineral Survey No. 4499, Wild Rose No. 1 lode.</p>
0.559	Intersect the N-S center line of sec. 21, at a point from which the center 1/4 sec. cor. of sec. 21, hereinafter described, bears S. 0°08'00" E., 0.236 chs. dist.
2.507	Intersect the E-W center line of sec. 21, at a point from which the center 1/4 sec. cor. of sec. 21, hereinafter described, bears N. 89°51'20" W., 1.932 chs. dist.
9.091	Point for Cor. No. 3, Wild Rose No. 1 lode, identical with Cor. No. 2, Wild Rose lode, both of Mineral Survey No. 4499, determined at record bearing and distance; there is no remaining evidence of the original corner. Not monumented.

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4499,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA



CHAINS	
	<p>Thence, S. 82°53'00" E., on line 2-3, Mineral Survey No. 4499, Wild Rose No. 2 lode.</p>
9.091	<p>Point for Cor. No. 3, Mineral Survey No. 4499, Wild Rose lode, determined at record bearing and distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">MS 4499 WR COR 3</p>  <p style="text-align: center;">S21 T13N R25E</p> <p style="text-align: center;">2003</p>
	<p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p>
	<p>Thence N. 7°07'00" E., on line 3-4, Mineral Survey No. 4499, Wild Rose lode.</p>
1.914	<p>Intersect the E-W center line of sec. 21, at a point from which the true point for the C-E 1/16 sec. cor. of sec. 21, hereinafter described, bears S. 89°51'20" E., 2.037 chs. dist.</p>
14.588	<p>Point selected for the witness cor. to Cor. No. 4, Mineral Survey No. 4499, Wild Rose lode.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">WC</p>  <p style="text-align: center;">MS 4531 C COR 4 WR MS 4499</p> <p style="text-align: center;">2003</p>
	<p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p>
18.616	<p>Intersect the N-S center line of the NE1/4 of sec. 21, at a point from which the true point for the C-E 1/16 sec. cor. of sec. 21, hereinafter described, bears S. 0°06'50" W., 16.579 chs. dist.</p>
22.727	<p>True point for Cor. No. 4, Mineral Survey No. 4499, Wild Rose lode, determined at record bearing and distance; there is no remaining evidence of the original corner. Cor. is located in open pit where it is impracticable to establish a permanent monument.</p>

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4531,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Reestablishment of the Survey Executed by G.W. Lloyd in 1922</p> <hr/> <p>Portions of Consolidated Fraction, Canidate, New Royal Blue Extension, New Royal Blue, New Blue Bird, New Blue Bird No. 1, New Blue Bird No. 2, Greenhorn, Katy-didn't, Blackhorse, West Starlight and Blue Star lodes</p> <p>From the point for Cor. No. 2, Mineral Survey No. 4531, Consolidated Fraction lode, determined at record bearing and distance utilizing Mineral Survey Nos. 4531 and 4778, and the record ties between these mineral surveys; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;">  <p>MS 4531 C COR 2 CF MS 4531 2004</p> </div> <p>Set a steel post, 5 ft. long, alongside the stainless steel post.</p> <p>From this corner, Cor. No. 4, Mineral Survey No. 4778, No. 38 lode, hereinbefore described, bears N. 66°12'10" W., 94.853 chs. dist.</p> <p>S. 82°22'00" E., on line 2-3, Mineral Survey No. 4531, Consolidated Fraction lode.</p> <p>0.668 Intersect line 4-1, Mineral Survey No. 4531, Canidate lode, at a point from which Cor. No. 4, hereinafter described, bears S. 82°57'00" E., 3.866 chs. dist.</p> <p>1.016 Intersect the N-S center line of the SE1/4 of sec. 16, at a point from which the E 1/16 sec. cor. of secs. 16 and 21, hereinafter described, bears S. 0°05'50" W., 8.410 chs. dist.</p> <p>2.028 Point for Cor. No. 3, Mineral Survey No. 4531, Consolidated Fraction lode, determined at record bearing and distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;">  <p>T13NR25E COR 3 CF MS 4531 S16 2004</p> </div>

## 131



DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4531,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a steel post, 5 ft. long, alongside the stainless steel post.</p> <hr/> <p>From the point for Cor. No. 4, Mineral Survey No. 4531, Canidate lode, determined at record bearing and distance utilizing Mineral Survey Nos. 4531 and 4778, and the record ties between these mineral surveys; there is no remaining evidence of original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;">  </div> <p>Set a steel post, 5 ft. long, alongside the stainless steel post.</p> <p>N. 82°57'00" W., on line 4-1, Mineral Survey No. 4531, Canidate lode.</p> <p>3.518 Intersect the N-S center line of the SE1/4 of sec. 16, at a point from which the E 1/16 sec. cor. of secs. 16 and 21, hereinafter described, bears S. 0°05'50" W., 8.414 chs. dist.</p> <p>3.866 Intersect line 2-3, Mineral Survey No. 4531, Consolidated Fraction lode, at a point from which Cor. No. 2, hereinbefore described, bears N. 82°22'00" W., 0.668 chs. dist.</p> <p>22.704 Cor. No. 1, Mineral Survey No. 4531, Canidate lode, identical with Cor. No. 1, North Star lode, both of Mineral Survey No. 4531, determined at record bearing and distance; there is no remaining evidence of the original corner. Cor. is located in open pit where it is impracticable to establish a permanent monument.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;">  </div> <p>Set a steel post, 5 ft. long, alongside the stainless steel post.</p> <hr/>
--------	---

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4531,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p>	<p>From the true point for Cor. No. 4, New Royal Blue Extension lode, identical with Cor. No. 3, Canidate lode, both of Mineral Survey No. 4531, determined at record bearing and distance utilizing Mineral Survey Nos. 4531 and 4778, and the record ties between these mineral surveys; there is no remaining evidence of original corner. The cor. is located in a petroleum storage facility where it is impracticable to establish a permanent monument.</p> <p>From this point, Cor. No. 4, Mineral Survey No. 4778, No. 38 lode, hereinbefore described, bears N. 72°07'00" W., 97.100 chs. dist.</p> <p>N. 7°06'00" E., on line 4-3, Mineral Survey No. 4531, New Royal Blue Extension lode.</p> <p>1.152 Point selected for the witness cor. to Cor. No. 4, New Royal Blue Extension lode, identical with Cor. No. 3, Canidate lode, both of Mineral Survey No. 4531.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="711 915 1117 1142" data-label="Diagram"> </div> <p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <p>3.115 Intersect the E-W center line of the SE1/4 of sec. 16, at a point from which the witness point on the E-W center line, hereinafter described, bears S. 89°42'50" E., 0.276 chs. dist.</p> <p>9.091 Point for Cor. No. 3, Mineral Survey No. 4531, New Royal Blue Extension lode, determined at record bearing and distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="820 1581 1088 1743" data-label="Diagram"> </div> <p>Set a carsonite post, 5 ft. long alongside the stainless steel post.</p>
---------------	---

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4531,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	Thence N. 82°57'00" W., on line 3-2, Mineral Survey No. 4531, New Royal Blue Extension lode.
5.748	Intersect the N-S center line of the SE1/4 of sec. 16, at a point from which the point for the SE 1/16 sec. cor. of sec. 16, hereinafter described, bears S. 0°05'50" W., 6.612 chs. dist.
11.718	Intersect the easterly bdy. of the Cactus lode, unsurveyed, at record bearing and distance. Not monumented.
21.372	Intersect the westerly bdy. of the Cactus lode, unsurveyed, at record bearing and distance. Not monumented.
22.704	<p>Point for Cor. No. 2, New Royal Blue Extension lode, identical with Cor. No. 4, New Royal Blue lode, both of Mineral Survey No. 4531, determined at record bearing and distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;">  <p>T13N R25E S16 COR 4 / COR 2 NRB / NRBE MS 4531 2003</p> </div> <p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p>
	<p>Thence N. 82°52'00" W., on a portion of line 4-3, Mineral Survey No. 4531, New Royal Blue lode.</p>
3.137	Intersect the N-S center line of sec. 16, at a point from which the center 1/4 sec. cor. of sec. 16, hereinafter described, bears N. 0°04'40" E., 11.220 chs. dist.
4.549	<p>Point for Cor. No. 4, Mineral Survey No. 4531, New Blue Bird lode; determined at record bearing and distance, there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;">  <p>MS 4531 / T13N R25E NBB / S16 COR 4 NRB MS 4531 2003</p> </div>

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4531,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <hr/> <p>Thence N. 7°09'00" E., on line 4-3, Mineral Survey No. 4531, New Blue Bird lode.</p> <p>1.898 Intersect the southerly end line of the Sagebrush lode, unsurveyed, at record bearing and distance. Not monumented.</p> <p>9.091 Point for Cor. No. 3, New Blue Bird lode, identical with Cor. No. 4, New Blue Bird No. 1 lode, both of Mineral Survey No. 4531, determined at record bearing and distance; there is no remaining evidence of the original corner. Not monumented.</p> <hr/> <p>Thence N. 7°09'00" E., on line 4-3, Mineral Survey No. 4531, New Blue Bird No. 1 lode.</p> <p>0.506 Intersect the westerly bdy. of the Sagebrush lode, unsurveyed, at record bearing and distance. Not monumented.</p> <p>2.040 Intersect the E-W center line of sec. 16, at a point from which the center 1/4 sec. cor. of sec. 16, hereinafter described, bears S. 89°31'10" E., 0.030 chs. dist.</p> <p>2.283 Intersect the N-S center line of sec. 16, at a point from which the center 1/4 sec. cor. of sec. 16, hereinafter described, bears S. 0°04'40" W., 0.241 chs. dist.</p> <p>9.091 Point for Cor. No. 3, New Blue Bird No. 1 lode, identical with Cor. No. 4, New Blue Bird No. 2 lode, both of Mineral Survey No. 4531, determined at record bearing and distance; there is no remaining evidence of the original corner. Not monumented.</p> <hr/> <p>Thence N. 7°09'00" E., on line 4-3, Mineral Survey No. 4531, New Blue Bird No. 2 lode.</p> <p>9.091 Point for Cor. No. 3, Mineral Survey No. 4531, Blue Bird No. 2 lode, determined at record bearing and distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13N R25E S16</p>  <p>MS 4531</p> <p>2003</p> </div> <p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <hr/>
--------	--

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4531,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA



CHAINS	
	Thence N. 82°52'00" W., on line 3-2, Mineral Survey No. 4531, New Blue Bird No. 2 lode.
1.973	Intersect the N-S center line of sec. 16, at a point from which the point for the C-N 1/16 sec. cor. of sec. 16, hereinafter described, bears N. 0°04'40" E., 3.959 chs. dist.
22.064	Intersect the N-S center line of the NW1/4 of sec. 16, at a point from which the NW 1/16 sec. cor. of sec. 16, hereinafter described, bears N. 0°03'10" E., 1.706 chs. dist.
22.727	<p>True point for Cor. No. 2, Mineral Survey No. 4531, New Blue Bird No. 2 lode, determined at record bearing and distance; there is no remaining evidence of the position of the original corner. Cor. is located in open pit where it is impracticable to establish a permanent monument.</p> <p>From this point, the point selected for the witness cor. to Cor. No. 2, Mineral Survey No. 4531, New Blue Bird No. 2 lode, bears S. 7°09'00" W., 3.372 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="857 947 1036 1203" data-label="Diagram"> </div> <p>2003</p> <p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p>
	<p>From the point for Cor. No. 2, Mineral Survey No. 4531, Greenhorn lode, determined at record bearing and distance utilizing Mineral Survey Nos. 4531 and 4778 and the record ties between these mineral surveys; there is no remaining evidence of the original corner. Cor. is located in open pit where it is impracticable to establish a permanent monument.</p> <p>From this point, Cor. No. 4, Mineral Survey No. 4778, No. 38 lode, hereinbefore described, bears N. 32°39'40" W., 35.470 chs. dist.</p> <p>S. 7°06'00" W., on line 2-1, Mineral Survey No. 4531, Greenhorn lode.</p> <p>Over open pit.</p>
9.091	Intersect line 4-1, Mineral Survey No. 4778, No. Seven lode, at a point from which the true point for Cor. No. 4, hereinafter described, bears S. 82°54'00" E., 0.040 chs. dist.

136

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4531,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
9.098	<p>True point for Cor. No. 1, Greenhorn lode, identical with Cor. No. 1, Katy-didn't lode, both of Mineral Survey No. 4531, determined at record bearing and distance; there is no remaining evidence of the original corner. Cor. is located in open pit where it is impracticable to establish a permanent monument.</p> <hr/> <p>Thence S. 7°09'00" W., on line 1-4, Mineral Survey No. 4531, Katy-didn't lode.</p>
5.894	<p>Intersect the line bet. secs. 17 and 20, at a point from which the E 1/16 sec. cor. of secs. 17 and 20, hereinbefore described, bears N. 89°55'20" W., 9.759 chs. dist.</p>
7.389	<p>Point selected for the witness cor. to Cor. No. 1, Greenhorn lode, identical with Cor. No. 1, Katy-didn't lode, both of Mineral Survey No. 4531.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="836 919 1112 1171" data-label="Diagram"> <p style="text-align: center;">WC</p> <p style="text-align: center;">S17 GH T13N COR 1 R25E MS COR 1 4531 KD</p> <p style="text-align: center;">2003</p> </div> <p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p>
9.091	<p>Point for Cor. No. 4, Katy-didn't lode, identical with Cor. No. 4, Black Horse lode, both of Mineral Survey No. 4531, determined at record bearing and distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="787 1512 1136 1732" data-label="Diagram"> <p style="text-align: center;">KD COR 4</p> <p style="text-align: center;">S20 T13N MS R25E COR 4 4531 BH</p> <p style="text-align: center;">2003</p> </div> <p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <hr/>

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4531,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA



CHAINS	
9.091	<p>Thence S. 7°03'00" W., on line 4-3, Mineral Survey No. 4531, Black Horse lode.</p> <p>Point for Cor. No. 3, Mineral Survey No. 4531, Black Horse lode, determined at record bearing and distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;">  </div> <p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <hr style="width: 30%; margin: 10px auto;"/>
12.444	<p>Thence S. 82°51'00" E., on line 3-2, Mineral Survey No. 4531, Black Horse lode.</p> <p>Intersect the W. bdy. of sec. 21, at a point from which the point for the N 1/16 sec. cor. of sec. 20 only, hereinbefore described, bears S. 0°38'20" E., 6.269 chs. dist.</p>
22.727	<p>Point for Cor. No. 2, Black Horse lode, identical with Cor. No. 4, West Starlight lode, both of Mineral Survey No. 4531, determined at record bearing and distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;">  </div> <p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <hr style="width: 30%; margin: 10px auto;"/>
2.00	<p>Thence S. 82°52'00" E., on line 4-3, Mineral Survey No. 4531, West Starlight lode.</p> <p>Enter open pit, edge bears N. 65° W. and S. 65° E.,</p>

## 138




DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4531,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
22.727	<p>Point for Cor. No. 3, West Starlight lode, identical with Cor. No. 4, Blue Star lode, both of Mineral Survey No. 4531, determined at record bearing and distance; there is no remaining evidence of the original corner.</p> <p>Set a copper coated steel stake, 24 ins. long, 1/2 in. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>MS 4531</p> <p>WS / BS</p> <p>COR 3 / COR 4</p> <hr style="width: 50%; margin: 0 auto;"/> <p>S21</p> <p>T13N R25E</p> <p>2003</p> </div> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, 2 lks. N. of cor.</p> <hr style="width: 50%; margin: 10px auto;"/> <p>Thence S. 82°57'00" E., on line 4-3, Mineral Survey 4531, Blue Star lode.</p>
0.300	<p>Intersect line 1-2, Mineral Survey No. 4499, Wild Rose No. 2 lode, at a point from which Cor. No. 1, hereinbefore described, bears N. 7°07'00" E., 0.032 chs. dist.</p>
6.389	<p>Point selected for the witness cor. to Cor. No. 3, Blue Star lode, identical with Cor. No. 4, Consolidated lode, both of Mineral Survey No. 4531.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC</p> <p>MS 4531</p> <p>BS / C</p> <p>COR 3 / COR 4</p> <hr style="width: 50%; margin: 0 auto;"/> <p>WR</p> <p>MS 4499</p> <p>2004</p> </div>
7.076	<p>Intersect the N-S center line of sec. 21, at a point from which the 1/4 sec. cor. of secs. 16 and 21, hereinbefore described, bears N. 0°08'00" W., 16.637 chs. dist.</p>
22.704	<p>True point for Cor. No. 3, Mineral Survey No. 4531, Blue Star lode, determined at record bearing and distance; there is no remaining evidence of the original corner. Cor. is located in open pit where it is impracticable to establish a permanent monument.</p> <hr style="width: 50%; margin: 10px auto;"/>


DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4531,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
1.628	<p style="text-align: center;">Cactus lode, unsurveyed</p> <p>From the intersection of the easterly bdy. of the Cactus lode, unsurveyed, and line 2-3 of New Royal Blue Extension lode, Mineral Survey No. 4531.</p> <p>S. 29°29'00" W., on a portion of the easterly bdy. of the Cactus lode, unsurveyed.</p> <p>Point for the SE cor. of the Cactus lode, unsurveyed, at intersection with the northerly bdy. of the Copper Fraction lode, unsurveyed, at record bearing and distance.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;">  <p>T13N R25E S16      NRBE             MS 4531             2003</p> </div> <p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p>
2.046	<p style="text-align: center;">Copper Fraction lode, unsurveyed</p> <p>From the SE cor. of the Cactus lode, unsurveyed, on the northerly bdy. of the Copper Fraction lode, unsurveyed.</p> <p>Thence S. 72°52'00" E., on a portion of the northerly bdy. of the Copper Fraction lode.</p> <p>Point for the NE cor. of the Copper Fraction lode, unsurveyed; determined at record bearing and distance; there is no remaining evidence of the claim corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;">  <p>T13N R25E S16      NRBE             MS 4531             2003</p> </div> <p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>Thence S. 26°37'00" W., on the easterly bdy. of the Copper Fraction lode, unsurveyed.</p>



DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4531,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
5.208	<p>Point for the SE cor. of the Copper Fraction lode, unsurveyed; determined at record bearing and distance; there is no remaining evidence of the claim corner.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	
	2003
	<p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p>
	<hr/> <p>Thence N. 72°52'00" W., on the southerly bdy. of the Copper Fraction lode, unsurveyed.</p>
11.185	<p>Point for the SW cor. of the Copper Fraction lode, unsurveyed; determined at record bearing and distance; there is no remaining evidence of the claim corner.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	
	2003
	<p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p>
	<hr/> <p>Thence N. 26°37'00" E., on a portion of the westerly bdy. of the Copper Fraction lode, unsurveyed.</p>
4.185	<p>Point for a witness point.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p>WP</p>
	
	2004


DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4531,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
5.108	<p>Intersect line 2-3, Mineral Survey No. 4531, New Royal Blue Extension lode, at a point from which Cor. No. 2, New Royal Blue Extension lode, identical with Cor. No. 4, New Royal Blue lode, both of Mineral Survey No. 4531, bears N. 82°57'00" W., 1.332 chs. dist. Not monumented.</p> <hr/> <p style="text-align: center;">Sagebrush lode, unsurveyed</p> <p>From the point of intersection of the southerly bdy. of the Sagebrush lode, unsurveyed, with line 3-4, Mineral Survey No. 4531, New Blue Bird lode.</p> <p>N. 65°55'00" W., on a portion of the southerly. bdy. of the Sagebrush lode, unsurveyed.</p>
2.938	<p>Point for the SW cor. of Sagebrush lode, unsurveyed; determined at record bearing and distance; there is no remaining evidence of the claim corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, over a plastic-encased magnet, in a collar of stone, 2 ft. base, with brass cap mkd.</p> <div style="text-align: center;">  <p>2003</p> </div> <p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <hr/> <p>Thence N. 29°29'00" E., on a portion of the westerly bdy. of the Sagebrush lode.</p>
6.714	<p>Point selected for a witness point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>WP</p> <p>MS 4531 / T13N R25E NBB / S16</p> <p>2004</p> </div> <p>Set a steel fence post alongside the stainless steel post.</p>
7.398	<p>Intersect line 3-4, New Blue Bird No. 1 lode, at a point from which Cor. No. 4, New Blue Bird No. 1 lode, identical with Cor. No. 3, New Blue Bird lode, both of Mineral Survey No. 4531, hereinbefore described, bears S. 7°09'00" W., 0.506 chs. dist.</p> <hr/>

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4778,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Reestablishment of the Survey Executed by C.V. Taylor in 1944</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Portions of No. 38, No. Seven, and No. Twenty Four lodes</p> <p>From the point for Cor. No. 1, Mineral Survey No. 4778, No. 38 lode, determined at record bearing and distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;">  <p>COR 1 N 38 MS 4778</p> </div> <p style="text-align: center;">2003</p> <p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <p>From this corner, Cor. No. 4, Mineral Survey No. 4778, No. 38 lode, hereinbefore described, bears N. 82°54'00" W., 22.727 chs. dist.</p> <p>S. 7°06'00" W., on line 1-2, Mineral Survey No. 4778, No. 38 lode.</p> <p>1.976 Intersect the E-W center line of sec. 17, at a point from which the 1/4 sec. cor. of sec. 17 only, on the W. bdy. of sec. 16, hereinbefore described, bears S. 89°56'40" E., 5.726 chs. dist.</p> <p>8.522 Point selected for the witness cor. to Cor. No. 2, No. 38 lode, identical with Cor. No. 1, No. Twenty Four lode and Cor. No. 1, No. Twenty Five lode, all of Mineral Survey No. 4778.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;">  <p>WC MS 4778 NO 38 COR 2 T13N R25E S17 COR 1 / COR 1 NT 5 / NT 4 MS 4778</p> </div> <p style="text-align: center;">2003</p> <p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p>
--------	---

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4778,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
9.091	<p>True point for Cor. No. 2, No. 38 lode, identical with Cor. No. 1, No. Twenty Four lode and Cor. No. 1, No. Twenty Five lode, all of Mineral Survey No. 4778, determined at record bearing and distance; there is no remaining evidence of the original corner. Cor. is located in open pit where it is impracticable to establish a permanent monument.</p> <hr/> <p>Thence S. 82°54'00" E., on line 1-2, Mineral Survey No. 4778, No. Twenty Four lode.</p>
6.648	<p>Intersect the W. bdy. of sec. 16, at a point from which the 1/4 sec. cor. of sec. 16 only, hereinbefore described, bears N. 0°04'40" E., 6.578 chs. dist.</p>
22.727	<p>True point for Cor. No. 2, Mineral Survey No. 4778, No. Twenty Four lode, determined at record bearing and distance; there is no remaining evidence of the original corner. Cor. is located in open pit where it is impracticable to establish a permanent monument.</p> <p>From this point, the point selected for the witness cor. to Cor. No. 2, Mineral Survey No. 4778, No. Twenty Four lode, bears N. 4°14'40" E., 0.983 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC</p>  <p>2003</p> </div> <p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <hr/> <p>From the point for Cor. No. 1, Mineral Survey No. 4778, No. Seven lode, determined at record bearing and distance; there is no remaining evidence of the original corner.</p> <p>Set a copper-coated steel stake, 24 ins. long, 1/2 in. diam., 26 ins. in the ground, the top is 2 ins. below the surface of the road, with brass cap mkd.</p> <div style="text-align: center;">  <p>2003</p> </div>

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4778,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS												
	<p>from which</p> <p>A PK nail with shiner, in concrete curb, bears S. 48°43'00" W., 0.178 chs. dist.</p> <p>A PK nail with shiner, in concrete curb, bears N. 20°08'00" W., 0.288 chs. dist.</p> <p>From this corner, Cor. No. 4, Mineral Survey No. 4778, No. 38 lode, bears N. 7°06'00" E., 36.364 chs. dist.</p> <p>S. 82°54'00" E., on line 1-4, Mineral Survey No. 4778, No. Seven lode.</p>											
2.036	<p>Intersect the N-S center line of the SW1/4SE1/4 of sec. 17, at a point from which the point for the SW-SE 1/64 sec. cor. of sec. 17, hereinafter described, bears N. 0°00'40" W., 1.609 chs. dist.</p>											
7.077	<p>Intersect the N-S center line of the SE1/4SW1/4SE1/4 of sec. 17, at a point from which the point for the C-E-SW-SE 1/256 sec. cor. of sec. 17, hereinafter described, bears North, 2.226 chs. dist.</p>											
12.118	<p>Intersect the N-S center line of the SE1/4 of sec. 17, at a point from which the point for the C-S-SE 1/64 sec. cor. of sec. 17, hereinafter described, bears N. 0°00'40" E., 2.844 chs. dist.</p>											
12.503	<p>Point selected for the witness cor. to Cor. No. 4, Mineral Survey No. 4778, No. Seven lode.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, over a plastic-encased magnet, encircled with a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC</p> <table border="0"> <tr> <td>MS 4778</td> <td rowspan="3"> </td> <td rowspan="3">→</td> </tr> <tr> <td>NO S</td> </tr> <tr> <td>COR 4</td> </tr> <tr> <td></td> <td>G</td> <td></td> </tr> <tr> <td></td> <td>MS 4531</td> <td></td> </tr> </table> <p>2004</p> </div>	MS 4778		→	NO S	COR 4		G			MS 4531	
MS 4778		→										
NO S												
COR 4												
	G											
	MS 4531											
22.687	<p>Intersect line 1-2, Greenhorn lode, at a point from which the true point for Cor. No. 1, Greenhorn lode, identical with Cor. No. 1, Katy-didn't lode, both of Mineral Survey No. 4531, hereinbefore described, bears S. 7°06'00" W., 0.007 chs. dist.</p>											
22.727	<p>True point for Cor. No. 4, Mineral Survey No. 4778, No. Seven lode, is located in open pit where it is impracticable to establish a permanent monument.</p> <hr/>											

SUBDIVISION OF SECTION 4,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the 1/4 sec. cor. of secs. 4 and 9.</p> <p>N. 0°24'20" E., on the N-S center line of sec. 4.</p> <p>Over mine tailings.</p>
19.895	<p>Point for the C-S 1/16 sec. cor. of sec. 4. Not monumented.</p> <p>From this point, a point determined as the C-S 1/16 sec. cor. of sec. 4, by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1986, monumented with a rebar, 5/8 in. diam., projecting 4 ins. above the ground, with an aluminum cap mkd. S 1/16 S4 C-C 1986 LS 4045, as recorded in Lyon County Survey File No. 102305, bears N. 84°25'00" E., 0.055 chs. dist. This position was determined using improper control and is not utilized in this survey.</p>
35.80	<p>Leave mine tailings, edge bears E. and W.; continue over nearly level agricultural land.</p>
39.790	<p>Point for the center 1/4 sec. cor. of sec. 4, at intersection with the E-W center line. The cor. is located in agricultural land, and was not monumented at the request of the land owner.</p>
77.538	<p>The 1/4 sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 3 and 4.</p> <p>N. 89°47'30" W., on the E-W center line of sec. 4.</p> <p>Over nearly level land.</p>
1.80	<p>U.S. Highway No. 95A, 60 lks. wide, asphalt surface, bears N. 5° E. and S. 5° W.</p>
20.011	<p>Point for the C-E 1/16 sec. cor. of sec. 4. Not monumented.</p>
40.022	<p>The point for the center 1/4 sec. cor. of sec. 4.</p>
60.001	<p>Point for the C-W 1/16 sec. cor. of sec. 4. Not monumented.</p>
79.980	<p>The 1/4 sec. cor. of sec. 4 only, on the W. bdy. of sec. 4.</p> <hr/> <p>From the E 1/16 sec. cor. of secs. 4 and 9.</p> <p>N. 0°24'20" E., on the N-S center line of the SE1/4 of sec. 4.</p> <p>Over nearly level land.</p>
19.946	<p>Point for the SE 1/16 sec. cor. of sec. 4, at intersection with the E-W center line of the SE1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

SUBDIVISION OF SECTION 4,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	SE 1/16 S 4
	2002
	Set a carsonite post, 5 ft. long, alongside the stainless steel post.
	From this corner, a point determined as the SE 1/16 sec. cor. of sec. 4, by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1986, monumented with a rebar, 5/8 in. diam., projecting 4 ins. above the ground, with an aluminum cap mkd. SE 1/16 S4 1986 LS 4045, as recorded in Lyon County Survey File No. 102305, bears N. 56°37'00" E., 0.037 chs. dist. This position was determined using improper control and is not utilized in this survey.
35.70	Enter mine tailings, edge bears E. and W.
39.886	The point for the C-E 1/16 sec. cor. of sec. 4
	<hr/> From the S 1/16 sec. cor. of secs. 3 and 4. N. 89°39'50" W., on the E-W center line of the SE1/4 of sec. 4. Over nearly level land.
2.80	U.S. Highway No. 95A, 60 lks. wide, asphalt surface, bears N. 5° E. and S. 5° W.
3.55	Graveled road, 20 lks. wide, bears NNE and SSW.
4.10	Wire fence, bears N. 8° E. and W.
10.85	Enter mine tailings, edge bears N. and S.
20.015	The SE 1/16 sec. cor. of sec. 4.
40.027	The point for the C-S 1/16 sec. cor. of sec. 4.
	<hr/> From the W 1/16 sec. cor. of secs. 4 and 9. N. 0°27'10" E., on the N-S center line of the SW1/4 of sec. 4. Over mine tailings.
19.847	Point for the SW 1/16 sec. cor. of sec. 4, at intersection with the E-W center line of the SW1/4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	SW 1/16 S 4
	2002
	Set a carsonite post, 5 ft. long, alongside the stainless steel post.

SUBDIVISION OF SECTION 4,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From this corner, a point determined as the SW 1/16 sec. cor. of sec. 4, by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1986, monumented with a rebar, 5/8 in. diam., projecting 4 ins. above the ground, with an aluminum cap mkd. SW 1/16 S4 1986 LS 4045, as recorded in Lyon County Survey File No. 102305, bears S. 88°36'00" E., 0.126 chs. dist. This position was determined using improper control and is not utilized in this survey.</p>
35.40	Leave mine tailings, edge bears E. and W.; over nearly level land.
39.694	The point for the C-W 1/16 sec. cor. of sec. 4.
	<hr/> <p>From the point for the C-S 1/16 sec. cor. of sec. 4. N. 89°39'20" W., on the E-W center line of the SW1/4 of sec. 4. Over mine tailings.</p>
19.996	The SW 1/16 sec. cor. of sec. 4.
39.992	The S 1/16 sec. cor. of sec. 4 only, on the W. bdy. of sec. 4.
	<hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 5, T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the true point for the 1/4 sec. cor. of secs. 5 and 8. N. 0°06'50" W., on the N-S center line of sec. 5. Over mine tailings.</p>
27.60	Graveled road, 75 lks. wide, bears N. 25° W. and S. 35° E.
38.40	Leave mine tailings, enter tailings pond, edge bears E. and W.
40.016	<p>True point for the center 1/4 sec. cor. of sec. 5, at intersection with the E-W center line of sec. 5, located in tailings pond where it is impracticable to establish a permanent monument.</p> <p>From this point, the point selected for the witness corner to the center 1/4 sec. cor. of sec. 5, bears N. 53°14'00" E., 2.203 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p>WC T13N R25E ← C 1/4 S 5 2002</p>

SUBDIVISION OF SECTION 5,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p>
41.70	Leave tailings pond; enter mine tailings, edge bears E. and W.
59.996	<p>Point for the C-N 1/16 sec. cor. of sec. 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> $\begin{array}{c} C \\ N \ 1/16 \   \ S \ 5 \\ C \end{array}$ <p style="text-align: center;">2002</p>
	<p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p>
70.30	Leave mine tailings, enter nearly level land.
75.10	Wire fence, bears E. and W.
75.880	The 1/4 sec. cor. of sec. 5 only, on the N. bdy. of the Tp.
	<hr/> <p>From the 1/4 sec. cor. of sec. 5 only, on the W. bdy. of sec. 4.</p> <p>S. 89°56'50" W., on the E-W center line of sec. 5.</p> <p>Over nearly level land.</p>
21.178	<p>Point for the C-E 1/16 sec. cor. of sec. 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> $\begin{array}{c} E \ 1/16 \\ C \ \frac{\quad}{\quad} \ C \\ S \ 5 \end{array}$ <p style="text-align: center;">2002</p>
	<p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <p>From this corner, a point determined as the C-E 1/16 sec. cor. of sec. 5, by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1986, monumented with a rebar, 5/8 in. diam., projecting 3 ins. above the ground, with an aluminum cap mkd. E 1/16 C-C S5 1986 LS 4045, as recorded in Lyon County Survey File No. 100056, bears S. 86°09'00" E., 0.400 chs. dist. This position was determined using improper control and is not utilized in this survey.</p>

SUBDIVISION OF SECTION 5,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
21.20	Enter tailings impoundment, edge bears N. and S.
34.20	Leave tailings impoundment, enter tailings pond, edge bears N. and S.
41.143	The true point for the center 1/4 sec. cor. of sec. 5.
43.30	Leave tailings pond, edge bears N. and S.; over nearly level land.
50.80	Graveled road, 75 lks. wide, bears N. 45° W. and S. 45° E.
58.70	Graveled road, 50 lks. wide, bears N. 15° E. and S. 15° W.
61.117	Point for the C-W 1/16 sec. cor. of sec. 5. Not monumented.
81.091	The 1/4 sec. cor. of secs. 5 and 6.
	<hr/>
	From the E 1/16 sec. cor. of secs. 5 and 8.
	N. 0°11'00" W., on the N-S center line of the SE1/4 of sec. 5.
	Over mine tailings.
40.016	The C-E 1/16 sec. cor. of sec. 5.
	<hr/>
	From the point for the C-W 1/16 sec. cor. of sec. 5.
	N. 0°03'20" W., on the N-S center line of the NW1/4 of sec. 5.
	Over nearly level land.
14.40	Graveled road, 75 lks. wide, bears N. 50° W. and S. 50° E.
19.970	Point for the NW 1/16 sec. cor. of sec. 5, at intersection with the E-W center line of the NW1/4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	NW 1/16 S 5
	2002
	Set a carsonite post, 5 ft. long, alongside the stainless steel post.
	From this corner, a point determined as the NW 1/16 sec. cor. of sec. 5, by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1986, monumented with a rebar, 5/8 in. diam., projecting 4 ins. above the ground, with an aluminum cap mkd. NW 1/16 S5 1986 LS 4045, as recorded in Lyon County Survey File No. 100056, bears N. 58°12'00" E., 0.017 chs. dist. This position was determined using improper control and is not utilized in this survey.

## 150

SUBDIVISION OF SECTION 5,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
28.50	Graveled road, 75 lks. wide, bears N. 50° E. and S. 50° W.
35.00	Wire fence, bears E. and W.
35.756	The W 1/16 sec. cor. of sec. 5 only, on the N. bdy. of the Tp.
	<hr/>
	From the C-N 1/16 sec. cor. of sec. 5.
	S. 89°55'00" W., on the E-W center line of sec. 5.
	Over mine tailings.
12.80	Leave mine tailings, edge bears N. and S; over nearly level land.
19.953	The NW 1/16 sec. cor. of sec. 5.
24.60	Graveled road, 75 lks. wide, bears N. 40° E. and S. 30° W.
39.905	The point for the N 1/16 sec. cor. of secs. 5 and 6.
	<hr/>
	SUBDIVISION OF SECTION 8, T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA
	<hr/>
	From the 1/4 sec. cor. of secs. 8 and 17.
	N. 0°01'00" E., on the N-S center line of sec. 8.
	Over mine tailings.
14.48	Graveled road, 75 lks. wide, bears N. 50° W. and S. 50° E.
19.990	Point for the C-S 1/16 sec. cor. of sec. 8. Not monumented.
	From this point, a point determined as the C-S 1/16 sec. cor. of sec. 8, by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1986, monumented with a rebar, 5/8 in. diam., projecting 2 ins. above the ground, with an aluminum cap mkd. C-S 1/16 S8 1988 RLS 4045, as recorded in Lyon County Survey File No. 100056, bears S. 36°06'00" E., 0.030 chs. dist. This position was determined using improper control and is not utilized in this survey.
39.980	Point for the center 1/4 sec. cor. of sec. 8, at intersection with the E-W center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T13N R25E C 1/4 S 8  2002

SUBDIVISION OF SECTION 8,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Set a carsonite post, 5 ft. long, alongside the stainless steel post.
59.977	Point for the C-N 1/16 sec. cor. of sec. 8. Not monumented.
79.974	The true point for the 1/4 sec. cor. of secs. 5 and 8.
	<hr/>
	From the 1/4 sec. cor. of sec. 8 only, on the W. bdy. of sec. 9.
	West, on the E-W center line of sec. 8.
14.40	Graveled road, 75 lks. wide, bears N. and S.
20.754	Point for the C-E 1/16 sec. cor. of sec. 8.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	$C \frac{E \ 1/16}{S \ 8} C$
	2002
	A rebar, 5/8 in. diam., was laying loosely on the ground, with aluminum cap mkd. E 1/16 S8 1986 LS 4045.
	Deposit the rebar and set a carsonite post, 5 ft. long, alongside the stainless steel post.
40.768	The center 1/4 sec. cor. of sec. 8.
60.780	Point for the C-W 1/16 sec. cor. of sec. 8. Not monumented.
72.35	Leave mine tailings, edge bears N. 15° E. and S. 15° W.; asc. NE slope.
79.00	Power transmission line, bears N. and S.
79.55	Power transmission line, bears N. and S.
80.792	The 1/4 sec. cor. of secs. 7 and 8.
	<hr/>
	From the C-E 1/16 sec. cor. of sec. 8.
	N. 0°01'20" E., on the N-S center line of the NE1/4 of sec. 8.
	Over mine tailings.
20.006	Point for the NE 1/16 sec. cor. of sec. 8, at intersection with the E-W center line of the NE1/4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

SUBDIVISION OF SECTION 8,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	NE 1/16 S 8
	2002
	Set a carsonite post, 5 ft. long, alongside the stainless steel post.
	From this corner, a point determined as the NE 1/16 sec. cor. of sec. 8, by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1986, monumented with a rebar, 5/8 in. diam., projecting 5 ins. above the ground, with an aluminum cap mkd. NE 1/16 S8 1986 LS 4045, as recorded in Lyon County Survey File No. 100056, bears N. 87°10'00" E., 0.111 chs. dist. This position was determined using improper control and is not utilized in this survey.
25.90	Graveled road, 75 lks. wide, bears E. and S. 70° W.
34.85	Graveled road, 75 lks. wide, bears N. 40° E. and S. 40° W.
40.012	The E 1/16 sec. cor. of secs. 5 and 8.
	From the N 1/16 sec. cor. of sec. 8 only, on the W. bdy. of sec. 9.
	S. 89°58'30" W., on the E-W center line of the NE1/4 of sec. 8.
	Over mine tailings.
14.70	Graveled road, 75 lks. wide, bears N. and S.
20.725	The NE 1/16 sec. cor. of sec. 8.
34.85	Graveled road, 75 lks. wide, bears N. 60° E. and S. 75° W.
38.35	Graveled road, 75 lks. wide, bears N. 70° W. and S. 70° E.
40.740	The point for the C-N 1/16 sec. cor. of sec. 8.
	From the E 1/16 sec. cor. of secs. 8 and 17.
	N. 0°00'40" E., on the N-S center line of the SE1/4 of sec. 8.
	Over nearly level land.
14.25	Graveled road, 75 lks. wide, bears N. 35° E. and S. 40° W.
17.40	Enter mine tailings, edge bears N. 25° E. and S. 25° W.
39.984	The C-E 1/16 sec. cor. of sec. 8.
	From the W 1/16 sec. cor. of secs. 8 and 17.
	N. 0°01'00" W., on the N-S center line of the SW1/4 of sec. 8.

SUBDIVISION OF SECTION 8,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Over nearly level land.
19.999	<p>Point for the SW 1/16 sec. cor. of sec. 8, at the intersection with the E-W center line of the SW1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SW 1/16 S 8</p> <p style="text-align: center;">2002</p> <p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <p>From this corner, a point determined as the SW 1/16 sec. cor. of sec. 8, by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1986, monumented with a rebar, 5/8 in. diam., projecting 2 ins. above the ground, with an aluminum cap mkd. SW 1/16 S8 1986 LS 4045, as recorded in Lyon County Survey File No. 100056, bears S. 84°59'00" E., 0.034 chs. dist. This position was determined using improper control and is not utilized in this survey.</p>
31.50	Graveled road, 60 lks. wide, bears N. 40° W. and S. 30° E.
39.998	The point for the C-W 1/16 of sec. 8.
	<hr/> <p>From the point for the C-S 1/16 sec. cor. of sec. 8.</p> <p>S. 89°58'30" W., on the E-W center line of the SW1/4 of sec. 8.</p> <p>Over mine tailings.</p>
6.35	Graveled road, 60 lks. wide, bears N. 50° W. and S. 50° E.
20.001	The SW 1/16 sec. cor. of sec. 8.
38.03	Graveled road, 60 lks. wide, bears N. 30° W. and S. 30° E.
39.00	Power transmission line, bears N. and S.
39.50	Power transmission line, bears N. and S.
40.002	The S 1/16 sec. cor. of secs. 7 and 8.
	<hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 9, T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 9 and 16.</p> <p>N. 0°14'00" E., on the N-S center line of sec. 9.</p> <p>Over rolling hills.</p>

SUBDIVISION OF SECTION 9,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
5.75	Asphalt road, 45 lks. wide, bears N. 80° W. and S. 75° E.
13.95	Ridge, bears N. 65° E. and S. 85° W.; desc. over N. slope.
19.70	Head of ravine, drains N. 70° E.
20.092	Point for the C-S 1/16 sec. cor. of sec. 9. Not monumented.
40.184	Point for the center 1/4 sec. cor. of sec. 9, at intersection with the E-W center line.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.  T13N R25E C 1/4 S 9  2002  Set a carsonite post, 5 ft. long, alongside the stainless steel post.  From this corner, a point determined as the center 1/4 sec. cor. of sec. 9, by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1986, monumented with a rebar, 5/8 in. diam., projecting 4 ins. above the ground, with an aluminum cap mkd. C1/4 S9 1986 RLS 4045, as recorded in Lyon County Survey File No. 100056, bears N. 49°49'00" E., 0.047 chs. dist. This position was determined using improper control and is not utilized in this survey.  From this same corner, Anaconda Control Station NN, monumented with an iron pipe, 2 ins. diam., firmly set in concrete, bears N. 69°38'24" E., 21.384 chs. dist.  From this same corner, Anaconda Control Station KK, monumented with an iron pipe, 2 ins. diam., firmly set in concrete, bears N. 73°48'00" W., 3.836 chs. dist.
41.50	Ridge, bears NE and W.
49.70	Enter mine tailings, edge bears N. 60° E. and N. 80° W.
60.099	Point for the C-N 1/16 sec. cor. of sec. 9. Not monumented.
80.014	The 1/4 sec. cor. of secs. 4 and 9.  From the 1/4 sec. cor. of secs. 9 and 10.  N. 89°24'10" W., on the E-W center line of sec. 9.  Over nearly level land.
3.00	U.S. Highway No. 95A, 60 lks. wide, asphalt surface, bears N. 5° W. and S. 5° E.

SUBDIVISION OF SECTION 9,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.013	Point for the C-E 1/16 sec. cor. of sec. 9. Not monumented.
40.026	The center 1/4 sec. cor. of sec. 9.
44.00	Ridge, bears N. and SSE.
54.25	Enter mine tailings, edge bears N. 15° E. and S. 25° E.
59.941	Point for the C-W 1/16 sec. cor. of sec. 9.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.  <div style="text-align: center;"> <math display="block">\begin{array}{c} \text{W } 1/16 \\ \text{C } \frac{\quad}{\quad} \text{C} \\ \text{S } 9 \\ \\ 2002 \end{array}</math> </div> Set a carsonite post, 5 ft. long, alongside the stainless steel post.  From this corner, a point determined as the C-W 1/16 sec. cor. of sec. 9, by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1986, monumented with a rebar, 5/8 in. diam., projecting 2 ins. above the ground, with an aluminum cap with illegible marks, as recorded in Lyon County Survey File No. 100056, bears N. 65°30'00" W., 0.084 chs. dist. This position was determined using improper control and is not utilized in this survey.
67.10	Graveled road, 50 lks. wide, bears N. 50° E. and S. 50° W.
79.856	The 1/4 sec. cor. of sec. 9 only, on the W. bdy. of sec. 9. <hr/>
	From the point for the C-E 1/16 sec. cor. of sec. 9. N. 0°14'10" E., on the N-S center line of the NE1/4 of sec. 9. Over rolling hills.
7.10	Ridge, bears E. and W.
15.75	Enter mine tailings, edge bears N. 70° E. and S. 70° W.
19.935	Point for the NE 1/16 sec. cor. of sec. 9, at intersection with the E-W center line of the NE1/4. Not monumented.
39.870	The E 1/16 sec. cor. of secs. 4 and 9. <hr/>
	From the N 1/16 sec. cor. of secs. 9 and 10. N. 89°27'40" W., on the E-W center line of the NE1/4 of sec. 9.

SUBDIVISION OF SECTION 9,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Over nearly level land.
4.90	U.S. Highway No. 95A, 60 lks. wide, asphalt surface, bears N. 5° W. and S. 5° E.
10.006	Point for the C-E-NE 1/64 sec. cor. of sec. 9.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.  S 9 C-E-NE 1/64  2002  Set a carsonite post, 5 ft. long, alongside the stainless steel post.
11.20	Enter mine tailings, edge bears N. and S.
20.012	The point for the NE 1/16 sec. cor. of sec. 9.
40.025	The point for the C-N 1/16 sec. cor. of sec. 9.
	From the C-E-NE 1/64 sec. cor. of sec. 9.  N. 0°14'10" E., on the N-S center line of the NE1/4NE1/4 of sec. 9.  Over mine tailings.
19.945	The E-E 1/64 sec. cor. of secs. 4 and 9.
	From the point for the W 1/16 sec. cor. of secs. 9 and 16.  N. 0°16'40" E., on the N-S center line of the SW1/4 of sec. 9.  Over mine tailings.
15.90	Graveled road, 40 lks. wide, bears N. 20° E. and S. 20° W.
20.036	Point for the SW 1/16 sec. cor. of sec. 9, at intersection with the E-W center line of the SE1/4.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.  SW 1/16 S 9  2002  Set a carsonite post, 5 ft. long, alongside the stainless steel post.

SUBDIVISION OF SECTION 9,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From this corner, a point determined as the SW 1/16 sec. cor. of sec. 9, by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1986, monumented with a rebar, 5/8 in. diam., projecting 2 ins. above the ground, with an aluminum cap mkd. SW 1/16 S9 1986 LS 4045, as recorded in Lyon County Survey File No. 100056, bears N. 65°17'00" W., 0.034 chs. dist. This position was determined using improper control and is not utilized in this survey.</p>
40.071	<p>The C-W 1/16 sec. cor. of sec. 9.</p> <hr/> <p>From the point for the C-S 1/16 sec. cor. of sec. 9. N. 89°14'20" W., on the E-W center line of the SW1/4 of sec. 9. Over rolling hills.</p>
5.70	Ridge, bears N. 10° W. and S. 10° E.
12.25	Enter mine tailings, edge bears N. and S.
18.95	Graveled road, 40 lks. wide, bears N. 20° E. and S. 20° W.
19.932	The SW 1/16 sec. cor. of sec. 9.
39.864	<p>The S 1/16 sec. cor. of sec. 9 only, on the W. bdy. of sec. 9.</p> <hr/> <p>From the C-W 1/16 sec. cor. of sec. 9. N. 0°05'10" E., on the N-S center line of the NW1/4 of sec. 9. Over mine tailings.</p>
19.895	<p>Point for the NW 1/16 sec. cor. of sec. 9, at intersection with the E-W center line of the NW1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S 9 2002</p> <p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p>
39.790	<p>From this corner, a point determined as the NW 1/16 sec. cor. of sec. 9, by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1986, monumented with a rebar, 5/8 in. diam., projecting 2 ins. above the ground, with an aluminum cap mkd. NW 1/16 S9 1986 RLS 4045, as recorded in Lyon County Survey File No. 100056, bears N. 66°31'00" E., 0.047 chs. dist. This position was determined using improper control and is not utilized in this survey.</p> <p>The W 1/16 sec. cor. of secs. 4 and 9.</p> <hr/>

## 158

SUBDIVISION OF SECTION 9,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the point for the C-N 1/16 sec. cor. of sec. 9. N. 89°27'40" W., on the E-W center line of the NW1/4 of sec. 9. Over mine tailings.</p>
19.964	The NW 1/16 sec. cor. of sec. 9.
39.928	The N 1/16 sec. cor. of sec. 9 only, on the W. bdy. of sec. 9.
<hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 16, T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>	
	<p>From the point for the 1/4 sec. cor. of secs. 16 and 21. N. 0°04'40" E., on the N-S center line of sec. 16. Over open pit.</p>
11.05	Leave open pit, edge bears N. 45° W. and S. 45° E.
20.207	Point for the C-S 1/16 sec. cor. of sec. 16. Not monumented.
23.35	Graveled road, 75 lks. wide, bears N. 55° W. and S. 55° E.
26.05	Graveled road, 45 lks. wide, bears N. 60° W. and S. 60° E.
27.40	Enter mine tailings, edge bears N. 60° W. and S. 60° E.
29.194	Intersect a portion of line 3-4, New Royal Blue lode, at a point from which Cor. No. 4, New Royal Blue lode identical with Cor. No. 2, New Royal Blue Extension lode, both of Mineral Survey No. 4531, hereinbefore described, bears S. 82°52'00" E., 3.137 chs. dist.
40.414	<p>Point for the center 1/4 sec. cor. of sec. 16, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T13N R25E C 1/4 S16</p> <p style="text-align: center;">2004</p>
	Set a steel fence post alongside the stainless steel post.
40.655	Intersect line 3-4, New Blue Bird No. 1 lode, at a point from which the point for Cor. No. 4, New Blue Bird No. 1 lode, identical with Cor. No. 3, New Blue Bird lode, both of Mineral Survey No. 4531, bears S. 7°09'00" W., 2.283 chs. dist.
56.678	Intersect line 2-3, Mineral Survey 4531, New Blue Bird No. 2 lode, at a point from which Cor. No. 3, hereinbefore described, bears S. 82°52'00" E., 1.973 chs. dist.

SUBDIVISION OF SECTION 16,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
60.637	Point for the C-N 1/16 sec. cor. of sec. 16. Not monumented.
70.61	Leave mine tailings, edge bears N. 45° E. and S. 45° W.
80.860	The 1/4 sec. cor. of secs. 9 and 16.
	<hr/> <p>From the 1/4 sec. cor. of secs. 15 and 16.</p> <p>N. 89°31'20" W., on the E-W center line of sec. 16.</p> <p>Over rolling hills.</p>
2.791	Nevada State Route No. 339, 60 lks. wide, asphalt surface, bears N. 5° E. and S. 5° W.
6.113	A property cor. determined by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1985, monumented with a rebar, 5/8 in. diam., with a plastic cap mkd. 4045, as recorded in Lyon County Survey File No. 96203.
	From this point, a rebar, 1/2 in. diam., set by person(s) unknown, bears S. 26°20'00" W., 0.021 chs. dist.
14.40	Ridge, bears N. and S.
18.85	Power transmission line, bears N. 10° W. and S. 10° E.
19.953	The C-E 1/16 sec. cor. of sec. 16, determined by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1985, monumented with a rebar, 5/8 in. diam., firmly set 2 ins. below the surface of the ground, with remains of a plastic cap, as recorded in Lyon County Survey File No. 96203. This is accepted as a careful and faithful determination of the position of the corner.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 30 ins. in the ground, the top is 2 ins. below surface of the ground, over a plastic-encased magnet, with brass cap mkd.
	$\begin{array}{c} \text{E } 1/16 \\ \text{C} \text{ --- } \text{C} \\ \text{S16} \\ 2002 \end{array}$
	Deposit rebar inside of the stainless steel post.
	From this corner, a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA B 88+50.00 POT STA E1-26+86.45 PC DIST 45.17 ANGLE 90 bears N. 60°40'30" E., 3.853 chs. dist.
	From this same corner, a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA B 86+12.41 PT DIST 45.53 ANGLE 90 bears S. 62°06'10" E., 3.662 chs. dist.
	<hr/>

SUBDIVISION OF SECTION 16,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 89°31'10" W., beginning new measurement.
4.15	Enter mine tailings, edge bears N. 10° W. and S. 10° E.
19.953	The center 1/4 sec. cor. of sec. 16.
19.983	Intersect line 3-4, New Blue Bird No. 1 lode, at a point from which the point for Cor. No. 4, New Blue Bird No. 1 lode, identical with Cor. No. 3, New Blue Bird lode, both of Mineral Survey No. 4531, hereinbefore described, bears S. 07°09'00" W., 2.040 chs. dist.
39.885	Point for the C-W 1/16 sec. cor. of sec. 16. Not monumented.
57.45	Leave mine tailings, edge bears N. 20° W. and S. 20° E.
59.817	The 1/4 sec. cor. of sec. 16 only, on the W. bdy. of sec. 16.
	<hr/>
	From the C-E 1/16 sec. cor. of sec. 16.
	N. 0°10'50" E., on the N-S center line of the NE1/4 of sec. 16.
	Over nearly level land.
13.450	From this point, a property cor. determined by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1985, monumented with a rebar, 5/8 in. diam., with a plastic cap mkd. 4045, as recorded in Lyon County Survey File No. 96203, bears East, 0.006 chs. dist.
19.035	From this point, a rebar, 1 in. diam., set by person(s) unknown, in a fence line, bears N. and S., bears East, 0.012 chs. dist.
27.608	From this point, a property cor. determined by Walter G. Reid, Nevada Registered Engineer No. 235, in 1966, monumented with a rebar, 5/8 in. diam., at intersection of fence lines, extending S. and E., as recorded in Lyon County Survey File No. 49295, bears East, 0.012 chs. dist.
33.966	From this corner, a property cor. determined by Walter G. Reid, Nevada Registered Engineer No. 235, in 1966, monumented with a rebar, 5/8 in. diam., as recorded in Lyon County Survey File No. 49295, bears East, 0.019 chs. dist.
40.335	The E 1/16 sec. cor. of secs. 9 and 16.
	<hr/>
	From the point for the E 1/16 sec. cor. of secs. 16 and 21.
	N. 0°05'50" E., on the N-S center line of the SE1/4 of sec. 16.
	Over open pit.
8.410	Intersect line 2-3, Mineral Survey No. 4531, Consolidated Fraction lode, at a point from which Cor. No. 3, hereinbefore described, bears S. 82°52'00" E., 1.012 chs. dist.
8.414	Intersect line 4-1, Mineral Survey No. 4531, Candidate lode, at a point from which Cor. No. 4, hereinbefore described, bears S. 82°57'00" E., 3.518 chs. dist.

## 161

SUBDIVISION OF SECTION 16,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.120	<p>Point for the SE 1/16 sec. cor. of sec. 16, at intersection with the E-W center line of the SE1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S16</p> <p style="text-align: center;">2004</p> <p>Set a steel fence post, 5 ft. long, alongside the stainless steel post.</p>
26.732	Intersect line 2-3, Mineral Survey No. 4531, New Royal Blue Extension lode, at a point from which Cor. No. 3, hereinbefore described, bears S. 82°57'00" E., 5.748 chs. dist.
40.259	<p>The C-E 1/16 sec. cor. of sec. 16.</p> <hr/> <p>From the S 1/16 sec. cor. of secs. 15 and 16.</p> <p>N. 89°42'50" W., on the E-W center line of the SE1/4 of sec. 16.</p> <p>Over nearly level land.</p>
4.75	Nevada State Route No. 339, 60 lks. wide, asphalt surface, bears N. 5° E. and S. 5° W.
5.502	A property cor. determined by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1984, monumented with a rebar, 5/8 in. diam., with a plastic cap mkd. 4045, as recorded in Lyon County Survey File No. 85452.
11.05	Ridge, bears N. 15° W. and S. 15° E.
11.467	A property cor. determined by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1984, monumented with a rebar, 5/8 in. diam., with a plastic cap mkd. 4045, as recorded in Lyon County Survey File No. 85452.
14.00	Power transmission line, bears N. 20° W. and S. 20° E.
14.696	<p>Point for a witness point on the E-W center line of the SE1/4 of sec. 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">WP S S ——— S 16 2004</p> <p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p>

SUBDIVISION OF SECTION 16,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
14.961	From this corner, a property cor. determined by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1989, monumented with a rebar, 5/8 in. diam., with a plastic cap mkd. 4045, as recorded in Lyon County Survey File No. 128595, bears South, 0.062 chs. dist.
14.972	Intersect line 3-4, New Royal Blue Extention lode, at a point from which the witness cor. to Cor. No. 4, New Royal Blue Extention lode, identical with Cor. No. 3, Canidate lode, both of Mineral Survey No. 4531, hereinbefore described, bears S. 7°06'00" W., 1.963 chs. dist.
19.951	The SE 1/16 sec. cor. of sec. 16.
39.889	The point for the C-S 1/16 sec. cor. of sec. 16.
	<hr/> From the point for the C-W 1/16 sec. cor. of sec. 16. N. 0°03'10" E., on the N-S center line of the NW1/4 of sec. 16. Over nearly level land.
18.594	Intersect line 2-3, Mineral Survey No. 4531, New Blue Bird No. 2 lode, at a point from which the true point for Cor. No. 2, hereinbefore described, bears N. 82°52'00" W., 0.663 chs. dist.
20.300	Point for the NW 1/16 sec. cor. of sec. 16, at intersection with the E-W center line of the NW1/4.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	NW 1/16 S16 2002
	Set a carsonite post, 5 ft. long, alongside the stainless steel post.
30.90	Enter mine tailings, edge bears N. 40° E. and S. 40° W.
31.50	Asphalt road, 60 lks. wide, bears N. 40° E. and S. 40° W.
33.00	Leave mine tailings, edge bears N. 70° E. and S. 70° W.; over nearly level land.
40.600	The point for the W 1/16 sec. cor. of secs. 9 and 16.
	<hr/> From the point for the C-N 1/16 sec. cor. of sec. 16. N. 89°17'50" W., on the E-W center line of the NW1/4 of sec. 16. Over mine tailings.

SUBDIVISION OF SECTION 16,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
19.941	The NW 1/16 cor. of sec. 16.
28.30	Leave mine tailings, edge bears N. 40° E. and S. 40° W.; over nearly level land.
32.21	Asphalt road, 60 lks. wide, bears N. 60° E. and S. 50° W.
39.882	The N 1/16 cor. of sec. 16 only, on the W. bdy. of sec. 16.
<hr/> SUBDIVISION OF SECTION 17, T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA <hr/>	
	From the 1/4 sec. cor. of secs. 17 and 20.
	N. 0°02'00" W., on the N-S center line of sec. 17.
	Over nearly level land.
9.982	Point for the C-S-S 1/64 sec. cor. of sec. 17. Not monumented.
14.973	Point for the C-N-S-S 1/256 sec. cor. of sec. 17. Not monumented.
19.964	Point for the C-S 1/16 sec. cor. of sec. 17. Not monumented.
29.946	Point for the C-N-S 1/64 sec. cor. of sec. 17. Not monumented.
39.928	Point for the center 1/4 sec. cor. of sec. 17, at intersection with the E-W center line.
	Set a copper-coated steel stake, 24 ins. long, 1/2 in. diam., 25 ins. in the ground, the top is 1 in. below the asphalt surface of driveway, with brass cap mkd.
	T13N R25E C 1/4 S17  2004
	from which
	A PK nail with shiner, in a concrete retaining wall, mkd. RM1 12.63 and an arrow pointing to the cor., bears N. 67°09'00" E., 0.191 chs. dist.
	A PK nail with shiner, in a concrete retaining wall, mkd. RM2 16.99 and an arrow pointing to the cor., bears N. 9°34'00" W., 0.257 chs. dist.
49.919	The C-S-N 1/64 sec. cor. of sec. 17, determined by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1987, monumented with a rebar, 5/8 in. diam., with plastic cap mkd. RLS 4045, as recorded in Lyon County Survey File No. 111528. This is accepted as a careful and faithful determination of the position of the corner.

SUBDIVISION OF SECTION 17,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S17 C-S-N 1/64</p> <p style="text-align: center;">2002</p> <p>Deposit the rebar and set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <hr/> <p>N. 0°01'10" W., beginning new measurement.</p> <p>5.10 Power transmission line, bears N. 55° W. and S. 55° E.</p> <p>7.12 Graveled road, 60 lks. wide, bears N. 55° W. and S. 55° E.</p> <p>10.004 Point for the C-N 1/16 sec. cor. of sec. 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">C N 1/16   S17 C</p> <p style="text-align: center;">2002</p> <p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <p>From this corner, Anaconda Control Station N, monumented with an iron pipe, 2 ins. diam., projecting 6 ins. above the ground, firmly set in concrete, 10 ins. diam., with threaded metal cap mkd. N, bears S. 59°05'10" W., 10.531 chs. dist.</p> <p>10.80 Enter mine tailings, edge bears N. 85° W. and S. 80° E.</p> <p>30.012 The 1/4 sec. cor. of secs. 8 and 17.</p> <hr/> <p>From the 1/4 sec. cor. of sec. 17 only, on the W. bdy. of sec. 16.</p> <p>N. 89°56'40" W., on the E-W center line of sec. 17.</p> <p>Over nearly level land.</p> <p>2.05 Graveled road, 80 lks. wide, bears N. 40° W. and S. 40° E.</p> <p>5.726 Intersect line 1-2, Mineral Survey No. 4778, No. 38 lode, at a point from which Cor. No. 1, hereinbefore described, bears N. 7°06'00" E., 1.976 chs. dist.</p>
--------	---

SUBDIVISION OF SECTION 17,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.496	<p>The C-E 1/16 sec. cor. of sec. 17, determined by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1987, monumented with a rebar, 5/8 in. diam., with a plastic cap mkd. RLS 4045, as recorded in Lyon County Survey File No. 111528. This is accepted as a careful and faithful determination of the position of the corner.</p> <hr style="width: 20%; margin: 10px auto;"/> <p style="text-align: center;">S. 89°58'00" W., beginning new measurement.</p>
20.033	The center 1/4 sec. cor. of sec. 17.
30.037	Point for the C-E-W 1/64 sec. cor. of sec. 17. Not monumented.
35.039	<p>The C-W-E-W 1/256 sec. cor. of sec. 17, determined by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1987, monumented with a rebar, 5/8 in. diam., with a plastic cap mkd. RLS 4045, as recorded in Lyon County Survey File No. 111528. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;">       S17        C-W-E-W        1/256         2002     </div> <p>Deposit the rebar inside and set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p style="text-align: center;">S. 89°58'00" W., beginning new measurement.</p>
5.002	<p>The C-W 1/16 sec. cor. of sec. 17, determined by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1987, monumented with a rebar, 5/8 in. diam., with a plastic cap mkd. RLS 4045, as recorded in Lyon County Survey File No. 111528. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;">       W 1/16        C ————— C        S17         2002     </div>

SUBDIVISION OF SECTION 17,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Deposit the rebar inside and set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <hr/> <p>N. 89°59'30" W., beginning new measurement.</p>
19.978	<p>The 1/4 sec. cor. of secs. 17 and 18.</p> <hr/> <p>From the C-E 1/16 sec. cor. of sec. 17.</p> <p>N. 0°02'10" W., on the N-S center line of the NE1/4 of sec. 17.</p> <p>Over nearly level land.</p>
4.80	<p>Enter mine tailings, edge bears N. 50° W. and S. 50° E.</p>
9.991	<p>Point for the C-S-NE 1/64 sec. cor. of sec. 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S17 C-S-NE 1/64  2002</p>
19.982	<p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <p>Point for the NE 1/16 sec. cor. of sec. 17, at intersection with the E-W center line of the NE1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S17  2002</p>
39.987	<p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <p>The E 1/16 sec. cor. of secs. 8 and 17.</p> <hr/> <p>From the point for the N 1/16 sec. cor. of sec. 17 only, on the W. bdy. of sec. 16.</p> <p>N. 89°59'50" W., on the E-W center line of the NE1/4 of sec. 17.</p> <p>Over nearly level land.</p>
20.517	<p>The NE 1/16 sec. cor. of sec, 17.</p>

SUBDIVISION OF SECTION 17,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
27.00	Enter mine tailings, edge bears N. 10° W. and S. 10° E.
27.90	Wire fence, bears N. 5° W. and S. 5° E.
32.20	Wire fence, bears N. 5° W. and S. 5° E.
40.545	The C-N 1/16 sec. cor. of sec. 17.
<hr/>	
	From the C-S-NE 1/64 sec. cor. of sec. 17.
	S. 89°58'00" W., on the E-W center line of the SW1/4NE1/4 of sec. 17.
	Over nearly level land.
5.00	Enter mine tailings, edge bears N. 20° W. and S. 30° E.
10.30	Graveled road, 80 lks. wide, bears N. 55° W. and S. 55° E.
12.80	Power transmission line, bears N. 55° W. and S. 55° E.
20.031	The C-S-N 1/64 sec. cor. of sec. 17.
<hr/>	
	From the point for the E 1/16 sec. cor. of secs. 17 and 20.
	N. 0°00'40" E., on the N-S center line of the SE1/4 of sec. 17.
	Over nearly level land.
2.10	Enter open pit, edge bears N. 40° W. and S. 40° E.
7.143	Intersect line 4-1, Mineral Survey No. 4778, No. Seven lode at a point from which the point for Cor. No. 4, hereinbefore described, bears S. 82°54'00" E., 10.609 chs. dist.
9.987	Point for the C-S-SE 1/64 sec. cor. of sec. 17. Not monumented.
19.974	Point for the SE 1/16 sec. cor. of sec. 17, at intersection with the E-W center line of the SE1/4. Not monumented.
39.965	The C-E 1/16 sec. cor. of sec. 17.
<hr/>	
	From the point for the S 1/16 sec. cor. of sec. 17, on the W. bdy. of sec. 16.
	N. 89°57'20" W., on the E-W center line of the SE1/4 of sec. 17.
	Over open pit.
20.476	The point for the SE 1/16 sec. cor. of sec. 17.
30.485	Point for the C-W-SE 1/64 sec. cor. of sec. 17. Not monumented.
40.494	The point for the C-S 1/16 sec. cor. of sec. 17.
<hr/>	

SUBDIVISION OF SECTION 17,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the point for the W-E 1/64 sec. cor. of secs. 17 and 20. N. 0°00'40" W., on the N-S center line of the SW1/4SE1/4 of sec. 17.</p> <p>Over open pit.</p>
8.376	<p>Intersect line 4-1, Mineral Survey No. 4778, No. Seven lode, at a point from which Cor. No. 1, hereinbefore described, bears N. 82°54'00" W., 2.036 chs. dist.</p>
9.985	<p>Point for the SW-SE 1/64 sec. cor. of sec. 17, at intersection with the E-W center line of the SW1/4SE1/4. Not monumented.</p>
19.969	<p>The point for the C-W-SE 1/64 sec. cor. of sec. 17.</p> <hr/> <p>From the point for the C-S-SE 1/64 sec. cor. of sec. 17. N. 89°56'20" W., on the E-W center line of the SW1/4SE1/4 of sec. 17.</p> <p>Over open pit.</p>
5.003	<p>Point for the C-E-SW-SE 1/256 sec. cor. of sec. 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet with brass cap mkd.</p> <p style="text-align: center;">C-E-SW-SE 1/256 S17  2004</p> <p>Set a steel fence post alongside the stainless steel post.</p>
10.006	<p>The point for the SW-SE 1/64 sec. cor. of sec. 17.</p>
20.011	<p>The point for the C-S-S 1/64 sec. cor. of sec. 17.</p> <hr/> <p>From the E-W-E 1/256 sec. cor. of secs. 17 and 20. North, on the N-S center line of the SE1/4SW1/4SE1/4 of sec. 17.</p> <p>Over nearly level land.</p>
7.760	<p>Intersect line 4-1, Mineral Survey No. 4778, No. Seven lode at a point from which Cor. No. 1, hereinbefore described, bears N. 82°54'00" W., 7.077 chs. dist.</p>
7.779	<p>A property cor. determined by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1987, monumented with a rebar, 5/8 in. diam., with plastic cap mkd. 4045, as recorded in Lyon County Survey File No. 11528.</p>
9.986	<p>The point for the C-E-SW-SE 1/256 sec. cor. of sec. 17.</p> <hr/>

SUBDIVISION OF SECTION 17,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the W 1/16 sec. cor. of secs. 17 and 20.</p> <p>N. 0°03'10" W., on the N-S center line of the SW1/4 of sec. 17.</p> <p>Descend over NE slope.</p>
9.978	Point for the C-S-SW 1/64 sec. cor. of sec. 17. Not monumented.
19.956	Point for the SW 1/16 sec. cor. of sec. 17, at intersection with the E-W center line of the SW1/4. Not monumented.
29.933	<p>The C-N-SW 1/64 sec. cor. of sec. 17, determined by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1987, monumented with a rebar, 5/8 in. diam., with a plastic cap mkd. RLS 4045, as recorded in Lyon County Survey File No. 111528. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S17 C-N-SW 1/64</p> <p style="text-align: center;">2002</p> <p>Deposit the rebar and set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°02'30" W., beginning new measurement.</p>
9.976	<p>The C-W 1/16 sec. cor. of sec. 17.</p> <hr style="width: 50%; margin: 10px auto;"/> <p>From the point for the C-S 1/16 sec. cor. of sec. 17.</p> <p>S. 89°58'30" W., on the E-W center line of the SW1/4 of sec. 17.</p> <p>Ascend over SW slope.</p>
5.001	Point for the C-E-E-SW 1/256 sec. cor. of sec. 17. Not monumented.
10.002	The C-E-SW 1/64 sec. cor. of sec. 17, determined by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1987, monumented with a rebar, 5/8 in. diam., with a plastic cap mkd. RLS 4045, as recorded in Lyon County Survey File No. 111528. This is accepted as a careful and faithful determination of the position of the corner.

SUBDIVISION OF SECTION 17,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S17 C-E-SW 1/64</p> <p style="text-align: center;">2002</p> <p>Deposit the rebar and set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <hr/>
5.002	<p>N. 89°58'00" W., beginning new measurement.</p> <p>The C-W-E-SW 1/256 sec. cor. of sec. 17, determined by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1987, monumented with a rebar, 5/8 in. diam., with a plastic cap mkd. RLS 4045, as recorded in Lyon County Survey File No. 111528. This is accepted as a careful and faithful determination of the position of the corner.</p>
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S17 C-W-E-SW 1/256</p> <p style="text-align: center;">2002</p> <p>Deposit the rebar and set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <hr/>
	<p>N. 89°59'40" W., beginning new measurement.</p>
4.999	<p>The point for the SW 1/16 sec. cor. of sec. 17.</p>
24.986	<p>The point for the S 1/16 sec. cor. of secs. 17 and 18.</p> <hr/>
	<p>From the C-E-SW 1/64 sec. cor. of sec. 17.</p> <p>N. 0°02'20" W., on the N-S center line of the NE1/4SW1/4 of sec. 17.</p> <p>Descend over NE slope.</p>
9.981	<p>Point for the NE-SW 1/64 sec. cor. of sec. 17, at intersection with the E-W center line of the NE1/4SW1/4. Not monumented.</p>
19.962	<p>The point for the C-E-W 1/64 sec. cor. of sec. 17.</p> <hr/>

SUBDIVISION OF SECTION 17,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the point for the C-N-S 1/64 sec. cor. of sec. 17.</p> <p>S. 89°58'20" W., on the E-W center line of the NE1/4SW1/4 of sec. 17.</p> <p>Ascend over NE slope.</p> <p>10.003 The point for the NE-SW 1/64 sec. cor. of sec. 17.</p> <p>15.007 The C-W-NE-SW 1/256 sec. cor. of sec. 17, determined by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1987, monumented with a rebar, 5/8 in. diam., with a plastic cap mkd. RLS 4045, as recorded in Lyon County Survey File No. 111528. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S17 C-W-NE-SW 1/256</p> <p style="text-align: center;">2002</p> <p>Deposit the rebar and set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <hr/> <p>N. 89°59'20" W., beginning new measurement.</p> <p>5.000 The C-N-SW 1/64 sec. cor. of sec. 17.</p> <hr/> <p>From the C-W-E-SW 1/256 sec. cor. of sec. 17.</p> <p>N. 0°03'00" W., on the N-S center line of the SW1/4NE1/4SW1/4 of sec. 17.</p> <p>Descend over NE slope.</p> <p>9.976 The C-W-NE-SW 1/256 sec. cor. of sec. 17.</p> <hr/> <p>From the point for the E-W 1/64 sec. cor. of secs. 17 and 20.</p> <p>N. 0°02'50" W., on the N-S center line of the SE1/4SW1/4 of sec. 17.</p> <p>Descend over NE slope.</p> <p>9.979 Point for the SE-SW 1/64 sec. cor. of sec. 17, at intersection with the E-W center line of the SE1/4SW1/4. Not monumented.</p>
--------	---

SUBDIVISION OF SECTION 17,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
14.963	<p>The C-N-SE-SW 1/256 sec. cor. of sec. 17, determined by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1987, monumented with a rebar, 5/8 in. diam., with a plastic cap mkd. RLS 4045, as recorded in Lyon County Survey File No. 111528. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S17 C-N-SE-SW 1/256</p> <p style="text-align: center;">2002</p> <p>Deposit the rebar and set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <hr/> <p>N. 0°02'40" W., beginning new measurement.</p>
4.992	<p>The C-E-SW 1/64 sec. cor. of sec. 17.</p> <hr/> <p>From the point for the C-S-S 1/64 sec. cor. of sec. 17.</p> <p>N. 89°59'40" W., on the E-W center line of the SE1/4SW1/4 of sec. 17.</p> <p>Ascend over NE slope.</p>
5.000	<p>Point for the CE-SE-SW 1/256 sec. cor. of sec. 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S17 CE-SE-SW 1/256</p> <p style="text-align: center;">2002</p> <p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p>
10.000	<p>The point for the SE-SW 1/64 sec. cor. of sec. 17.</p>
20.001	<p>The point for the C-S-SW 1/64 sec. cor. of sec. 17.</p> <hr/> <p>From the CE-SE-SW 1/256 sec. cor. of sec. 17.</p> <p>N. 0°02'20" W., on the N-S center line of the NE1/4SE1/4SW1/4 of sec. 17.</p>

SUBDIVISION OF SECTION 17,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Over nearly level land.</p> <p>4.984 The NE-SE-SW 1/256 sec. cor. of sec. 17, determined by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1987, monumented with a rebar, 5/8 in. diam., with a plastic cap mkd. RLS 4045, as recorded in Lyon County Survey File No. 111528. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S17 NE-SE-SW 1/256  2002</p> <p>Deposit the rebar and set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <hr/> <p>N. 0°02'30" W., beginning new measurement.</p>
	<p>4.995 The point for the C-E-E-SW 1/256 sec. cor. of sec. 17.</p> <hr/> <p>From the point for the C-N-S-S 1/256 sec. cor. of sec. 17.</p> <p>S. 89°55'50" W., on the E-W center line of the NE1/4SE1/4SW1/4 of sec. 17.</p> <p>Ascend over NE slope.</p>
	<p>5.001 The NE-SE-SW 1/256 sec. cor. of sec. 17.</p> <hr/> <p>N. 89°59'40" W., beginning new measurement.</p>
	<p>5.001 The C-N-SE-SW 1/256 sec. cor. of sec. 17.</p> <hr/> <p>From the E-E-W 1/256 sec. cor. of secs. 17 and 20.</p> <p>N. 0°03'00" W., on the N-S center line of the SE1/4SE1/4SW1/4 of sec. 17.</p> <p>Over nearly level land.</p>
	<p>9.980 The CE-SE-SW 1/256 sec. cor. of sec. 17.</p> <hr/> <p>From the C-W 1/16 sec. cor. of sec. 17.</p> <p>North, on the N-S center line of the NW1/4 of sec. 17.</p>

SUBDIVISION OF SECTION 17,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Over nearly level land.
10.000	Point for the C-S-NW 1/64 sec. cor. of sec. 17. Not monumented.
20.000	Point for the NW 1/16 sec. cor. of sec. 17, at intersection with the E-W center line of the NW1/4. Not monumented.
29.00	Power transmission line, bears N. 55° W. and S. 55° E.
30.90	Graveled road, 80 lks. wide, bears N. 55° W. and S. 55° E.
32.95	Enter mine tailings, edge bears N. 75° W. and S. 60° E.
39.998	The W 1/16 sec. cor. of secs. 8 and 17.
	<hr/>
	From the C-N 1/16 sec. cor. of sec. 17.
	S. 89°58'40" W., on the E-W center line of the NW1/4 of sec. 17.
	Over nearly level land.
4.15	Graveled road, 80 lks. wide, bears N. 55° W. and S. 55° E.
7.25	Power transmission line, bears N. 55° W. and S. 55° E.
9.999	Point for the C-E-NW 1/64 sec. cor. of sec. 17. Not monumented.
19.998	The point for the NW 1/16 sec. cor. of sec. 17.
39.981	The point for the N 1/16 sec. cor. of secs. 17 and 18.
	<hr/>
	From the point for the C-E-W 1/64 sec. cor. of sec. 17.
	N. 0°00'50" W., on the N-S center line of the SE1/4NW1/4 of sec. 17.
	Over nearly level land.
9.994	Point for the SE-NW 1/64 sec. cor. of sec. 17. Not monumented.
19.997	The point for the C-E-NW 1/64 sec. cor. of sec. 17.
	<hr/>
	From the C-S-N 1/64 sec. cor. of sec. 17.
	S. 89°59'00" W., on the E-W center line of the SE1/4NW1/4 of sec. 17.
	Over nearly level land.
10.001	The point for the SE-NW 1/64 sec. cor. of sec. 17. Not monumented.

SUBDIVISION OF SECTION 17,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
14.999	<p>The C-W-SE-NW 1/256 sec. cor. of sec. 17, determined by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1987, monumented with a rebar, 5/8 in. diam., with a plastic cap mkd. RLS 4045, as recorded in Lyon County Survey File No. 111528. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S17 C-W-SE-NW 1/256</p> <p style="text-align: center;">2002</p> <p>Deposit the rebar and set a carsonite post, 5 ft. long, alongside the stainless steel post.</p>
	<p>N. 89°59'20" W., beginning new measurement.</p>
5.003	<p>The point for the C-S-NW 1/64 sec. cor. of sec. 17.</p> <hr/> <p>From the C-W-E-W 1/256 sec. cor. of sec. 17.</p> <p>N. 0°00'20" E., on the N-S center line of the SW1/4SE1/4NW1/4 of sec. 17.</p> <p>Over nearly level land.</p>
9.995	<p>The C-W-SE-NW 1/256 sec. cor. of sec. 17.</p> <hr/>
	<p style="text-align: center;">SUBDIVISION OF SECTION 20, T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 20 and 29.</p>
	<p>N. 0°02'10" W., on the N-S center line of sec. 20.</p>
	<p>Ascend S. slope.</p>
1.80	<p>Ridge, bears E and W.</p>
8.30	<p>Ridge, bears N. 80° E. and W.</p>
12.00	<p>Draw, drains N. 75° E.</p>
17.40	<p>Ridge, bears N. 75° E. and S. 75° W.</p>
26.40	<p>Dirt road, 25 lks. wide, bears N. 60° W. and S. 85° E.</p>

SUBDIVISION OF SECTION 20,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
33.30	Draw, drains S. 75° E.
37.90	Ridge, bears N. 70° E. and W.
39.802	Point for the center 1/4 sec. cor. of sec. 20, at intersection with the E-W center line.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.  T13N R25E C 1/4 S20  2002  Deposit the rebar and set a carsonite post, 5 ft. long, alongside the stainless steel post.
44.10	Draw, drains N. 60° E.
56.10	Ridge, bears N. 40° E. and S. 50° W.
59.786	Point for the C-N 1/16 sec. cor. of sec. 20. Not monumented.
69.778	The C-N-N 1/64 sec. cor. of sec. 20, determined by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1987, monumented with a rebar, 5/8 in. diam., with a plastic cap mkd. RLS 4045, as recorded in Lyon County Survey file No. 111657. This is accepted as a careful and faithful determination of the position of the corner.  At the corner point  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.  C-N-N 1/64 S20  2002  Deposit the rebar and set a carsonite post, 5 ft. long, alongside the stainless steel post.  From this corner, Anaconda Control Station UU, monumented with an iron pipe, 2 ins. diam., projecting 10 ins. above ground, firmly set in concrete, 10 ins. diam., with a threaded metal cap mkd. UU, bears S. 17°02'50" E., 8.799 chs. dist.  N. 0°01'20" W., beginning new measurement.
9.988	The 1/4 sec. cor. of secs. 17 and 20.

SUBDIVISION OF SECTION 20,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the 1/4 sec. cor. of sec. 20 only, on the W. bdy. of sec. 21.</p> <p>N. 89°53'00" W., on the E-W center line of sec. 20.</p> <p>Over mine tailings.</p> <p>17.60 Leave mine tailings, edge bears N. 20° W. and S. 40° E.</p> <p>20.10 Asphalt road, 50 lks. wide, bears N. 10° W. and S. 15° E.</p> <p>20.870 Point for the C-E 1/16 sec. cor. of sec. 20. Not monumented.</p> <p>27.70 Dirt road, 20 lks. wide, bears N. 35° W. and S. 25° E.</p> <p>40.860 The center 1/4 sec. cor. of sec. 20.</p> <p>48.50 Ridge, bears N. 30° W. and S. 30° E.</p> <p>54.20 Dirt road, 20 lks. wide, bears N. 15° W. and S. 15° E.</p> <p>60.60 Ridge, bears N. 65° W. and S. 65° E.</p> <p>60.906 Point for the C-W 1/16 sec. cor. of sec. 20. Not monumented.</p> <p>71.40 Draw, drains S. 35° E.</p> <p>80.952 The 1/4 sec. cor. of secs. 19 and 20.</p> <hr/> <p>From the point for the C-E 1/16 sec. cor. of sec. 20.</p> <p>N. 0°02'10" W., on the N-S center line of the NE1/4 of sec. 20.</p> <p>Over nearly level land.</p> <p>3.90 Asphalt road, 50 lks. wide, bears N. 10° W. and S. 10° E.</p> <p>19.990 Point for the NE 1/16 sec. cor. of sec. 20, at intersection with the E-W center line of the NE1/4. Not monumented.</p> <p>29.984 Point for the C-N-NE 1/64 sec. cor. of sec. 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">C-N-NE 1/64 S20  2004</p> <p>39.978 The point for the E 1/16 sec. cor. of secs. 17 and 20.</p> <hr/> <p>From the point for the N 1/16 sec. cor. of sec. 20 only, on the W. bdy. of sec. 21.</p> <p>N. 89°53'40" W., on the E-W center line of the NE1/4 of sec. 20.</p>
--------	--

SUBDIVISION OF SECTION 20,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Over nearly level land.
17.60	Enter mine tailings, edge bears N. 20° E. and S. 20° W.
20.649	The point for the NE 1/16 sec. cor. of sec. 20.
23.50	Asphalt road, 40 lks. wide, bears N. 20° W. and S. 20° E.
30.648	Point for the C-W-NE 1/64 sec. cor. of sec. 20. Not monumented.
40.647	The point for the C-N 1/16 sec. cor. of sec. 20.
	<hr/>
	From the point for the C-W-NE 1/64 sec. cor. of sec. 20.
	N. 0°00'20" W., on the N-S center line of the NW1/4NE1/4 of sec. 20.
	Over nearly level land.
10.002	The NW-NE 1/64 cor. of sec. 20, determined by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1987, monumented with a rebar, 5/8 in. diam., with a plastic cap mkd. RLS 4045, as recorded in Lyon County Survey File No. 111657. This is accepted as a careful and faithful determination of the position of the corner.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	NW-NE 1/64 S20  2002
	Deposit the rebar and set a carsonite post, 5 ft. long, alongside the stainless steel post.
	<hr/>
	N. 0°02'00" W., beginning new measurement.
9.982	The point for the W-E 1/64 cor. of secs. 17 and 20.
	<hr/>
	From the C-N-NE 1/64 cor. of sec. 20.
	N. 89°45'30" W., on the E-W center line of the NW1/4NE1/4 of sec. 20.
	Over nearly level land.
5.002	The C-E-NW-NE 1/256 sec. cor. of sec. 20, determined by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1987, monumented with a rebar, 5/8 in. diam., with a plastic cap mkd. RLS 4045, as recorded in Lyon County Survey File No. 111657. This is accepted as a careful and faithful determination of the position of the corner.

SUBDIVISION OF SECTION 20,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S20 C-E-NW-NE 1/256</p> <p style="text-align: center;">2002</p> <p>Deposit the rebar and set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <hr/> <p>N. 89°56'20" W., beginning new measurement.</p>
5.001	<p>The NW-NE 1/64 sec. cor. of sec. 20.</p> <hr/> <p>N. 89°57'30" W., beginning new measurement.</p>
10.004	<p>The C-N-N 1/64 sec. cor. of sec. 20.</p> <hr/> <p>From the C-E-NW-NE 1/256 sec. cor. of sec. 20.</p> <p>N. 0°01'50" W., on the N-S center line of the NE1/4NW1/4NE1/4 of sec. 20.</p> <p>Over nearly level land.</p>
9.981	<p>The E-W-E 1/256 sec. cor. of secs. 17 and 20.</p> <hr/> <p>From the point for the C-W 1/16 sec. cor. of sec. 20.</p> <p>N. 0°02'10" E., on the N-S center line of the NW1/4 of sec. 20.</p> <p>Over nearly level land.</p>
19.966	<p>Point for the NW 1/16 sec. cor. of sec. 20, at intersection with the E-W center line of the NW1/4. Not monumented.</p>
29.948	<p>Point for the C-N-NW 1/64 sec. cor. of sec. 20. Not monumented.</p>
39.930	<p>The point for the W 1/16 sec. cor. of secs. 17 and 20.</p> <hr/> <p>From the point for the C-N 1/16 sec. cor. of sec. 20.</p> <p>N. 89°56'20" W., on the E-W center line of the NW1/4 of sec. 20.</p>

SUBDIVISION OF SECTION 20,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Over nearly level land.
10.010	Point for the C-E-NW 1/64 sec. cor. of sec. 20. Not monumented.
20.020	The point for the NW 1/16 sec. cor. of sec. 20.
40.042	The point for the N 1/16 sec. cor. of secs. 19 and 20.
	<hr/>
	From the point for the C-E-NW 1/64 sec. cor. of sec. 20. N. 0°00'10" E., on the N-S center line of the NE1/4NW1/4 of sec. 20.
	Over nearly level land.
9.987	Point for the NE-NW 1/64 sec. cor. of sec. 20. Not monumented.
19.971	The point for the E-W 1/64 sec. cor. of secs. 17 and 20.
	<hr/>
	From the C-N-N 1/64 sec. cor. of sec. 20. N. 89°57'30" W., on the E-W center line of the NE1/4NW1/4 of sec. 20.
5.002	The C-E-NE-NW 1/256 sec. cor. of sec. 20, determined by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1987, monumented with a rebar, 5/8 in. diam., with a plastic cap mkd. RLS 4045, as recorded in Lyon County Survey File No. 111657. This is accepted as a careful and faithful determination of the position of the corner.  At the corner point  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.  S20 C-E-NE-NW 1/256  2002  Deposit the rebar and set a carsonite post, 5 ft. long, alongside the stainless steel post.  <hr/>
	N. 89°58'10" W., beginning new measurement.
5.002	The point for the NE-NW 1/64 sec. cor. of sec. 20.
15.007	The point for the C-N-NW 1/64 sec. cor. of sec. 20.
	<hr/>

SUBDIVISION OF SECTION 20,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the C-E-NE-NW 1/256 sec. cor. of sec. 20.</p> <p>N. 0°00'10" E., on the N-S center line of the NE1/4NE1/4NW1/4 of sec. 20.</p> <p>Over nearly level land.</p>
9.987	<p>The E-E-W 1/256 sec. cor. of secs. 17 and 20.</p> <hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 21, T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 21 and 28.</p> <p>N. 0°08'00" W., on the N-S center line of sec. 21.</p> <p>Over mine tailings.</p>
9.936	Point for the C-S-S 1/64 sec. cor. of sec. 21. Not monumented.
19.872	Point for the C-S 1/16 sec. cor. of sec. 21. Not monumented.
39.744	<p>Point for the center 1/4 sec. cor. of sec. 21, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T13N R25E C 1/4 S21</p> <p style="text-align: center;">2002</p>
39.980	<p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <p>Intersect line 2-3, Wild Rose No. 1 lode, at a point from which the point for Cor. No. 2, Wild Rose No. 1 lode, identical with Cor. No. 3, Wild Rose No. 2 lode, both of Mineral Survey No. 4499, hereinbefore described, bears N. 82°53'00" W., 0.559 chs. dist.</p>
50.80	Leave mine tailings, edge bears N. 85° W. and S. 70° E.
51.20	Graveled road, 75 lks. wide, bears N. 85° W. and S. 75° E.
52.30	Enter open pit, edge bears N. 85° W. and S. 70° E.
62.849	Intersect line 3-4, Blue Star lode, at a point from which Cor. No. 4, Blue Star lode, identical with Cor. No. 3, West Starlight lode, both of Mineral Survey No. 4531, hereinbefore described, bears N. 82°57'00" W., 7.076 chs. dist.
79.486	<p>The point for the 1/4 sec. cor. of secs. 16 and 21.</p> <hr/>

SUBDIVISION OF SECTION 21,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	From the 1/4 sec. cor. of secs. 21 and 22. N. 89°51'20" W., on the E-W center line of sec. 21.
3.00	Right bank of Walker River, course North.
3.90	Left bank of Walker River, course North.
17.00	Nevada State Route No. 339, 60 lks. wide, asphalt surface, bears N. 5° E. and S. 5° W.
19.762	True point for the C-E 1/16 sec. cor. of sec. 21, is located inside a well pump house where it is impracticable to establish a permanent monument.  From this point, the point selected for the witness cor. to the C-E 1/16 sec. cor. of sec. 21, bears N. 77°38'50" W., 1.000 chs. dist.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.  <div style="text-align: center;"> <p style="text-align: center;">WC E 1/16 C ————— C S21 ↘ 2002</p> </div>
	Set a carsonite post, 5 ft. long, alongside the stainless steel post.
21.799	Intersect line 3-4, Mineral Survey No. 4499, Wild Rose lode, at a point from which Cor. No. 3, hereinbefore described, bears S. 7°07'00" W., 1.914 chs. dist.
22.50	Enter mine tailings, edge bears N. 10° E. and S. 10° W.
37.592	Intersect line 2-3, Wild Rose No. 1 lode, at a point from which the point for Cor. No. 2, Wild Rose No. 1 lode, identical with Cor. No. 3, Wild Rose No. 2 lode, both of Mineral Survey No. 4499, hereinbefore described, bears N. 82°53'00" W., 2.507 chs. dist.
39.524	The center 1/4 sec. cor. of sec. 21.
79.044	The 1/4 sec. cor. of sec. 21 only.
	From the true point for the C-E 1/16 sec. cor. of sec. 21. N. 0°06'50" E., on the N-S center line of the NE1/4 of sec. 21.
8.50	Graveled road, 60 lks. wide, bears N. 30° E. and S. 30° W.
14.60	Enter open pit, edge bears N. 20° E. and S. 20° W.

SUBDIVISION OF SECTION 21,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
16.579	Intersect line 3-4, Mineral Survey No. 4499, Wild Rose lode, at a point from which the witness cor. to Cor. No. 4, hereinbefore described, bears S. 7°07'00" W., 4.028 chs. dist.
39.778	The point for the E 1/16 sec. cor. of secs. 16 and 21. <hr/>
	From the point of the E 1/16 sec. cor. of secs. 21 and 28. N. 0°07'10" E., on the N-S center line of the SE1/4 of sec. 21.
9.946	Point for the C-S-SE 1/64 sec. cor. of sec. 21.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.  S21 C-S-SE 1/64  2002  Set a carsonite post, 5 ft. long, alongside the stainless steel post.
16.70	Nevada State Route No. 339, 60 lks. wide, asphalt surface, bears N. 17° E. and S. 17° W.
19.892	Point for the SE 1/16 sec. cor. of sec. 21, at intersection with the E-W center line of the SE1/4. Not monumented.
39.785	The true point for the C-E 1/16 sec. cor. of sec. 21. <hr/>
	From the S 1/16 sec. cor. of secs. 21 and 22. N. 89°47'50" W., on the E-W center line of the SE1/4 of sec. 21.
19.676	The point for the SE 1/16 sec. cor. of sec. 21.
27.00	Enter mine tailings, edge bears N. 15° E. and S. 15° W.
29.514	Point for the C-W-SE 1/64 sec. cor. of sec. 21. Not monumented.
39.352	The point for the C-S 1/16 sec. cor. of sec. 21. <hr/>
	From the point for the W-E 1/64 sec. cor. of secs. 21 and 28. N. 0°00'30" W., on the N-S center line of the SW1/4SE1/4 of sec. 21.
9.942	Point for the SW-SE 1/64 sec. cor. of sec. 21, at intersection with the E-W center line of the SW1/4SE1/4. Not monumented.
19.884	The point for the C-W-SE 1/64 sec. cor. of sec. 21. <hr/>

SUBDIVISION OF SECTION 21,  
T. 13 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the C-S-SE 1/64 sec. cor. of sec. 21.</p> <p>N. 89°46'10" W., on the E-W center line of the SW1/4SE1/4 of sec. 21.</p> <p>2.10 Nevada State Route No. 339, 60 lks. wide, asphalt surface, bears N. 17° E. and S. 17° W.</p> <p>4.908 Point for the C-E-SW-SE 1/256 sec. cor. of sec. 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S21 C-E-SW-SE 1/256</p> <p style="text-align: center;">2002</p> <p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <p>7.20 Enter mine tailings, edge bears N. and S.</p> <p>9.816 The point for the SW-SE 1/64 sec. cor. of sec. 21.</p> <p>19.632 The point for the C-S-S 1/64 sec. cor. of sec. 21.</p> <hr/> <p>From the E-W-E 1/256 sec. cor. of secs. 21 and 28.</p> <p>N. 0°03'20" E., on the N-S center line of the SE1/4SW1/4SE1/4 of sec. 21.</p> <p>9.944 The C-E-SW-SE 1/256 sec. cor. of sec. 21.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The lands included in this survey are located in Lyon County, Nevada, about 2 miles west of the community of Yerington, Nevada. The area drains easterly into Walker River. The average elevation is about 4500 feet above sea level.</p> <hr/>
--------	--

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Clay W. Morrow

Surveying Technician

Jeremiah J. Lee

Survey Aid

CERTIFICATE OF SURVEY

I, Don R. Aschenbach, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 28th day of March, 2002, I have dependently resurveyed a portion of the south boundary of Township 14 North, Range 25 East; a portion of the subdivisional lines and portions of Mineral Survey Nos. 4499, 4531, and 4778, and subdivided certain sections, Township 13 North, Range 25 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

December 3, 2004  
(Date)

Don R. Aschenbach  
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Reno, Nevada

The foregoing field notes of the dependent resurvey of a portion of the south boundary of Township 14 North, Range 25 East; a portion of the, subdivisional lines and portions of Mineral Survey Nos. 4499, 4531, and 4778, and the subdivision of certain sections, Township 13 North, Range 25 East, Mount Diablo Meridian, Nevada, executed by Don R. Aschenbach, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

December 14, 2004  
(Date)

David J. Clark  
Acting (Chief Cadastral Surveyor, Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 13 N., R. 25 E., Mount Diablo Meridian, Nevada, is a true copy of the original field notes.~~

~~\_\_\_\_\_  
(Date)~~

~~\_\_\_\_\_  
(Chief Cadastral Surveyor, Nevada)~~