

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF PORTIONS

OF THE ORIGINAL WALKER RIVER INDIAN RESERVATION BOUNDARY,

A PORTION OF THE SUBDIVISIONAL LINES,

AND A PORTION OF THE SUBDIVISION-OF-SECTION LINES OF SECTION 20

AND THE SUBDIVISION OF CERTAIN SECTIONS,

TOWNSHIP 15 NORTH, RANGE 26 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

EXECUTED BY

Don R. Aschenbach, Cadastral Surveyor

Under Special Instructions dated September 9, 2005,

and approved September 9, 2005,

which provided for the surveys included under Group No. 830,

and Assignment Instructions dated September 19, 2005.

Survey commenced September 19, 2005

Survey completed March 5, 2007

INDEX DIAGRAM

TOWNSHIP 15 NORTH, RANGE 26 EAST, MOUNT DIABLO MERIDIAN, NEVADA

6	5	4	3	2	1
7	8	9	10	11	12
18	17 13	16	15 11	14 10 9	13 6
19	20 12	21 12 11	22	8 23 8	24
30	29	28	27	26	25 6 5
31	32	33	34	35	36

Dependent Resurvey of Portions of the
Original Walker River Indian Reservation Boundary pp. 2 - 4.
Dependent Resurvey of a Portion of the
Subdivision-of-Section Lines of Section 20 pp. 14 - 15.
Subdivision of Section 14 pp. 15 - 17.
Subdivision of Section 15 p. 17.
Subdivision of Section 16 p. 18.
Subdivision of Section 17 p. 18.
Subdivision of Section 26 pp. 19 - 20.

TOWNSHIP 15 NORTH, RANGE 26 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The following field notes are those of the dependent resurvey of portions of the Original Walker River Indian Reservation Boundary, a portion of the subdivisional lines, and a portion of the subdivision-of-section lines of section 20, and the subdivision of certain sections, T. 15 N., R. 26 E., Mount Diablo Meridian, Nevada.

The original Walker River Indian Reservation boundaries were surveyed by E.B. Monroe in 1864. The north boundary (Third Standard Parallel North) was surveyed by U.S. Deputy Surveyors R.A. Chase and A.J. Lash, Jr. in 1867 under Contract No. 4. The south, east, and west boundaries were surveyed by U.S. Deputy Surveyors R.A. Chase and A.J. Lash, Jr. in 1868 under Contract No. 8. A portion of the subdivisional lines was surveyed by U.S. Deputy Surveyor R.A. Chase in 1870 under Contract No. 29. The original Walker River Indian Reservation boundaries were resurveyed by N.L. Berdan in 1880 under Contract No. 94. The east boundary was resurveyed by U.S. Deputy Surveyors H.E. Franks and J.S. Mullen in 1904 under Contract No. 237. A portion of the subdivisional lines was surveyed by U.S. Deputy Surveyors W. Kearney and H. Thurtell in 1908 under Contract No. 257. Portions of the south, east and west boundaries and a portion of the subdivisional lines were retraced, and the north boundary (Third Standard Parallel North), a portion of the east boundary and a portion of the subdivisional lines were resurveyed, and the remaining unsurveyed portions of the subdivisional lines were surveyed by U.S. Transitman H.W. Reppert in 1913-1915 under Group No. 22. The east boundary of section 36 was dependently resurveyed by Cadastral Surveyor R.A. Pratt in 1989 under Group No. 670. A portion of the subdivisional lines was dependently resurveyed, and the subdivision of section 20 was surveyed by Cadastral Surveyor R.A. Pratt in 1989 under Group No. 672.

Before restoring the corners, the lines of the original surveys were retraced and diligent search made for any evidence of the original corners and other calls of the original field note record.

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 830, dated September 9, 2005.

Measurements were made with Trimble 5700 GPS receivers using real-time kinematic (RTK) methods and refer to the true meridian, based on geodetic methods. The mean bearings of the lines and horizontal equivalents of ground distances only are entered in the field notes.

TOWNSHIP 15 NORTH, RANGE 26 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The NAD 83 geographic position of the cor. of secs. 25 and 36 only, on the E. bdy. of the Tp., determined from Global Positioning System (GPS) static observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) GARL GARLIC CORS ARP, UPSA UPSAL HOGBACK CORS ARP, AND GABB GABBS CORS ARP, in 2006, and carried forward by RTK observations, is as follows:

Latitude: 39°07'44.340" N. Longitude: 119°00'48.763" W.

The 1993 mean magnetic declination is 15° E., as shown on the U.S. Geological Survey 7 1/2 minute quadrangle map "PARKER BUTTE, NEVADA" provisional edition and minor revision dated 1987 and 1993.

DEPENDENT RESURVEY OF PORTIONS OF THE
ORIGINAL WALKER RIVER INDIAN RESERVATION BOUNDARY,
T. 15 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of Portions of the Survey Executed by
E.B. Monroe in 1864 and the Dependent Resurvey Executed by
N.L. Berdan in 1880

Beginning at the point for the closing cor. of secs. 21 and 28, at the intersection with line AP14-AP15 of the Original Walker River Indian Reservation Boundary, hereinafter described.

From this point, Angle Point No. 14 of the Original Walker River Indian Reservation Boundary, bears S. 55°17'40" E., 83.396 chs. dist., monumented with a basalt stone, 35x24x24 ins., firmly set, projecting 30 ins. above ground, in a mound of stone, 3 ft. base, 1 ft. high, mkd. with a 14 faintly chiseled and lines extending southeast and northwest on the N. face.

At the corner point

Set a brass tablet, 3 1/4 ins. diam., 2 1/2-in. stem, cemented flush in drill hole on top of monument stone, with top mkd.

T15N R26E
S27
AP 14
S27 \ WRIR

2005

This control line was fully retraced and no remaining evidence of the intervening corners was found.

N. 55°17'40" W., on a portion of line AP14-AP15 of the Original Walker River Indian Reservation Boundary.

Over rolling hills covered with scattered sagebrush and native grasses.

DEPENDENT RESURVEY OF PORTIONS OF THE
ORIGINAL WALKER RIVER INDIAN RESERVATION BOUNDARY,
T. 15 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
9.10	Dry wash, 20 lks. wide, drains N.
10.50	Dry wash, 30 lks. wide, drains NE.
11.40	Spur, slopes NE.
36.409	Point for the 1 1/2 mile corner of line AP14-AP15 of the Original Walker River Indian Reservation Boundary, at proportionate distance; there is no remaining evidence of the original corner.
	POINT NOT MONUMENTED.
47.50	Trail road, 20 lks. wide, bears NE. and SW.
48.257	Point for the closing cor. of secs. 20 and 21, hereinafter described.
	From this point, Angle Point No. 15 of the Original Walker River Indian Reservation Boundary bears N. 55°17'40" W., 65.907 chs. dist., hereinafter described. The control line was fully retraced and no remaining evidence of the intervening corners was found.
	From the point for the closing subdivision-of-section cor. on the E-W center line of the NW1/4 of sec. 20, at intersection with line AP14-AP15 of the Original Walker River Indian Reservation Boundary, hereinafter described.
	From this point, Angle Point No. 14 of the Original Walker River Indian Reservation Boundary, bears S. 55°17'40" E., 185.227 chs. dist., hereinbefore described.
	N. 55°17'40" W., on a portion of line AP14-AP15 of the Original Walker River Indian Reservation Boundary.
	Over rolling hills covered with scattered sagebrush and native grasses.
2.50	Metal corral fence, bears E. and W.
2.70	Gravel road, 20 lks. wide, bears E. and W.
3.00	Underground natural gas line, bears NE. and SW.
12.333	Angle Point No. 15 of the Original Walker River Indian Reservation Boundary, monumented with a mound of stone, 4 ft. diam., 1 1/2 ft. high. This is accepted as the best available evidence of the original corner.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over plastic-encased magnet, encased in concrete and surrounded in a collar of stone, with brass cap mkd.

DEPENDENT RESURVEY OF PORTIONS OF THE
ORIGINAL WALKER RIVER INDIAN RESERVATION BOUNDARY,
T. 15 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T15N R26E S20 S20 AP15 WRIR 2005
	<hr/> 2005
	<p>N. 22°08'30" W., on a portion of line AP15-AP1 of the Original Walker River Indian Reservation Boundary.</p> <p>Over rolling hills covered with scattered sagebrush and native grasses.</p>
8.00	Saddle on ridge, bears SE. and NW.
8.80	Gravel road, 30 lks. wide, bears NE. and SW.
15.531	Point for the closing subdivision-of-section cor. on the N. and S. center line of the NW1/4 of sec. 20, hereinafter described.
16.273	Point for the closing cor. of secs. 17 and 20, hereinafter described.
40.305	Point for the 1/2 mile corner of line AP15-AP1 of the Original Walker River Indian Reservation Boundary, at proportionate distance; there is no remaining evidence of the original corner.
	POINT NOT MONUMENTED.
59.403	Point for the closing subdivision-of-section cor. on the E-W center line of sec. 17, hereinafter described.
	<p>From this point, the 1 mile corner of line AP15-AP1 of the Original Walker River Indian Reservation Boundary, bears N. 22°08'30" W., 21.207 chs. dist., monumented with a limestone, 20x8x6 ins., firmly set, projecting 16 ins. above ground, in mound of stone, 4 ft. base, 1 ft. high, mkd. 80 RC on S. side.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over plastic-encased magnet, in mound of stone, 4 ft. base, to top, with brass cap mkd.</p>
	T15N R26E S18 S18 1M WRIR 2005
	<p>Deposit the mkd. limestone alongside the stainless steel post.</p> <hr/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Reestablishment of Portions of the Survey Executed by U.S. Deputy Surveyors H.E. Franks and J.S. Mullen in 1904, the Survey Executed by Deputy Surveyors W. Kearney and H. Thurtell in 1908, the Survey and Resurvey Executed by U.S. Surveyor W.H. Reppert in 1913-1915 and the Survey and Resurvey Executed by R.A. Pratt in 1989</p> <hr/> <p>From the cor. of secs. 25 and 36 only, on the E. bdy. of the Tp., monumented with stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, in a fence extending N. and S., with brass cap mkd. as described in the field notes of the dependent resurvey of T. 15 N., R. 27 E., executed under Group No. 670.</p> <p>N. 89°58'50" W., bet. secs. 25 and 36.</p> <p>Over flats covered with widely scattered sagebrush and native grasses.</p>
25.30	Barbed wire fence, bears SE. and NW.
34.40	Dry wash, 10 lks. wide, drains NW.
40.003	<p>The 1/4 sec. cor. of secs. 25 and 36, monumented with a redwood post, 4x3 ins., firmly set, projecting 12 ins. above ground, no mks. visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T15N R26E</p> <p> S25</p> <p>1/4 <u> </u></p> <p> S36</p> <p>2005</p> </div> <p>Deposit the unmkd. redwood post alongside the stainless steel post and set a steel boundary marker post alongside.</p> <hr/> <p>S. 89°59'10" W., beginning new measurement.</p> <p>Over flats covered with widely scattered sagebrush and native grasses.</p>
6.40	Dry wash, 10 lks. wide, drains NW.
9.30	Buried fiber optic cable, bears SE. and NW.
24.10	Trail road, 20 lks. wide, bears SE. and NW.
24.80	Dry wash, 20 lks. wide, drains NE.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS							
40.031	<p>The cor. of secs. 25, 26, 35 and 36, monumented with a redwood post, 4x4 ins., firmly set, projecting 12 ins. above ground, with faint scribing on S. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T15N</td><td>R26E</td></tr> <tr><td>S26</td><td>S25</td></tr> <tr><td>S35</td><td>S36</td></tr> </table> <p>2006</p> </div> <p>Deposit the mkd. redwood post alongside the stainless steel post and set a steel boundary marker post alongside.</p> <hr/>	T15N	R26E	S26	S25	S35	S36
T15N	R26E						
S26	S25						
S35	S36						
	<p>N. 0°56'10" E., bet. secs. 25 and 26.</p> <p>Over flats covered with widely scattered sagebrush and native grasses.</p>						
13.90	Dry wash, 30 lks. wide, drains NE.						
14.00	Trail road, 20 lks. wide, bears SE. and NW.						
40.746	<p>The 1/4 sec. cor. of secs. 25 and 26, monumented with a redwood post, 4x4 ins., firmly set, projecting 18 ins. above ground, plainly scribed 26 on W. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T15N</td><td>R26E</td></tr> <tr><td>1/4</td><td></td></tr> <tr><td>S26</td><td>S25</td></tr> </table> <p>2005</p> </div> <p>Deposit the mkd. redwood post alongside the stainless steel post and set a steel boundary marker post alongside.</p> <hr/>	T15N	R26E	1/4		S26	S25
T15N	R26E						
1/4							
S26	S25						
	<p>From the cor. of secs. 13 and 24 only, on the E. bdy. of the Tp., monumented with a granite stone, 10x10x7 ins., firmly set, projecting 7 ins. above ground, mkd. with 3 notches on N. and S. faces.</p>						
	At the corner point						
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over plastic-encased magnet, with brass cap mkd.						

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T15N R26E R27E S13 <u> </u> S18 S24 </p> <p style="text-align: center;">2005</p> <p>Deposit the mkd. stone alongside the stainless steel post and set a steel boundary marker post alongside.</p> <p>N. 89°56'50" W., bet. secs. 13 and 24.</p> <p>Over flats covered with widely scattered sagebrush and native grasses.</p> <p>34.20 Barbed wire fence, bears NE. and SW.</p> <p>40.065 Point for the 1/4 sec. cor. of secs. 13 and 24, at proportionate distance, there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T15N R26E S13 1/4 <u> </u> S24</p> <p style="text-align: center;">2006</p> <p>Set a steel boundary marker post alongside.</p>
	<p>65.50 Trail road, 20 lks. wide, bears SE. and NW.</p>
	<p>80.130 The cor. of secs. 13, 14, 23 and 24, monumented with a granite stone, 18x10x9 ins., firmly set, projecting 12 ins. above ground, mkd. with 3 notches on S. and 1 notch on E. edges.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T15N R26E S14 S13 <u> </u> S23 S24</p> <p style="text-align: center;">2005</p> <p>Deposit the mkd. stone alongside the stainless steel post and set a steel boundary marker post alongside.</p> <hr/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the 1/4 sec. cor. of secs. 23 and 26, monumented with a redwood post, 4x3 ins., firmly set, projecting 16 ins. above ground, faintly scribed 1/4 S23 on N. face and S26 on S. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T15N R26E</p> <p> S23</p> <p>1/4 <u> </u></p> <p> S26</p> <p>2005</p> </div> <p>Deposit the mkd. redwood post alongside the stainless steel post and set a steel boundary marker post alongside.</p> <p>N. 89°56'00" W., bet. secs. 23 and 26.</p> <p>Over flats covered with widely scattered sagebrush and native grasses.</p> <p>26.50 Barbed wire fence, bears SE. and NW.</p> <p>28.70 Trail road, 20 lks. wide, bears SE. and NW.</p> <p>40.041 The cor. of secs. 22, 23, 26 and 27, monumented with a quartzite stone, 16x12x8 ins., firmly set, projecting 12 ins. above ground, mkd. with 2 notches on S. and E. edges, with a mound of stone, 4 ft. base, 1 ft. high, W. of cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over plastic-encased magnet, in mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T15N R26E</p> <p> S22 S23</p> <p> S27 S26</p> <p>2005</p> </div> <p>Deposit the mkd. stone alongside the stainless steel post and set a steel boundary marker post alongside.</p> <hr style="width: 50%; margin: 10px auto;"/> <p>N. 0°04'40" W., bet. secs. 22 and 23.</p> <p>Over flats covered with widely scattered sagebrush and native grasses.</p> <p>7.80 Barbed wire fence, bears SE. and NW.</p> <p>8.40 Trail road, 20 lks. wide, bears SE. and NW.</p>
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.293	<p>The 1/4 sec. cor. of secs. 22 and 23, monumented with a redwood post, 31x4x4 ins., laying loose, no visible mks., with chiseled point. Accepted base of post as the best available evidence of the original corner position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15N R26E 1/4 S22 S23 2005</p> <p>Deposit the unmkd. redwood post alongside the stainless steel post.</p> <hr style="width: 30%; margin: auto;"/> <p>N. 0°00'20" E., beginning new measurement.</p>
38.50	Right bank of the Walker River, course S. 45° E.
39.00	Left bank of the Walker River, course S. 45° E.
39.953	<p>Point for the cor. of secs. 14, 15, 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15N R26E S15 S14 S22 S23 2005</p> <p>Raise a mound of stone, 4 ft. base, 2 ft. high, W. of cor.</p> <hr style="width: 30%; margin: auto;"/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>N. 89°47'20" W., bet. secs. 14 and 23.</p> <p>Over flats covered with widely scattered sagebrush and native grasses.</p>
39.704	<p>Record distance for the original witness corner to the 1/4 sec. cor. of secs. 14 and 23, from the proportioned position of said 1/4 sec. cor. A redwood post was found lying loose at the base of an erosive hillside, with its original position undeterminable. This position serves no further function and the redwood post was destroyed.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.80	Top of bluff, 60 ft. high, bears SE. and NW.
40.044	Point for the 1/4 sec. cor. of secs. 14 and 23, at proportionate distance. This point falls on the side of a steep bluff where it is impracticable to establish a permanent monument.
40.951	<p>Point selected for the witness cor. to the 1/4 sec. cor. of secs. 14 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC T15N R26E S14 1/4 → S23</p> <p>2005</p> </div> <p>Set a steel fence post 1.5 ft. S.</p>
41.80	Barbed wire fence, bears SE. and NW.
46.90	Gravel road, 30 lks. wide, bears SE. and NW.
58.00	Left bank of the Walker River, course S. 40° E.
60.00	Right bank of the Walker River, course S. 40° E.
68.50	Right bank of the Walker River, course N.
70.40	Left bank of the Walker River, course N.
80.088	<p>The cor. of secs. 14, 15, 22 and 23.</p> <hr/> <p>N. 0°01'10" W., bet. secs. 14 and 15.</p> <p>Over flats covered with widely scattered sagebrush and native grasses.</p>
9.50	Gravel road, 30 lks. wide, bears NE. and SW.
20.20	Gravel road, 30 lks. wide, bears SE. and NW.
22.40	Barbed wire fence, bears SE. and NW.
36.00	Gravel road, 30 lks. wide, bears NE. and SW.
39.953	The 1/4 sec. cor. of secs. 14 and 15, monumented with a granite stone, 13x9x9 ins., firmly set, projecting 8 ins. above ground, mkd. 1/4 on W. face, with a mound of stone, 2 ft. base, 2 ft. high, W. of cor.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15N R26E 1/4 S15 S14</p> <p style="text-align: center;">2005</p> <p>Deposit the mkd. stone alongside the stainless steel post and rebuild mound.</p> <hr/> <p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>N. 89°52'50" W., bet. secs. 15 and 22.</p> <p>Over flats covered with widely scattered sagebrush and native grasses.</p>
0.60	Left bank of the Walker River, course S. 45° E.
1.40	Right bank of the Walker River, course S. 45° E.
3.20	Overhead power line, bears N. 4°19' E. and S. 4°19' W.
5.20	Gravel road, 30 lks. wide, bears NE. and SW.
36.20	Top of bluff, 30 ft. high, bears NE. and SW.
40.044	<p>The 1/4 sec. cor. of secs. 15 and 22, monumented with a redwood post, 2x2 ins., firmly set, projecting 8 ins. above ground, no mks. visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15N R26E S15 1/4 ——— S22</p> <p style="text-align: center;">2005</p> <p>Deposit the unmkd. redwood post alongside the stainless steel post, and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 21 and 28, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. as described in the field notes of the survey of T. 15 N., R. 26 E., executed under Group No. 22.</p> <p>N. 89°56'10" W., bet. secs. 21 and 28.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Over flats covered with widely scattered sagebrush and native grasses.
0.280	<p>Intersect line AP14-AP15 of the Original Walker River Indian Reservation Boundary.</p> <p>Point for the closing cor. of secs. 21 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="862 600 1089 804" style="text-align: center;"> <p>T15N R26E S21 W S21 R I CC S28 S28 R</p> <p>2005</p> </div>
39.934	<p>Set a steel boundary marker post 1.0 ft. E.</p> <p>The cor. of secs. 21 and 28 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. as described in the field notes of the survey executed under Group No. 22 and the dependent resurvey executed under Group No. 672 of T. 15 N., R. 26 E.</p>
17.894	<p>N. 0°02'00" W., on the W. bdy. of sec. 21.</p> <p>Over flats covered with widely scattered sagebrush and native grasses.</p> <p>The S 1/16 sec. cor. of sec. 20 only, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. as shown in the field notes of the dependent resurvey of T. 15 N., R. 26 E., executed under Group No. 672.</p>
27.433	<p>Intersect line AP14-AP15 of the Original Walker River Indian Reservation Boundary.</p> <p>Point for the closing cor. of secs. 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="878 1650 1024 1854" style="text-align: center;"> <p>T15N R26E S20 S21 W S21 R I S20 S21 CC</p> <p>2005</p> </div>

231

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Set a steel boundary marker post 1.5 ft. SE.
37.903	The 1/4 sec. cor. of sec. 20 only, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. as described in the field notes of the survey executed under Group No. 22 and the dependent resurvey executed under Group No. 672 of T. 15 N., R. 26 E.
39.00	Trail road, 20 lks. wide, bears NE. and SW.
40.028	The 1/4 sec. cor. of sec. 21 only, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. as described in the field notes of the resurvey of T. 15 N., R. 26 E., executed under Group No. 672.
	From the 1/4 sec. cor. of sec. 17 only, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. as described in the field notes of the survey executed under Group No. 22 and the dependent resurvey executed under Group No. 672 of T. 15 N., R. 26 E.
	N. 89°59'50" W., on the S. bdy. of sec. 17.
	Over flats covered with widely scattered sagebrush and native grasses.
1.472	The 1/4 sec. cor. of sec. 20 only, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. as described in the field notes of the survey executed under Group No. 22 and the dependent resurvey executed under Group No. 672 of T. 15 N., R. 26 E.
20.017	The W 1/16 sec. cor. of sec. 20 only, monumented with a stainless steel post, 2 1/2 ins., firmly set, projecting 5 ins. above ground, in a collar of stone, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 15 N., R. 26 E., executed under Group No. 672.
20.273	Intersect line AP15-AP1 of the Original Walker River Indian Reservation Boundary.
	Point for the closing cor. of secs. 17 and 20.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over plastic-encased magnet, in collar of stone, with brass cap mkd.
	2005

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
27.10	Barbed wire fence, bears SE. and NW.
36.50	Ridge, bears N. and S.
38.565	The closing cor. of secs. 19 and 20 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, with brass cap mkd. as shown in the field notes of the survey executed under Group No. 22 and the dependent resurvey executed under Group No. 672 of T. 15 N., R. 26 E.
40.021	The cor. of secs. 17 and 18 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above mound of stone, 2 ft. base, 1 ft. high, with brass cap mkd. as shown in the field notes of the survey executed under Group No. 22 and the dependent resurvey executed under Group No. 672 of T. 15 N., R. 26 E.
<hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISION-OF-SECTION LINES OF SECTION 20, T. 15 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>	
<p>Reestablishment of a Portion of the Survey Executed by R.A. Pratt in 1989</p> <hr/>	
	<p>From the NW 1/16 sec. cor. of sec. 20, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. as described in the field notes of the survey of the subdivision of sec. 20, of T. 15 N., R. 26 E., executed under Group No. 672.</p> <p>N. 1°58'40" W., on the N-S center line of the NW1/4 of sec. 20.</p>
21.400	<p>Intersect line AP15-AP1 of the Original Walker River Indian Reservation Boundary.</p> <p>Point for the closing subdivision-of-section cor. on the N-S center line of the NW1/4 of sec. 20.</p> <p>POINT NOT MONUMENTED.</p>
22.087	The W 1/16 sec. cor. of sec. 20 only.
<hr/> <p>From the center N 1/16 sec. cor. of sec. 20, reestablished by Bruce L. Rice, Nevada Professional Land Surveyor No. 4248, in 1996, monumented with a rebar, 5/8 in. diam., with aluminum cap, 2 ins. diam., firmly set 6 ins. below the surface of the ground, as recorded in Lyon County, Nevada, Survey File No. 190682, with aluminum cap having no visible markings. This is accepted as a careful and faithful reestablishment of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 3 ins. below the surface of the ground, over plastic-encased magnet, with brass cap mkd.</p>	

DEPENDENT RESURVEY OF A PORTION OF THE
 SUBDIVISION-OF-SECTION LINES OF SECTION 20,
 T. 15 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div style="text-align: center;"> $\begin{array}{c} C \\ N\ 1/16 \left S20 \\ C \end{array}$ <p>2005</p> <p>Deposit the rebar alongside the stainless steel post and set a steel fence post 1.0 ft. N. of corner.</p> <p>N. 89°55'20" W., on the E-W center line of the NW1/4 of sec. 20.</p> <p>Over nearly level ground with no vegetation.</p> </div>
2.50	Metal corral fence, bears N. and S.
4.057	<p>Intersect line AP14-AP15 of the Original Walker River Indian Reservation Boundary.</p> <p>Point for the closing subdivision-of-section cor. on the E-W center line of the NW1/4 of sec. 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with ground, over plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> </div> <p>2005</p> <p>from which</p> <p>A PK nail and shiner set in a wooden fence post, 6 ins. diam., for a reference monument, bears S. 89°56' E., 160.4 lks. dist.</p> <p>A PK nail and shiner set in a wood power pole, 10 ins. diam., for a reference monument, bears S. 56°45' W., 28.9 lks. dist.</p> <p>A PK nail and shiner set in a wooden fence post, 6 ins. diam., for a reference monument, bears N. 39°28' W., 87.1 lks. dist.</p>
5.10	Metal corral fence, bears N. and S.
19.312	The NW 1/16 sec. cor. of sec. 20.
<hr/> <p>SUBDIVISION OF SECTION 14, T. 15 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>	
<p>From the true point for the 1/4 sec. cor. of secs. 14 and 23. N. 0°01'40" W., on the N-S center line of sec. 14.</p>	

SUBDIVISION OF SECTION 14,
T. 15 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Over rolling hills covered with widely scattered sagebrush and native grasses.</p>
1.60	Top of bluff, 60 ft high, bears SE. and NW.
21.00	Dry wash, 30 lks. wide, drains SW.
32.50	Top of ridge, bears E. and W.
39.983	<p>Point for the center 1/4 sec. cor. of sec. 14, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over plastic-encased magnet, in collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T15N R26E C 1/4 S14 2005</p> <p>Set a steel boundary marker post 2 ft. S.</p>
47.00	Top of ridge, bears E. and W.
70.50	Trail road, 20 lks. wide, bears SE. and NW.
79.891	<p>The 1/4 sec. cor. of secs. 11 and 14, monumented with a basalt stone, 20x12x9 ins., firmly set, projecting 10 ins. above ground, mkd. 1/4 on N. face, with a mound of stone, 3 ft. base, 1 ft. high, N. of cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15N R26E S11 1/4 $\frac{S11}{S14}$ 2005</p> <p>Deposit the mkd. stone alongside the stainless steel post, and rebuild mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 13 and 14, monumented with a basalt stone, 15x11x7 ins., firmly set, projecting 10 ins. above ground, mkd. 1/4 on W. face, and a mound of stone, 2 ft. base, 1 ft. high, W. of cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over plastic-encased magnet, with brass cap mkd.</p>

SUBDIVISION OF SECTION 14,
T. 15 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">T15N R26E 1/4 S14 S13 2005</p> <p>Deposit the mkd. stone alongside the stainless steel post, and rebuild mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>N. 89°49'50" W., on the E-W center line of sec. 14.</p> <p>Over flats covered with widely scattered sagebrush and native grasses.</p> <p>3.50 Trail road, 20 lks. wide, bears SE. and NW.</p> <p>40.063 The center 1/4 sec. cor. of sec. 14.</p> <p>41.10 Top of ridge, bears N. and W.</p> <p>75.76 Gravel road, 30 lks. wide, bears N. and SW.</p> <p>80.098 The 1/4 sec. cor. of secs. 14 and 15.</p> <hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 15, T. 15 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 14 and 15.</p> <p>S. 89°42'40" W., on the E-W center line of sec. 15.</p> <p>Over flats covered with widely scattered sagebrush and native grasses.</p> <p>3.40 Center of power transmission line, bears NE. and SW.</p> <p>40.50 Trail road, 20 lks. wide, bears SE. and NW.</p> <p>44.00 Barbed wire fence, bears SE. and W.</p> <p>79.969 The 1/4 sec. cor. of secs. 15 and 16, monumented with a redwood post, 31x5x4 ins., laying loose, with faint scribing on one face. Accepted base of post as the best available evidence of the original corner position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15N R26E 1/4 S16 S15 2005</p> <p>Deposit the mkd. redwood post alongside the stainless steel post.</p> <hr/>
--------	---

SUBDIVISION OF SECTION 16,
T. 15 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p> <p>79.735</p>	<p>From the 1/4 sec. cor. of secs. 15 and 16.</p> <p>N. 89°40'50" W., on the E-W center line of sec. 16.</p> <p>Over flats covered with widely scattered sagebrush and native grasses, along fence.</p> <p>The 1/4 sec. cor. of secs. 16 and 17, monumented with an iron post, 1 in. diam., firmly set flush with ground, with brass cap mkd. as described in the field notes of the survey of T. 15 N., R. 26 E., executed under Group No. 22.</p>
<p>SUBDIVISION OF SECTION 17, T. 15 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA</p>	
<p>0.20</p> <p>46.80</p> <p>53.10</p> <p>76.538</p>	<p>From the 1/4 sec. cor. of secs. 16 and 17.</p> <p>S. 89°58'10" W., on the E-W center line of sec. 17.</p> <p>Over flats covered with widely scattered sagebrush and native grasses, along fence.</p> <p>Trail road, 30 lks. wide, bears SW. and NE.</p> <p>Ridge, bears NE. and SW.</p> <p>Dry wash, 20 lks. wide, drains NE.</p> <p>Intersect line AP15-AP1 of the Original Walker River Indian Reservation Boundary.</p> <p>Point for the closing subdivision-of-section cor. on the E-W center line of sec. 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over plastic-encased magnet, with brass cap mkd.</p>
<p>80.085</p>	<div data-bbox="841 1348 1055 1539" data-label="Diagram"> <p style="text-align: center;">2005</p> <p>The 1/4 cor. of secs. 17 and 18, monumented with an iron post, 1 in. diam., firmly set, projecting 30 ins. above ground, in a mound of stone, 4 ft. base, 2 1/2 ft. high, with brass cap mkd. as described in the field notes of the survey of T. 15 N., R. 26 E., executed under Group No. 22.</p> </div>

SUBDIVISION OF SECTION 26,
T. 15 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the 1/4 sec. cor. of secs. 26 and 35, monumented with a redwood post, 3x1 ins., firmly set, projecting 12 ins. above ground, no mks. visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15N R26E S26 1/4 <u> </u> S35</p> <p style="text-align: center;">2006</p> <p>Deposit the unmkd. redwood post alongside the stainless steel post and set a steel fence post 1.0 ft W.</p> <p>N. 0°02'00" E., on the N-S center line of sec. 26.</p> <p>Over flats covered with widely scattered sagebrush and native grasses.</p>
40.528	<p>Point for the center 1/4 sec. cor. of sec. 26, at intersection with the E-W center line. A redwood post of unknown origin, 30x4x4 ins., was found lying loose nearby, with the original position undeterminable.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15N R26E C 1/4 S26</p> <p style="text-align: center;">2005</p> <p>Deposit the redwood post alongside the stainless steel post and set a steel fence post 2.0 ft. N.</p>
52.80	<p>Buried fiber optic cable, bears SE. and NW.</p>
56.90	<p>Trail road, 20 lks. wide, bears SE. and NW.</p>
64.90	<p>Barbed wire fence, bears SE. and NW.</p>
80.211	<p>The 1/4 sec. cor. of secs. 23 and 26.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 25 and 26.</p> <p>S. 89°32'00" W., on the E-W center line of sec. 26.</p> <p>Over flats covered with widely scattered sagebrush and native grasses.</p>
24.50	<p>Buried fiber optic cable, bears SE. and NW.</p>

SUBDIVISION OF SECTION 26,
T. 15 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
26.10	Trail road, 20 lks. wide, bears SE. and NW.
40.777	The center 1/4 sec. cor. of sec. 26.
80.745	<p>The 1/4 sec. cor. of secs. 26 and 27, monumented with the bottom portion of an iron post, 1 in. diam., firmly set, broken off flush with the ground, with brass cap and top portion of iron post laying nearby, mkd. as described in the field notes of the survey of T. 15 N., R. 26 E., executed under Group No. 22.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15N R26E 1/4 S27 S26 2006</p> <p>Deposit the top and bottom portions of the iron post alongside the stainless steel post and set a steel fence post alongside.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The area resurveyed within Township 15 North, Range 26 East is gently rolling to nearly level bottom land. The elevation ranges from 4300 to 4500 ft. above sea level. The soil ranges from sandy clay loam to rocks and sand. The vegetation consists of sagebrush and bunchgrass to meadow land along the Walker River which flows easterly through the area.</p> <p>The area is used by ranchers for cattle grazing.</p> <p>There are no apparent mineral formations in the area.</p> <hr/>

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Steve E. Dagitz	Surveying Technician
Derrick J. Rader	Surveying Technician
Joseph J. Johnson	Surveying Technician

CERTIFICATE OF SURVEY

I, Don R. Aschenbach, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of Special Instructions bearing date of the 9th day of September, 2005, I have dependently resurveyed portions of the Original Walker River Indian Reservation Boundary, a portion of the subdivisional lines, and a portion of the subdivision-of-section lines of section 20 and subdivided certain sections, Township 15 North, Range 26 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

March 29, 2007
(Date)

Don R. Aschenbach
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of the dependent resurvey of portions of the Original Walker River Indian Reservation Boundary, a portion of the subdivisional lines, and a portion of the subdivision-of-section lines of section 20 and the subdivision of certain sections, Township 15 North, Range 26 East, Mount Diablo Meridian, Nevada, having been critically examined and found correct, are hereby approved.

April 3, 2007
(Date)

David H. Morla
(Chief Cadastral Surveyor, Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I Certify That the foregoing transcript of the field notes of the above described surveys in T. 15 N., R. 26 E., Mount Diablo Meridian, Nevada, is a true copy of the original field notes.~~

~~_____
(Date)~~

~~_____
(Chief Cadastral Surveyor, Nevada)~~