

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

THE THIRD STANDARD PARALLEL NORTH,

THROUGH A PORTION OF RANGE 62 EAST

AND A PORTION OF THE SUBDIVISIONAL LINES,

THE METES-AND-BOUNDS SURVEY OF THE NORTHERLY RIGHT-OF-WAY LINE OF
HEADHOUSE ROAD THROUGH SECTIONS 20, 21, 29 AND A PORTION OF SECTION 30,
AND THE METES-AND-BOUNDS SURVEY OF THE CENTERLINE OF U.S. HIGHWAY NO. 6
THROUGH SECTIONS 9, 16, 17, 19, 20 AND A PORTION OF SECTION 30,

TOWNSHIP 15 NORTH, RANGE 62 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

EXECUTED BY

Wayne S. Hancock, Cadastral Surveyor

Mark G. Petrosine, Surveying Technician

Under Special Instructions dated February 5, 2007,
and approved February 5, 2007,
which provided for the surveys included under Group No. 844,
and Assignment Instructions dated February 5, 2007.

Survey commenced February 6, 2007

Survey completed August 27, 2007

INDEX DIAGRAM

TOWNSHIP 15 NORTH, RANGE 62 EAST, MOUNT DIABLO MERIDIAN, NEVADA

			3	2		
6	5	4	11	3	2	1
		20				
7	8	19	9	9	10	11
	30		18			12
18	29	17	16	16	7	15
28		27		16		14
19	26	20	14	21	4	22
25		24		14		23
30	23	29	12	28		27
22		21				26
31	32	33				35
				34		36

Metes-and-Bounds Survey of the Northerly Right-of-Way Line of Headhouse Road Through Sections 20, 21, 29 and a Portion of Section 30.. pp. 31-37
 Metes-and-Bounds Survey of the Centerline of U.S. Highway No. 6 Through Sections 9, 16, 17, 19, 20 and a Portion of Section 30..... pp. 37-43

TOWNSHIP 15 NORTH, RANGE 62 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The following field notes are those of the dependent resurvey of the Third Standard Parallel North, through a portion of Range 62 East and a portion of the subdivisional lines, the metes-and-bounds survey of the northerly right-of-way line of Headhouse Road through sections 20, 21, 29 and a portion of section 30, and the metes-and-bounds survey of the centerline of U.S. Highway No. 6 through sections 9, 16, 17, 19, 20 and a portion of section 30, Township 15 North, Range 62 East, Mount Diablo Meridian, Nevada.

The north boundary (Third Standard Parallel North) was surveyed by U.S. Deputy Surveyor E.B. Monroe in 1871 under Contract No. 44. The south, east and west boundaries, and subdivisional lines were surveyed by U.S. Deputy Surveyors E.B. Monroe and A.G. Bateman in 1873 under Contract No. 60. A portion of the north boundary (Third Standard Parallel North) and the west boundary were dependently resurveyed by Cadastral Engineer R.F. Wilson in 1953 under Group No. 277.

Before restoring the corners, the lines of the original surveys were retraced and diligent search made for any evidence of the original corners and other calls of the original field note record.

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 844, dated February 5, 2007.

Measurements were made with Trimble 4700 Global Positioning System (GPS) receivers using the real-time kinematics method and refer to the true meridian based on geodetic methods. The mean bearings of the lines and horizontal equivalents of ground distances only are entered in the field notes.

The NAD 83 (CORS96) geographic position of the cor. of secs. 15, 16, 21 and 22, determined from Global Positioning System (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) "RAIL RAILROAD VALLEY CORS ARP", "EGAN EGAN_BRGN_NV1996 CORS ARP" and "ECHO ECHO_BRGN_NV1999 CORS ARP", and carried forward by RTK observations, is as follows:

Latitude: 39°09'26.240" N.

Longitude: 115°00'01.507" W.

The February 6, 2007, mean magnetic declination was determined to be 13°23' E. from the National Oceanic and Atmospheric Administration's National Geophysical Data Center declination calculator.

DEPENDENT RESURVEY OF THE THIRD STANDARD PARALLEL NORTH,
THROUGH A PORTION OF RANGE 62 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">Reestablishment of a Portion of the Survey Executed by E.B. Monroe, U.S. Deputy Surveyor, in 1871</p> <hr/> <p>Beginning at the standard 1/4 sec. cor. of sec. 33, monumented with a limestone, 12x8x5 ins., firmly set, projecting 2 ins. above the ground, and in an embedded mound of earth and stone, 3 ft. base, mkd. 1/4 on N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">SC T16N R62E <u>1/4 S33</u></p> <p style="text-align: center;">2007</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears N. 45°26' E., 67.4 lks. dist., mkd. 1/4 S33 SC BT.</p> <p style="padding-left: 40px;">A juniper, 4 ins. diam., bears N. 44°10' W., 49.4 lks. dist., mkd. X BT.</p> <p>Deposit the mkd. stone and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located on an E. facing slope, in sagebrush, bunch grass, juniper and pine timber.</p> <p>N. 89°47'40" W., on the S. bdy. of sec. 33.</p> <p>3.20 Ravine, 50 lks. wide, drains S. 45° E.</p> <p>9.433 Point for the closing cor. of secs. 3 and 4, T. 15 N., R. 62 E., hereinafter described.</p> <p>18.35 Powerline and dirt road, 12 lks. wide, bears N. 29° E. and S. 29° W.</p> <p>38.20 Center of jeep trail, 11 lks. wide, bears N. 67° E. and S. 67° W.</p> <p>39.717 Point for the standard cor. of secs. 32 and 33, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 1 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">SC T16N R62E <u>S32 S33</u></p> <p style="text-align: center;">2007</p>
--------	---

DEPENDENT RESURVEY OF THE THIRD STANDARD PARALLEL NORTH,
THROUGH A PORTION OF RANGE 62 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>from which</p> <p>A pine, 5 ins. diam., bears N. 20°36' E., 55.9 lks. dist., mkd. S33 SC BT.</p> <p>A juniper, 5 ins. diam., bears N. 57°08' W., 9.1 lks. dist., mkd. S32 SC BT.</p> <p>Cor. is located on nearly level ground, in pine and juniper timber.</p> <p>From this point, a steel fence post of unknown origin, firmly set, projecting 4 ft. above ground, bears S. 26°42'10" W., 2.217 chs. dist. This position is not harmoniously related to surrounding corners, cannot be reconciled with proper procedures and is not utilized during the course of this survey.</p> <hr/> <p>N. 89°47'40" W., on the S. bdy. of sec. 32.</p> <p>10.50 Center of dirt road, 21 lks. wide, bears S. 35° E. and N. 35° W.</p> <p>39.717 Point for the standard 1/4 sec. cor. of sec. 32, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">SC T16N R62E <u>1/4 S32</u></p> <p style="text-align: center;">2007</p> <p>from which</p> <p>A juniper, 8 ins. diam., bears N. 58°59' E., 21.4 lks. dist., mkd. 1/4 S32 SC BT.</p> <p>A pine, 8 ins. diam., bears N. 29°43' W., 85.3 lks. dist., mkd. 1/4 S32 SC BT.</p> <p>Cor. is located on a W. facing slope, in pine and juniper timber.</p> <p>40.04 Powerline and dirt road, 15 lks. wide, bears N. 23° E. and S. 23° W.</p> <p>78.90 Shallow wash, 50 lks. wide, drains S. 20° W.</p> <p>79.434 The standard cor. of secs. 31 and 32, monumented with a limestone, 12x10x8 ins., firmly set, projecting 5 ins. above the ground, and in an embedded collar of earth and stone, 2 ft. base, mkd. with 1 groove on W. face and 3 notches on E. edge.</p>
--------	--

DEPENDENT RESURVEY OF THE THIRD STANDARD PARALLEL NORTH,
THROUGH A PORTION OF RANGE 62 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, over a plastic-encased magnet, and in a collar of stone, 2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>SC T16N R62E <u>S31 S32</u></p> <p>2007</p> </div> <p>from which</p> <p style="padding-left: 40px;">A juniper, 5 ins. diam., bears N. 84°30' E., 72.0 lks. dist., mkd. T16N R62E S32 SC BT.</p> <p style="padding-left: 40px;">A pine, 7 ins. diam., bears N. 26°37' W., 103.0 lks. dist., mkd. T16N R62E S31 SC BT.</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <p>Cor. is located on a SE. facing slope, in sagebrush, pine and juniper timber.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 15 N., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of a Portion of the Survey Executed by E.B. Monroe and A.G. Bateman, U.S. Deputy Surveyors, in 1873</p> <hr/> <p>From the point for the cor. of secs. 21, 22, 27 and 28, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T15N R62E <u>S21 S22</u> S28 S27</p> <p>2007</p> </div> <p>from which</p> <p style="padding-left: 40px;">A pinon, 7 ins. diam., bears N. 35°01' E., 69.4 lks. dist., mkd. T15N R62E S22 BT.</p> <p style="padding-left: 40px;">A juniper, 4 ins. diam., bears S. 50°45' E., 95.8 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A forked juniper, 5 ins. diam. on scribed trunk, bears S. 74°26' W., 84.1 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A forked juniper, 5 ins. diam. on scribed trunk, bears N. 37°22' W., 52.7 lks. dist., mkd. X BT.</p>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 N., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located on a gentle W. facing slope, in scattered juniper and pine timber.</p> <p>From this point, the cor. of secs. 22, 23, 26 and 27, bears N. 89°43'10" E., 80.582 chs. dist., monumented with a limestone, 11x9x7 ins., firmly set, projecting 6 ins. above the ground, and in a mound of stone, 2 1/2 ft. base, 6 ins. high, with no discernible marks, witnessed by an old wood stake, 16x2x1 ins., loosely set alongside, mkd. with 4 grooves on a face. This position has been adopted and recorded in Nevada Corner Perpetuation and Filing Records, White Pine County, Nevada, and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2">T15N R62E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S22</td> <td style="padding: 0 5px;">S23</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S27</td> <td style="padding: 0 5px;">S26</td> </tr> </table> <p>2007</p> </div> <p>from which</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears N. 22°19' E., 108.8 lks. dist., mkd. T15N R62E S23 BT.</p> <p style="padding-left: 40px;">A juniper, 8 ins. diam., bears S. 37°53' E., 73.8 lks. dist., mkd. T15N R62E S26 BT.</p> <p style="padding-left: 40px;">A juniper, 9 ins. diam., bears S. 46°58' W., 53.0 lks. dist., mkd. T15N R62E S27 BT.</p> <p style="padding-left: 40px;">A pine, 9 ins. diam., bears N. 79°12' W., 41.0 lks. dist., mkd. T15N R62E S22 BT.</p> <p>Deposit unmarked stone and wood stake alongside the stainless steel post.</p> <p>Cor. is located on a N. facing slope, in juniper, mahogany and pine timber.</p> <p>This control line was fully retraced, and no evidence of the intervening cor. was found.</p> <p>From this same point, the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., bears S. 0°07'20" W., 160.396 chs. dist., monumented with a limestone, 11x4x3 ins., firmly set, projecting 6 ins. above the ground, in an embedded mound of stone, 3 ft. base, mkd. with 3 notches on E. edge and 3 notches on W. edge.</p>	T15N R62E		S22	S23	S27	S26
T15N R62E							
S22	S23						
S27	S26						

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 N., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS																	
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T15N</td><td>R62E</td></tr> <tr><td>S33</td><td>S34</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 4</td><td>S 3</td></tr> <tr><td colspan="2">T14N</td></tr> </table> <p>2007</p> </div> <p>from which</p> <p>A juniper, 5 ins. diam., bears N. 80°27' E., 50.6 lks. dist., mkd. X BT.</p> <p>A juniper, 7 ins. diam., bears S. 30°50' E., 32.3 lks. dist., mkd. T14N R62E S3 BT.</p> <p>A forked pinon, 9 ins. diam. on scribed trunk, bears S. 85°52' W., 18.4 lks. dist., mkd. T14N R62E S4 BT.</p> <p>A pinon, 6 ins. diam., bears N. 64°12' W., 22.1 lks. dist., mkd. X BT.</p> <p>Deposit the mkd. stone in the mound of stone and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located on a SW. facing slope, in pine and juniper timber.</p> <p>This control line was fully retraced, and no evidence of the intervening cors. was found.</p> <p>N. 0°39'40" E., bet. secs. 21 and 22.</p> <p>21.50 Wash, 9 lks. wide, drains N. 48° W.</p> <p>23.488 Apparent centerline of Headhouse Road, dirt surfaced, 15 lks. wide, bears S. 62° E. and N. 62°17'20" W.</p> <p>23.998 Point for a witness point at the intersection of the northerly right-of-way line of Headhouse Road with the line bet. secs. 21 and 22, hereinafter described.</p> <p>40.102 Point for the 1/4 sec. cor. of secs. 21 and 22, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 1 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T15N</td><td>R62E</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S21</td><td>S22</td></tr> </table> <p>2007</p> </div>	T15N	R62E	S33	S34	<hr/>		S 4	S 3	T14N		T15N	R62E	1/4		S21	S22
T15N	R62E																
S33	S34																
<hr/>																	
S 4	S 3																
T14N																	
T15N	R62E																
1/4																	
S21	S22																

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 N., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>from which</p> <p>A pine, 7 ins. diam., bears N. 88°42' E., 30.8 lks. dist., mkd. 1/4 S22 BT.</p> <p>A juniper, 6 ins. diam., bears S. 64°53' W., 55.9 lks. dist., mkd. 1/4 S21 BT.</p> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located on a NW. facing slope, in juniper and pine timber.</p>						
45.60	Wash, 50 lks. wide, drains S. 77° W.						
80.204	<p>The cor. of secs. 15, 16, 21 and 22, determined at the center of an embedded mound of stone, 3 ft. base, with a portion of a limestone, 10x6x5 ins. (Record: 16x12x6 ins.), laying loose nearby, mkd. with 3 notches on one edge.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in an embedded mound of stone, 3 ft. base, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1" data-bbox="889 1003 1036 1094"> <tr><td colspan="2">T15N R62E</td></tr> <tr><td>S16</td><td>S15</td></tr> <tr><td>S21</td><td>S22</td></tr> </table> <p>2007</p> </div> <p>from which</p> <p>A juniper, 5 ins. diam., bears N. 41°47' E., 48.3 lks. dist., mkd. T15N R62E S15 BT.</p> <p>A juniper, 4 ins. diam., bears S. 22°26' E., 72.0 lks. dist., mkd. X BT.</p> <p>A juniper, 5 ins. diam., bears S. 58°43' W., 103.3 lks. dist., mkd. T15N R62E S21 BT.</p> <p>A juniper, 6 ins. diam., bears N. 70°47' W., 87.6 lks. dist., mkd. T15N R62E S16 BT.</p> <p>Deposit the mkd. stone in the mound of stone and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located on a W. facing slope, in sagebrush, juniper and pine timber.</p> <hr/> <p>N. 0°13'20" W., bet. secs. 15 and 16.</p>	T15N R62E		S16	S15	S21	S22
T15N R62E							
S16	S15						
S21	S22						
20.64	Holt Creek, intermittent creek, 10 lks. wide, drains N. 67° W.						
20.80	Center of Holt Creek Road, dirt surfaced, 12 lks. wide, bears S. 67° E. and N. 67° W.						

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 N., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.400	<p>The 1/4 sec. cor. of secs. 15 and 16, monumented with a limestone, 15x10x5 ins., firmly set, projecting 8 ins. above the ground, and in an mound of stone, 3 ft. base, with no discernible mks. This position is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T15N R62E 1/4 S16 S15</p> <p style="text-align: center;">2007</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 6 ins. diam., bears N. 80°46' E., 28.6 lks. dist., mkd. 1/4 S15 BT.</p> <p style="padding-left: 40px;">A juniper, 5 ins. diam., bears S. 15°36' W., 55.7 lks. dist., mkd. 1/4 S16 BT.</p> <p>Bury the unmarked stone and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located on a gentle W. facing slope, in juniper and pine timber.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°16'40" E., beginning new measurement.</p>
40.986	<p>The cor. of secs. 9, 10, 15 and 16, monumented with a limestone, 12x7x5 ins., firmly set, projecting 4 ins. above the ground, and in an embedded mound of stone, 2 ft. base, mkd. with 4 notches on one edge.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T15N R62E S 9 S10 S16 S15</p> <p style="text-align: center;">2007</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 4 ins. diam., bears N. 78°00' E., 173.9 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A juniper, 9 ins. diam., bears S. 16°32' E., 283.6 lks. dist., mkd. T15N R62E S15 BT.</p> <p>No other suitable accessories available.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 N., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Deposit the mkd. stone and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located on a gentle, open, W. facing slope, in bunch grass and scattered juniper and pine timber.</p>
	<p>N. 0°11'30" W., bet. secs. 9 and 10.</p>
25.70	<p>White Sage Wash, 2 chs. wide, drains N. 57° W.</p>
26.90	<p>Center of White Sage Wash Road, dirt surfaced, 14 lks. wide, bears S. 57° E. and N. 57° W.</p>
27.46	<p>Barbed wire fence, bears S. 22° E. and N. 22° W.</p>
41.197	<p>Point for the 1/4 sec. cor. of secs. 9 and 10, at proportionate dist.; there is no remaining evidence of the original cor.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 1 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T15N R62E 1/4 S 9 S10</p>
	<p style="text-align: center;">2007</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A juniper, 5 ins. diam., bears S. 7°21' E., 44.5 lks. dist., mkd. 1/4 S10 BT.</p>
	<p style="padding-left: 40px;">A pine, 11 ins. diam., bears S. 75°55' W., 78.2 lks. dist., mkd. 1/4 S9 BT.</p>
	<p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p>
	<p>Cor. is located in a shallow swale, coursing W., in sagebrush, bunch grass, juniper and pine timber.</p>
	<p>From this point, a mound of stone of unknown origin, 3 ft. base, 1 ft. high, bears S. 54°11'40" W., 5.319 chs. dist. This position is not harmoniously related to surrounding corners, cannot be reconciled with proper procedures and is not utilized during the course of this survey.</p>
82.394	<p>Point for the cor. of secs. 3, 4, 9 and 10, at proportionate dist.; there is no remaining evidence of the original cor.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T15N R62E S 4 S 3 S 9 S10</p>
	<p style="text-align: center;">2007</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 N., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>from which</p> <p>A juniper, 7 ins. diam., bears N. 66°50' E., 111.7 lks. dist., mkd. T15N R62E S3 BT.</p> <p>A pine, 5 ins. diam., bears S. 51°32' E., 115.9 lks. dist., mkd. S10 BT.</p> <p>A juniper, 6 ins. diam., bears S. 60°04' W., 13.0 lks. dist., mkd. T15N R62E S9 BT.</p> <p>A juniper, 5 ins. diam., bears N. 43°43' W., 33.6 lks. dist., mkd. X BT.</p> <p>Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor. and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located on level ground, on W. edge of a firebreak road, 12 lks. wide, bears N. and S., in juniper and pine timber.</p> <p>From this cor., the cor. of secs. 2, 3, 10 and 11, bears S. 88°00'40" E., 81.152 chs. dist., monumented with the broken remains of a limestone, 12x9x7 ins. (Record: 13x11x10 ins.), firmly set, projecting 10 ins. above the ground, and in an embedded mound of stone, 2 1/2 ft. base, 6 ins. high, with no discernible notches. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2">T15N R62E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 3</td> <td style="padding: 0 5px;">S 2</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S10</td> <td style="padding: 0 5px;">S11</td> </tr> </table> <p>2007</p> </div> <p>from which</p> <p>A pine, 7 ins. diam., bears N. 39°10' E., 28.5 lks. dist., mkd. T15N R62E S2 BT.</p> <p>A juniper, 7 ins. diam., bears S. 34°34' E., 53.5 lks. dist., mkd. T15N R62E S11 BT.</p> <p>A juniper, 8 ins. diam., bears S. 66°57' W., 50.8 lks. dist., mkd. T15N R62E S10 BT.</p> <p>A juniper, 4 ins. diam., bears N. 42°25' W., 52.4 lks. dist., mkd. X BT.</p> <p>Bury the unmarked stone alongside the stainless steel post.</p> <p>Cor. is located on a SW. facing slope, in pine, juniper and mahogany timber.</p> <p>This control line was fully retraced, and no evidence of the intervening cor. was found.</p>	T15N R62E		S 3	S 2	S10	S11
T15N R62E							
S 3	S 2						
S10	S11						

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 N., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 6°24'40" W., bet. secs. 3 and 4.
18.50	Center of Lion Spring Road, dirt surfaced, 12 lks. wide, bears S. 60° E. and N. 60° W.
20.30	Lion Spring Wash, 3 chs. wide, drains N. 48° W.
41.456	Point for the 1/4 sec. cor. of secs. 3 and 4, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd. T15N R62E 1/4 S 4 S 3 2007 from which A pine, 6 ins. diam., bears N. 39°55' E., 34.4 lks. dist., mkd. 1/4 S3 BT. A juniper, 6 ins. diam., bears S. 60°45' W., 30.2 lks. dist., mkd. 1/4 S4 BT. Set a steel sign post, 6 ft. long, alongside the stainless steel post. Cor. is located on a NW. facing slope, in pine and juniper timber.
46.00	Center of Dead Horse Wash Road, dirt surfaced, 14 lks. wide, bears N. 69° E. and S. 69° W.
48.60	Dead Horse Wash, 1 ch. wide, drains S. 80° W.
51.25	Center of asphalt surface of U.S. Highway No. 6, 55 lks. wide, bears N. 28° E. and S. 28° W.
56.70	Wash, 1 ch. wide, drains S. 67° W.
82.964	Intersect the Third Standard Parallel North. Point for the closing cor. of secs. 3 and 4, on the N. bdy. of the Tp., at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 1 1/2 ft. base, to top, with brass cap mkd. T16N R62E S33 S 4 S 3 T15N R62E CC 2007

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 N., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>from which</p> <p>A forked pine, 5 ins. diam. on scribed trunk, bears S. 60°24' E., 33.3 lks. dist., mkd. T15N R62E S3 CC BT.</p> <p>A juniper, 5 ins. diam., bears S. 44°23' W., 30.2 lks. dist., mkd. S4 CC BT.</p> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located on a SW. facing slope, in sagebrush, bunch grass, juniper and pine timber.</p> <p>From this point, the standard 1/4 sec. cor. of sec. 33, T. 16 N., R. 62 E., bears S. 89°47'40" E., 9.433 chs. dist., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 28, 29, 32 and 33, monumented with a limestone, 14x13x6 ins., firmly set, projecting 7 ins. above ground, and in an embedded mound of stone, 2 ft. base, mkd. with 1 notch on S. edge and 4 notches on E. edge.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 2 ft. base, to top, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T15N R62E</td> </tr> <tr> <td style="text-align: center;">S29</td> <td style="text-align: center;">S28</td> </tr> <tr> <td style="text-align: center;">S32</td> <td style="text-align: center;">S33</td> </tr> </table> <p style="text-align: center;">2007</p> <p>from which</p> <p>A juniper, 7 ins. diam., bears N. 76°58' E., 47.4 lks. dist., mkd. T15N R62E S28 BT.</p> <p>A juniper, 10 ins. diam., bears S. 41°31' E., 62.0 lks. dist., mkd. T15N R62E S33 BT.</p> <p>A juniper, 9 ins. diam., bears S. 3°24' E., 36.8 lks. dist., mkd. T15N R62E BT X.</p> <p>A juniper, 17 ins. diam., bears N. 25°52' W., 48.6 lks. dist., mkd. T15N R62E S29 BT.</p> <p>Deposit mkd. stone in the mound of stone.</p> <p>Cor. is located on a gentle NW. facing slope, in sagebrush, bunch grass and juniper timber.</p> <p>NORTH, bet. secs. 28 and 29.</p>	T15N R62E		S29	S28	S32	S33
T15N R62E							
S29	S28						
S32	S33						
12.60	Wash, 1 ch. wide, drains W.						

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 N., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
29.80	Center of dirt road, 12 lks. wide, bears N. 10° E. and S. 10° W.
32.70	Wash, 2 chs. wide, drains S. 77° W.
39.858	<p>Point for the 1/4 sec. cor. of secs. 28 and 29, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 1 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T15N R62E 1/4 S29 S28</p> <p style="text-align: center;">2007</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 6 ins. diam., bears S. 14°33' E., 60.9 lks. dist., mkd. 1/4 S28 BT.</p> <p style="padding-left: 40px;">A juniper, 5 ins. diam., bears S. 48°42' W., 74.5 lks. dist., mkd. 1/4 S29 BT.</p> <p>Cor. is located on nearly level ground, 88 lks. W. of the center of a dirt road, 26 lks. wide, bears N. 8° E. and S. 8° W., in sagebrush, bunch grass, scattered juniper and pine timber.</p>
79.716	<p>Point for the cor. of secs. 20, 21, 28 and 29, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 1 ft. base, with brass cap mkd.</p> <p style="text-align: center;">T15N R62E S20 S21 S29 S28</p> <p style="text-align: center;">2007</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 6 ins. diam., bears N. 83°13' E., 26.5 lks. dist., mkd. T15N R62E S21 BT.</p> <p style="padding-left: 40px;">A juniper, 7 ins. diam., bears S. 21°23' E., 56.7 lks. dist., mkd. T15N R62E S28 BT.</p> <p style="padding-left: 40px;">A juniper, 5 ins. diam., bears S. 41°58' W., 52.1 lks. dist., mkd. T15N R62E S29 BT.</p> <p style="padding-left: 40px;">A pine, 6 ins. diam., bears N. 47°40' W., 91.5 lks. dist., mkd. X BT.</p> <p>Cor. is located on level ground, in sagebrush, bunch grass, juniper and scattered pine timber.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 N., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	From the cor. of secs. 21, 22, 27 and 28.
	S. 89°47'40" W., bet. secs. 21 and 28.
12.61	Barbed wire fence, bears N. and S.
25.50	Center of dirt road, 12 lks. wide, bears S. 1° E. and N. 1° W.
40.230	Point for the 1/4 sec. cor. of secs. 21 and 28, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 1 1/2 ft. base, to top, with brass cap mkd.
	T15N R62E S21 1/4 $\frac{\quad}{\quad}$ S28
	2007
	from which
	A juniper, 8 ins. diam., bears S. 76°10' W., 4.9 lks. dist., mkd. 1/4 S28 BT.
	A pine, 5 ins. diam., bears N. 2°06' W., 33.6 lks. dist., mkd. 1/4 S21 BT.
	Cor. is located on a gentle W. facing slope, in bunch grass, sagebrush, pine and juniper timber.
74.80	Center of dirt road, 18 lks. wide, bears N. 7° E. and S. 7° W.
80.460	The cor. of secs. 20, 21, 28 and 29.
	N. 1°53'50" E., bet. secs. 20 and 21.
22.36	Holt Camp Creek, intermittent creek, 2 chs. wide, drains S. 82° W.
27.692	Apparent centerline of Headhouse Road, dirt surfaced, 24 lks. wide, bears S. 81°22'00" W. and N. 81°22'00" E., soon N. 83°07'20" E.
28.154	Point for a witness point at the intersection of the northerly right-of-way line of Headhouse Road with the line bet. secs. 20 and 21, hereinafter described.
39.880	The 1/4 sec. cor. of secs. 20 and 21, monumented with a limestone, 15x5x4 ins., firmly set, projecting 6 ins. above the ground, dimly mkd. 1/4 on W. face.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 1 ft. base, to top, with brass cap mkd.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 N., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">T15N R62E 1/4 S20 S21 2007</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 6 ins. diam., bears S. 84°11' E., 86.7 lks. dist., mkd. 1/4 S21 BT.</p> <p style="padding-left: 40px;">A juniper, 6 ins. diam., bears S. 43°59' W., 101.5 lks. dist., mkd. 1/4 S20 BT.</p> <p>Deposit mkd. stone alongside stainless steel post.</p> <p>Cor. is located on a gentle W. facing slope, in sagebrush, bunch grass and scattered juniper timber.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°56'40" W., beginning new measurement.</p>
40.854	<p>The cor. of secs. 16, 17, 20 and 21, monumented with a limestone, 15x10x7 ins., firmly set, projecting 6 ins. above the ground, and in an embedded mound of stone, 1 1/2 ft. base, mkd. with 3 notches on S. edge and 4 notches on E. edge.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 1 1/2 ft. base, with brass cap mkd.</p> <p style="text-align: center;">T15N R62E S17 S16 <hr style="width: 10%; margin: 0 auto;"/>S20 S21 2007</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 5 ins. diam., bears N. 87°15' E., 172.0 lks. dist., mkd. T15N R62E S16 BT.</p> <p style="padding-left: 40px;">A juniper, 5 ins. diam., bears S. 11°02' E., 71.8 lks. dist., mkd. T15N R62E S21 BT.</p> <p style="padding-left: 40px;">A juniper, 6 ins. diam., bears S. 59°10' W., 95.3 lks. dist., mkd. T15N R62E S20 BT.</p> <p style="padding-left: 40px;">A juniper, 4 ins. diam., bears N. 28°09' W., 149.4 lks. dist., mkd. X BT.</p> <p>Deposit mkd. stone in the collar of stone.</p> <p>Cor. is located on a gentle W. facing slope, in sagebrush, bunch grass, mahogany scrub and scattered juniper timber.</p> <hr style="width: 20%; margin: 10px auto;"/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 N., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	From the cor. of secs. 15, 16, 21 and 22.
	N. 89°38'00" W., bet. secs. 16 and 21.
9.50	Center of dirt road, 11 lks. wide, bears S. 1° E. and N. 1° W.
12.74	Barbed wire fence, bears N. 1° E. and S. 1° W.
13.70	Center of dirt road, 14 lks. wide, bears N. 2° E. and S. 2° W.
40.323	The 1/4 sec. cor. of secs. 16 and 21, monumented with a limestone, 8x7x6 ins., firmly set, projecting 4 ins. above the ground, and in an embedded mound of stone, 1 1/2 ft. base, mkd. 1/4 on N. face.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 1 1/2 ft. base, to top, with brass cap mkd.
	T15N R62E S16 1/4 ——— S21 2007
	from which
	A juniper, 5 ins. diam., bears S. 44°54' E., 20.6 lks. dist., mkd. 1/4 S21 BT.
	A juniper, 6 ins. diam., bears N. 86°28' W., 83.9 lks. dist., mkd. 1/4 S16 BT.
	Deposit mkd. stone in the collar of stone.
	Cor. is located on a gentle W. facing slope, in bunch grass, sagebrush and scattered juniper timber.

	S. 89°56'50" W., beginning new measurement.
25.60	Center of dirt road, 12 lks. wide, bears N. 8° E. and S. 8° W.
40.399	The cor. of secs. 16, 17, 20 and 21.

	N. 0°14'20" W., bet. secs. 16 and 17.
25.70	Center of dirt road, 12 lks. wide, bears S. 70° E. and N. 70° W.
28.40	Wash, 5 lks. wide, drains N. 89° W.
29.50	Wash, 14 lks. wide, drains S. 77° W.
34.40	Wash, 33 lks. wide, drains S. 82° W.
40.671	The 1/4 sec. cor. of secs. 16 and 17, monumented with a limestone, 15x10x7 ins., firmly set, projecting 10 ins. above the ground, and in an embedded mound of stone, 2 1/2 ft. base, mkd. 1/4 on E. face.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 N., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T15N R62E 1/4 S17 S16 2007</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 5 ins. diam., bears S. 80°07' E., 22.6 lks. dist., mkd. 1/4 S16 BT.</p> <p style="padding-left: 40px;">A juniper, 7 ins. diam., bears N. 57°20' W., 20.5 lks. dist., mkd. 1/4 S17 BT.</p> <p>Deposit mkd. stone in the mound of stone.</p> <p>Cor. is located on a gentle W. facing slope, in juniper and pine timber.</p> <hr style="width: 30%; margin: 20px auto;"/> <p>N. 0°38'40" E., beginning new measurement.</p> <p>7.80 Wash, 5 lks. wide, drains N. 64° W.</p> <p>10.20 Wash, 1 ch. wide, drains S. 69° W.</p> <p>17.50 Wash, 50 lks. wide, drains S. 87° W.</p> <p>25.80 Wash, 1 ch. wide, drains S. 83° W.</p> <p>28.74 Easterly right-of-way fence line of U.S. Highway No. 6, bears N. 28° E. and S. 28° W.</p> <p>35.280 Point for a witness point, at the intersection of the centerline of U.S. Highway No. 6 with the line bet. secs. 16 and 17, hereinafter described.</p> <p>40.573 The cor. of secs. 8, 9, 16 and 17, monumented with a limestone, 8x5x4 ins., firmly set, projecting 3 ins. above the ground, and in an embedded mound of stone, 2 1/2 ft. base, mkd. with 4 notches on E. edge.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T15N R62E S 8 S 9 S17 S16 2007</p>
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 N., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>from which</p> <p>A juniper, 5 ins. diam., bears N. 36°35' E., 36.4 lks. dist., mkd. T15N R62E S9 BT.</p> <p>A juniper, 6 ins. diam., bears S. 45°56' E., 35.9 lks. dist., mkd. T15N R62E S16 BT.</p> <p>A juniper, 4 ins. diam., bears S. 45°14' W., 29.5 lks. dist., mkd. T15N R62E S17 BT.</p> <p>A juniper, 5 ins. diam., bears N. 87°28' W., 24.5 lks. dist., mkd. S8 BT.</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <p>Cor. is located on level ground, 2.79 chs. W. of the asphalt center of U.S. Highway No. 6, 55 lks. wide, bears N. 28° E. and S. 28° W., and 65 1/2 lks. E. of a fence line, bears N. 28° E. and S. 28° W., in juniper and pine timber.</p> <hr/> <p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>S. 89°44'30" W., bet. secs. 9 and 16.</p>
10.61	Barbed wire fence, bears N. 16° E. and S. 16° W.
11.00	Center of dirt road, 15 lks. wide, bears N. 16° E. and S. 16° W.
40.346	<p>The 1/4 sec. cor. of secs. 9 and 16, monumented with a limestone, 9x5x4 ins., firmly set, projecting 3 ins. above the ground, and in an embedded mound of stone, 2 1/2 ft. base, mkd. 1/4 on N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T15N R62E S 9 1/4 <u> </u> S16</p> <p style="text-align: center;">2007</p>
	<p>from which</p> <p>A juniper, 5 ins. diam., bears S. 34°26' E., 47.7 lks. dist., mkd. 1/4 S16 BT.</p> <p>A juniper, 6 ins. diam., bears N. 87°34' W., 68.3 lks. dist., mkd. 1/4 S9 BT.</p> <p>Deposit mkd. stone in the mound of stone.</p> <p>Cor. is located on a gentle N. facing slope, in pine and juniper timber.</p> <hr/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 N., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 89°37'50" W., beginning new measurement.
17.20	Center of dirt road, 12 lks. wide, bears S. 5° E. and N. 5° W.
33.88	Easterly right-of-way fence line of U.S. Highway No. 6, bears N. 28° E. and S. 28° W.
37.338	Point for a witness point, at the intersection of the centerline of U.S. Highway No. 6 with the line bet. secs. 9 and 16, hereinafter described.
40.115	The cor. of secs. 8, 9, 16 and 17.
	N. 0°37'50" W., bet. secs. 8 and 9.
1.19	Westerly right-of-way fence line of U.S. Highway No. 6, bears N. 28° E. and S. 28° W.
40.523	Point for the 1/4 sec. cor. of secs. 8 and 9, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 1 1/4 ft. base, to top, with brass cap mkd. <div style="text-align: center;"> T15N R62E 1/4 S 8 S 9 2007 </div>
	from which <div style="margin-left: 40px;"> A pine, 7 ins. diam., bears S. 35°00' E., 61.2 lks. dist., mkd. 1/4 S9 BT. A juniper, 8 ins. diam., bears S. 52°58' W., 33.2 lks. dist., mkd. 1/4 S8 BT. </div>
42.50	Center of gravel and broken pavement of abandoned highway, 36 lks. wide, bears N. 30° E. and S. 30° W.
81.046	The cor. of secs. 4, 5, 8 and 9, monumented with a limestone, 7x6x5 ins., firmly set, projecting 3 ins. above the ground, and in an embedded mound of earth and stone, 2 ft. base, mkd. with 5 notches on S. edge. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd. <div style="text-align: center;"> T15N R62E S 5 S 4 S 8 S 9 2007 </div>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 N., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>from which</p> <p>A pine, 8 ins. diam., bears N. 61°11' E., 58.5 lks. dist., mkd. T15N R62E S4 BT.</p> <p>A juniper, 5 ins. diam., bears S. 35°05' E., 45.9 lks. dist., mkd. S9 BT.</p> <p>A pine, 9 ins. diam., bears S. 40°06' W., 162.7 lks. dist., mkd. T15N R62E S8 BT.</p> <p>A juniper, 4 ins. diam., bears N. 59°27' W., 51.5 lks. dist., mkd. S5 BT.</p> <p>Deposit mkd. stone alongside stainless steel post.</p> <p>Cor. is located on a SE. facing slope, in sagebrush, pine and juniper timber.</p> <hr/> <p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>S. 89°05'50" W., bet. secs. 4 and 9.</p>
10.63	Barbed wire fence, bears N. and S.
13.10	Center of dirt road, 15 lks. wide, bears N. 8° E. and S. 8° W.
29.93	Easterly right-of-way fence line of U.S. Highway No. 6, bears N. 28° E. and S. 28° W.
33.403	Point for a witness point, at the intersection of the centerline of U.S. Highway No. 6 with the line bet. secs. 4 and 9, hereinafter described.
36.87	Westerly right-of-way fence line of U.S. Highway No. 6, bears N. 28° E. and S. 28° W.
40.536	<p>Point for the 1/4 sec. cor. of secs. 4 and 9, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15N R62E S 4 1/4 $\frac{\quad}{\quad}$ S 9'</p> <p style="text-align: center;">2007</p>
	<p>from which</p> <p>A pine, 6 ins. diam., bears S. 25°02' E., 68.3 lks. dist., mkd. 1/4 S9 BT.</p> <p>A juniper, 6 ins. diam., bears N. 87°14' W., 19.5 lks. dist., mkd. 1/4 S4 BT.</p> <p>Cor. is located on level ground, in juniper and pine timber.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 N., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
47.26	Center of gravel and broken pavement of abandoned highway, 24 lks. wide, bears N. 43° E. and S. 43° W.
81.072	The cor. of secs. 4, 5, 8 and 9.
	<hr/> <p>From the cor. of secs. 28, 29, 32 and 33. N. 89°37'10" W., bet. secs. 29 and 32.</p>
3.70	Center of dirt road, 12 lks. wide, bears N. 6° E. and S. 6° W.
40.034	<p>Point for the 1/4 sec. cor. of secs. 29 and 32, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T15N R62E S29 1/4 <u> </u> S32</p> <p>2007</p> </div> <p>from which</p> <p style="padding-left: 40px;">A juniper, 6 ins. diam., bears S. 37°43' E., 48.4 lks. dist., mkd. 1/4 S32 BT.</p> <p style="padding-left: 40px;">A juniper, 5 ins. diam., bears N. 13°44' W., 93.2 lks. dist., mkd. 1/4 S29 BT.</p> <p>Cor. is located on level ground, in sagebrush, bunch grass and scattered juniper timber.</p>
80.068	<p>The cor. of secs. 29, 30, 31 and 32, determined at the center of a hollow, 3 ins. diam., in an earthen mound, 2 ft. base, 6 ins. high, with a hewn wood post, 40x3x3 ins., laying loose alongside, mkd. SXXX on one face and illegible mks. on other faces.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 1 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T15N R62E S30 S29 <u> </u> S31 S32</p> <p>2007</p> </div> <p>from which</p> <p style="padding-left: 40px;">A juniper, 7 ins. diam., bears N. 20°48' E., 53.5 lks. dist., mkd. T15N R62E S29 BT.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 N., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>A juniper, 5 ins. diam., bears S. 46°40' E., 109.1 lks. dist., mkd. X BT.</p> <p>A juniper, 9 ins. diam., bears S. 46°46' W., 31.8 lks. dist., mkd. T15N R62E S31 BT.</p> <p>A juniper, 8 ins. diam., bears N. 38°32' W., 13.9 lks. dist., mkd. T15N R62E S30 BT.</p> <p>Deposit the mkd. post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located on a gentle NW. facing slope, in sagebrush and scattered juniper timber.</p>
42.072	<p>S. 89°52'20" W., bet. secs. 30 and 31.</p> <p>Point for the 1/4 sec. cor. of secs. 30 and 31, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 1 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T15N R62E S30 1/4 ——— S31</p> <p style="text-align: center;">2007</p> <p>from which</p> <p>A juniper, 4 ins. diam., bears N. 8°58' E., 76.7 lks. dist., mkd. 1/4 S30 BT.</p> <p>A juniper, 6 ins. diam., bears S. 70°41' W., 106.7 lks. dist., mkd. 1/4 S31 BT.</p> <p>Cor. is located on a gentle SW. facing slope, in sagebrush, bunch grass and scattered juniper timber.</p>
42.48	Easterly right-of-way fence line of U.S. Highway No. 6, bears N. 28° E. and S. 28° W.
45.93	Center of asphalt of U.S. Highway No. 6, 55 lks. wide, bears N. 28° E. and S. 28° W.
49.37	Westerly right-of-way fence line of U.S. Highway No. 6, bears N. 28° E. and S. 28° W.
58.92	Center of gravel and broken pavement of abandoned highway, 36 lks. wide, bears N. 25° E. and S. 25° W.
78.885	The cor. of secs. 30 and 31 only, on the W. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the 1953 Dependent Resurvey, W. Bdy., T. 15 N., R. 62 E., Survey, E. Bdy., T. 15 N., R. 61 E., executed under Group No. 277.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 N., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>from which a new bearing tree</p> <p>A juniper, 5 ins. diam., bears N. 4°38' E., 132.1 lks. dist., mkd. T15N R62E S30 BT.</p> <p>Cor. is located on a SE. facing slope, in sagebrush, bunch grass and scattered juniper timber.</p> <hr/> <p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0°23'20" W., bet. secs. 29 and 30.</p>
9.10	Wash, 2 chs. wide, drains N. 81° W.
14.80	Center of dirt road, 9 lks. wide, bears N. 83° E. and S. 69° W.
40.721	<p>Point for the 1/4 sec. cor. of secs. 29 and 30, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 1 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T15N R62E 1/4 S30 S29 2007</p>
	<p>from which</p> <p>A juniper, 5 ins. diam., bears S. 80°47' E., 90.2 lks. dist., mkd. 1/4 S29 BT.</p> <p>A juniper, 6 ins. diam., bears N. 58°18' W., 165.2 lks. dist., mkd. 1/4 S30 BT.</p> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located on level ground, in sagebrush, bunch grass and scattered juniper timber.</p>
65.50	Holt Camp Creek, intermittent creek, 3 chs. wide, drains S. 63° W.
76.219	Apparent centerline of Headhouse Road, dirt surfaced, 24 lks. wide, bears S. 70°56'50" W. and N. 70°56'50" E., soon N. 76°56'40" E.
76.699	Point for a witness point at the intersection of the northerly right-of-way line of Headhouse Road with the line bet. secs. 29 and 30, hereinafter described.
77.96	Easterly right-of-way fence line of U.S. Highway No. 6, bears N. 28° E. and S. 28° W.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 N., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS							
81.442	<p>The cor. of secs. 19, 20, 29 and 30, monumented with a rebar of unknown origin, 37 ins. long, 1/2 in. diam., firmly set, projecting 26 ins. above the ground, with no cap. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 1 ft. base, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T15N</td><td>R62E</td></tr> <tr><td>S19</td><td>S20</td></tr> <tr><td>S30</td><td>S29</td></tr> </table> <p style="text-align: center;">2007</p> <p>from which</p> <p>A juniper, 7 ins. diam., bears N. 36°19' E., 76.9 lks. dist., mkd. T15N R62E S20 BT.</p> <p>A 60D nail and brass washer, 1 1/2 ins. diam., stamped BLM CADASTRAL SURVEY, attached to a fence post, 6 ins. diam., 4 1/2 ft. high, bears S. 49°52' E., 170.8 lks. dist., with fences extending N. 28° E. and S. 28° W.</p> <p>No other suitable accessories available.</p> <p>Deposit the rebar inside and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located on level ground, in sagebrush and scattered juniper timber.</p>	T15N	R62E	S19	S20	S30	S29
T15N	R62E						
S19	S20						
S30	S29						
40.317	<p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>N. 88°23'50" W., bet. secs. 20 and 29.</p> <p>Point for the 1/4 sec. cor. of secs. 20 and 29, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 1 1/2 ft. base, to top, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T15N</td><td>R62E</td></tr> <tr><td>1/4</td><td>S20</td></tr> <tr><td></td><td>S29</td></tr> </table> <p style="text-align: center;">2007</p> <p>from which</p> <p>A juniper, 6 ins. diam., bears S. 65°54' E., 91.8 lks. dist., mkd. 1/4 S29 BT.</p> <p>A juniper, 5 ins. diam., bears N. 61°33' W., 105.2 lks. dist., mkd. 1/4 S20 BT.</p>	T15N	R62E	1/4	S20		S29
T15N	R62E						
1/4	S20						
	S29						

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 N., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Cor. is located on level ground, in sagebrush and scattered juniper timber.
52.90	Holt Camp Creek, intermittent creek, 2 chs. wide, drains S. 69° W.
60.803	Apparent centerline Headhouse Road, dirt surfaced, 24 lks. wide, bears N. 74°24'30" E. and S. 74°24'30" W., soon S. 76°56'40" W.
62.341	Point for a witness point at the intersection of the northerly right-of-way line of Headhouse Road with the line bet. secs. 20 and 29, hereinafter described.
78.77	Easterly right-of-way fence line of U.S. Highway No. 6, bears N. 28° E. and S. 28° W.
80.634	The cor. of secs. 19, 20, 29 and 30.
	S. 89°48'00" W., bet. secs. 19 and 30.
1.550	Point for a witness point at the intersection of the centerline of U.S. Highway No. 6 with the line bet. secs. 19 and 30, hereinafter described.
5.00	Westerly right-of-way fence line of U.S. Highway No. 6, bears N. 28° E. and S. 28° W.
19.86	Center of gravel and broken pavement of abandoned highway, 36 lks. wide, bears N. 25° E. and S. 25° W.
41.966	Point for the 1/4 sec. cor. of secs. 19 and 30, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 1 ft. base, to top, with brass cap mkd. <div style="text-align: center;"> T15N R62E S19 1/4 $\frac{\quad}{\quad}$ S30 2007 </div> from which A juniper, 5 ins. diam., bears N. 11°37' E., 3.141 chs. dist., mkd. 1/4 S19 BT. A juniper, 4 ins. diam., bears S. 62°12' W., 5.006 chs. dist., mkd. 1/4 S30 BT. Set a steel sign post, 6 ft. long, alongside the stainless steel post. Cor. is located on level ground, in sagebrush, bunch grass and scattered juniper timber.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 N., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
64.40	Powerline and dirt road, 15 lks. wide, bears N. 24° E. and S. 24° W.
78.10	Center of dirt road, 12 lks. wide, bears N. 17° E. and S. 17° W.
78.581	<p>The cor. of secs. 19 and 30 only, on the W. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. as described in the field notes of the 1953 Dependent Resurvey, W. Bdy., T. 15 N., R. 62 E., Survey, E. Bdy., T. 15 N., R. 61 E., executed under Group No. 277, from which the 1953 bearing tree</p> <p style="padding-left: 40px;">A juniper, 5 ins. diam., bears S. 23 1/2° E., 92 lks. dist., mkd. BT on a partly healed blaze.</p> <p>Cor. is located on level, open ground, in sagebrush and scattered juniper timber.</p> <hr/> <p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0°07'30" E., bet. secs. 19 and 20.</p>
2.890	Point for a witness point at the intersection of the centerline of U.S. Highway No. 6 with the line bet. secs. 19 and 20, hereinafter described.
9.32	Westerly right-of-way fence line of U.S. Highway No. 6, bears N. 28° E. and S. 28° W.
40.742	<p>Point for the 1/4 sec. cor. of secs. 19 and 20, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 1 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T15N R62E 1/4 S19 S20 2007</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 5 ins. diam., bears N. 54°40' E., 49.8 lks. dist., mkd. 1/4 S20 BT.</p> <p style="padding-left: 40px;">A juniper, 5 ins. diam., bears S. 89°17' W., 12.1 lks. dist., mkd. 1/4 S19 BT.</p> <p>Cor. is located on level ground, in sagebrush and scattered juniper timber.</p>
41.73	Center of gravel and broken pavement of abandoned highway, 36 lks. wide, bears N. 25° E. and S. 25° W.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 N., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS									
81.484	<p>The cor. of secs. 17, 18, 19 and 20, monumented with a rebar of unknown origin, 17 ins. long, 1/2 in. diam., firmly set, projecting 6 ins. above the ground, with no cap, and with portions of juniper post laying alongside. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 1 ft. base, to top, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T15N R62E</td></tr> <tr><td>S18</td><td>S17</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S19</td><td>S20</td></tr> </table> <p style="text-align: center;">2007</p> <p>from which</p> <p style="padding-left: 40px;">A 60D nail and brass washer, 1 1/2 ins. diam., stamped BLM CADASTRAL SURVEY, attached to a fence corner post, 5 ins. diam., 5 1/2 ft. high, bears N. 53°35' E., 7.463 chs. dist., with fences extending N. and E.</p> <p style="padding-left: 40px;">A 60D nail and brass washer, 1 1/2 ins. diam., stamped BLM CADASTRAL SURVEY, attached to a utility pole, 14 ins. diam., bears S. 66°11' E., 16.506 chs. dist.</p> <p>No other suitable accessories available.</p> <p>Deposit the rebar inside and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located on level ground, in bunch grass and sagebrush.</p>	T15N R62E		S18	S17	<hr/>		S19	S20
T15N R62E									
S18	S17								
<hr/>									
S19	S20								
	<hr/> <p>From the cor. of secs. 16, 17, 20 and 21.</p>								
	<p>N. 87°51'30" W., bet. secs. 17 and 20.</p>								
36.46	<p>Easterly right-of-way fence line of U.S. Highway No. 6, bears N. 28° E. and S. 28° W.</p>								
39.838	<p>Point for a witness point at the intersection of the centerline of U.S. Highway No. 6 with the line bet. secs. 17 and 20, hereinafter described.</p>								
40.556	<p>Point for the 1/4 sec. cor. of secs. 17 and 20, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 1 ft. base, to top, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T15N R62E</td></tr> <tr><td></td><td>S17</td></tr> <tr><td>1/4</td><td><hr/></td></tr> <tr><td></td><td>S20</td></tr> </table> <p style="text-align: center;">2007</p>	T15N R62E			S17	1/4	<hr/>		S20
T15N R62E									
	S17								
1/4	<hr/>								
	S20								

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 N., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>from which</p> <p>A forked juniper, 4 ins. diam. on scribed trunk, bears S. 70°23' W., 149.8 lks. dist., mkd. 1/4 S20 BT.</p> <p>A 60D nail and brass washer, 1 1/2 ins. diam., stamped BLM CADASTRAL SURVEY, attached to a fence post, 4x5 ins. diam., bears N. 53°57' W., 240.6 lks. dist., with fences extending N. 28° E. and S. 28° W.</p> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located on level ground, in bunch grass, sagebrush and scattered juniper timber.</p> <p>43.21 Westerly right-of-way fence line of U.S. Highway No. 6, bears N. 28° E. and S. 28° W.</p> <p>62.70 Center of gravel and broken pavement of abandoned highway, 36 lks. wide, bears N. 25° E. and S. 25° W.</p> <p>81.112 The cor. of secs. 17, 18, 19 and 20.</p> <hr/> <p>S. 89°41'50" W., bet. secs. 18 and 19.</p> <p>27.82 Powerline and dirt road, 15 lks. wide, bears N. 24° E. and S. 24° W.</p> <p>42.222 Point for the 1/4 sec. cor. of secs. 18 and 19, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 1 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T15N R62E S18 1/4 $\frac{\quad}{\quad}$ S19</p> <p style="text-align: center;">2007</p> <p>from which</p> <p>A juniper, 5 ins. diam., bears S. 52°32' W., 4.364 chs. dist., mkd. 1/4 S19 BT.</p> <p>A juniper, 7 ins. diam., bears N. 69°43' W., 192.3 lks. dist., mkd. 1/4 S18 BT.</p> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located on level ground, in bunch grass, sagebrush and scattered juniper timber.</p> <p>53.10 Center of dirt road, 12 lks. wide, bears N. 17° E. and S. 17° W.</p>
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 N., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
79.008	<p>The cor. of secs. 18 and 19 only, on the W. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, and in a collar of stone, 1 ft. base, with brass cap mkd. as described in the field notes of the 1953 Dependent Resurvey, W. Bdy., T. 15 N., R. 62 E., Survey, E. Bdy., T. 15 N., R. 61 E., executed under Group No. 277, from which the 1953 bearing trees</p> <p style="padding-left: 40px;">A juniper, 9 ins. diam., bears N. 55° E., 20 lks. dist., mkd. S18 BT on an open blaze.</p> <p style="padding-left: 40px;">A juniper, 9 ins. diam., bears S. 42° E., 86 lks. dist., mkd. T15N R62E S19 BT on an open blaze.</p> <p>Cor. is located on level ground, in scattered juniper timber.</p> <hr/> <p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 0°19'10" E., bet. secs. 17 and 18.</p>
40.775	<p>Point for the 1/4 sec. cor. of secs. 17 and 18, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 1 ft. base, with brass cap mkd.</p> <p style="text-align: center;">T15N R62E 1/4 S18 S17 2007</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 8 ins. diam., bears N. 54°28' E., 49.1 lks. dist., mkd. 1/4 S17 BT.</p> <p style="padding-left: 40px;">A juniper, 7 ins. diam., bears N. 83°27' W., 109.7 lks. dist., mkd. 1/4 S18 BT.</p> <p>Cor. is located on level ground, in sagebrush and juniper timber.</p>
62.35	<p>Powerline and dirt road, 15 lks. wide, bears N. 24° E. and S. 24° W.</p>
81.550	<p>The cor. of secs. 7, 8, 17 and 18, monumented with a hewn wood post, 26x2x2 ins., loosely set, projecting 24 ins. above the ground, mkd. TXVNRLXIIIESXVIII on one face and illegible mks. on other faces, attached with wire to a carriage bolt, 17 ins. long, 1/2 in. diam., firmly set, projecting 7 ins. above the ground, with convex head, 1 1/4 ins. diam., mkd. P.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 1 ft. base, with brass cap mkd.</p>


DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 N., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T15N R62E S 7 S 8 ----- S18 S17</p> <p style="text-align: center;">2007</p> <p>from which</p> <p>A juniper, 5 ins. diam., bears N. 4°17' E., 65.0 lks. dist., mkd. T15N R62E S8 BT.</p> <p>A juniper, 9 ins. diam., bears S. 11°11' E., 12.3 lks. dist., mkd. T15N R62E S17 BT.</p> <p>A juniper, 5 ins. diam., bears S. 71°37' W., 43.9 lks. dist., mkd. X BT.</p> <p>A juniper, 9 ins. diam., bears N. 74°21' W., 64.1 lks. dist., mkd. T15N R62E S7 BT.</p> <p>Set mkd. wood post alongside, and deposit the carriage bolt inside the stainless steel post.</p> <p>Cor. is located on a gentle SW. facing slope, in juniper timber.</p> <hr/> <p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>N. 87°38'10" W., bet. secs. 8 and 17.</p>
0.64	Westerly right-of-way fence line of U.S. Highway No. 6, bears N. 28° E. and S. 28° W.
24.41	Center of gravel and broken pavement of abandoned highway, 36 lks. wide, bears N. 29° E. and S. 29° W.
40.471	Point for the 1/4 sec. cor. of secs. 8 and 17, at proportionate dist.; there is no remaining evidence of the original cor.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T15N R62E S 8 1/4 ----- S17</p> <p style="text-align: center;">2007</p> <p>from which</p> <p>A juniper, 9 ins. diam., bears S. 63°34' E., 38.9 lks. dist., mkd. 1/4 S17 BT.</p> <p>A pine, 6 ins. diam., bears N. 54°52' W., 193.3 lks. dist., mkd. 1/4 S8 BT.</p> <p>Cor. is located on S. edge of a shallow wash, 1/2 ch. wide, drains W., in sagebrush, juniper and pine timber.</p>





DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 N., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS							
72.55	Powerline and dirt road, 15 lks. wide, bears N. 24° E. and S. 24° W.						
80.942	The cor. of secs. 7, 8, 17 and 18.						
	<hr/> <p>METES-AND-BOUNDS SURVEY OF THE NORTHERLY RIGHT-OF-WAY LINE OF HEADHOUSE ROAD THROUGH SECTIONS 20, 21, 29 AND A PORTION OF SECTION 30, T. 15 N., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>						
	<p>MEMORANDUM</p> <p>The southerly boundary of Parcel 3 of the Ely Shoshone Expansion in T. 15 N., R. 62 E., Mount Diablo Meridian, Nevada, as described in the White Pine County Conservation, Recreation and Development Act of 2006 is identified as the northerly right-of-way line of Headhouse Road, a reserved Right-of-Way grant filed under Bureau of Land Management Serial No. N-7766. This was converted to a section 507 FLPMA right-of-way reservation on November 5, 1998.</p> <p>The northerly right-of-way line of Headhouse Road is a line parallel with and 30 feet northerly of the centerline of the existing road. Witness points were established at intersections of the northerly right-of-way line of Headhouse Road with appropriate section lines and with the centerline of U.S. Highway No. 6. Angle points were established where there was a change in alignment.</p> <hr/> <p>From the point for a witness point at the intersection of the northerly right-of-way line of Headhouse Road with the line bet. secs. 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 1 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>WP</p> <table style="margin: auto;"> <tr> <td>T15N</td> <td> </td> <td>R62E</td> </tr> <tr> <td>S21</td> <td>└─┘</td> <td>S22</td> </tr> </table> <p>2007</p> </div> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located on a W. facing slope, in sagebrush, bunch grass, pine and juniper timber.</p> <p>N. 62°17'20" W., on the northerly right-of-way line of Headhouse Road through sec. 21.</p>	T15N		R62E	S21	└─┘	S22
T15N		R62E					
S21	└─┘	S22					
14.15	Barbed wire fence, bears N. and S.						
26.70	Center of dirt road, 12 lks. wide, bears N. 6° E.						



METES-AND-BOUNDS SURVEY OF THE NORTHERLY RIGHT-OF-WAY LINE
 OF HEADHOUSE ROAD THROUGH SECTIONS 20, 21, 29
 AND A PORTION OF SECTION 30,
 T. 15 N., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
27.392	<p>Point for Angle Point No. 1, sec. 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 1 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T15N R62E AP 1  S21 2007</p> <hr style="width: 30%; margin: auto;"/> <p>S. 75°27'40" W., on line 1-2, on the northerly right-of-way line of Headhouse Road through sec. 21.</p>
6.847	<p>Point for Angle Point No. 2, sec. 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 1 1/4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T15N R62E AP 2  S21 2007</p> <hr style="width: 30%; margin: auto;"/> <p>S. 63°51'10" W., on line 2-3, on the northerly right-of-way line of Headhouse Road through sec. 21.</p>
8.096	<p>Point for Angle Point No. 3, sec. 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 1 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T15N R62E AP 3  S21 2007</p> <hr style="width: 30%; margin: auto;"/> <p>S. 76°27'20" W., on line 3-4, on the northerly right-of-way line of Headhouse Road through sec. 21.</p>
21.205	<p>Point for Angle Point No. 4, sec. 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 1 ft. base, to top, with brass cap mkd.</p>




METES-AND-BOUNDS SURVEY OF THE NORTHERLY RIGHT-OF-WAY LINE
 OF HEADHOUSE ROAD THROUGH SECTIONS 20, 21, 29
 AND A PORTION OF SECTION 30,
 T. 15 N., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T15N R62E AP 4</p>  <p style="text-align: center;">S21 2007</p>
8.440	<p>S. 86°43'50" W., on line 4-5, on the northerly right-of-way line of Headhouse Road through sec. 21.</p> <p>Point for Angle Point No. 5, sec. 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 1 1/2 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T15N R62E AP 5</p>  <p style="text-align: center;">S21 2007</p>
3.10	<p>N. 84°20'20" W., on line 5-6, on the northerly right-of-way line of Headhouse Road through sec. 21.</p> <p>Center of dirt road, 14 lks. wide, bears N. 2° W.</p>
4.667	<p>Point for Angle Point No. 6, sec. 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 1 1/2 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T15N R62E AP 6</p>  <p style="text-align: center;">S21 2007</p>
2.00	<p>N. 62°31'20" W., on line 6-7, on the northerly right-of-way line of Headhouse Road through sec. 21.</p> <p>Center of dirt road, 12 lks. wide, bears N. 48° E.</p>
4.139	<p>Point for Angle Point No. 7, sec. 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 1 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T15N R62E AP 7</p>  <p style="text-align: center;">S21 2007</p>



METES-AND-BOUNDS SURVEY OF THE NORTHERLY RIGHT-OF-WAY LINE
OF HEADHOUSE ROAD THROUGH SECTIONS 20, 21, 29
AND A PORTION OF SECTION 30,
T. 15 N., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p> <p>4.327</p>	<p>S. 83°07'20" W., on the northerly right-of-way line of Headhouse Road through sec. 21.</p> <p>Point for a witness point at the intersection of the northerly right-of-way line of Headhouse Road with the line bet. secs. 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 1 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;">  <p>WP T15N R62E S20 S21</p> </div> <p>2007</p> <p>Cor. is located on level ground, in sagebrush, bunch grass and juniper timber.</p>
<p>7.073</p>	<p>S. 81°22'00" W., on the northerly right-of-way line of Headhouse Road through sec. 20.</p> <p>Point for Angle Point No. 1, sec. 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 1 1/4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;">  <p>T15N R62E AP 1 S20</p> </div> <p>2007</p>
<p>11.748</p>	<p>S. 63°07'20" W., on line 1-2, on the northerly right-of-way line of Headhouse Road through sec. 20.</p> <p>Point for Angle Point No. 2, sec. 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 1 1/4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;">  <p>T15N R62E AP 2 S20</p> </div> <p>2007</p>
	<p>S. 89°27'30" W., on line 2-3, on the northerly right-of-way line of Headhouse Road through sec. 20.</p>

METES-AND-BOUNDS SURVEY OF THE NORTHERLY RIGHT-OF-WAY LINE
OF HEADHOUSE ROAD THROUGH SECTIONS 20, 21, 29
AND A PORTION OF SECTION 30,
T. 15 N., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
1.236	<p>Point for Angle Point No. 3, sec. 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 1 ft. base, with brass cap mkd.</p> <p style="text-align: center;">T15N R62E AP 3  S20 2007</p> <hr/> <p>N. 62°49'30" W., on line 3-4, on the northerly right-of-way line of Headhouse Road through sec. 20.</p>
3.752	<p>Point for Angle Point No. 4, sec. 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 1 ft. base, with brass cap mkd.</p> <p style="text-align: center;">T15N R62E AP 4  S20 2007</p> <hr/> <p>S. 58°50'30" W., on line 4-5, on the northerly right-of-way line of Headhouse Road through sec. 20.</p>
32.835	<p>Point for Angle Point No. 5, sec. 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 1 ft. base, with brass cap mkd.</p> <p style="text-align: center;">T15N R62E AP 5  S20 2007</p> <hr/> <p>S. 69°15'10" W., on line 5-6, on the northerly right-of-way line of Headhouse Road through sec. 20.</p>
11.539	<p>Point for Angle Point No. 6, sec. 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 1 ft. base, with brass cap mkd.</p>

METES-AND-BOUNDS SURVEY OF THE NORTHERLY RIGHT-OF-WAY LINE
OF HEADHOUSE ROAD THROUGH SECTIONS 20, 21, 29
AND A PORTION OF SECTION 30,
T. 15 N., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
2.402	<p style="text-align: center;">T15N R62E AP 6  S20 2007</p> <p>S. 74°24'30" W., on the northerly right-of-way line of Headhouse Road through sec. 20.</p> <p>Point for a witness point at the intersection of the northerly right-of-way line of Headhouse Road with the line bet. secs. 20 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 1 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">WP T15N R62E  S20 S29 2007</p> <p>Cor. is located on level ground, in sagebrush, bunch grass and scattered juniper timber.</p>
18.739	<p>S. 76°56'40" W., on the northerly right-of-way line of Headhouse Road through sec. 29.</p> <p>Point for a witness point at the intersection of the northerly right-of-way line of Headhouse Road with the line bet. secs. 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 1 1/4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">WP T15N R62E  S30 S29 2007</p> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located on level ground, in bunch grass, sagebrush and scattered juniper timber.</p>

METES-AND-BOUNDS SURVEY OF THE NORTHERLY RIGHT-OF-WAY LINE
OF HEADHOUSE ROAD THROUGH SECTIONS 20, 21, 29
AND A PORTION OF SECTION 30,
T. 15 N., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p> <p>0.871</p>	<p>S. 70°56'50" W., on the northerly right-of-way line of Headhouse Road through a portion of sec. 30.</p> <p>Point for Angle Point No. 1, sec. 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 1 ft. base, with brass cap mkd.</p> <p style="text-align: center;">T15N R62E AP 1 /_____ S30 2007</p> <p>Cor. is located 1 1/2 lks. E. of easterly right-of-way fence line of U.S. Highway No. 6, bears N. 28° E. and S. 28° W.</p> <p>From this point, an iron pipe, set by persons unknown, 1 in. diam., loosely set, projecting 12 ins. above the ground, and in a collar of stone, 2 ft. base, bears S. 78°44' W., 1.063 chs. dist., not utilized in the course of this survey.</p>
<p>3.802</p>	<p>S. 81°27'50" W., on the northerly right-of-way line of Headhouse Road through a portion of sec. 30.</p> <p>Point for a witness point at the intersection of the northerly right-of-way line of Headhouse Road with the centerline of U.S. Highway No. 6, hereinafter described.</p> <hr/> <p>METES-AND-BOUNDS SURVEY OF THE CENTERLINE OF U.S. HIGHWAY NO. 6 THROUGH SECTIONS 9, 16, 17, 19, 20 AND A PORTION OF SECTION 30, T. 15 N., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">MEMORANDUM</p> <p>The centerline of U.S. Highway No. 6 was determined utilizing monuments set by the Nevada Department of Transportation. Witness points were established at intersection of the centerline of U.S. Highway No. 6 and section lines.</p> <p>The mean geodetic bearing of a straight line, based on the existing centerline of U.S. Highway No. 6 as measured from Station 560+62.90 to Station 770+73.86, is N. 28°15'50" E. The following field notes describe mean bearings of the centerline of U.S. Highway No. 6, through each particular section, which when combined, equal the total mean bearing of N. 28°15'50" E.</p> <hr/> <p>From the point for a witness point at the intersection of the northerly right-of-way line of Headhouse Road with the centerline of U.S. Highway No. 6.</p>

METES-AND-BOUNDS SURVEY OF THE CENTERLINE OF U.S. HIGHWAY NO. 6
THROUGH SECTIONS 9, 16, 17, 19, 20 AND A PORTION OF SECTION 30,
T. 15 N., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p> <p>3.287</p>	<p>N. 28°15'20" E., the mean geodetic bearing through sec. 19, on the centerline of U.S. Highway No. 6, the overall mean geodetic bearing of a straight line being N. 28°15'50" E.</p> <p>Point for a witness point at the intersection of the centerline of U.S. Highway No. 6 with the line bet. secs. 19 and 20.</p> <p>Set a PK nail flush with the asphalt surface.</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground, for a reference monument, over a plastic-encased magnet, and in a collar of stone, 1 ft. base, to top, bears N. 73°16'50" E., 4.268 chs. dist., with brass cap mkd. RM WP T15N R62E S20 281.7 FT. TO COR. 2007 and an arrow pointing to the cor.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground, for a reference monument, over a plastic-encased magnet, and in a collar of stone, 1 ft. base, to top, bears N. 16°46'20" W., 4.256 chs. dist., with brass cap mkd. RM WP T15N R62E S19 280.9 FT. TO COR. 2007 and an arrow pointing to the cor.</p>
<p>1.018</p>	<p>N. 28°15'30" E., the mean geodetic bearing through sec. 20, on the centerline of U.S. Highway No. 6, the overall mean geodetic bearing of a straight line being N. 28°15'50" E.</p> <p>Point on Tangent.</p> <p>POINT NOT MONUMENTED</p> <p>From this point, a Nevada Department of Transportation highway station utilized to determine the center of the right-of-way, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, bears S. 61°44'30" E., 78.1 lks. dist., mkd. DIST 51.55 STA C589+54.15.</p> <p>From this same point, a Nevada Department of Transportation highway station utilized to determine the center of the right-of-way, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, bears N. 61°44'30" W., 96.3 lks. dist., mkd. DIST 63.55 STA C589+54.15.</p>
<p>49.843</p>	<p>Point on Tangent.</p> <p>POINT NOT MONUMENTED</p> <p>From this point, a Nevada Department of Transportation highway station utilized to determine the center of the right-of-way, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, bears S. 61°44'30" E., 74.2 lks. dist., mkd. DIST 48.94 STA C621+76.32.</p>

METES-AND-BOUNDS SURVEY OF THE CENTERLINE OF U.S. HIGHWAY NO. 6
THROUGH SECTIONS 9, 16, 17, 19, 20 AND A PORTION OF SECTION 30,
T. 15 N., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From this same point, a Nevada Department of Transportation highway station utilized to determine the center of the right-of-way, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, bears N. 61°44'30" W., 87.2 lks. dist., mkd. DIST 57.53 STA C621+76.32.</p>
87.478	<p>Point for a witness point at the intersection of the centerline of U.S. Highway No. 6 with the line bet. secs. 17 and 20.</p> <p>Set a PK nail 1 in. below the asphalt surface.</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground, for a reference monument, over a plastic-encased magnet, and in a collar of stone, 1 1/4 ft. base, to top, bears N. 44°59'10" E., 4.165 chs. dist., with brass cap mkd. RM WP T15N R62E S17 274.9 FT. TO COR. 2007 and an arrow pointing to the cor.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground, for a reference monument, over a plastic-encased magnet, and in a collar of stone, 1 1/4 ft. base, to top, bears S. 44°57'10" E., 108.6 lks. dist., with brass cap mkd. RM WP T15N R62E S20 71.7 FT. TO COR. 2007 and an arrow pointing to the cor.</p>
6.147	<p>N. 28°15'50" E., the mean geodetic bearing through sec. 17, on the centerline of U.S. Highway No. 6, the mean overall geodetic bearing of a straight line being N. 28°15'50" E.</p> <p>Point on Tangent.</p> <p>POINT NOT MONUMENTED</p> <p>From this point, a Nevada Department of Transportation highway station utilized to determine the center of the right-of-way, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, bears S. 61°44'10" E., 100.2 lks. dist., mkd. DIST 66.16 STA C650+65.64.</p> <p>From this same point, a Nevada Department of Transportation highway station utilized to determine the center of the right-of-way, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, bears N. 61°44'10" W., 103.1 lks. dist., mkd. DIST 68.04 STA C650+65.64.</p>
48.859	<p>Point on Tangent.</p> <p>POINT NOT MONUMENTED</p> <p>From this point, a Nevada Department of Transportation highway station utilized to determine the center of the right-of-way, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, bears S. 61°44'10" E., 115.7 lks. dist., mkd. DIST 76.36 STA C678+84.52.</p>

METES-AND-BOUNDS SURVEY OF THE CENTERLINE OF U.S. HIGHWAY NO. 6
THROUGH SECTIONS 9, 16, 17, 19, 20 AND A PORTION OF SECTION 30,
T. 15 N., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From this same point, a Nevada Department of Transportation highway station utilized to determine the center of the right-of-way, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, bears N. 61°44'10" W., 94.6 lks. dist., mkd. DIST 62.45 STA C678+84.52.</p>
84.539	<p>Point for a witness point at the intersection of the centerline of U.S. Highway No. 6 with the line bet. secs. 16 and 17.</p> <p>Set a PK nail 1 in. below the asphalt surface.</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 21 ins. in the ground, for a reference monument, over a plastic-encased magnet, and in a collar of stone, 1 1/4 ft. base, to top, bears S. 16°52'10" E., 162.7 lks. dist., with brass cap mkd. RM WP T15N R62E S16 107.4 FT. TO COR. 2007 and an arrow pointing to the cor.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 20 ins. in the ground to bedrock, for a reference monument, over a plastic-encased magnet, and in a collar of stone, 1 1/2 ft. base, to top, bears S. 73°02'20" W., 120.6 lks. dist., with brass cap mkd. RM WP T15N R62E S17 79.6 FT. TO COR. 2007 and an arrow pointing to the cor.</p>
5.174	<p>N. 28°16'00" E., the mean geodetic bearing through sec. 16, on the centerline of U.S. Highway No. 6, the overall mean geodetic bearing of a straight line being N. 28°15'50" E.</p> <p>Point on Tangent</p> <p>POINT NOT MONUMENTED</p> <p>From this point, a Nevada Department of Transportation highway station utilized to determine the center of the right-of-way, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, bears S. 61°44'00" E., 110.8 lks. dist., mkd. DIST 73.12 STA C705+80.90.</p> <p>From this same point, a Nevada Department of Transportation highway station utilized to determine the center of the right-of-way, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, bears N. 61°44'00" W., 94.3 lks. dist., mkd. DIST 62.24 STA C705+80.90.</p>
5.989	<p>Point for a witness point at the intersection of the centerline of U.S. Highway No. 6 with the line bet. secs. 9 and 16.</p> <p>Set a PK nail 1 in. below the asphalt surface.</p>

METES-AND-BOUNDS SURVEY OF THE CENTERLINE OF U.S. HIGHWAY NO. 6
THROUGH SECTIONS 9, 16, 17, 19, 20 AND A PORTION OF SECTION 30,
T. 15 N., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 20 ins. in the ground, for a reference monument, over a plastic-encased magnet, and in a collar of stone, 1 1/2 ft. base, to top, bears N. 89°59'30" E., 3.451 chs. dist., with brass cap mkd. RM WP T15N R62E S9 227.8 FT. TO COR. 2007 and an arrow pointing to the cor.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 20 ins. in the ground, for a reference monument, over a plastic-encased magnet, and in a collar of stone, 1 ft. base, to top, bears S. 89°59'40" W., 119.8 lks. dist., with brass cap mkd. RM WP T15N R62E S16 79.1 FT. TO COR. 2007 and an arrow pointing to the cor., witnessed by a steel sign post, 6 ft. long, set alongside the stainless steel post.</p> <hr/> <p>N. 28°16'10" E., the mean geodetic bearing through sec. 9, on the centerline of U.S. Highway No. 6, the overall mean geodetic bearing of a straight line being N. 28°15'50" E.</p>
47.746	<p>Point on Tangent.</p> <p>POINT NOT MONUMENTED</p> <p>From this point, a Nevada Department of Transportation highway station utilized to determine the center of the right-of-way, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, bears S. 61°43'50" E., 128.2 lks. dist., mkd. DIST 84.59 STA C737+86.07.</p> <p>From this same point, a Nevada Department of Transportation highway station utilized to determine the center of the right-of-way, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, bears N. 61°43'50" W., 100.6 lks. dist., mkd. DIST 66.42 STA C737+86.07.</p>
92.891	<p>Point for a witness point at the intersection of the centerline of U.S. Highway No. 6 with the line bet. secs. 4 and 9.</p> <p>Set a PK nail 1 in. below the asphalt surface.</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 21 ins. in the ground, for a reference monument, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, bears N. 73°00'20" E., 138.8 lks. dist., with brass cap mkd. RM WP T15N R62E S4 91.6 FT. TO COR. 2007 and an arrow pointing to the cor.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground, for a reference monument, over a plastic-encased magnet, and in a collar of stone, 2 ft. base, to top, bears S. 16°56'10" E., 132.3 lks. dist., with brass cap mkd. RM WP T15N R62E S9 87.3 FT. TO COR. 2007 and an arrow pointing to the cor.</p>

METES-AND-BOUNDS SURVEY OF THE CENTERLINE OF U.S. HIGHWAY NO. 6
THROUGH SECTIONS 9, 16, 17, 19, 20 AND A PORTION OF SECTION 30,
T. 15 N., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From this point, a Nevada Department of Transportation highway station utilized to determine the center of the right-of-way, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, bears N. 15°47'10" E., 4.784 chs. dist., mkd. DIST 68.25 STA C770+73.86.</p> <p>From this same point, a Nevada Department of Transportation highway station utilized to determine the center of the right-of-way, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, bears N. 42°15'00" E., 4.815 chs. dist., mkd. DIST 76.75 STA C770+73.86.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The lands included in this survey are located in White Pine County, Nevada, about 10 miles southwest of the community of Ely, Nevada. Access is gained by way of U.S. Highway No. 6.</p> <p>Ward Mountain rises east of the area. Several intermittent washes and creeks drain westerly down the slope of this range, namely: Dead Horse Wash, Lion Spring Wash, White Sage Wash, Holt Creek and Holt Camp Creek. Many of these drainages are significantly diminished west of U.S. Highway No. 6, probably due to the barrier this highway presents. The average elevation of the area surveyed is approximately 6700 feet above sea level.</p> <p>No apparent mineral activity was noted in the area during this survey.</p> <hr/>
--------	---

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

George E. Allen	Supervisory Cadastral Surveyor
Gene R. Dollarhide	Cadastral Surveyor
Michelle E. Martin	Supervisory Range Technician
Douglas H. Crawford	Survey Aid

CERTIFICATE OF SURVEY

We, Wayne S. Hancock, Cadastral Surveyor, and Mark G. Petrosine, Surveying Technician, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 5th day of February, 2007, we have dependently resurveyed the Third Standard Parallel North, through a portion of Range 62 East and a portion of the subdivisional lines, surveyed by metes and bounds the northerly right-of-way line of Headhouse Road through sections 20, 21, 29 and a portion of section 30, and surveyed by metes and bounds the centerline of U.S. Highway No. 6 through sections 9, 16, 17, 19, 20 and a portion of section 30, Township 15 North, Range 62 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

March 4, 2008

(Date)

Wayne S. Hancock

(Cadastral Surveyor)

February 6, 2008

(Date)

Mark G. Petrosine

(Surveying Technician)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of the dependent resurvey of the Third Standard Parallel North through a portion of Range 62 East and a portion of the subdivisional lines, the metes-and-bounds survey of the northerly right-of-way line of Headhouse Road through sections 20, 21, 29 and a portion of section 30, and the metes-and-bounds survey of the centerline of U.S. Highway No. 6 through sections 9, 16, 17, 19, 20 and a portion of section 30, Township 15 North, Range 62 East, of the Mount Diablo Meridian, in the State of Nevada, executed by Wayne S. Hancock, Cadastral Surveyor, and Mark G. Petrosine, Surveying Technician, having been critically examined and found correct, are hereby approved.

March 19, 2008

(Date)

David D. Morlan

(Chief Cadastral Surveyor, Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above described surveys in T. 15 N., R. 62 E., Mount Diablo Meridian, Nevada, is a true copy of the original field notes.~~

~~_____~~
(Date)

~~_____~~
(Chief Cadastral Surveyor, Nevada)