

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

A PORTION OF THE SUBDIVISIONAL LINES,

THE SUBDIVISION OF SECTION 13,

AND

A METES-AND-BOUNDS SURVEY IN SECTION 13,

TOWNSHIP 15 NORTH, RANGE 63 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

EXECUTED BY

Wayne S. Hancock, Cadastral Surveyor

Mark G. Petrosine, Surveying Technician

Under Special Instructions dated February 9, 2007,

and approved February 9, 2007,

which provided for the surveys included under Group No. 846,

and Assignment Instructions dated February 9, 2007.

Survey commenced February 16, 2007

Survey completed November 1, 2007

INDEX DIAGRAM

TOWNSHIP 15 NORTH, RANGE 63 EAST, MOUNT DIABLO MERIDIAN, NEVADA

6	5	4	3	2	1
7	8	9	10	11	12
					4
18	17	16	15	14	3 13
					2
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Subdivision of Section 13 pp. 6 - 10.
 Metes-and-Bounds Survey in Section 13 pp. 10 - 13.

TOWNSHIP 15 NORTH, RANGE 63 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines, the subdivision of section 13, and a metes-and-bounds survey in section 13, Township 15 North, Range 63 East, Mount Diablo Meridian, Nevada.

The north boundary (Third Standard Parallel North) was surveyed by U.S. Deputy Surveyors E.B. Monroe and A.G. Bateman in 1871 under Contract No. 44. A portion of the south boundary, the east boundary, and a portion of the subdivisional lines were surveyed by U.S. Deputy Surveyors E.B. Monroe and A.G. Bateman in 1872 under Contract No. 48. A portion of the south boundary, the west boundary, and a portion of the subdivisional lines were surveyed by U.S. Deputy Surveyors E.B. Monroe and A.G. Bateman in 1872 under Contract No. 60. A portion of the north boundary (Third Standard Parallel North) was dependently resurveyed by Cadastral Surveyors H.G. Parker and R.A. Pratt in 1967 under Group No. 446. The west boundary of T. 15 N., R. 64 E. was dependently resurveyed by Cadastral Surveyors H.G. Parker, E.W. Sibley and R.A. Pratt in 1967-1968 under Group No. 454. A portion of the east boundary was dependently resurveyed under this same Group.

Before restoring the corners, the lines of original surveys were retraced and a diligent search made for all corners and other calls of record.

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 846, dated February 9, 2007.

Measurements were made with Trimble 4700, 5700, and 5800 Global Positioning System (GPS) receivers using the real-time kinematic method and refer to the true meridian based on geodetic methods. The mean bearings of the lines and horizontal equivalents of ground distances only are entered in the field notes.

The NAD 83 (CORS 96) geographic position of the corner of sections 13, 18, 19 and 24, determined from GPS static observations processed by the National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) "ECHO_BRGN_NV1999 CORS ARP", "EGAN_BRGN_NV1996 CORS ARP" and "RAILROAD VALLEY CORS ARP", in 2007, and carried forward by RTK measurement, is as follows:

Latitude: 39°09'30.151" N. Longitude: 114°50'12.627" W.

The February 16, 2007, mean magnetic declination was determined to be 13°20' E. from the National Oceanic and Atmospheric Administration's National Geophysical Data Center declination calculator.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Reestablishment of a Portion of the Survey Executed by E.B. Monroe and A.G. Bateman, U.S. Deputy Surveyors, in 1872</p> <hr/>
	<p>Beginning at the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the W. bdy. of T. 15 N., R. 64 E., executed under Group No. 454, with a mound of stone, 3 ft. base, 1/2 ft. high, W. of cor., an iron pipe, 1 in. diam., projecting 12 ins. above the ground, NW. of the cor. and a steel fence post, projecting 4 ft. above the ground, SW. of the cor.</p>
	<p>S. 87°55'40" W., bet. secs. 13 and 24.</p>
	<p>Across rolling land covered with scattered juniper, pinon pine, sagebrush and bunchgrass.</p>
5.45	<p>Powerline, extends S. 29° E. and N. 29° W.</p>
30.15	<p>Center of dirt road, 15 lks. wide, bears NE. and SW.</p>
35.390	<p>Apparent centerline of unimproved dirt road (N-7743), 15 lks. wide, bears N. 30° E. and S. 30° W.</p>
35.927	<p>Point for a witness point at the intersection of the northerly right-of-way line of an unimproved dirt road (N-7743) with the line bet. secs. 13 and 24, hereinafter described.</p>
39.844	<p>Point for the 1/4 sec. cor. of secs. 13 and 24, at proportionate distance, there is no remaining evidence of the original corner.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, 2 ft. base, with brass cap mkd.</p>
	$\begin{array}{r} \text{T15N R63E} \\ \text{S13} \\ 1/4 \frac{\quad}{\quad} \\ \text{S24} \end{array}$
	<p>2007</p>
	<p>Set a steel sign post alongside the stainless steel post.</p>
49.805	<p>Point for the E-W 1/64 sec. cor. of secs. 13 and 24.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	$\begin{array}{r} \text{S13} \\ \text{E-W 1/64} \\ \text{S24} \end{array}$
	<p>2007</p>
	<p>Set a steel sign post alongside the stainless steel post.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS							
55.45	Four-wheel drive trail, 10 lks. wide, bears NE. and SW.						
59.766	Point for the W 1/16 sec. cor. of secs. 13 and 24.						
	POINT NOT MONUMENTED						
62.00	Four-wheel drive trail, 10 lks. wide, bears NE. and SW.						
79.688	<p>The cor. of secs. 13, 14, 23 and 24, perpetuated by Richard W. Forman, Nevada Professional Land Surveyor No. 2898, monumented with a metal garden stake, 1 in. wide, projecting 24 ins. above the ground, in a well-embedded collar of stone, 2 ft. base, with attached brass tag, 3/4 in. diam., mkd. RLS 2898, and a charred wood stake, 28 ins. long, 1 in. diam., sharpened at an end, lying alongside. This is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <table border="1" data-bbox="889 919 1036 1010"> <tr> <td colspan="2" data-bbox="889 919 1036 940">T15N R63E</td> </tr> <tr> <td data-bbox="889 940 964 968">S14</td> <td data-bbox="964 940 1036 968">S13</td> </tr> <tr> <td data-bbox="889 968 964 995">S23</td> <td data-bbox="964 968 1036 995">S24</td> </tr> </table> <p data-bbox="932 1031 997 1058">2007</p> <p>Deposit charred stake and brass tag inside stainless steel post, and reset garden stake alongside.</p>	T15N R63E		S14	S13	S23	S24
T15N R63E							
S14	S13						
S23	S24						
	N. 0°13'20" E., bet. secs. 13 and 14.						
	Across rolling land covered with scattered juniper, pinon pine, sagebrush and bunchgrass, and along posted Forest Service boundary.						
2.25	Four-wheel drive trail, 10 lks. wide, bears NE. and SW.						
11.40	Four-wheel drive trail, 10 lks. wide, bears NE. and SW.						
20.990	Point for the S 1/16 sec. cor. of secs. 13 and 14.						
	POINT NOT MONUMENTED						
41.980	<p>Point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate distance, there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <table border="1" data-bbox="889 1745 1036 1835"> <tr> <td colspan="2" data-bbox="889 1745 1036 1766">T15N R63E</td> </tr> <tr> <td colspan="2" data-bbox="889 1766 1036 1793">1/4</td> </tr> <tr> <td data-bbox="889 1793 964 1820">S14</td> <td data-bbox="964 1793 1036 1820">S13</td> </tr> </table> <p data-bbox="932 1856 997 1883">2007</p>	T15N R63E		1/4		S14	S13
T15N R63E							
1/4							
S14	S13						

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS							
62.970	<p>Point for the N 1/16 sec. cor. of secs. 13 and 14.</p> <p>POINT NOT MONUMENTED</p>						
82.25	<p>Barbed wire fence, steel fence posts, bears E. and W., 8 lks. E. of cedar fence post, fences extending N. and E.</p>						
83.960	<p>The cor. of secs. 11, 12, 13 and 14, monumented with a steel fence post of unknown origin, projecting 4 ft. above the ground, with attached brass tag, 3/4 in. diam., mkd. PLS 2898, and in a collar of stone, 2 ft. base, 1 ft. high. The position was accepted by Richard W. Forman, Nevada Professional Land Surveyor No. 2898, as shown on County Map No. 232, recorded in White Pine County, Nevada as File No. 221328. Dean Neubauer, Nevada Professional Land Surveyor No. 9393, accepted this same position as shown on County Map No. 459, recorded in White Pine County, Nevada as File No. 285894. This position has been adopted by adjacent landowners and professional land surveyors and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T15N R63E</td> </tr> <tr> <td style="text-align: center;">S11</td> <td style="text-align: center;">S12</td> </tr> <tr> <td style="text-align: center;">S14</td> <td style="text-align: center;">S13</td> </tr> </table> <p style="text-align: center;">2007</p> <p>Deposit brass tag inside stainless steel post and reset the fence post alongside.</p> <p>Corner is located 9 lks. E. of a barbed wire fence, steel posts, bears N. and S.</p>	T15N R63E		S11	S12	S14	S13
T15N R63E							
S11	S12						
S14	S13						
5.04	<p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the W. bdy., T. 15 N., R. 64 E., executed under Group No. 454, with a mound of stone, 2 ft. base, 1 ft. high, W. of cor. Corner is located 4 lks. SE. of a fence corner, from which woven wire fences with cedar posts extends N. and W. and a barbed wire fence with steel posts extends E.</p> <p>N. 89°56'30" W., bet. secs. 12 and 13.</p> <p>Across rolling land covered with sagebrush and bunchgrass, and along woven wire fence, juniper posts.</p> <p>From this point, the E. end of a barbed wire fence, steel posts, bears S., 0.010 chs. dist., with a barbed wire fence extending S. 88 3/4° W.</p>						

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Continue along woven wire fence, and along N. side of barbed wire fence.</p> <p>9.942 The E-E 1/64 sec. cor. of secs. 12 and 13, determined by Richard E. Fonger, Nevada Professional Land Surveyor No. 4235, monumented with a rebar, 5/8 in. diam., firmly set, projecting 6 ins. above the ground, no marks found, as shown on County Map No. 611, recorded in White Pine County, Nevada as File No. 298933. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>Corner is located on the S. side of a treated wood fence corner post, with woven wire fences and juniper posts extending N. and E., and a woven wire fence with treated wood posts extending W.</p> <hr/> <p>N. 89°57'00" W., beginning new measurement.</p> <p>9.945 The E 1/16 sec. cor. of secs. 12 and 13, determined by Richard W. Forman, Nevada Professional Land Surveyor No. 2898, monumented with a rebar, 5/8 in. diam., firmly set, projecting 6 ins. above the ground, no marks found, as shown on County Map No. 422, recorded in White Pine County, Nevada as File No. 278844. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>From this corner, a treated wood fence corner post, with woven wire fences and treated wood posts extending N. and E., bears N. 77° E., 0.01 chs. dist.</p> <hr/> <p>N. 89°58'30" W., beginning new measurement.</p> <p>19.873 The 1/4 sec. cor. of secs. 12 and 13, reestablished by Richard W. Forman, Nevada Professional Land Surveyor No. 2898, monumented with a steel fence post, projecting 4 ft. above the ground, with attached brass tag, 3/4 in. diam., mkd. PLS 2898, and in a collar of stone, 2 ft. base, as shown on County Map No. 402, recorded in White Pine County, Nevada as File No. 277470. This is accepted as a careful and faithful reestablishment of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, 2 1/2 ft. base, with brass cap mkd.</p> <p style="text-align: center;">T15N R63E S12 1/4 <hr style="width: 10%; margin: 0 auto;"/> S13</p> <p style="text-align: center;">2007</p> <p>Deposit brass tag inside stainless steel post and reset the fence post alongside.</p> <hr/>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>N. 89°56'50" W., beginning new measurement.</p> <p>Across rolling land covered with scattered juniper, pinon pine, sagebrush and bunchgrass.</p> <p>9.944 Point for the E-W 1/64 sec. cor. of secs. 12 and 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, 2 ft. base, with brass cap mkd.</p> <p style="text-align: center;">S12 E-W 1/64 S13</p> <p style="text-align: center;">2007</p> <p>Point falls on the E. side of railroad tie fence corner post, 8x6 ins., from which barbed wire fences extend N. and SSE., and an H brace extends E.</p> <p>10.10 Powerline, bears S. 29° E. and N. 29° W.</p> <p>19.888 Point for W 1/16 sec. cor. of secs. 12 and 13.</p> <p>POINT NOT MONUMENTED</p> <p>39.776 The cor. of secs. 11, 12, 13 and 14.</p> <hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 13, T. 15 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 13 and 24.</p> <p>N. 0°12'20" E., on the N-S center line of sec. 13.</p> <p>Across rolling land covered with scattered juniper, pinon pine, sagebrush and bunchgrass.</p> <p>13.40 Four-wheel drive trail, 10 lks. wide, bears NE. and SW.</p> <p>16.05 Four-wheel drive trail, 10 lks. wide, bears ENE. and WSW.</p> <p>20.626 Point for C-S 1/16 sec. cor. of sec. 13.</p> <p>POINT NOT MONUMENTED</p> <p>41.252 Point for center 1/4 sec. cor. of sec. 13, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T15N R63E C 1/4 S13</p> <p style="text-align: center;">2007</p> <p>Set a steel sign post alongside the stainless steel post.</p>
--------	--

SUBDIVISION OF SECTION 13,
T. 15 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
46.90	Four-wheel drive trail, 10 lks. wide, bears NE. and NW.
61.866	<p>Point for the C-N 1/16 sec. cor. of sec. 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, 2 1/2 ft. base, with brass cap mkd.</p>
	<p style="text-align: center;"> $\begin{array}{c} \text{C} \\ \text{N } 1/16 \text{ S13} \\ \text{C} \end{array}$ </p> <p style="text-align: center;">2007</p>
	Set a steel sign post alongside the stainless steel post.
64.00	Powerline, bears S. 29° E. and N. 29° W.
64.15	Center of dirt road, 15 lks. wide, parallels powerline.
81.64	Barbed wire fence, steel posts, bears ENE. and WSW.
82.480	The 1/4 sec. cor. of secs. 12 and 13.
	<hr/> <p>From the 1/4 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the W. bdy., T. 15 N., R. 64 E., executed concurrently under this same group, with a mound of stone, 2 1/2 ft. base, 1 ft. high, W. of cor.</p> <p>S. 88°58'40" W., on the E-W center line of sec. 13.</p> <p>Across rolling land covered with scattered juniper, pinon pine, sagebrush and bunchgrass.</p>
27.35	Center of dirt road, 15 lks. wide, parallels powerline.
27.45	Powerline, bears S. 29° E. and N. 29° W.
39.790	The center 1/4 sec. cor. of sec. 13.
44.85	Four-wheel drive trail, 10 lks. wide, bears NE. and SW.
49.741	Point for the C-E-W 1/64 sec. cor. of sec. 13.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, in a collar of stone, 2 1/2 ft. base, with brass cap mkd.</p>
	<p style="text-align: center;"> $\begin{array}{c} \text{E-W } 1/64 \\ \text{C} \text{-----} \text{C} \\ \text{S13} \end{array}$ </p> <p style="text-align: center;">2007</p>
	Set a steel sign post alongside the stainless steel post.

SUBDIVISION OF SECTION 13,
T. 15 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
59.692	Point for the C-W 1/16 sec. cor. of sec. 13. POINT NOT MONUMENTED
79.594	The 1/4 sec. cor. of secs. 13 and 14. <hr/>
	From the N 1/16 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the W. bdy., T. 15 N., R. 64 E., executed concurrently under this same group. S. 89°30'40" W., on the E-W center line of the NE1/4 of sec. 13. Across rolling land covered with scattered juniper, pinon pine, sagebrush and bunchgrass.
38.50	Center of dirt road, 15 lks. wide, parallels powerline.
38.60	Powerline, bears S. 29° E., and N. 29° W.
39.773	The C-N 1/16 sec. cor. of sec. 13. <hr/>
	From the point for the W 1/16 sec. cor. of secs. 13 and 24. N. 0°12'50" E., on the N-S center line of the SW1/4 of sec. 13. Across rolling land covered with scattered juniper, pinon pine, sagebrush and bunchgrass.
2.15	Four-wheel drive trail, 10 lks. wide, bears NE. and SW.
17.50	Four-wheel drive trail, 10 lks. wide, bears NE. and SW.
20.808	Point for the SW 1/16 sec. cor. of sec. 13, at intersection with the E-W center line of the SW1/4. POINT NOT MONUMENTED
25.65	Four-wheel drive trail, 10 lks. wide, bears NE. and SW.
41.616	The point for the C-W 1/16 sec. cor. of sec. 13. <hr/>
	From the point for the C-S 1/16 sec. cor. of sec. 13. S. 88°27'00" W., on the E-W center line of the SW1/4 of sec. 13. Across rolling land covered with scattered juniper, pinon pine, sagebrush and bunchgrass.
9.956	Point for the C-E-SW 1/64 sec. cor. of sec. 13. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

SUBDIVISION OF SECTION 13,
T. 15 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	S13 C-E-SW 1/64 2007
	Set a steel sign post alongside the stainless steel post.
16.55	Four-wheel drive trail, 10 lks. wide, bears NE. and SW.
19.912	The point for the SW 1/16 sec. cor. of sec. 13.
25.70	Four-wheel drive trail, 10 lks. wide, bears NE. and SW.
39.823	The point for the S 1/16 sec. cor. of secs. 13 and 14.
	<hr/> From the C-E-SW 1/64 sec. cor. of sec. 13. N. 0°12'30" E., on the N-S center line of the NE1/4 of the SW1/4 of sec. 13. Across rolling land covered with scattered juniper, pinon pine, sagebrush and bunchgrass.
11.05	Four-wheel drive trail, 10 lks. wide, bears NE. and SW.
20.716	The C-E-W 1/64 sec. cor. of sec. 13.
	<hr/> From the E-W 1/64 sec. cor. of secs. 13 and 24. N. 0°12'30" E., on the N-S center line of the SE1/4 of the SW1/4 of sec. 13. Across rolling land covered with scattered juniper, pinon pine, sagebrush and bunchgrass.
6.40	Four-wheel drive trail, 10 lks. wide, bears NE. and SW.
10.10	Four-wheel drive trail, 10 lks. wide, bears NE. and SW.
20.717	The C-E-SW 1/64 sec. cor. of sec. 13.
	<hr/> From the point for the C-W 1/16 sec. cor. of sec. 13. N. 0°12'50" E., on the N-S center line of the NW1/4 of sec. 13. Across rolling land covered with scattered juniper, pinon pine, sagebrush and bunchgrass.
20.802	Point for the NW 1/16 sec. cor. of sec. 13, at intersection with the E-W center line of the NW1/4. POINT NOT MONUMENTED
40.32	Barbed wire fence, steel posts, bears ENE. and WSW.
41.603	The point for the W 1/16 sec. cor. of secs. 12 and 13.

SUBDIVISION OF SECTION 13,
T. 15 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p> <p>9.947</p>	<p>From the C-N 1/16 sec. cor. of sec. 13.</p> <p>S. 89°30'50" W., on the E-W center line of the NW1/4 of sec. 13.</p> <p>Across rolling land covered with scattered juniper, pinon pine, sagebrush and bunchgrass.</p> <p>Point for the C-E-NW 1/64 sec. cor. of sec. 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S13 C-E-NW 1/64 2007</p> <p>Set a steel sign post alongside the stainless steel post.</p>
<p>19.894</p> <p>39.789</p>	<p>The point for the NW 1/16 sec. cor. of sec. 13.</p> <p>The point for the N 1/16 sec. cor. of secs. 13 and 14.</p> <hr/> <p>From the C-E-W 1/64 sec. cor. of sec. 13.</p> <p>N. 0°12'30" E., on the N-S center line of the SE1/4 of the NW1/4 of sec. 13.</p> <p>Across rolling land covered with scattered juniper, pinon pine, sagebrush and bunchgrass.</p>
<p>20.708</p>	<p>The C-E-NW 1/64 sec. cor. of sec. 13.</p> <hr/> <p style="text-align: center;">METES-AND-BOUNDS SURVEY IN SECTION 13, T. 15 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">MEMORANDUM</p> <p>The following metes-and-bounds survey identifies certain irregular boundaries of Parcel 2 of the Ely Shoshone Expansion in T. 15 N., R. 63 E., Mount Diablo Meridian, as described in the White Pine County Conservation, Recreation and Development Act of 2006.</p> <p>The southern boundary of Parcel 2 is defined as the northerly right-of-way line of an unimproved dirt road, a reserved right-of-way granted under Bureau of Land Management Serial No. N-7743. This was converted to a section 507 FLPMA right-of-way reservation on March 10, 1998. The northerly right-of-way line of the unimproved dirt road (N-7743) is a line parallel to and 30 feet northerly of the apparent centerline of the existing road.</p> <p>Witness points were established at intersections marking the beginning and terminus of the metes-and-bounds survey. Angle points were established where there was a change in alignment.</p> <hr/>

METES-AND-BOUNDS SURVEY IN SECTION 13,
T. 15 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p> <p>8.002</p> <p>9.367</p> <p>2.50</p> <p>2.60</p> <p>5.623</p>	<p>N. 36°31'00" E., on line 2-3, along the northerly right-of-way line.</p> <p>Continue across gentle NE. slope covered with sagebrush and bunchgrass.</p> <p>Point for Angle Point No. 3, sec. 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15N R63E AP3 / S13 2007</p> <p>Set steel sign post alongside the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 50°06'30" E., on line 3-4, along the northerly right-of-way line.</p> <p>Point for Angle Point No. 4, sec. 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15N R63E AP4 / S13 2007</p> <p>Set steel sign post alongside the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 60°45'40" E., on line 4-5, along the northerly right-of-way line.</p> <p>Center of road, 15 lks. wide, parallels powerline.</p> <p>Powerline, bears S. 29° E. and N. 29° W.</p> <p>Point for Angle Point No. 5, sec. 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
--	--

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Lance A. Barney	Cadastral Surveyor
Dale A. Graff	Cadastral Surveyor
Michelle E. Martin	Supervisory Range Technician
Douglas E. Crawford	Surveying Technician
Phillip B. Hunt	Surveying Technician
Christopher O. Oloruntola	Surveying Technician
Nathan P. Trapp	Surveying Technician
Ryan T. Spreeman	Survey Aid

CERTIFICATE OF SURVEY

We, Wayne S. Hancock, Cadastral Surveyor, and Mark G. Petrosine, Surveying Technician, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 9th day of February, 2007, we have dependently resurveyed a portion of the subdivisional lines, subdivided section 13, and surveyed by metes-and-bounds in section 13, Township 15 North, Range 63 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

December 20, 2007

(Date)

Wayne S. Hancock
(Cadastral Surveyor)

January 10, 2008

(Date)

Mark G. Petrosine
(Surveying Technician)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of the dependent resurvey of a portion of the subdivisional lines, the subdivision of section 13, and a metes-and-bounds survey in section 13, Township 15 North, Range 63 East, Mount Diablo Meridian, Nevada, executed by Wayne S. Hancock, Cadastral Surveyor and Mark G. Petrosine, Surveying Technician, having been critically examined and found correct, are hereby approved.

January 15, 2008

(Date)

David P. Moran
(Chief Cadastral Surveyor, Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 15 N., R. 63 E., Mount Diablo Meridian, Nevada, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor, Nevada)~~