

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

A PORTION OF THE SUBDIVISIONAL LINES,
THE SUBDIVISION OF CERTAIN SECTIONS,
THE METES-AND-BOUNDS SURVEY OF U.S. HIGHWAY NOS. 6, 50 AND 93
THROUGH PORTIONS OF SECTIONS 26 AND 35,

AND

METES-AND-BOUNDS SURVEYS IN CERTAIN SECTIONS,
TOWNSHIP 16 NORTH, RANGE 63 EAST,
OF THE MOUNT DIABLO MERIDIAN,
IN THE STATE OF NEVADA

EXECUTED BY

Wayne S. Hancock, Cadastral Surveyor
Mark G. Petrosine, Surveying Technician

Under Special Instructions dated February 21, 2007,
and approved February 21, 2007,
which provided for the surveys included under Group No. 847,
and Assignment Instructions dated February 21, 2007.

Survey commenced February 27, 2007

Survey completed November 2, 2007

INDEX DIAGRAM

TOWNSHIP 16 NORTH, RANGE 63 EAST, MOUNT DIABLO MERIDIAN, NEVADA

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23 4	24
30	29	28	27 5	26 3 3	25
31	32	33	34	2 35	2 36

Subdivision of Section 25 pp. 6 - 8.
 Subdivision of Section 26 pp. 8 - 11.
 Subdivision of Section 27 pp. 11 - 17.
 Subdivision of Section 34 pp. 18 - 20.
 Subdivision of Section 35 pp. 20 - 25.
 Subdivision of Section 36 pp. 26 - 27.
 Metes-and-Bounds Survey of U.S. Highway Nos. 6, 50 and 53
 through portions of Sections 26 and 35 ... pp. 27 - 31.
 Metes-and Bounds Survey in Section 26 pp. 31 - 32.
 Metes-and Bounds Survey in Section 27 pp. 32 - 33.
 Metes-and Bounds Survey in Section 34 p. 33.
 Metes-and Bounds Survey in Section 35 pp. 34 - 35.
 Metes-and Bounds Survey in Section 36 p. 35.

TOWNSHIP 16 NORTH, RANGE 63 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines, the subdivision of certain sections, the metes-and-bounds survey of U.S. Highway Nos. 6, 50 and 93 through portions of sections 26 and 35, and metes-and-bounds surveys in certain sections, Township 16 North, Range 63 East, Mount Diablo Meridian, Nevada.

The south boundary (Third Standard Parallel North) was surveyed by Deputy Surveyors E.B. Monroe and A.G. Bateman in 1871 under Contract No. 44. The east boundary, a portion of the north boundary and a portion of the subdivisional lines were surveyed by Deputy Surveyors E.B. Monroe and A.G. Bateman in 1872 under Contract No. 48. The west boundary, a portion of the north boundary and a portion of the subdivisional lines were surveyed by Deputy Surveyor W.N. McGill in 1878 under Contract No. 80. A portion of the south boundary (Third Standard Parallel North), a portion of the east boundary, a portion of the subdivisional lines, and Mineral Survey No. 3458 were dependently resurveyed and Tract 37 was surveyed by Cadastral Surveyors H.G. Parker and R.A. Pratt in 1967 under Group No. 446. Section 22 was subdivided and Parcel A was surveyed by Cadastral Surveyor L.A. Walter in 1978 under Group No. 559. The history of other former surveys remote to the area of this survey are omitted.

Before restoring the corners, the lines of prior surveys were retraced and a diligent search made for all corners and other calls of record.

In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 847, dated February 21, 2007.

The metes-and-bounds surveys included herein identify certain boundaries of Parcel 1 of the Ely Shoshone Expansion in T. 16 N., R. 63 E., Mount Diablo Meridian, as described in the White Pine County Conservation, Recreation and Development Act of 2006.

Measurements were made with Trimble 4700, 5700 and 5800 Global Positioning System(GPS) receivers using the real-time kinematic method and refer to the true meridian based on geodetic methods. The mean bearings of the lines and horizontal equivalents of ground distances only are entered in the field notes.

The NAD 83(CORS 96) geographic position of the 1/4 section corner of section 36, on the S. bdy. of the Tp., determined from Global Positioning System(GPS) static observations processed by National Geodetic Survey, Online Positioning User Service(OPUS), utilizing Continuously Operating Reference Stations (CORS) "ECHO_BRGN_NV1999 CORS ARP", "EGAN_BRGN_NV1996 CORS ARP" and "RAILROAD VALLEY CORS ARP", in 2007 and carried forward by real time kinematic(RTK) observations, is as follows:

Latitude: 39°12'05.562" N. Longitude: 114°49'59.043" W.

The February 27, 2007, mean magnetic declination was determined to be 13°20' E. from the National Oceanic and Atmospheric Administration's National Geophysical Data Center declination calculator.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 16 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Reestablishment of a Portion of the Survey Executed by E.B. Monroe and A.G. Bateman, U.S. Deputy Surveyors, in 1872, and a Portion of the Dependent Resurvey by H.G. Parker and R.A. Pratt, Cadastral Surveyors, in 1967</p>
	<p>Beginning at the 1/4 sec. cor. of secs. 35 and 36, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, in a collar of stone, 2 ft. base, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 16 N., R. 63 E., executed under Group No. 446, with a steel fence post, projecting 3 1/2 ft. above the ground, SE. of cor.</p>
	<p>N. 0°13'30" W., bet. secs. 35 and 36.</p>
	<p>Across gentle NE. slope, through scattered undergrowth.</p>
1.515	<p>Point for a witness point at the intersection of a line parallel to and 100 ft. northerly of the E-W center line of sec. 35 with the line bet. secs. 35 and 36, hereinafter described. The monument for this witness point also occupies the position for a witness point at the intersection of a line parallel to and 100 ft. northerly of the E-W center line of sec. 36 with the line bet. secs. 35 and 36, also hereinafter described.</p>
19.797	<p>The N 1/16 sec. cor. of secs. 35 and 36, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above the ground, in a collar of stone, 2 ft. base, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 16 N., R. 63 E., executed under Group No. 446.</p>
	<p>From the 1/4 sec. cor. of secs. 34 and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 16 N., R. 63 E., executed under Group No. 446.</p> <p>N. 0°23'20" W., bet. secs. 34 and 35.</p> <p>Across gentle NE. slope, through scattered juniper and undergrowth.</p>
1.515	<p>Point for a witness point at the intersection of a line parallel to and 100 ft. northerly of the E-W center line of sec. 34, with the line bet. secs. 34 and 35, hereinafter described. The monument for this witness point also occupies the position for a witness point at the intersection of a line parallel to and 100 ft. northerly of the E-W center line of sec. 35, with the line bet. secs. 34 and 35, also hereinafter described.</p>
19.696	<p>The N 1/16 sec. cor. of secs. 34 and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above the ground, in a mound of stone, 5 ft. base, 1/2 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 16 N., R. 63 E., executed under Group No. 446, with a steel fence post, projecting 4 ft. above the ground, W. of cor.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 16 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the 1/4 sec. cor. of secs. 26 and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 16 N., R. 63 E., executed under Group No. 446, with a mound of stone, 2 ft. base, 1/2 ft. high, W. of cor.</p> <p>S. 89°41'30" W., bet. secs. 26 and 35.</p> <p>Across rolling land, through scattered junipers, sagebrush and bunchgrass, along the N. side of a developed lot.</p>
10.697	<p>Point for a witness point at the intersection of the centerline of U.S. Highway Nos. 6, 50 and 93, with the line bet. secs. 26 and 35, hereinafter described.</p> <p>Continue across rolling land, through scattered junipers, sagebrush and bunchgrass.</p>
20.105	<p>The W 1/16 sec. cor. of secs. 26 and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, in a collar of stone, 2 ft. base, to top, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 16 N., R. 63 E., executed under Group No. 446, with a rebar, 5/8 in. diam., projecting 3 ft. above the ground, W. of cor.</p> <hr/> <p>S. 89°43'00" W., beginning new measurement.</p>
1.37	<p>From this point, a power pole bears S., 0.07 chs. dist., from which powerlines extend SSE. and W.</p> <p>Continue along powerline.</p>
10.040	<p>Point for the W-W 1/64 sec. cor. of secs. 26 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S26 W-W 1/64 S35 2007</p> <p>Set a steel sign post alongside the stainless steel post.</p>
20.080	<p>The cor. of secs. 26, 27, 34 and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 16 N., R. 63 E., executed under Group No. 446, with a mound of stone, 2 1/2 ft. base, 1/2 ft. high, W. of cor.</p> <hr/> <p>From the S 1/16 sec. cor. of secs. 26 and 27, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 16 N., R. 63 E., executed under Group No. 446, with a mound of stone, 3 1/2 ft. base, 1 ft. high, W. of cor.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 16 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°13'30" W., bet. secs. 26 and 27.
	Across rolling land, through scattered junipers and sagebrush and bunchgrass.
4.833	Point for a witness point at the intersection of a metes-and-bounds survey in sec. 26 with the line bet. secs. 26 and 27, identical with the intersection of a metes-and-bounds survey in sec. 27 with the line bet. secs. 26 and 27, hereinafter described.
10.50	Center of graded dirt road, 50 lks. wide, bears NE. and SW.
19.768	The 1/4 sec. cor. of secs. 26 and 27, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 16 N., R. 63 E., executed under Group No. 446, with a mound of stone, 3 ft. base, 1 ft. high, W. of cor.
MEMORANDUM	
<p>The 1967 resurvey by Parker and Pratt found no original evidence at the 1/4 sec. cor. of secs. 23 and 26 and established monuments on the line bet. secs. 23 and 26 at the 1/4, E 1/16 and W 1/16 sec. cors. These monuments are found to have been placed in error and outside the closure limits that were in effect at the time the monuments were established. These monuments have since been utilized by local landowners to further identify patented lands in the south half of sec. 23, which are good faith locations and which bona fide rights have been vested. Local private surveyors have also since relied on the positions of the monuments during the course of their surveys. Based on the fact that the error was in the latitudinal direction, which would not affect the position of the existing center 1/4 sec. cor. of sec. 23, the patents issued prior to the 1967 dependent resurvey in the north half of sec. 23 are not adversely affected by the 1967 positions. By acceptance of the Parker and Pratt locations, this survey also maintains locally accepted property corners, protecting the issued patents in the south half of sec. 23.</p>	
<p>From the cor. of secs. 23, 24, 25 and 26, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 9 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 16 N., R. 63 E., executed under Group No. 446, with a mound of stone, 3 ft. base, 1 ft. high, W. of cor.</p>	
<p>N. 89°27'50" W., bet. secs. 23 and 26.</p> <p>Across rolling land, covered with sagebrush and bunchgrass.</p>	
20.075	The E 1/16 sec. cor. of secs. 23 and 26, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 16 N., R. 63 E., executed under Group No. 446, with a mound of stone, 2 ft. base, 1/2 ft. high, N. of cor.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 16 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 89°27'40" W., beginning new measurement.
20.087	The 1/4 sec. cor. of secs. 23 and 26, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 16 N., R. 63 E., executed under Group No. 446, with a mound of stone, 2 1/2 ft. base, 1 ft. high, N. of cor.
20.082	<p>N. 89°28'20" W., beginning new measurement.</p> <p>The W 1/16 sec. cor. of secs. 23 and 26, perpetuated by Barry A. Fitzpatrick, Nevada Professional Land Surveyor No. 7809, monumented with a rebar, 24 ins. long, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, in a scattered mound of stone, with plastic cap mkd. LUMOS&ASSOC PLS 809 remaining, as shown on County Map No. 585, recorded in White Pine County, Nevada as File No. 296689. This monument is accepted as a careful and faithful perpetuation of the 1967 position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{r} \text{W } 1/16 \text{ } \frac{\text{S23}}{\text{S26}} \\ \text{2007} \end{array}$ </div> <p>Deposit rebar inside and set a steel sign post alongside the stainless steel post.</p>
20.107	<p>S. 86°29'30" W., beginning new measurement.</p> <p>The cor. of secs. 22, 23, 26 and 27, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 9 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 16 N., R. 63 E., executed under Group No. 446, with a mound of stone, 3 ft. base, 1/2 ft. high, W. of cor.</p>
10.062	<p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>N. 89°31'00" W., bet. secs. 27 and 34.</p> <p>Across rolling land, through scattered junipers, sagebrush, and bunchgrass, and along N. side of a powerline.</p>
10.062	<p>Point for the E-E 1/64 sec. cor. of secs. 27 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 16 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>S27 E-E 1/64 S34 2007</p>
	<p>Set a steel sign post alongside the stainless steel post.</p>
20.124	<p>The E 1/16 sec. cor. of secs. 27 and 34, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 11 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 16 N., R. 63 E., executed under Group No. 446, with a mound of stone, 2 1/2 ft. base, 1/2 ft. high, N. of cor.</p>
	<hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 25, T. 16 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 25 and 36, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 16 N., R. 63 E., executed under Group No. 446, with a mound of stone, 2 ft. base, 1 ft. high, N. of cor.</p>
	<p>N. 0°34'40" W., on the N-S center line of sec. 25.</p>
	<p>Across rolling land, through scattered undergrowth.</p>
12.90	<p>Center of graded dirt road, 15 lks. wide, bears NW. and SE.</p>
15.41	<p>From this point, the cor. of barbed wire fences extending N. and SE. bears E., 0.21 chs. dist. Continue along fence line.</p>
19.922	<p>Point for the C-S 1/16 sec. cor. of sec. 25. POINT NOT MONUMENTED</p>
28.19	<p>From this point, the cor. of barbed wire fences extending NW. and S. bears W., 0.05 chs. dist. Leave fence line and continue along W. side of level grasslands.</p>
39.844	<p>Point for the center 1/4 sec. cor. of sec. 25, at intersection with the E-W center line. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T16N R63E C 1/4 S25 2007</p>
	<p>Set a steel sign post alongside the stainless steel post.</p>

SUBDIVISION OF SECTION 25,
T. 16 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
79.696	<p>The 1/4 sec. cor. of secs. 24 and 25, monumented with an iron post, 28 ins. long, 2 1/2 ins. diam., loosely set flush with the surface of the ground, leaning at an angle, in a submerged stone base, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 16 N., R. 63 E., executed under Group No. 446. Accepted base of iron post as the best available evidence of the position of the 1967 corner.</p> <p>At the corner point</p> <p>Reset the iron post 26 ins. in the ground, over a plastic-encased magnet, and in a supporting collar of stone, 2 ft. base, submerged below the surface of the ground. Add the marks 2007 to the brass cap.</p> <p>Set a steel fence post alongside the stainless steel post.</p>
	<hr/> <p>From the 1/4 sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the E. bdy. of T. 16 N., R. 63 E., executed under Group No. 446.</p> <p>S. 89°21'10" W., on the E-W center line of sec. 25.</p> <p>Across open grassland.</p>
38.90	<p>Irrigation ditch, 10 lks. wide, 2 ft. deep, drains NE.</p> <p>Enter scattered undergrowth and ascend gentle E. slope.</p>
40.637	<p>The center 1/4 sec. cor. of sec. 25.</p>
45.17	<p>Barbed wire fence, bears NW. and SE.</p>
46.65	<p>Center of dirt road, 15 lks. wide, parallels fence line.</p>
60.703	<p>Point for the C-W 1/16 sec. cor. of sec. 25.</p> <p>POINT NOT MONUMENTED</p>
80.769	<hr/> <p>The 1/4 sec. cor. of secs. 25 and 26, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 9 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 16 N., R. 63 E., executed under Group No. 446, with a mound of stone, 3 ft. base, 1 ft. high, W. of cor.</p> <hr/> <p>From the W 1/16 sec. cor. of secs. 25 and 36, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 16 N., R. 63 E., executed under Group No. 446, with a mound of stone, 3 ft. base, 1/2 ft. high, N. of cor.</p> <p>N. 0°28'00" W., on the N-S center line of the SW1/4 of sec. 25.</p>

SUBDIVISION OF SECTION 25,
T. 16 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Across rolling land, through scattered sagebrush and bunchgrass.</p>
19.876	<p>Point for the SW 1/16 sec. cor. of sec. 25, at intersection with the E-W center line of the SW1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SW 1/16 S25</p> <p style="text-align: center;">2007</p> <p>Set a steel sign post alongside the stainless steel post.</p>
39.750	<p>The point for the C-W 1/16 sec. cor. of sec. 25.</p> <hr/> <p>From the point for the C-S 1/16 sec. cor. of sec. 25.</p> <p>S. 89°29'10" W., on the E-W center line of the SW1/4 of sec. 25.</p> <p>Across rolling land, through scattered sagebrush and bunchgrass.</p>
1.50	<p>Center of graded dirt road, 15 lks. wide, bears NNW. and SSE.</p>
20.105	<p>The SW 1/16 sec. cor. of sec. 25.</p>
40.220	<p>The S 1/16 sec. cor. of secs. 25 and 26, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 16 N., R. 63 E., executed under Group No. 446, with a mound of stone, 3 1/2 ft. base, 1 ft. high, W. of cor.</p> <hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 26, T. 16 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 26 and 35.</p> <p>N. 0°11'40" W., on the N-S center line of sec. 26.</p> <p>Across rolling land, through scattered sagebrush and bunchgrass.</p>
19.793	<p>Point for the C-S 1/16 sec. cor. of sec. 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">C S 1/16 S26 C</p> <p style="text-align: center;">2007</p> <p>Set a steel sign post alongside the stainless steel post.</p>


SUBDIVISION OF SECTION 26,
T. 16 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	From this point, a rebar of unknown origin, 5/8 in. diam., firmly set, projecting 9 ins. above the ground, bears N. 12°31' E., 0.263 chs. dist. This position is not utilized in the course of this survey.
24.30	Ravine, drains NE.
39.586	Point for the center 1/4 sec. cor. of sec. 26, at intersection with the E-W center line. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 1 ft. base, with brass cap mkd. T16N R63E C 1/4 S26 2007 Set a steel sign post alongside the stainless steel post.
49.55	Center of graded dirt road, 15 lks. wide, bears NW. and SE.
56.65	Center of graded dirt road, 15 lks. wide, bears NE. and SW.
79.909	The 1/4 sec. cor. of secs. 23 and 26. <hr/>
	From the 1/4 sec. cor. of secs. 25 and 26. S. 89°37'30" W., on the E-W center line of sec. 26. Across rolling land, through scattered sagebrush and bunchgrass.
32.55	Center of graded dirt road, 15 lks. wide, bears NW. and SE.
40.099	The center 1/4 sec. cor. of sec. 26.
60.183	Point for the C-W 1/16 sec. cor. of sec. 26. POINT NOT MONUMENTED
67.592	Point for a witness point at the intersection of the centerline of U.S. Highway Nos. 6, 50 and 93, with the E-W center line of sec. 26, hereinafter described.
80.267	The 1/4 sec. cor. of secs. 26 and 27. <hr/>
	From the W 1/16 sec. cor. of secs. 26 and 35. N. 0°10'00" W., on the N-S center line of the SW1/4 of sec. 26. Across rolling land, through scattered undergrowth.
13.220	Point for a witness point at the intersection of a metes-and-bounds survey in sec. 26, with the N-S center line of the SW1/4 of sec. 26, hereinafter described.
19.782	Point for the SW 1/16 sec. cor. of sec. 26, at intersection with the E-W center line of the SW1/4.

SUBDIVISION OF SECTION 26,
T. 16 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SW 1/16 S26</p> <p style="text-align: center;">2007</p> <p>Set a steel sign post alongside the stainless steel post.</p> <p>21.216 Point for a witness point at the intersection of the centerline of U.S. Highway Nos. 6, 50 and 93, with the N-S center line of the SW1/4 of sec. 26, hereinafter described.</p> <p>39.562 The point for the C-W 1/16 sec. cor. of sec. 26.</p> <hr/> <p>From the C-S 1/16 sec. cor. of sec. 26.</p> <p>S. 89°39'30" W., on the E-W center line of the SW1/4 of sec. 26.</p> <p>Across rolling land, through scattered undergrowth.</p> <p>19.515 Point for a witness point at the intersection of the centerline of U.S. Highway Nos. 6, 50 and 93, with the E-W center line of the SW1/4 of sec. 26, hereinafter described.</p> <p>20.094 The SW 1/16 sec. cor. of sec. 26.</p> <p>30.126 Point for the C-W-SW 1/64 sec. cor. of sec. 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S26 C-W-SW 1/64</p> <p style="text-align: center;">2007</p> <p>Set a steel sign post alongside the stainless steel post.</p> <p>40.158 The S 1/16 sec. cor. of secs. 26 and 27.</p> <hr/> <p>From the W-W 1/64 sec. cor. of secs. 26 and 35.</p> <p>N. 0°08'50" W., on the N-S center line of the SW1/4 of the SW1/4 of sec. 26.</p> <p>Across rolling land, through scattered sagebrush and bunchgrass.</p> <p>7.485 Point for a witness point at the intersection of a metes-and-bounds survey in sec. 26, with the N-S center line of the SW1/4 of sec. 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
--------	---

SUBDIVISION OF SECTION 26,
T. 16 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	 <p>2007</p>
19.771	<p>The C-W-SW 1/64 sec. cor. of sec. 26.</p>
<p>SUBDIVISION OF SECTION 27, T. 16 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA</p>	
<p>MEMORANDUM</p>	
<p>In 1990, Richard E. Fonger, Nevada Professional Land Surveyor No. 4235, established positions and set monuments relevant to the boundary of the SE1/4 of sec. 27, as shown on County Map No. 358, recorded in White Pine County, Nevada as File No. 265429. These positions are accepted as careful and faithful determinations. Subsequent positions established at locations differing from the Fonger survey are not utilized in the course of this survey.</p>	
<p>From the 1/4 sec. cor. of secs. 27 and 34, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 9 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 16 N., R. 63 E., executed under Group No. 446, with a steel fence post, projecting 4 ft. above the ground, SE. of the cor.</p> <p>Cor. is located on the SW. side of a steel fence post, from which wire fences, steel posts extend N. and E.</p> <p>N. 0°16'30" W., on the N-S center line of sec. 27.</p> <p>Across rolling land, through scattered junipers, sagebrush, and bunchgrass, along wire fence.</p>	
4.807	<p>A position established by Richard W. Forman, Nevada Professional Land Surveyor No. 2898, monumented with a rebar, 5/8 in. diam., firmly set, projecting 6 ins. above the ground, with plastic cap mkd. BFI R 98 remaining, as shown on County Map No. 819, recorded in White Pine County, Nevada, as File No. 320275.</p>
9.603	<p>From this point, a position established by Dean Neubauer, Nevada Professional Land Surveyor No. 9392, monumented with a steel fence post, firmly set, projecting 4 1/2 ft. above the ground, with attached brass tag, 3/4 in. diam., mkd. PLS 9392, as shown on County Map No. 419, recorded in White Pine County, Nevada, as File No. 278533, bears WEST, 0.009 chs. dist.</p>
14.424	<p>A rebar of unknown origin, 5/8 in. diam., firmly set, projecting 7 ins. above the ground.</p>
19.21	<p>From this point, a steel post from which wire fences, steel posts, extend E. and S., bears E., 0.006 chs. dist.</p>

SUBDIVISION OF SECTION 27,
T. 16 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
19.221	From this point, a position established by Dean Neubauer, Nevada Professional Land Surveyor No. 9392, monumented with a rebar, 5/8 in. diam., firmly set flush with the surface of the ground, with aluminum cap mkd. BFI T16N R63E C C S1/16 S27 1991 PLS 9392, bears WEST, 0.005 chs. dist. (Record: A fence post with PLS tag No. 9392, as shown on County Map No. 415, recorded in White Pine County, Nevada as File No. 278312).
19.225	Point for the C-S 1/16 sec. cor. of sec. 27. POINT NOT MONUMENTED
24.042	From this point, a position established by Richard W. Forman, Nevada Professional Land Surveyor No. 2898, monumented with a rebar, 5/8 in. diam., firmly set, projecting 4 ins. above the ground, with plastic cap mkd. RLS 2898, as shown on County Map No. 819, recorded in White Pine County, Nevada as File No. 320275, bears WEST, 0.009 chs. dist.
28.844	From this point, a position established by Richard W. Forman, Nevada Professional Land Surveyor No. 2898, monumented with a rebar, 5/8 in. diam., firmly set, projecting 4 ins. above the ground, with plastic cap mkd. RLS 2898 as shown on County Map No. 819, recorded in White Pine County, Nevada as File No. 320272, bears WEST, 0.010 chs. dist. From this same point, a fence cor. from which wire fences extend N. and E., bears E., 0.006 chs. dist.
36.85	Fence cor., from which woven wire fences extend NE. parallel with Pinon Pine Road, and also extend S.
37.55	Center of Pinon Pine Road, graded dirt surface, 40 lks. wide, bears NE. and SW.
38.450	The center 1/4 sec. cor. of sec. 27, determined at intersection of woven wire fences bearing N. and W. and occupied by a steel fence cor. post, 2 ins. diam. This position is harmoniously related to the position faithfully established by Richard E. Fonger, Nevada Professional Land Surveyor No. 4235, as shown on County Map No. 452, recorded in White Pine County as File No. 283651 and is accepted as the best available evidence of the Fonger position. from which A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground for a reference monument, bears S. 45°10' E., 6.1 lks. dist., with brass cap mkd. RM C 1/4 S27 4.0 FT TO COR 2007 and an arrow pointing to the cor. A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 44°31' W., 4.5 lks. dist., with brass cap mkd. RM C 1/4 S27 3.0 FT TO COR 2007 and an arrow pointing to the cor. From this point, a position established by Dean Neubauer, Nevada Professional Land Surveyor No. 9392, monumented with a rebar, 5/8 in. diam., firmly set flush with the surface of the ground, with aluminum cap mkd. BFI T16N R63E C1/4 S27 1991 PLS 9392,

SUBDIVISION OF SECTION 27,
T. 16 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>bears S. 82°39' W., 0.007 chs. dist. (Record: A fence post with PLS Tag No. 9392, as shown on County Map No. 419, recorded in White Pine County, Nevada as File No. 278533.) This position is not utilized during the course of this survey.</p> <hr/> <p>N. 0°15'00" W., beginning new measurement.</p> <p>Continue along fence.</p>
4.80	Cor. of woven wire fences bearing N., E., and S.
7.234	From this point, a position established by Dean Neubauer, Nevada Professional Land Surveyor No. 9392, monumented with a rebar, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with plastic cap mkd. BFI PLS 9392, bears WEST, 0.010 chs. dist., as shown on County Map No. 468, recorded in White Pine County, Nevada as File No. 286342.
9.611	The C-S-N 1/64 sec. cor. of sec. 27, determined by Richard E. Fonger, Nevada Professional Land Surveyor No. 4235, monumented with a rebar, 5/8 in. diam., firmly set, projecting 5 ins. above the ground, with plastic cap mkd. FONGER SURVEY RLS 4235, as shown on County Map No. 452, recorded in White Pine County, Nevada as File No. 283657. This is accepted as a careful and faithful determination of the position of the corner.
	<hr/> <p>N. 0°17'30" W., beginning new measurement.</p>
9.61	From this point, a steel fence cor. post, 2 ins. diam., from which wire fences extend E. and S., bears W., 0.005 chs. dist.
27.307	A position established by Dean Neubauer, Nevada Professional Land Surveyor No. 9392, monumented with a rebar, 5/8 in. diam., firmly set, projecting 1 in. above the ground, with damaged plastic cap, no marks remaining, as shown on County Map No. 491, recorded in White Pine County, Nevada as File No. 288276.
28.822	The 1/4 sec. cor. of secs. 22 and 27, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 16 N., R. 63 E., executed under Group No. 446, with a steel fence post, projecting 3 ft. above the ground, SE. of the corner.
	<hr/> <p>From the 1/4 sec. cor. of secs. 26 and 27.</p> <p>S. 88°57'50" W., on the E-W center line of sec. 27.</p> <p>Across rolling land, through scattered junipers sagebrush and bunchgrass.</p>
10.080	The C-E-E 1/64 sec. cor. of sec. 27, determined by Richard E. Fonger, Nevada Professional Land Surveyor No. 4235, monumented with a rebar, 18 ins. long, 5/8 in. diam., firmly set, projecting 1 in. above the ground, with plastic cap mkd. FONGER SURVEY RLS 4235, as shown on County Map No. 357, recorded in White Pine County, Nevada as File No. 265284. This is accepted as a careful and faithful determination of the position of the corner.

SUBDIVISION OF SECTION 27,
T. 16 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	S. 88°57'10" W., beginning new measurement.
9.631	From this point, a position established by Dean Neubauer, Nevada Professional Land Surveyor No. 9392, monumented with a steel fence post, projecting 3 ft. above the ground, with attached brass tag, 3/4 in. diam., mkd. PLS 9392, bears SOUTH, 0.004 chs. dist., as shown on County Map No. 420, recorded in White Pine County, Nevada as File No. 278534.
10.086	From this point, a position established by Dean Neubauer, Nevada Professional Land Surveyor No. 9392, monumented with a steel fence post, projecting 3 ft. above the ground, with attached brass tag, 3/4 in. diam., mkd. PLS 9392, bears SOUTH, 0.006 chs. dist., as shown on County Map No. 420, recorded in White Pine County, Nevada as File No. 278534.
10.25	Center of graded dirt road, 30 lks. wide, bears N. and S.
10.46	From this point, a power pole bears S., 0.06 chs. dist., from which powerlines extend S. and W. Continue along powerline.
10.55	From this point, a wood fence cor. post bears S., 0.01 chs. dist., from which wire fences extend S. and W. Continue along fence line.
16.40	Wooden cor. post, from which wire fences extend E. parallel with Pinon Pine Road and also extend SW.,
17.75	Pinon Pine Road, graded dirt surface, 40 lks. wide, bears NE. and SW.
20.159	The center 1/4 sec. cor. of sec. 27. _____
	S. 88°57'30" W., beginning new measurement. Continue along woven wire fence.
20.155	From this point, a position established by Richard W. Forman, Nevada Professional Land Surveyor No. 2898, monumented with a rebar, 5/8 in. diam., firmly set, projecting 6 ins. above the ground, with damaged plastic cap, the marks BFI RL 892 remaining, bears SOUTH, 0.012 chs. dist., as shown on County Map No. 789, recorded in White Pine County, Nevada as File No. 317969.
20.16	The W. end of woven wire fence.
40.295	The 1/4 sec. cor. of secs. 27 and 28, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 16 N., R. 63 E., executed under Group No. 446, with a mound of stone, 3 ft. base, 1/2 ft. high, W. of cor. _____
	From the E 1/16 sec. cor. of secs. 27 and 34. N. 0°14'00" W., on the N-S center line of the SE1/4 of sec. 27.

SUBDIVISION OF SECTION 27,
T. 16 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Across rolling land, through scattered junipers, pinon pine, sagebrush and bunchgrass.
9.748	From this point, a position established by Dean Neubauer, Nevada Professional Land Surveyor No. 9392, monumented with a steel fence post, firmly set, projecting 4 ft. above the ground, with attached brass tag, 3/4 in. diam., mkd. PLS 9392, bears WEST, 0.006 chs. dist., as shown on County Map No. 415, recorded in White Pine County, Nevada as File No. 278312.
19.496	<p>Point for the SE 1/16 sec. cor. of sec. 27, at intersection with the E-W center line of the SE1/4.</p> <p>Set a copper coated steel rod, 24 ins. long, 1/2 in. diam., 9 ins. below the surface of a graded dirt road, with brass cap, 1 1/2 ins. diam., mkd.</p> <p style="text-align: center;">BLM SE 1/16 S27 2007</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 20 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 45°27' E., 85.8 lks. dist., with brass cap mkd. RM SE 1/16 S27 56.6 FT TO COR 2007 and an arrow pointing to the cor. Set a steel sign post alongside the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 46°20' E., 87.9 lks. dist., with brass cap mkd. RM SE 1/16 S27 58.0 FT TO COR 2007 and an arrow pointing to the cor. Set a steel sign post alongside the stainless steel post.</p> <p>Cor. is located in the center of a graded dirt road, 50 lks. wide, bears E. and W.</p>
24.372	From this point, a position established by Dean Neubauer, Nevada Professional Land Surveyor No. 9392, monumented with a steel fence post, firmly set, projecting 4 ft. above the ground, with attached brass tag, 3/4 in. diam., mkd. PLS 9392, bears WEST, 0.005 chs. dist. as shown on County Map No. 417, recorded in White Pine County, Nevada as File No. 278392.
29.247	From this point, a position established by Dean Neubauer, Nevada Professional Land Surveyor No. 9392, monumented with a steel fence post, firmly set, projecting 4 ft. above the ground, with attached brass tag, 3/4 in. diam., mkd. PLS 9392, bears WEST, 0.006 chs. dist., as shown on County Map No. 417, recorded in White Pine County, Nevada as File No. 278392. This position is not utilized during the course of this survey.
38.993	The C-E 1/16 sec. cor. of sec. 27.

SUBDIVISION OF SECTION 27,
T. 16 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the S 1/16 sec. cor. of secs. 26 and 27.</p> <p>S. 89°43'40" W., on the E-W center line of the SE1/4 of sec. 27.</p> <p>Across rolling land, through scattered junipers and undergrowth.</p>
8.459	<p>Point for a witness point at the intersection of a metes-and-bounds survey in sec. 27, with the E-W center line of the SE1/4 of sec. 27, hereinafter described.</p>
10.079	<p>Point for the C-E-SE 1/64 sec. cor. of sec. 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S27 C-E-SE 1/64</p> <p style="text-align: center;">2007</p> <p>Set a steel sign post alongside the stainless steel post.</p>
17.40	<p>Intersect curve in center of graded dirt road, 50 lks. wide, bears W. and curves NE., continue along graded dirt road.</p>
20.158	<p>The SE 1/16 sec. cor. of sec. 27.</p>
40.300	<p>The point for the C-S 1/16 sec. cor. of sec. 27.</p> <hr/> <p>From the E-E 1/64 sec. cor. of secs. 27 and 34.</p> <p>N. 0°10'40" W., on the N-S center line of the SE1/4 of the SE1/4 of sec. 27.</p>
18.703	<p>Point for a witness point at the intersection of a metes-and-bounds survey in sec. 27, with the N-S center line of the SE1/4 of the SE1/4 of sec. 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">WP E-E S 27 E-E</p> <p style="text-align: center;">2007</p> <p>Set a steel sign post alongside the stainless steel post.</p>
19.629	<p>The C-E-SE 1/64 sec. cor. of sec. 27.</p> <hr/>

SUBDIVISION OF SECTION 34,
T. 16 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From the standard 1/4 sec. cor. of sec. 34, on the S. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the Third Standard Parallel North, T. 16 N., R. 63 E., executed under Group No. 446, with a mound of stone, 2 ft. base, 1 ft. high, N., the original cedar post with illegible scribe marks lying alongside, and a steel fence post, projecting 2 ft. above the ground, E. of cor.</p> <p>N. 0°22'10" W., on the N-S center line of sec. 34.</p> <p>Across rolling land, through scattered pinon pine, juniper, sagebrush and bunchgrass.</p>
16.48	Powerline, bears S. 29° E. and N. 29° W.
36.40	Center of dirt road, 10 lks. wide, bears NE. and SW.
39.411	<p>Point for the center 1/4 sec. cor. of sec. 34, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T16N R63E C 1/4 S34</p> <p style="text-align: center;">2007</p>
59.110	<p>Set a steel sign post alongside the stainless steel post.</p> <p>Point for the C-N 1/16 sec. cor. of sec. 34.</p> <p>POINT NOT MONUMENTED</p>
75.65	Center of dirt road, 10 lks. wide, bears NE. and SW.
78.809	The 1/4 sec. cor. of secs. 27 and 34.
10.070	<hr/> <p>From the 1/4 sec. cor. of secs. 34 and 35.</p> <p>N. 89°31'50" W., on the E-W center line of sec. 34.</p> <p>Across rolling land, through scattered pinon pine, juniper, sagebrush and bunchgrass.</p> <p>Point for the C-E-E 1/64 sec. cor. of sec. 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 2 ft. base, with brass cap mkd.</p> <p style="text-align: center;">E-E 1/64 C—C S34</p> <p style="text-align: center;">2007</p> <p>Set steel sign post alongside the stainless steel post.</p>

SUBDIVISION OF SECTION 34,
T. 16 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.140	Point for the C-E 1/16 sec. cor. of sec. 34. POINT NOT MONUMENTED
38.05	Ravine, drains NE.
38.30	Center of dirt road, 15 lks. wide, parallels ravine.
40.280	The center 1/4 sec. cor. of sec. 34.
52.66	Powerline, bears S. 29° E. and N. 29° W.
80.542	The 1/4 sec. cor. of secs. 33 and 34, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 16 N., R. 63 E., executed under Group No. 446, with a mound of stone, 2 1/2 ft. base, 1/2 ft. high, W. of cor.
	<hr/> From the point for the C-E 1/16 sec. cor. of sec. 34. N. 0°22'40" W., on the N-S center line of the NE1/4 of sec. 34. Across rolling land, through scattered pinon pine, juniper, sagebrush and bunchgrass.
19.698	Point for the NE 1/16 sec. cor. of sec. 34, at intersection with the E-W center line of the NE1/4. POINT NOT MONUMENTED
38.60	Powerline, bears N. 87° E. and S. 87° W.
39.390	The E 1/16 sec. cor. of secs. 27 and 34.
	<hr/> From the N 1/16 sec. cor. of secs. 34 and 35. N. 89°31'30" W., on the E-W center line of the NE1/4 of sec. 34. Across rolling land, through scattered pinon pine, juniper, sagebrush and bunchgrass.
10.067	Point for the C-E-NE 1/64 sec. cor. of sec. 34. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<p style="text-align: center;">S34 C-E-NE 1/64 2007</p>
	Set a steel sign post alongside the stainless steel post.

SUBDIVISION OF SECTION 34,
T. 16 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.134	The point for the NE 1/16 sec. cor. of sec. 34.
40.270	The point for the C-N 1/16 sec. cor. of sec. 34. <hr/>
	From the C-E-NE 1/64 sec. cor. of sec. 34. N. 0°23'30" W., on the N-S center line of the NE1/4 of the NE1/4 of sec. 34. Across rolling land, through scattered pinon pine, juniper, sagebrush and bunchgrass.
19.45	Powerline, bears N. 87° E. and S. 87° W.
19.691	The E-E 1/64 sec. cor. of secs. 27 and 34. <hr/>
	From the C-E-E 1/64 sec. cor. of sec. 34. N. 0°23'00" W., on the N-S center line of the SE1/4 of the NE1/4 of sec. 34. Across rolling land, through scattered pinon pine, juniper, sagebrush and bunchgrass.
1.515	Point for a witness point at the intersection of a line parallel to and 100 ft. northerly of the E-W center line of sec. 34, with the N-S center line of the SE1/4 of the NE1/4 of sec. 34, hereinafter described.
19.696	The C-E-NE 1/64 sec. cor. of sec. 34. <hr/>
	SUBDIVISION OF SECTION 35, T. 16 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA <hr/>
	From the standard 1/4 sec. cor. of sec. 35, on the S. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 13 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the Third Standard Parallel North, T. 16 N., R. 63 E., executed under Group No. 446, with a mound of stone, 2 ft. base, 1 ft. high, N. of cor. N. 0°19'10" W., on the N-S center line of sec. 35. Across gentle NE. slope covered with sagebrush and bunchgrass.
4.934	The C-S-S-S 1/256 sec. cor. of sec. 35, determined by Dean Neubauer, Nevada Professional Land Surveyor No. 9892, monumented with a rebar, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with aluminum cap, 1 1/2 ins. diam., mkd. PLS 9392 SUMMIT, as shown on County Map No. 971, recorded in White Pine County, Nevada as File No. 334013. This is accepted as a careful and faithful determination of the position of the corner. <hr/>

SUBDIVISION OF SECTION 35,
T. 16 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°19'10" W., beginning new measurement.
9.872	The C-N-S-S 1/256 sec. cor. of sec. 35, determined by Dean Neubauer, Nevada Professional Land Surveyor No. 9892, monumented with a rebar, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with aluminum cap, 1 1/2 ins. diam., mkd. PLS 9392 SUMMIT, with a steel post alongside, as shown on County Map No. 910, recorded in White Pine County, Nevada as File No. 331401. This is accepted as a careful and faithful determination of the position of the corner.

	N. 0°20'30" W., beginning new measurement.
4.935	The C-S 1/16 sec. cor. of sec. 35, determined by Dean Neubauer, Nevada Professional Land Surveyor No. 9392, monumented with a rebar, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with aluminum cap, 1 1/2 ins. diam., mkd. PLS 9392 SUMMIT, with a steel post alongside, as shown on County Map No. 910, recorded in White Pine County, Nevada as File No. 331401. This is accepted as a careful and faithful determination of the position of the corner.

	N. 0°20'30" W., beginning new measurement.
4.934	The C-S-N-S 1/256 sec. cor. of sec. 35, determined by Dean Neubauer, Nevada Professional Land Surveyor No. 9892, monumented with a rebar, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with aluminum cap, 1 1/2 ins. diam., mkd. PLS 9392 SUMMIT, as noted on County Map No. 553, recorded in White Pine County, Nevada as File No. 294649. (Record monument: Steel fence post with P.L.S. Tag No. 9392.)

	N. 0°19'30" W., beginning new measurement.
14.802	Point for the center 1/4 sec. cor. of sec. 35, at intersection with the E-W center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T16N R63E C 1/4 S35 2007
	Set a steel sign post alongside the stainless steel post.
15.25	Center of graded dirt road, 50 lks. wide, bears E. and W.
34.552	The C-N 1/16 sec. cor. of sec. 35, monumented with a rebar of unknown origin, 5/8 in. diam., firmly set, with top 12 ins. bent at an angle to the surface of the ground. Accepted vertical position at base of rebar as a careful and faithful determination of the corner point.

SUBDIVISION OF SECTION 35,
T. 16 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} C \\ N\ 1/16\ \ S35 \\ C \end{array}$ <p>2007</p> </div> <p>Deposit rebar alongside the stainless steel post.</p> <p>Cor. is located on the west shoulder of U.S. Highway Nos. 6, 50 and 93.</p> <hr/> <p>N. 0°19'20" W., beginning new measurement.</p>
0.991	Point for a witness point at the intersection of the centerline of U.S. Highway Nos. 6, 50 and 93, with the N-S center line of sec. 35, hereinafter described.
4.023	A position established by Richard W. Forman, Nevada Professional Land Surveyor No. 2898, monumented with a rebar, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with plastic cap mkd. BFI PLS 9392, as shown on the unrecorded survey map titled "Portion of the NE1/4 NW1/4, APN 10-420-82", dated August 19, 1998, on file with Smoke Signals in Ely, Nev.
19.739	The 1/4 sec. cor. of secs. 26 and 35.
	<hr/> <p>From the 1/4 sec. cor. of secs. 35 and 36.</p> <p>S. 89°50'50" W., on the E-W center line of sec. 35.</p>
4.563	A position established by Dean Neubauer, Nevada Professional Land Surveyor No. 9392, monumented with a steel fence post, firmly set, projecting 4 ft. above the ground, with attached brass tag, 3/4 in. diam., mkd. PLS 9392, as shown on County Map No. 535, recorded in White Pine County, Nevada as File No. 293594.
26.356	A position established by Dean Neubauer, Nevada Professional Land Surveyor No. 9392, monumented with a steel fence post, firmly set, projecting 4 ft. above the ground, with attached brass tag, 3/4 in. diam., mkd. PLS 9392, as shown on County Map No. 535, recorded in White Pine County, Nevada as File No. 293594.
28.108	Point for a witness point at the intersection of the centerline of U.S. Highway Nos. 6, 50 and 93, with the E-W center line of sec. 35, hereinafter described.
	Continue along the S. side of a graded dirt road, 50 lks. wide, bears W.
40.132	The center 1/4 sec. cor. of sec. 35.

SUBDIVISION OF SECTION 35,
T. 16 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
60.206	<p>The C-W 1/16 sec. cor. of sec. 35, determined by Dean Neubauer, Nevada Professional Land Surveyor No. 9392, monumented with a steel fence post, firmly set, projecting 4 ft. above the ground, with attached brass tag, 3/4 in. diam., mkd. PLS 9392, as shown on County Map No. 535, recorded in White Pine County, Nevada as File No. 293594. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> $\begin{array}{c} \text{W } 1/16 \\ \text{C} \text{---} \text{C} \\ \text{S35} \end{array}$ <p style="text-align: center;">2007</p> <p>Deposit brass tag inside stainless steel post and reset fence post alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°51'20" W., beginning new measurement.</p>
5.02	<p>From this point, the cor. of a vinyl rail fence bears S., 0.02 chs. dist., from which fences extend S. and W.</p> <p>Continue along N. side of fence.</p>
10.030	<p>Point for the C-W-W 1/64 sec. cor. of sec. 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> $\begin{array}{c} \text{W-W } 1/64 \\ \text{C} \text{---} \text{C} \\ \text{S35} \end{array}$ <p style="text-align: center;">2007</p> <p>Cor. is located 0.02 chs. N. of the cor. of a vinyl rail fence, from which fences extend S. and E.</p>
15.045	<p>The C-W-W-W 1/256 sec. cor. of sec. 35, determined by Richard W. Forman, Nevada Professional Land Surveyor No. 2898, monumented with a steel fence post, firmly set, projecting 4 ft. above the ground, with attached brass tag, 3/4 in. diam., mkd. RLS 2898, as shown on County Map No. 301, recorded in White Pine County, Nevada as File No. 241711. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

SUBDIVISION OF SECTION 35,
T. 16 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>W-W-W 1/256 C———C S35</p> <p>2007</p>
	<p>Deposit brass tag inside and reset fence post alongside the stainless steel post.</p> <hr/> <p>S. 89°51'20" W., beginning new measurement.</p>
0.40	<p>Center of graded dirt road, 40 lks. wide, bears S. and curves NE.</p> <p>Continue across rolling land, through scattered pinon pine, juniper, sagebrush and bunchgrass.</p>
5.019	<p>The 1/4 sec. cor. of secs. 34 and 35.</p> <hr/> <p>From the C-W 1/16 sec. cor. of sec. 35.</p> <p>N. 0°22'30" W., on the N-S center line of the NW1/4 of sec. 35.</p> <p>Across rolling land, through scattered pinon pine, juniper, sagebrush and bunchgrass.</p>
0.75	<p>Center of graded dirt road, 50 lks. wide, bears E. and W.</p>
19.728	<p>The NW 1/16 sec. cor. of sec. 35, monumented with a steel fence post of unknown origin, firmly set, twisted and bent to the surface of the ground, with a rebar, 5/8 in. diam., projecting 3 ft. above the ground, set alongside. Accepted vertical position of post as having been adopted by the adjacent landowner and this position is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over the lower portion of the steel fence post, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S35</p> <p style="text-align: center;">2007</p> <p>Reset the upper portion of the steel fence post alongside the stainless steel post.</p> <hr/> <p>N. 0°22'00" W., beginning new measurement.</p> <p>Continue along the W. side of the KOA campground.</p>
6.75	<p>Power pole, from which a powerline bears N., 0.37 chs. to the cor. of powerlines extending S. and N. 7° W.</p>
19.707	<p>The W 1/16 sec. cor. of secs. 26 and 35.</p> <hr/>

SUBDIVISION OF SECTION 35,
T. 16 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From the C-N 1/16 sec. cor. of sec. 35.</p> <p>S. 89°46'50" W., on the E-W center line of the NW1/4 of sec. 35.</p> <p>Across rolling land, sagebrush and bunchgrass and along the S. side of the KOA campground.</p>
1.174	<p>A position established by Dean Neubauer, Nevada Professional Land Surveyor No. 9392, monumented with a rebar, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with plastic cap mkd. B.F.I. PLS 9392.</p>
20.091	<p>The NW 1/16 sec. cor. of sec. 35.</p> <hr/> <p>S. 89°46'00" W., beginning new measurement.</p> <p>Across rolling land, through scattered pinon pine, juniper, sagebrush and bunchgrass.</p>
10.034	<p>Point for the C-W-NW 1/64 sec. cor. of sec. 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S35 C-W-NW 1/64 2007</p> <p>Set a steel sign post alongside the stainless steel post.</p>
20.068	<p>The N 1/16 sec. cor. of secs. 34 and 35.</p> <hr/> <p>From the C-W-W 1/64 sec. cor. of sec. 35.</p> <p>N. 0°23'20" W., on the N-S center line of the SW1/4 of the NW1/4 of sec. 35.</p> <p>Across rolling land, through scattered pinon pine, juniper, sagebrush and bunchgrass.</p>
1.515	<p>Point for a witness point at the intersection of a line 100 ft. northerly of and parallel to the E-W center line of sec. 35, with the N-S center line of the SW1/4 of the NW1/4 of sec. 35, hereinafter described.</p>
19.711	<p>The C-W-NW 1/64 sec. cor. of sec. 35.</p> <hr/> <p>N. 0°23'10" W., on the N-S center line of the NW1/4 of the NW1/4 of sec. 35.</p> <p>Across rolling land, through scattered pinon pine, juniper, sagebrush and bunchgrass.</p>
19.698	<p>The W-W 1/64 sec. cor. of secs. 26 and 35.</p> <hr/>

SUBDIVISION OF SECTION 36,
T. 16 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From the standard 1/4 sec. cor. of sec. 36, on the S. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the Third Standard Parallel North, T. 16 N., R. 63 E., executed under Group No. 446, with a mound of stone, 3 ft. base, 1/2 ft. high, N. of cor.</p>
	<p>N. 0°06'40" W., on the N-S center line of sec. 36.</p>
	<p>Across rolling land, sagebrush and bunchgrass.</p>
19.40	<p>Center of graded dirt road, 15 lks. wide, bears NW. and SE.</p>
27.90	<p>Center of graded dirt road, 15 lks. wide, bears ENE. and WSW.</p>
39.807	<p>Point for the center 1/4 sec. cor. of sec. 36, at intersection with the E-W center line.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T16N R63E C 1/4 S36 2007</p>
	<p>Set a steel sign post alongside the stainless steel post.</p>
79.623	<p>The 1/4 sec. cor. of secs. 25 and 36.</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 31 and 36, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the E. bdy., T. 16 N., R. 63 E., executed under Group No. 446, with a mound of stone, 2 ft. base, 1/2 ft. high, W. of cor.</p>
	<p>S. 89°57'50" W., on the E-W center line of sec. 36.</p>
	<p>Across rolling land, sagebrush and bunchgrass.</p>
21.95	<p>Barbed wire fence, bears NW. and SE.</p>
22.30	<p>Center of graded dirt road, 15 lks. wide, parallels fence.</p>
40.229	<p>The center 1/4 sec. cor. of sec. 36.</p>
58.00	<p>Center of graded dirt road; 15 lks. wide, bears NW. and SE.</p>
60.345	<p>Point for the C-W 1/16 sec. cor. of sec. 36.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

SUBDIVISION OF SECTION 36,
T. 16 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;"> $\frac{W \ 1/16}{C \ \frac{\quad}{S36} \ C}$ </p> <p style="text-align: center;">2007</p> <p>Set a steel sign post alongside the stainless steel post.</p> <p>80.461 The 1/4 sec. cor. of secs. 35 and 36.</p> <hr/> <p>From the C-W 1/16 sec. cor. of sec. 36.</p> <p>N. 0°09'10" W., on the N-S center line of the NW1/4 of sec. 36.</p> <p>Across rolling land, sagebrush and bunchgrass.</p> <p>1.515 Point for a witness point at the intersection of a line parallel to and 100 ft. northerly of the E-W center line of sec. 36, with the N-S center line of the NW1/4 of sec. 36, hereinafter described.</p> <p>39.695 The W 1/16 sec. cor. of secs. 25 and 36.</p> <hr/> <p style="text-align: center;"> METES-AND-BOUNDS SURVEY OF U.S. HIGHWAY NOS. 6, 50 AND 93 THROUGH PORTIONS OF SECTIONS 26 AND 35, T. 16 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA </p> <hr/> <p>From the point for a witness point at the intersection of the centerline of U.S. Highway Nos. 6, 50 and 93, with the E-W center line of sec. 35.</p> <p>Set a PK nail flush with the asphalt surface.</p> <p>from which</p> <p style="padding-left: 40px;"> A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground for a reference monument, bears N. 16°32' E., 130.0 lks. dist., with brass cap mkd. RM WP S35 85.8 FT TO COR 2007 and an arrow pointing to the cor. Set a steel sign post alongside the stainless steel post. </p> <p style="padding-left: 40px;"> A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 78°18' E., 173.4 lks. dist., with brass cap mkd. RM WP S35 114.4 FT TO COR 2007 and an arrow pointing to the cor. Set a steel sign post alongside the stainless steel post. </p> <p>From this point, a Nevada Dept. of Transportation highway station utilized to determine the centerline of the right-of-way, monumented with a standard brass tablet, set flush with the surface of the ground, encased in concrete, mkd. DIST. 42.00 STA. 20403+4POT ANGLE 90 ELEV 6640.568, bears S. 29°27'40" E., 39.645 chs. dist.</p> <p>N. 30°22'50" W., on the centerline of U.S. Highway Nos. 6, 50 and 93, through the NE1/4 of sec. 35.</p>
--------	--

METES-AND-BOUNDS SURVEY OF U.S. HIGHWAY NOS. 6, 50 AND 93
THROUGH PORTIONS OF SECTIONS 26 AND 35,
T. 16 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
1.754	<p>Point for a witness point at the intersection of a line parallel to and 100 ft. northerly of the E-W center line of sec. 35, with the centerline of U.S. Highway Nos. 6, 50 and 93, hereinafter described.</p>
24.011	<p>Point for a witness point, at the intersection of the centerline of U.S. Highway Nos. 6, 50 and 93, with the N-S center line of sec. 35.</p> <p>Set a PK nail flush with the asphalt surface.</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 45°07' W., 140.5 lks. dist., with brass cap mkd. RM WP S35 92.7 FT TO COR 2007 and an arrow pointing to the cor. Set a steel sign post alongside the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground for a reference monument, bears N. 50°33' W., 280.0 lks. dist., with brass cap mkd. RM WP S35 184.8 FT TO COR 2007 and an arrow pointing to the cor. Set a steel sign post alongside the stainless steel post.</p> <p>From this point, a position established by Richard W. Forman, Nevada Professional Land Surveyor No. 2898, as shown on an unrecorded survey map titled "Portion of the NE1/4 NW1/4, APN 10-420-82", dated August 19, 1998, on file with Smoke Signals in Ely, NV, monumented with a rebar, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with plastic cap mkd. BFI PLS 9392, and utilized to determine the centerline of the right-of-way at Point of Tangency, Sta. "O" 151+95.91 P.T. shown on Sheet No. 3, Project FED WP10, Nevada Dept. of Transportation, bears N. 36°03'00" W., 15.337 chs. dist.</p> <p>From this same point, a reference position reestablished by Dean Neubauer, Nevada Professional Land Surveyor No. 9392, monumented with a rebar, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with plastic cap mkd. BFI PLS 9392, and utilized to determine the centerline of the right-of-way at Point of Tangency, Sta. "O" 151+95.91 P.T., as shown on Sheet No. 3, Project FED WP10, Nevada Dept. of Transportation, bears N. 24°42'30" W., 15.336 chs. dist.</p> <hr/> <p>From the point for a witness point at the intersection of the centerline of U.S. Highway Nos. 6, 50 and 93, with the line bet. secs. 26 and 35.</p> <p>Set a PK nail flush with the asphalt surface.</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground for a reference monument, bears N. 57°13' E., 95.0 lks. dist., with brass cap mkd. T16N R63E RM WP S26 62.7 FT TO COR 2007 and an arrow pointing to the cor. Set a steel sign post alongside the stainless steel post.</p>

METES-AND-BOUNDS SURVEY OF U.S. HIGHWAY NOS. 6, 50 AND 93
THROUGH PORTIONS OF SECTIONS 26 AND 35,
T. 16 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground for a reference monument, bears N. 54°28' E., 195.8 lks. dist., with brass cap mkd. T16N R63E RM WP S35 129.2 FT TO COR 2007 and an arrow pointing to the cor. Set a steel sign post alongside the stainless steel post.</p> <p>From this point, a position established by Richard W. Forman, Nevada Professional Land Surveyor No. 2898, as shown on an unrecorded survey map titled "Portion of the NE1/4 NW1/4, APN 10-420-82", dated August 19, 1998, on file with Smoke Signals in Ely, NV, monumented with a rebar, hereinbefore described, and utilized to determine the centerline of the right-of-way at Point of Tangency, Sta. "O" 151+95.91 P.T. shown on Sheet No. 3, Project FED WP10, Nevada Dept. of Transportation, bears, S. 42°43'50" E., 6.469 chs. dist.</p> <p>From this same point, an unrecorded position established by Dean Neubauer, Nevada Professional Land Surveyor No. 9392, monumented with a rebar hereinbefore described, and utilized to determine the centerline of the right-of-way at Point of Tangency, Sta. "O" 151+95.91 P.T. shown on Sheet No. 3, Project FED WP10, Nevada Dept. of Transportation, bears S. 15°45'40" E., 6.530 chs. dist.</p> <p>Thence on the centerline of U.S. Highway Nos. 6, 50 and 93, through the SW1/4 of sec. 26, along the arc of a circular curve to the right having a radius of 10,000 ft.; the chord of said arc bears N. 25°05'26" W., 15.340 chs. dist.</p>
11.65	Center of intermittent stream, drains NE.
15.347	<p>Point for a witness point and Point of Curvature, Sta. 137+66.19 P.C., as shown on Sheet No. 3, Project FED WP10, Nevada Dept. of Transportation.</p> <p>Set a PK nail flush with the asphalt surface.</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground for a reference monument, bears N. 22°39' E., 163.8 lks. dist., with brass cap mkd. RM WP S26 108.1 FT TO COR 2007 and an arrow pointing to the cor. Set a steel sign post alongside the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground for a reference monument, bears N. 61°39' W., 188.7 lks. dist., with brass cap mkd. RM WP S26 124.5 FT TO COR 2007 and an arrow pointing to the cor. Set a steel sign post alongside the stainless steel post.</p> <hr/> <p>Thence N. 22°11'20" W., beginning new measurement, continuing on the centerline of U.S. Highway Nos. 6, 50 and 93.</p>
0.854	<p>Point for a witness point located in the SE1/4 of the SW1/4 of sec. 26.</p> <p>Set a PK nail flush with the asphalt surface.</p>



METES-AND-BOUNDS SURVEY OF U.S. HIGHWAY NOS. 6, 50 AND 93
THROUGH PORTIONS OF SECTIONS 26 AND 35,
T. 16 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 27 ins. in the ground for a reference monument, bears S. 84°14' E., 88.2 lks. dist., with brass cap mkd. RM WP S26 58.2 FT TO COR 2007 and an arrow pointing to the cor. Set a steel sign post alongside the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground for a reference monument, bears S. 18°59' W., 137.0 lks. dist., with brass cap mkd. RM WP S26 90.4 FT TO COR 2007 and an arrow pointing to the cor. Set a steel sign post alongside the stainless steel post.</p>
6.310	<p>Point for a witness point at the intersection of the centerline of U.S. Highway Nos. 6, 50 and 93, with the E-W center line of the SW1/4 of sec. 26.</p> <p>Set a PK nail flush with the asphalt surface.</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground for a reference monument, bears N. 21°17' E., 123.5 lks. dist., with brass cap mkd. RM WP S26 81.5 FT TO COR 2007 and an arrow pointing to the cor. Set a steel sign post alongside the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground for a reference monument, bears S. 69°33' E., 130.3 lks. dist., with brass cap mkd. RM WP S26 86.0 FT TO COR 2007 and an arrow pointing to the cor. Set a steel sign post alongside the stainless steel post.</p>
7.856	<p>Point for a witness point at the intersection of the centerline of U.S. Highway Nos. 6, 50 and 93, with the N-S center line of the SW1/4 of sec. 26.</p> <p>Set a PK nail flush with the asphalt surface.</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 24°51' W., 167.0 lks. dist., with brass cap mkd. RM WP S26 110.2 FT TO COR 2007 and an arrow pointing to the cor. Set a steel sign post alongside the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground for a reference monument, bears N. 68°08' W., 148.5 lks. dist., with brass cap mkd. RM WP S26 98.0 FT TO COR 2007 and an arrow pointing to the cor. Set a steel sign post alongside the stainless steel post.</p>
20.854	<p>Point for a witness point located in the NW1/4 of the SW1/4 of sec. 26.</p>

METES-AND-BOUNDS SURVEY OF U.S. HIGHWAY NOS. 6, 50 AND 93
THROUGH PORTIONS OF SECTIONS 26 AND 35,
T. 16 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA


<p>CHAINS</p>	<p>Set a PK nail flush with the asphalt surface.</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground for a reference monument, bears S. 35°05' W., 113.0 lks. dist., with brass cap mkd. RM WP S26 74.6 FT TO COR 2007 and an arrow pointing to the cor. Set a steel sign post alongside the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 49°33' W., 207.6 lks. dist., with brass cap mkd. RM WP S26 137.0 FT TO COR 2007 and an arrow pointing to the cor. Set a steel sign post alongside the stainless steel post.</p>
<p>27.616</p>	<p>Point for a witness point at the intersection of the centerline of U.S. Highway Nos. 6, 50 and 93, with the E-W center line of sec. 26.</p> <p>Set a PK nail flush with the asphalt surface.</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 20°56' E., 153.5 lks. dist., with brass cap mkd. RM WP S26 101.3 FT TO COR 2007 and an arrow pointing to the cor. Set a steel sign post alongside the stainless steel post.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 69°37' E., 153.6 lks. dist., with brass cap mkd. RM WP S26 101.4 FT TO COR 2007 and an arrow pointing to the cor. Set a steel sign post alongside the stainless steel post.</p> <p>From this point, a Nevada Dept. of Transportation highway station utilized to determine the centerline of the right-of-way, monumented with a standard brass tablet set flush with the surface of the ground, encased in concrete, bears N. 49°36'40" W., 2.113 chs. dist., mkd. DIST. 64.22 STA. 0 118+20.67 POT ANGLE 90 ELEV 6608.977.</p> <hr/> <p style="text-align: center;">METES-AND-BOUNDS SURVEY IN SECTION 26, T. 16 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the witness point located in the SE1/4 of the SW1/4 of sec. 26 and on the centerline of U.S. Highway Nos. 6, 50 and 93, hereinbefore described.</p> <p>Thence S. 60°00'00" W.</p>
<p>3.027</p>	<p>Point for a witness point at intersection with the N-S center line of the SW1/4 of sec. 26.</p>

METES-AND-BOUNDS SURVEY IN SECTION 26,
T. 16 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;">  <p>WP W S 26 W</p> </div> <p>2007</p>
14.597	<p>The witness point at intersection with the N-S center line of the SW1/4 of the SW1/4 of sec. 26, hereinbefore described.</p> <hr/> <p>From the witness point located in the NW1/4 of the SW1/4 of sec. 26 and on the centerline of U.S. Highway Nos. 6, 50 and 93, hereinbefore described.</p> <p>Thence S. 60°00'00" W.</p>
17.516	<p>Point for a witness point at the intersection of a metes-and-bounds survey in sec. 26 with the line bet. secs. 26 and 27, identical with the intersection of a metes-and-bounds survey in sec. 27, with the line bet. secs. 26 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;">  <p>WP T16N R63E S S 27 26</p> </div> <p>2007</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr/> <p style="text-align: center;">METES-AND-BOUNDS SURVEY IN SECTION 27, T. 16 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the witness point at the intersection of a metes-and-bounds survey in sec. 26 with the line bet. secs. 26 and 27, identical with the intersection of a metes-and-bounds survey in sec. 27, with the line bet. secs. 26 and 27, hereinbefore described.</p> <p>Thence S. 60°00'00" W.</p>
9.746	<p>Point for a witness point at intersection with the E-W center line of the SE1/4 of sec. 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

METES-AND-BOUNDS SURVEY IN SECTION 27,
T. 16 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS



2007

Set a steel sign post alongside the stainless steel post.


11.613

The witness point on the N-S center line of the SE1/4 of the SE1/4 of sec. 27, hereinbefore described.

METES-AND-BOUNDS SURVEY IN SECTION 34,
T. 16 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

From the point for a witness point at the intersection of a line parallel to and 100 ft. northerly of the E-W center line of sec. 34 with the line bet. secs. 34 and 35.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.



2007

Set a steel sign post alongside the stainless steel post.


This monument occupies the position of the intersection of a line parallel to and 100 ft. northerly of the E-W center line of sec. 35 with the line bet. secs. 34 and 35, hereinafter described.

N. 89°31'20" W., on a line parallel to and 100 ft. northerly of the E-W center line of sec. 34.

10.070

Point for a witness point at the intersection of a line parallel to and 100 ft. northerly of the E-W center line of sec. 34 with the N-S center line of the SE1/4 of the NE1/4 of sec. 34.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, 1/2 ft. high, with brass cap mkd.



2007

Set a steel sign post alongside the stainless steel post.

METES-AND-BOUNDS SURVEY IN SECTION 35,
T. 16 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
10.034	<div data-bbox="906 285 992 426" style="text-align: center;"> WP W-W S — 35 W-W </div> <div data-bbox="927 453 992 478" style="text-align: center;">2007</div> <p data-bbox="456 508 1360 533">Set a steel sign post alongside the stainless steel post.</p> <p data-bbox="456 560 1461 611">S. 89°51'20" W., on a line parallel to and 100 ft. northerly of the E-W center line of sec. 35.</p> <p data-bbox="456 638 1477 823">Point for a witness point at the intersection of a line parallel to and 100 ft. northerly of the E-W center line of sec. 35 with the line bet. secs. 34 and 35. This position is occupied by a monument established for the witness point at intersection of a line parallel to and 100 ft. northerly of the E-W center line of sec. 34 with the line bet. secs. 34 and 35, hereinbefore described.</p> <hr/> <div data-bbox="574 884 1360 934" style="text-align: center;"> METES-AND-BOUNDS SURVEY IN SECTION 36, T. 16 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA </div> <hr/> <p data-bbox="456 993 1446 1068">From the point for a witness point at intersection with a line parallel to and 100 ft. northerly of the E-W center line of sec. 36 and the N-S center line of the NW1/4 of sec. 36.</p> <p data-bbox="456 1098 1477 1176">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="906 1207 992 1348" style="text-align: center;"> WP W S — 36 W </div> <div data-bbox="927 1388 992 1413" style="text-align: center;">2007</div> <p data-bbox="456 1442 1360 1470">Set a steel sign post alongside the stainless steel post.</p> <p data-bbox="456 1497 1461 1547">S. 89°57'50" W., on a line parallel to and 100 ft. northerly of the E-W center line of sec. 36.</p> <p data-bbox="310 1575 1477 1759">20.118 Point for a witness point at the intersection of a line parallel to and 100 ft. northerly of the E-W center line of sec. 36, with the line bet. secs. 35 and 36. This position is occupied by a monument established for the witness point at the intersection of a line parallel to and 100 ft. northerly of the E-W center line of sec. 35 with the line bet. secs. 35 and 36, hereinbefore described.</p> <hr/>

TOWNSHIP 16 NORTH, RANGE 63 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	GENERAL DESCRIPTION
	<p data-bbox="451 331 1455 436">The land encompassed in this survey is located on the southeast outskirts of Ely, Nevada, located along U.S. Highway Nos. 6, 50 and 93, at an approximate elevation of about 6700 ft. above sea level.</p> <p data-bbox="451 468 1442 573">The topography is rolling land sloping gently to the northeast with small ravines and washes draining the foothills of the Egan Range to the west, into the grassy meadows along Steptoe Creek to the east.</p> <p data-bbox="451 604 1442 678">The vegetation is low sagebrush and bunchgrass, with scattered junipers and pinon pine generally west of U.S. Highway Nos. 6, 50 and 93.</p> <p data-bbox="451 709 1442 793">Development in section 27 and the south half of section 35 is generally rural lots with some urban development in the north half of section 27.</p> <hr data-bbox="451 814 1474 823"/>

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

George E. Allen	Supervisory Land Surveyor
Dale Graff	Cadastral Surveyor
Michelle E. Martin	Supervisory Range Technician
Douglas E. Crawford	Surveying Technician
Christopher O. Oloruntola	Survey Aid

CERTIFICATE OF SURVEY

We, Wayne S. Hancock, Cadastral Surveyor, and Mark G. Petrosine, Surveying Technician, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 21st day of February, 2007, we have dependently resurveyed a portion of the subdivisional lines, subdivided certain sections, executed a metes-and-bounds survey of U.S. Highway Nos. 6, 50 and 93 through portions of sections 26 and 35, and executed metes-and-bounds surveys in certain sections, Township 16 North, Range 63 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

December 20, 2007

(Date)

Wayne S. Hancock
(Cadastral Surveyor)

January 10, 2008

(Date)

Mark G. Petrosine
(Surveying Technician)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of the dependent resurvey of a portion of the subdivisional lines, the subdivision of certain sections, the metes-and-bounds survey of U.S. Highway Nos. 6, 50 and 93 through portions of sections 26 and 35, and metes-and-bounds surveys in certain sections, Township 16 North, Range 63 East, Mount Diablo Meridian, Nevada, executed by Wayne S. Hancock, Cadastral Surveyor, and Mark G. Petrosine, Surveying Technician, having been critically examined and found correct, are hereby approved.

January 15, 2008

(Date)

David D. York
(Chief Cadastral Surveyor, Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above described surveys in T. 16 N., R. 63 E., Mount Diablo Meridian, Nevada, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor, Nevada)~~