

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

PORTIONS OF THE SOUTH, WEST AND NORTH BOUNDARIES,

A PORTION OF THE SUBDIVISIONAL LINES,

AND THE MEANDERS OF CARSON LAKE,

AND

THE COMPLETION SURVEY OF THE SOUTH BOUNDARY,

AND THE SURVEY OF TRACT 37,

TOWNSHIP 17 NORTH, RANGE 30 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

EXECUTED BY

Brock R. Clifford, Cadastral Surveyor

Thomas E. Casinger, Cadastral Surveyor

Under Special Instructions dated June 10, 1996,

and approved June 10, 1996,

and Supplemental Special Instructions dated April 30, 1998,

and approved April 30, 1998,

which provided for the surveys included under Group No. 763,

and Assignment Instructions dated June 10, 1996

and November 3, 1997.

Survey commenced May 31, 1996

Survey completed July 2, 1998

INDEX DIAGRAM

TOWNSHIP 17 NORTH, RANGE 30 EAST

5	8	7	6				
	6	23 5	14 4	9 3	2	1	
	22	22	14				
	7	21 8	13 9	8 10	11	12	
	20	20					
	18	19 17	12 16	15	14	13	
	19	18					
	19	18	20	11 21	22	23	24
		17					
	30	29	10 28	27	26	25	
	16	16	15				
	31	15 32	33	34	35	36	
	4	3	2				

Dependent resurvey of the meanders of Carson Lake . . . . Pages 24-26  
 Completion survey of the south boundary . . . . . Page 26  
 Survey of Tract 37 . . . . . Pages 26-29

## TOWNSHIP 17 NORTH, RANGE 30 EAST, MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

The following field notes are those of the dependent resurvey of portions of the south, west and north boundaries, a portion of the subdivisional lines, and the meanders of Carson Lake, and the completion survey of the south boundary, and the survey of Tract 37, Township 17 North, Range 30 East, Mount Diablo Meridian, Nevada.

Portions of the south and north boundaries, and the east boundary were surveyed by U.S. Deputy Surveyor E.B. Monroe, in 1868, under Contract No. 10. Portions of the south and north boundaries were resurveyed, and the completion of the north boundary and portions of the south and west boundaries and a portion of the subdivisional lines and the meanders of Carson Lake were surveyed by U.S. Deputy Surveyors M.F. Reilly and T.A. Magee, in 1881, under Contract No. 108. The cor. of Tps. 17 and 18 N., Rs. 29 and 30 E., was remonumented during the resurvey of a portion of the south boundary and a portion of the subdivisional lines of T. 18 N., R. 29 E., by U.S. Surveyor Winfred A. Prey, in 1912, under Group No. 16. Other surveys remote to this area are not included.

The survey of a portion of the subdivisional lines of T. 16 N., R. 30 E., and the completion survey of the east boundary of T. 17 N., R. 29 E., were executed concurrently under this same group.

Before restoring the corners, the lines of the original surveys were retraced and diligent search made for any evidence of the original corners and other calls of the original field note record.

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, the Special Instructions dated June 10, 1996, and the Supplemental Special Instructions dated April 30, 1998.

The direction of the lines of this survey were determined by azimuth taken from GPS positions at the cor. of secs. 31 and 32 only, and the  $\frac{1}{4}$  sec. cor. of sec. 33 only, on the S. bdy. of the Tp., and by use of Global Positioning System satellite data, using the real time kinematic survey process, and refer to the true meridian. The lines were carried forward by sustained angulation throughout the progress of the survey.

The vertical angles of measurements made on the slope were ascertained with a theodolite in good adjustment; the horizontal equivalents only are entered in the field notes.

The geographic position for the cor. of Tps. 17 and 18 N., Rs. 29 and 30 E., is at Lat.  $39^{\circ}22'22.635''$  N. and Long.  $118^{\circ}40'09.503''$  W. - NAD 83 (1986), as determined by survey grade GPS receivers, in 1996, from NGS stations "WYE" and "X 46".

The 1980 mean magnetic declination is  $16^{\circ}$ E., as shown on U.S.G.S. quadrangle map "CARSON LAKE, NEV." dated 1985.


DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 17 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>(Reestablishment of the Survey Executed by E.B. Monroe, U.S. Deputy Surveyor, in 1868, and the Resurvey and Survey Executed by M.F. Reilly and T.A. Magee, U.S. Deputy Surveyors, in 1881)</p> <hr/> <p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 4 and 33, monumented with a basalt stone, 16X12X8 ins., mkd. <math>\frac{1}{4}</math> on S. face, firmly set in a mound of stone. This cor. will now function as the <math>\frac{1}{4}</math> sec. cor. of sec. 33 only.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 20 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T17N R30E <math>\frac{1}{4}</math> S33 <hr/>T16N R30E</p> <p style="text-align: center;">1996</p> <p>Deposit the original cornerstone alongside the stainless steel post.</p> <p>N. <math>89^{\circ}46'40''</math> W., on the S. bdy. of sec. 33.</p> <p>Over rolling land, covered with scattered shadscale and greasewood.</p>
17.60	Buried gas line, bears S. $32\frac{1}{2}^{\circ}$ E. and N. $32\frac{1}{2}^{\circ}$ W.
17.75	Trail road, parallels gas line.
33.183	The closing cor. of secs. 4 and 5, T. 16 N., R. 30 E., monumented with a stainless steel post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of T. 16 N., R. 30 E., executed concurrently under this same group.
40.210	<p>The cor. of secs. 4, 5, 32 and 33, monumented with a basalt stone, 15X9X4 ins., mkd. with 4 grooves on E. face and 2 grooves on W. face, firmly set in a mound of stone. This cor. will now function as the cor. of secs. 32 and 33 only.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T17N R30E S32   S33 <hr/>S 5 T16N</p> <p style="text-align: center;">1996</p>

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 17 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Deposit the original cornerstone alongside the stainless steel post and rebuild the mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <hr/> <p>N. 89°48'30" W., on the S. bdy. of sec. 32.</p> <p>Over alkali flat.</p>
32.965	<p>The <math>\frac{1}{4}</math> sec. cor. of sec. 5 only, T. 16 N., R. 30 E., monumented with a stainless steel post, <math>2\frac{1}{2}</math> ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of T. 16 N., R. 30 E., executed concurrently under this same group.</p>
40.206	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 5 and 32, monumented with a basalt stone, 16x12x9 ins., dimly mkd. <math>\frac{1}{4}</math> on S. face, firmly set in a mound of earth. This cor. will now function as the <math>\frac{1}{4}</math> sec. cor. of sec. 32 only.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T17N R30E <math>\frac{1}{4}</math> S32</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">T16N R30E</p> <p style="text-align: center;">1996</p>
	<p>Deposit the original cornerstone and set a steel fence post, 5 ft. long, alongside the stainless steel post.</p> <hr/> <p>N. 89°48'40" W., beginning new measurement.</p> <p>Over alkali flat.</p>
32.751	<p>The closing cor. of secs. 5 and 6, T. 16 N., R. 30 E., monumented with a stainless steel post, <math>2\frac{1}{2}</math> ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of T. 16 N., R. 30 E., executed concurrently under this same group.</p>
40.252	<p>The cor. of secs. 5, 6, 31 and 32, monumented with a basalt stone, 12X9X6 ins., mkd. with 5 notches on E. edge and 1 notch on W. edge, firmly set in the ground. This cor. will now function as the cor. of secs. 31 and 32 only.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 17 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	T17N R30E S31   S32 <hr style="width: 50%; margin: auto;"/> S 6 T16N  1996
	<hr/> WEST, on the S. bdy. of sec. 31.  Over alkali flat.
1.70	Fence, bears NE. and SW.
4.60	Enter greasewood, shadscale and native grass.
20.000	Point for the 1868 meander cor. of secs. 6 and 31, at record distance; there is no remaining evidence of the original corner. This will no longer function as a corner.
32.499	The $\frac{1}{4}$ sec. cor. of sec. 6 only, T. 16 N., R. 30 E., monumented with a stainless steel post, 2 $\frac{1}{2}$ ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of T. 16 N., R. 30 E., executed concurrently under this same group.
40.000	Point for $\frac{1}{4}$ sec. cor. of secs. 6 and 31, determined at record bearing and distance; there is no remaining evidence of the original corner. This cor. will now function as the $\frac{1}{4}$ sec. cor. of sec. 31 only.  Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T17N R30E $\frac{1}{4}$ S31 <hr style="width: 50%; margin: auto;"/> T16N R30E  1996
48.000	Set a steel fence post, 5 ft. long, alongside the stainless steel post.  Point for the meander cor. of secs. 6 and 31, determined at record bearing and distance; there is no remaining evidence of the original corner. This cor. will now function as the meander cor. of sec. 31 only, and also as Angle Pt. No. 3, Tract 37.  Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	 1998

129

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 17 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

Set a steel fence post, 5 ft. long, alongside the stainless steel post.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,  
T. 17 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

(Reestablishment of the Survey Executed by  
M.F. Reilly and T.A. Magee, U.S. Deputy Surveyors, in 1881)

From the cor. of Tps. 17 and 18 N., Rs. 29 and 30 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of T. 18 N., R. 29 E., executed under Group No. 16. This cor. will now also function as Angle Pt. No. 1, Tract 37, T. 17 N., R. 29 E.

Remark the brass cap to read

	T18N	
	R29E R30E	
	S36   S31	
	-----	
	AP 1   S 6	
	TR 37	
	T17N	
	1998	
	1912	

Cor. is located in fence, bears E. and W., 10 lks. W. of corner of fences, bears N., S. and W.

SOUTH, bet. secs. 1 and 6.

Over bottom land.

10.000

Point for the meander cor. of secs. 1 and 6, determined at record bearing and distance; there is no remaining evidence of the original corner. This cor. will now function as the meander cor. of sec. 6 only, and also as Angle Pt. No. 1, Tract 37, and Angle Pt. No. 11, Tract 37, T. 17 N., R. 29 E.

Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

T17N	
R30E	
S 6	
MC	
	1998

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
T. 17 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS																									
	<p>(Reestablishment of the Survey Executed by E.B. Monroe, U.S. Deputy Surveyor, in 1868, and the Resurvey and Survey Executed by M.F. Reilly and T.A. Magee, U.S. Deputy Surveyors, in 1881)</p> <hr/> <p>From the cor. of secs. 3, 4, 33 and 34, monumented with a basalt stone, 20X12x10 ins., dimly mkd. with 3 notches on E. edge and 3 notches on W. edge, firmly set in the ground, with a steel fence post, 5<sup>1</sup>/<sub>2</sub> ft. long, and a pine post, 4 ins. square, 4 ft. long, set alongside.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T18N</td> <td>R30E</td> </tr> <tr> <td>S33</td> <td>S34</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td>S 4</td> <td>S 3</td> </tr> <tr> <td colspan="2" style="text-align: center;">T17N</td> </tr> <tr> <td colspan="2" style="text-align: center;">1996</td> </tr> </table> <p>Deposit the original cornerstone and reset the steel fence post and pine post, alongside the stainless steel post.</p> <p>N. 89°08'40" W., bet. secs. 4 and 33.</p> <p>Over alkali flat.</p> <p>39.353 The <sup>1</sup>/<sub>4</sub> sec. cor. of secs. 4 and 33, monumented with a basalt stone, 10X6X5 ins., dimly mkd. <sup>1</sup>/<sub>4</sub> on N. face, firmly set in the ground.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T18N</td> <td>R30E</td> </tr> <tr> <td>S33</td> <td></td> </tr> <tr> <td>1/4</td> <td style="border-top: 1px solid black;"></td> </tr> <tr> <td>S 4</td> <td></td> </tr> <tr> <td colspan="2" style="text-align: center;">T17N</td> </tr> <tr> <td colspan="2" style="text-align: center;">1998</td> </tr> </table> <p>Deposit the original cornerstone and set a steel fence post, 5 ft. long, alongside the stainless steel post.</p> <hr/> <p>S. 89°58'30" W., beginning new measurement.</p> <p>Enter rolling sandy hills, covered with greasewood, shadscale and native grass.</p> <p>7.30 Low sandy ridge, bears N. and S.</p> <p>40.00 Bladed gravel road, bears SSE. and NNW.</p>	T18N	R30E	S33	S34			S 4	S 3	T17N		1996		T18N	R30E	S33		1/4		S 4		T17N		1998	
T18N	R30E																								
S33	S34																								
S 4	S 3																								
T17N																									
1996																									
T18N	R30E																								
S33																									
1/4																									
S 4																									
T17N																									
1998																									

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
T. 17 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS 40.935	<p>Point for the cor. of secs. 4, 5, 32 and 33, at proportionate distance; there is no remaining evidence of the 1881 corner.</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T18N</td> <td>R30E</td> </tr> <tr> <td>S32</td> <td>S33</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td>S 5</td> <td>S 4</td> </tr> <tr> <td colspan="2" style="text-align: center;">T17N</td> </tr> <tr> <td colspan="2" style="text-align: center;">1998</td> </tr> </table> <p>Set a steel fence post, 5 ft. long, alongside the stainless steel post.</p> <hr/> <p>S. 89°58'30" W., bet. secs. 5 and 32.</p> <p>Over low rolling sandy hills, covered with greasewood, shadscale and native grass.</p>	T18N	R30E	S32	S33			S 5	S 4	T17N		1998	
T18N	R30E												
S32	S33												
S 5	S 4												
T17N													
1998													
1.00	Bladed gravel road, bears NNE. and SSW.												
40.935	<p>Point for the <sup>1</sup>/<sub>4</sub> sec. cor. of secs. 5 and 32, at proportionate distance; there is no remaining evidence of the 1881 corner.</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T18N</td> <td>R30E</td> </tr> <tr> <td>S32</td> <td></td> </tr> <tr> <td>1/4</td> <td style="border-top: 1px solid black;"></td> </tr> <tr> <td>S 5</td> <td></td> </tr> <tr> <td colspan="2" style="text-align: center;">T17N</td> </tr> <tr> <td colspan="2" style="text-align: center;">1998</td> </tr> </table> <p>Set a steel fence post, 5 ft. long, alongside the stainless steel post.</p>	T18N	R30E	S32		1/4		S 5		T17N		1998	
T18N	R30E												
S32													
1/4													
S 5													
T17N													
1998													
53.20	Improved gravel road, bears S. 20° E. and N. 20° W.												
54.10	Buried gas line, parallels gravel road.												
54.60	Fence, parallels gravel road.												
81.870	<p>The cor. of secs. 5, 6, 31 and 32, monumented with a basalt stone, 10X8X5 ins., mkd. with 5 notches on E. edge and 1 notch on W. edge, firmly set in the ground. This is accepted as the best available evidence of the 1881 corner position. (Record, wood post)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>												

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
T. 17 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T18N R30E S31   S32 ----- S 6   S 5 T17N  1996</p> <p>Deposit the basalt stone and set a steel fence post, 5 ft. long, alongside the stainless steel post.</p> <hr/> <p>S. 88°57'00" W., bet. secs. 6 and 31.</p> <p>Over pasture land, covered with native grass and widely scattered greasewood and shadscale.</p>
1.70	Canal, 30 lks. wide, 3 ft. deep, bears S. and NW.
16.500	Point for the 1868 meander cor. of secs. 6 and 31, at record distance; there is no remaining evidence of the original corner. This will no longer function as a corner.
40.336	Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner.
	<p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T18N R30E S31 1/4 ----- S 6 T17N  1996</p>
81.277	The cor. of Tps. 17 and 18 N., Rs. 29 and 30 E., identical with Angle Pt. No. 1, Tract 37, T. 17 N., R. 29 E.
	<hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 17 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">(Reestablishment of the Survey Executed by M.F. Reilly and T.A. Magee, U.S. Deputy Surveyors, in 1881)</p> <hr/> <p>From the cor. of secs. 9, 10, 15 and 16, monumented with a limestone, 13X7X5 ins., mkd. with 4 grooves on S. face and 3 grooves on E. face, firmly set in a mound of stone. This cor. will now function as the cor. of secs. 9 and 16 only.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 17 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T17N R30E S 9   <hr style="width: 50px; margin: 0 auto;"/>S16  </p> <p style="text-align: center;">1996</p> <p>Deposit the original cornerstone alongside the stainless steel post and rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>N. 0°15'20" E., on the E. bdy. of sec. 9.</p> <p>Over gently rolling land, covered with scattered greasewood and shadscale.</p>
16.80	Trail road, bears ESE. and WNW.
40.426	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 9 and 10, at proportionate distance; there is no remaining evidence of the original corner. This cor. will now function as the <math>\frac{1}{4}</math> sec. cor. of sec. 9 only.</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T17N R30E 1/4   S 9  </p> <p style="text-align: center;">1998</p> <p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <p>Enter alkali flat.</p>
80.852	<p>Point for the cor. of secs. 3, 4, 9 and 10, determined proportionately between the cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp. and the cor. of secs. 9 and 16 only; there is no remaining evidence of the original corner. This cor. will now function as the cor. of secs. 4 and 9 only.</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T17N R30E S 4   <hr style="width: 50px; margin: 0 auto;"/>S 9  </p> <p style="text-align: center;">1996</p> <p>Set a steel fence post, 5 ft. long, alongside the stainless steel post.</p> <hr style="width: 80%; margin: 10px auto;"/>
	<p>N. 0°15'20" E., on the E. bdy. of sec. 4.</p> <p>Over alkali flat.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 17 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 40.426</p>	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner. This cor. will now function as the <math>\frac{1}{4}</math> sec. cor. of sec. 4 only.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T17N R30E 1/4   S 4  </p> <p style="text-align: center;">1998</p> <p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p>
<p>80.326</p>	<p>The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp.</p> <hr/> <p>From the cor. of secs. 28, 29, 32 and 33, monumented with a basalt stone, 12X9X6 ins., mkd. with 4 grooves on E. face and 1 groove on S. face, firmly set in a mound of stone.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T17N R30E S29   S28 ----- S32   S33</p> <p style="text-align: center;">1996</p> <p>Deposit the original cornerstone and set a steel fence post, 5 ft. long, alongside the stainless steel post.</p> <p>N. <math>0^{\circ}10'10''</math> E., bet. secs. 28 and 29.</p> <p>Over low rolling hills, covered with greasewood, shadscale and native grass.</p>
<p>0.05</p>	<p>Wash, 4 lks. wide, 1 ft. deep, drains WSW.</p>
<p>27.60</p>	<p>Spur, projects W.</p>
<p>38.977</p>	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 28 and 29, monumented with a trapstone, 17X10X4 ins., mkd. <math>\frac{1}{4}</math> on W. face, firmly set in a mound of stone.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 10 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 17 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T17N R30E 1/4 S29   S28</p> <p style="text-align: center;">1996</p> <p>Deposit the original cornerstone alongside the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°19'40" W., beginning new measurement.</p> <p>Over low rolling hills.</p>
15.90	Rocky ridge, bears E. and W.
39.827	<p>The cor. of secs. 20, 21, 28 and 29, monumented with a granite stone, 22X12X9 ins., mkd. with 2 grooves on S. face and 4 grooves on E. face, firmly set in a mound of stone.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T17N R30E S20   S21</p> <hr style="width: 20%; margin: auto;"/> <p style="text-align: center;">S29   S28</p> <p style="text-align: center;">1996</p> <p>Deposit the original cornerstone alongside the stainless steel post and rebuild the mound of stone, 4 ft. base, 2 ft. high, W. of cor.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°13'10" E., bet. secs. 20 and 21.</p> <p>Over gently rolling land covered with greasewood, shadscale and native grass.</p>
40.174	<p>The <sup>1</sup>/<sub>4</sub> sec. cor. of secs. 20 and 21, monumented with a basalt stone, 11X9X3 ins., mkd. <sup>1</sup>/<sub>4</sub> on W. face, firmly set in a mound of stone.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T17N R30E 1/4 S20   S21</p> <p style="text-align: center;">1996</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 17 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS						
	<p>Deposit the original cornerstone alongside the stainless steel post and rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <hr/>					
	<p>N. 0°20'30" E., beginning new measurement.</p>					
28.20	<p>Improved gravel road, bears NE. and SW.</p>					
40.333	<p>The cor. of secs. 16, 17, 20 and 21, monumented with a mound of stone, 3 ft. base, 2 ft. high, with no mkd. stone found in the mound. This mound of stone correlates well with other existing original corners and is accepted as the best available evidence of the position of the original corner.</p>					
	<p>At the corner point</p>					
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>					
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: center;">T17N R30E</td> </tr> <tr> <td style="text-align: center;">S17   S16</td> </tr> <tr> <td style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">S20   S21</td> </tr> <tr> <td style="text-align: center;">1996</td> </tr> </table>	T17N R30E	S17   S16	-----	S20   S21	1996
T17N R30E						
S17   S16						
-----						
S20   S21						
1996						
	<p>Rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <hr/>					
	<p>N. 0°22'40" W., bet. secs. 16 and 17.</p>					
	<p>Over gently rolling land, covered with greasewood, shadscale and native grass.</p>					
22.80	<p>Improved gravel road, bears SE. and NW.</p>					
40.344	<p>The ¼ sec. cor. of secs. 16 and 17, monumented with a basalt stone, 11X7X5 ins., mkd. ¼ on W. face, firmly set in a mound of stone.</p>					
	<p>At the corner point</p>					
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>					
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: center;">T17N R30E</td> </tr> <tr> <td style="text-align: center;">1/4</td> </tr> <tr> <td style="text-align: center;">S17   S16</td> </tr> <tr> <td style="text-align: center;">1996</td> </tr> </table>	T17N R30E	1/4	S17   S16	1996	
T17N R30E						
1/4						
S17   S16						
1996						
	<p>Deposit the original cornerstone alongside the stainless steel post and rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <hr/>					
	<p>N. 0°31'10" E., beginning new measurement.</p>					
	<p>Ascend over low rolling hills.</p>					

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 17 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS 18.00	Top of knob on ridge, bears SE. and NW.								
38.10	Wash, 5 lks. wide, drains NE.								
40.259	<p>The cor. of secs. 8, 9, 16 and 17, monumented with a basalt stone, 10X9X8 ins., mkd. with 4 notches on S. edge, with no other marks visible, firmly set in a mound of stone.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 17 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2">T17N R30E</td> </tr> <tr> <td>S 8</td> <td>S 9</td> </tr> <tr> <td colspan="2"><hr/></td> </tr> <tr> <td>S17</td> <td>S16</td> </tr> </table> <p style="text-align: center;">1996</p> <p>Deposit the original cornerstone alongside the stainless steel post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <hr/> <p>N. 0°09'20" E., bet. secs. 8 and 9.</p> <p>Over rolling land, covered with greasewood, shadscale and native grass.</p>	T17N R30E		S 8	S 9	<hr/>		S17	S16
T17N R30E									
S 8	S 9								
<hr/>									
S17	S16								
23.50	Low ridge, bears NE. and SW.								
40.359	<p>The <sup>1</sup>/<sub>4</sub> sec. cor. of secs. 8 and 9, monumented with a basalt stone, 10X8X4 ins., mkd. <sup>1</sup>/<sub>4</sub> on W. face, firmly set in a mound of stone.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2">T17N R30E</td> </tr> <tr> <td colspan="2"><sup>1</sup>/<sub>4</sub></td> </tr> <tr> <td>S 8</td> <td>S 9</td> </tr> </table> <p style="text-align: center;">1998</p> <p>Deposit the original cornerstone, set a steel fence post, 5 ft. long, alongside the stainless steel post and rebuild the mound of stone, 2 ft. base, 1<sup>1</sup>/<sub>2</sub> ft. high, W. of cor.</p> <hr/> <p>N. 0°27'50" E., beginning new measurement.</p> <p>Over gently rolling land.</p>	T17N R30E		<sup>1</sup> / <sub>4</sub>		S 8	S 9		
T17N R30E									
<sup>1</sup> / <sub>4</sub>									
S 8	S 9								
40.953	Point for the cor. of secs. 4, 5, 8 and 9, determined latitudinally at proportionate distance, and longitudinally at record distance from the cor. of secs. 4 and 9 only. There is no remaining evidence of the original corner.								

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 17 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS									
	<p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T17N</td><td>R30E</td></tr> <tr><td>S 5</td><td>S 4</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 8</td><td>S 9</td></tr> </table> <p style="text-align: center;">1998</p> <p>Set a steel fence post, 5 ft. long, alongside the stainless steel post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>	T17N	R30E	S 5	S 4	<hr/>		S 8	S 9
T17N	R30E								
S 5	S 4								
<hr/>									
S 8	S 9								
	<hr/> <p>From the cor. of secs. 4 and 9 only.</p> <p>S. 89°40'20" W., bet. secs. 4 and 9.</p> <p>Over alkali flat.</p>								
40.035	<p>Point for the <sup>1</sup>/<sub>4</sub> sec. cor. of secs. 4 and 9, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T17N</td><td>R30E</td></tr> <tr><td>S 4</td><td></td></tr> <tr><td>1/4</td><td><hr/></td></tr> <tr><td>S 9</td><td></td></tr> </table> <p style="text-align: center;">1998</p>	T17N	R30E	S 4		1/4	<hr/>	S 9	
T17N	R30E								
S 4									
1/4	<hr/>								
S 9									
80.070	<p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <p>The cor. of secs. 4, 5, 8 and 9.</p> <hr/>								
	<p>N. 0°05'30" E., bet. secs. 4 and 5.</p> <p>Over alkali flat.</p>								
40.952	<p>Point for the <sup>1</sup>/<sub>4</sub> sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T17N</td><td>R30E</td></tr> <tr><td>1/4</td><td></td></tr> <tr><td>S 5</td><td>S 4</td></tr> </table> <p style="text-align: center;">1998</p> <p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <p>Enter rolling land, covered with scattered greasewood, shadscale and native grass.</p>	T17N	R30E	1/4		S 5	S 4		
T17N	R30E								
1/4									
S 5	S 4								


DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 17 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
81.351	The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp.
	From the cor. of secs. 31 and 32 only, on the S. bdy. of the Tp. N. 0°07'10" E., bet. secs. 31 and 32. Over alkali flat.
2.40	Fence, bears NE. and SW.
7.10	Enter greasewood, shadscale and native grass.
40.000	Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.  <div style="text-align: center;">           T17N R30E  <math>\frac{1}{4}</math>            S31   S32             1996         </div>
47.70	Bladed road, bears NE. and SW.
80.000	Point for the cor. of secs. 29, 30, 31 and 32, determined at record distance latitudinally from the cor. of secs. 31 and 32 only, on the S. bdy. of the Tp. and at record distance longitudinally from the cor. of secs. 28, 29, 32 and 33. There is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.  <div style="text-align: center;">           T17N R30E            S30   S29  <hr/>           S31   S32             1996         </div>
	From the cor. of secs. 28, 29, 32 and 33. N. 88°21'00" W., bet. secs. 29 and 32. Over rolling land, covered with greasewood, shadscale and native grass.
10.00	Buried gas line, bears S. 10° E. and N. 10° W.
10.30	Bladed road, parallels gas line.
33.30	Trail road, bears NNE. and SSW.
33.40	Fence, parallels trail road.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 17 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 40.066</p>	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 29 and 32, at proportionate distance; there is no remaining evidence of the original corner.</p>
	<p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T17N R30E S29 1/4 ——— S32  1996</p>
	<p>Set a steel fence post, 5 ft. long, alongside the stainless steel post.</p>
51.60	Enter bottom land.
69.90	Bladed road, bears NNE. and SSW.
80.132	The cor. of secs. 29, 30, 31 and 32.
	<hr/>
	<p>WEST, bet. secs. 30 and 31.</p>
	<p>Over bottom land.</p>
3.350	<p>Point for the meander cor. of secs. 30 and 31, determined at record bearing and distance; there is no remaining evidence of the original corner. This cor. will now also function as Angle Pt. No. 6, Tract 37.</p>
	<p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">MC / T17N S30 ————— S31 R30E  1998</p>
	<hr/>
	<p>From the cor. of secs. 29, 30, 31 and 32.</p>
	<p>NORTH, bet. secs. 29 and 30.</p>
	<p>Over bottom land.</p>
11.600	<p>Point for the meander cor. of secs. 29 and 30, determined at record bearing and distance; there is no remaining evidence of the original corner. This cor. will now also function as Angle Pt. No. 7, Tract 37.</p>
	<p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>




DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 17 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	 <p style="text-align: center;">1998</p>
	<p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>WEST, bet. secs. 20 and 29.</p> <p>Over gently rolling land, covered with greasewood shadscale and native grass.</p>
9.60	Buried gas line, bears N. 5° E. and S. 5° W.
9.90	Improved gravel road, parallels gas line.
20.90	Fence, bears NNE. and SSW.
40.000	<p>Point for the 1/4 sec. cor. of secs. 20 and 29, determined at record bearing and distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T17N R30E S20 1/4 ——— S29  1996</p> <p>Set a steel fence post, 5 ft. long, alongside the stainless steel post.</p> <p>Enter bottom land.</p>
62.80	Bladed road, bears N. and S.
74.440	<p>Point for the meander cor. of secs. 20 and 29, determined at record bearing and distance; there is no remaining evidence of the original corner. This cor. will now also function as Angle Pt. No. 9, Tract 37.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T17N S20 MC ——— S29 R30E  1998</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 17 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>N. 87°11'40" W., bet. secs. 17 and 20.</p> <p>Over gently rolling land, covered with greasewood, shadscale and native grass.</p>
4.60	Buried gas line, bears N. 6° E. and S. 6° W.
8.50	Fence, bears NNE. and SSW.
40.048	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 17 and 20, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T17N R30E S17 1/4 <u>        </u> S20  1996</p> </div> <p>Set a steel fence post, 5 ft. long, alongside the stainless steel post.</p> <p>Enter bottom land.</p>
71.90	Bladed road, bears SSE. and NNW.
80.096	<p>Point for the cor. of secs. 17, 18, 19 and 20, determined at record distance latitudinally from the cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp. and at record distance longitudinally from the cor. of secs. 16, 17, 20 and 21. There is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T17N R30E S18   S17 <u>        </u> S19   S20  1996</p> </div> <hr/> <p>SOUTH, bet. secs. 19 and 20.</p> <p>Over bottom land.</p>
5.350	<p>Point for the meander cor. of secs. 19 and 20, determined at record bearing and distance; there is no remaining evidence of the original corner. This cor. will now also function as Angle Pt. No. 11, Tract 37.</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>


DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 17 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	 <p style="text-align: center;">T17N R30E S19 MC S20 1998</p>
0.700	<p>From the cor. of secs. 17, 18, 19 and 20. WEST, bet. secs. 18 and 19. Over bottom land.</p> <p>Point for the meander cor. of secs. 18 and 19, determined at record bearing and distance; there is no remaining evidence of the original corner. This cor. will now also function as Angle Pt. No. 12, Tract 37.</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
40.000	 <p style="text-align: center;">T17N R30E S18 MC S19 1998</p> <p>From the cor. of secs. 17, 18, 19 and 20. N. 0°01'40" W., bet. secs. 17 and 18. Over pasture land, covered with native grass, widely scattered greasewood and shadscale with willows and cattails along water ways.</p> <p>Point for the <sup>1</sup>/<sub>4</sub> sec. cor. of secs. 17 and 18, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
59.70	 <p style="text-align: center;">T17N R30E 1/4 S18   S17 1996</p> <p>Bladed road, bears SE. and NW.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 17 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS 60.30	Canal, 30 lks. wide, 2 ft. deep, parallels road.								
80.000	<p>Point for the cor. of secs. 7, 8, 17 and 18, determined at record distance latitudinally from the cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp. and at record distance longitudinally from the cor. of secs. 8, 9, 16 and 17. There is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T17N</td> <td>R30E</td> </tr> <tr> <td>S 7</td> <td>S 8</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td>S18</td> <td>S17</td> </tr> </table> <p style="text-align: center;">1996</p> <p>Set a steel fence post, 5 ft. long, alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>N. 87°37'40" W., bet. secs. 8 and 17.</p> <p>Over rolling land, covered with greasewood, shadscale and native grass.</p>	T17N	R30E	S 7	S 8			S18	S17
T17N	R30E								
S 7	S 8								
S18	S17								
9.50	Low ridge, bears SSE. and NNW.								
23.10	Improved gravel road, bears S. 14° E. and N. 14° W.								
25.80	Buried gas line, parallels gravel road.								
26.90	Fence, parallels gravel road.								
40.094	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 8 and 17, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T17N</td> <td>R30E</td> </tr> <tr> <td>S 8</td> <td></td> </tr> <tr> <td>1/4</td> <td style="border-top: 1px solid black;"></td> </tr> <tr> <td>S17</td> <td></td> </tr> </table> <p style="text-align: center;">1996</p> <p>Set a steel fence post, 5 ft. long, alongside the stainless steel post.</p> <p>Enter bottom land.</p>	T17N	R30E	S 8		1/4		S17	
T17N	R30E								
S 8									
1/4									
S17									
80.188	<p>The cor. of secs. 7, 8, 17 and 18.</p> <hr/> <p>WEST, bet. secs. 7 and 18.</p> <p>Over bottom land.</p>								

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 17 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS 6.40	Canal, 30 lks. wide, 2 ft. deep, bears SE. and NW.
6.70	Bladed road, parallels canal.
16.110	<p>Point for the meander cor. of secs. 7 and 18, determined at record bearing and distance; there is no remaining evidence of the original corner. This cor. will now also function as Angle Pt. No. 14, Tract 37.</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<div style="text-align: center;">  <p>T17N S7 MC ——— S18 R30E</p> </div> <p style="text-align: center;">1998</p> <hr/> <p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 0°16'30" E., bet. secs. 7 and 8.</p> <p>Over rolling land, covered with greasewood, shadscale and native grass.</p>
40.000	<p>Point for the <sup>1</sup>/<sub>4</sub> sec. cor. of secs. 7 and 8, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T17N R30E 1/4 S 7   S 8</p> </div> <p style="text-align: center;">1996</p> <p>Set a steel fence post, 5 ft. long, alongside the stainless steel post.</p>
66.10	Trail road, bears E. and W.
66.50	Fence, parallels road.
80.000	<p>Point for the cor. of secs. 5, 6, 7 and 8, determined at record distance latitudinally from the cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp. and at record distance longitudinally from the cor. of secs. 4, 5, 8 and 9. There is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>


## 146

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 17 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T17N R30E S 6   S 5 <hr style="width: 50%; margin: 0 auto;"/> S 7   S 8  1996  Set a steel fence post, 5 ft. long, alongside the stainless steel post.  <hr/> From the cor. of secs. 4, 5, 8 and 9.  N. 88°34'00" W., bet. secs. 5 and 8.  Over rolling land, covered with greasewood, shadscale and native grass.  24.30      Spur, slopes N.  37.70      Improved gravel road, bears N. 10° E. and S. 10° W.  38.60      Buried gas line, parallels road.  40.092     Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 8, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.  <div style="text-align: center;">             T17N R30E              S 5              1/4 <hr style="width: 50%; margin: 0 auto;"/> S 8               1998           </div> Set a steel fence post, 5 ft. long, alongside the stainless steel post.  40.90      Fence, bears NNE. and SSW.  80.184     The cor. of secs. 5, 6, 7 and 8.  <hr/> WEST, bet. secs. 6 and 7.  Over gently rolling land, covered with greasewood, shadscale and native grass.  40.000     Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 7, determined at record bearing and distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

147

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 17 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T17N R30E S 6 1/4 <math>\frac{\quad}{\quad}</math> S 7  1996</p>
	<p>Set a steel fence post, 4 ft. long, alongside the stainless steel post.</p>
40.20	Bladed road, bears N. and S.
40.50	Fence, parallels road; enter pasture.
44.00	Canal, 30 lks. wide, 2 ft. deep, bears NNE. and SSW.
75.000	<p>Point for the meander cor. of secs. 6 and 7, determined at record bearing and distance; there is no remaining evidence of the original corner. This cor. will now also function as Angle Pt. No. 17, Tract 37.</p>
	<p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;">  <p style="text-align: center;">1998</p> </div>
	<hr/> <p>From the cor. of secs. 5, 6, 7 and 8. N. 1°09'10" W., bet. secs. 5 and 6. Over gently rolling land, covered with greasewood, shadscale and native grass.</p>
40.008	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T17N R30E 1/4 S 6   S 5  1996</p>
79.326	<p>The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp.</p> <hr/>

DEPENDENT RESURVEY OF THE MEANDERS OF CARSON LAKE,  
T. 17 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

(Reestablishment of the Survey Executed by  
M.F. Reilly and T.A. Magee, U.S. Deputy Surveyors, in 1881)

From the meander cor. of sec. 31 only, on the S. bdy. of the Tp.,  
identical with Angle Pt. No. 3, Tract 37, hereinbefore described.

Thence northerly with the adjusted original meanders of sec. 31,  
identical with the bdy. bet. sec. 31 and a portion of Tract 37,  
describing a fixed and limiting boundary.

N. 43°05'20" E., 31.989 chs., Point for the adjusted position of  
Angle Pt. No. 1, and will now also  
function as Angle Pt. No. 4,  
Tract 37. Point not monumented.

N. 29°05'00" E., 28.979 chs., Point for the adjusted position of  
Angle Pt. No. 2, and will now also  
function as Angle Pt. No. 5,  
Tract 37. Point not monumented.

N. 15°49'20" E., 32.547 chs., the meander cor. of secs. 30 and  
31, identical with Angle Pt.  
No. 6, Tract 37, hereinbefore  
described.

Thence northerly with the adjusted original meander line of  
sec. 30, identical with the bdy. bet. sec. 30 and a portion of  
Tract 37, describing a fixed and limiting boundary.

N. 16°06'30" E., 12.074 chs., the meander cor. of secs. 29 and  
30, identical with Angle Pt.  
No. 7, Tract 37, hereinbefore  
described.

Thence northerly with the adjusted original meanders of sec. 29,  
identical with the bdy. bet. sec. 29 and a portion of Tract 37,  
describing a fixed and limiting boundary.

N. 8°47'30" E., 30.975 chs., Point for the adjusted position of  
Angle Pt. No. 1, and will now also  
function as Angle Pt. No. 8,  
Tract 37. Point not monumented.

N. 1°20'00" E., 34.293 chs., the meander cor. of secs. 20 and  
29, identical with Angle Pt.  
No. 9, Tract 37, hereinbefore  
described.

Thence northerly with the adjusted original meanders of sec. 20,  
identical with the bdy. bet. sec. 20 and a portion of Tract 37,  
describing a fixed and limiting boundary.

N. 3°26'40" W., 62.288 chs., Point for the adjusted position of  
Angle Pt. No. 1, and will now also  
function as Angle Pt. No. 10,  
Tract 37. Point not monumented.

DEPENDENT RESURVEY OF THE MEANDERS OF CARSON LAKE,  
T. 17 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>N. 4°52'00" W., 16.961 chs., the meander cor. of secs. 19 and 20, identical with Angle Pt. No. 11, Tract 37, hereinbefore described.</p>
	<p>Thence northerly with the adjusted original meander line of sec. 19, identical with the bdy. bet. sec. 19 and a portion of Tract 37, describing a fixed and limiting boundary.</p>
	<p>N. 7°27'20" W., 5.396 chs., the meander cor. of secs. 18 and 19, identical with Angle Pt. No. 12, Tract 37, hereinbefore described.</p>
	<p>Thence northerly with the adjusted original meanders of sec. 18, identical with the bdy. bet. sec. 18 and a portion of Tract 37, describing a fixed and limiting boundary.</p>
	<p>N. 8°19'20" W., 59.872 chs., Point for the adjusted position of Angle Pt. No. 1, and will now also function as Angle Pt. No. 13, Tract 37. Point not monumented.</p>
	<p>N. 18°05'30" W., 21.839 chs., the meander cor. of secs. 7 and 18, identical with Angle Pt. No. 14, Tract 37, hereinbefore described.</p>
	<p>Thence northerly with the adjusted original meanders of sec. 7, identical with the bdy. bet. sec. 7 and a portion of Tract 37, describing a fixed and limiting boundary.</p>
	<p>N. 24°37'40" W., 38.889 chs., Point for the adjusted position of Angle Pt. No. 1, and will now also function as Angle Pt. No. 15, Tract 37. Point not monumented.</p>
	<p>N. 49°11'00" W., 18.968 chs., Point for the adjusted position of Angle Pt. No. 2, and will now also function as Angle Pt. No. 16, Tract 37. Point not monumented.</p>
	<p>N. 40°55'10" W., 42.679 chs., the meander cor. of secs. 6 and 7, identical with Angle Pt. No. 17, Tract 37, hereinbefore described.</p>
	<p>Thence northerly with the adjusted original meanders of sec. 6, identical with the bdy. bet. sec. 6 and a portion of Tract 37, describing a fixed and limiting boundary.</p>
	<p>N. 22°50'10" E., 53.883 chs., Point for the adjusted position of Angle Pt. No. 1, and will now also function as Angle Pt. No. 18, Tract 37. Point not monumented.</p>

DEPENDENT RESURVEY OF THE MEANDERS OF CARSON LAKE,  
T. 17 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>N. 41°50'00" W., 15.023 chs., Point for the adjusted position of Angle Pt. No. 2, and will now also function as Angle Pt. No. 19, Tract 37. Point not monumented.</p>
	<p>N. 69°37'50" W., 20.022 chs., the meander cor. of secs. 1 and 6, on the W. bdy. of the Tp., identical with Angle Pt. No. 1, Tract 37 and also identical with Angle Pt. No. 11, Tract 37, T. 17 N., R. 29 E., hereinbefore described.</p>
<hr/> <p>COMPLETION SURVEY OF THE SOUTH BOUNDARY, T. 17 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>	
	<p>From the meander cor. of sec. 31 only, on the S. bdy. of the Tp., identical with Angle Pt. No. 3, Tract 37, hereinbefore described.</p> <p>WEST, on the S. bdy. of the Tp., identical with line 3-2, Tract 37.</p> <p>Over nearly level land.</p>
24.499	<p>The 80 1/16 sec. cor. of sec. 6 only, T. 16 N., R. 30 E., monumented with a stainless steel post, 2<sup>1</sup>/<sub>2</sub> ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the subdivisional lines of T. 16 N., R. 30 E., executed concurrently under this same group.</p>
36.952	<p>The cor. of Tps. 16 and 17 N., Rs. 29 and 30 E., identical with Angle Pt. No. 2, Tract 37 and also identical with Angle Pt. No. 1, Tract 37, T. 16 N., R. 29 E. and Angle Pt. No. 10, Tract 37, T. 17 N., R. 29 E., monumented with a stainless steel post, 2<sup>1</sup>/<sub>2</sub> ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. as described in the field notes of the completion survey of the E. bdy. of T. 16 N., R. 29 E., executed concurrently under this same group.</p> <p>Land, nearly level. Soil, sand and clay. Vegetation, native grass and scattered greasewood.</p>
<hr/> <p>SURVEY OF TRACT 37, T. 17 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>	
	<p>Beginning at Angle Pt. No. 1, Tract 37, identical with the meander cor. of sec. 6 only, on the W. bdy. of the Tp. and also identical with Angle Pt. No. 11, Tract 37, T. 17 N., R. 29 E., hereinbefore described.</p> <p>S. 0°20'50" W., on line 1-2, Tract 37, identical with a portion of the W. bdy. of the Tp. and also identical with line 11-10, Tract 37, T. 17 N., R. 29 E.</p>

SURVEY OF TRACT 37,  
T. 17 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS 468.756	<p>Angle Pt. No. 2, Tract 37, identical with the cor. of Tps. 16 and 17 N., Rs. 29 and 30 E. and also identical with Angle Pt. No. 1, Tract 37, T. 16 N., R. 29 E. and Angle Pt. No. 10, Tract 37, T. 17 N., R. 29 E., hereinbefore described.</p> <hr/> <p>EAST, on line 2-3, Tract 37, identical with a portion of the S. bdy. of the Tp.</p>
12.453	The 80 <sup>1</sup> / <sub>16</sub> sec. cor. of sec. 6 only, T. 16 N., R. 30 E., hereinbefore described.
36.952	<p>Angle Pt. No. 3, Tract 37, identical with the meander cor. of sec. 31 only, hereinbefore described.</p> <hr/> <p>N. 43°05'20" E., on line 3-4, Tract 37, identical with a portion of the adjusted original meanders of Carson Lake, sec. 31.</p>
31.989	<p>The point for Angle Pt. No. 4, Tract 37, identical with Angle Pt. No. 1 of the adjusted original meanders of Carson Lake, sec. 31, hereinbefore described.</p> <hr/> <p>N. 29°05'00" E., on line 4-5, Tract 37, identical with a portion of the adjusted original meanders of Carson Lake, sec. 31.</p>
28.979	<p>The point for Angle Pt. No. 5, Tract 37, identical with Angle Pt. No. 2 of the adjusted original meanders of Carson Lake, sec. 31, hereinbefore described.</p> <hr/> <p>N. 15°49'20" E., on line 5-6, Tract 37, identical with a portion of the adjusted original meanders of Carson Lake, sec. 31.</p>
32.547	<p>Angle Pt. No. 6, Tract 37, identical with the meander cor. of secs. 30 and 31, hereinbefore described.</p> <hr/> <p>N. 16°06'30" E., on line 6-7, Tract 37, identical with the adjusted original meander line of Carson Lake, sec. 30.</p>
12.074	<p>Angle Pt. No. 7, Tract 37, identical with the meander cor. of secs. 29 and 30, hereinbefore described.</p> <hr/> <p>N. 8°47'30" E., on line 7-8, Tract 37, identical with a portion of the adjusted original meanders of Carson Lake, sec. 29.</p>
30.975	<p>The point for Angle Pt. No. 8, Tract 37, identical with Angle Pt. No. 1 of the adjusted original meanders of Carson Lake, sec. 29, hereinbefore described.</p> <hr/> <p>N. 1°20'00" E., on line 8-9, Tract 37, identical with a portion of the adjusted original meanders of Carson Lake, sec. 29.</p>
34.293	<p>Angle Pt. No. 9, Tract 37, identical with the meander cor. of secs. 20 and 29, hereinbefore described.</p> <hr/>

SURVEY OF TRACT 37,  
T. 17 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	N. 3°26'40" W., on line 9-10, Tract 37, identical with a portion of the adjusted original meanders of Carson Lake, sec. 20.
62.288	The point for Angle Pt. No. 10, Tract 37, identical with Angle Pt. No. 1 of the adjusted original meanders of Carson Lake, sec. 20, hereinbefore described.
	N. 4°52'00" W., on line 10-11, Tract 37, identical with a portion of the adjusted original meanders of Carson Lake, sec. 20.
16.961	Angle Pt. No. 11, Tract 37, identical with the meander cor. of secs. 19 and 20, hereinbefore described.
	N. 7°27'20" W., on line 11-12, Tract 37, identical with the adjusted original meander line of Carson Lake, sec. 19.
5.396	Angle Pt. No. 12, Tract 37, identical with the meander cor. of secs. 18 and 19, hereinbefore described.
	N. 8°19'20" W., on line 12-13, Tract 37, identical with a portion of the adjusted original meanders of Carson Lake, sec. 18.
59.872	The point for Angle Pt. No. 13, Tract 37, identical with Angle Pt. No. 1 of the adjusted original meanders of Carson Lake, sec. 18, hereinbefore described.
	N. 18°05'30" W., on line 13-14, Tract 37, identical with a portion of the adjusted original meanders of Carson Lake, sec. 18.
21.839	Angle Pt. No. 14, Tract 37, identical with the meander cor. of secs. 7 and 18, hereinbefore described.
	N. 24°37'40" W., on line 14-15, Tract 37, identical with a portion of the adjusted original meanders of Carson Lake, sec. 7.
38.889	The point for Angle Pt. No. 15, Tract 37, identical with Angle Pt. No. 1 of the adjusted original meanders of Carson Lake, sec. 7, hereinbefore described.
	N. 49°11'00" W., on line 15-16, Tract 37, identical with a portion of the adjusted original meanders of Carson Lake, sec. 7.
18.968	The point for Angle Pt. No. 16, Tract 37, identical with Angle Pt. No. 2 of the adjusted original meanders of Carson Lake, sec. 7, hereinbefore described.
	N. 40°55'10" W., on line 16-17, Tract 37, identical with a portion of the adjusted original meanders of Carson Lake, sec. 7.
42.679	Angle Pt. No. 17, Tract 37, identical with the meander cor. of secs. 6 and 7, hereinbefore described.

SURVEY OF TRACT 37,  
T. 17 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>N. 22°50'10" E., on line 17-18, Tract 37, identical with a portion of the adjusted original meanders of Carson Lake, sec. 6.</p>
53.883	<p>The point for Angle Pt. No. 18, Tract 37, identical with Angle Pt. No. 1 of the adjusted original meanders of Carson Lake, sec. 6, hereinbefore described.</p> <hr/>
15.023	<p>N. 41°50'00" W., on line 18-19, Tract 37, identical with a portion of the adjusted original meanders of Carson Lake, sec. 6.</p> <p>The point for Angle Pt. No. 19, Tract 37, identical with Angle Pt. No. 2 of the adjusted original meanders of Carson Lake, sec. 6, hereinbefore described.</p> <hr/>
20.022	<p>N. 69°37'50" W., on line 19-1, Tract 37, identical with a portion of the adjusted original meanders of Carson Lake, sec. 6.</p> <p>Angle Pt. No. 1, Tract 37, identical with the meander cor. of sec. 6 only, on the W. bdy. of the Tp. and also identical with Angle Pt. No. 11, Tract 37, T. 17 N., R. 29 E. and point of beginning.</p> <hr/>
GENERAL DESCRIPTION	
<p>The area surveyed and resurveyed within Township 17 North, Range 30 East, varies from mountainous in the east and north portions, with the remaining terrain being gently rolling to fairly flat. The elevation ranges from 3,925 to 4,475 ft. above sea level. The soil varies from sandy clay loam and gravel to sandy clay loam and rocky in the higher elevations. The vegetation consists of sagebrush, rabbitbrush, Brigham tea and native grass.</p> <p>Access is by improved gravel roads and trail roads.</p> <hr/>	

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENTFIELD ASSISTANTS

Ronald E. Williams	Cadastral Surveyor
Daryl K. Moistner	Surveying Technician
Clay W. Morrow	Surveying Technician
Peter F. Perazzo	Surveying Technician

CERTIFICATE OF SURVEY

We, Brock R. Clifford and Thomas E. Casinger, Cadastral Surveyors, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 10th day of June, 1996, and Supplemental Special Instructions bearing date of the 30th day of April, 1998, we have dependently resurveyed portions of the south, west and north boundaries, a portion of the subdivisional lines, and the meanders of Carson Lake, and completed the survey of the south boundary, and surveyed Tract 37, Township 17 North, Range 30 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by us and under our directions; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

11/23/98

(Date)

*David J. Clark*

/For Brock R. Clifford

(Cadastral Surveyor)

11/23/98

(Date)

*Thomas E. Casinger*

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Reno, Nevada

The foregoing field notes of the dependent resurvey of portions of the south, west and north boundaries, a portion of the subdivisional lines, and the meanders of Carson Lake, and the completion survey of the south boundary, and the survey of Tract 37, Township 17 North, Range 30 East, Mount Diablo Meridian, Nevada, executed by Brock R. Clifford and Thomas E. Casinger, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

11/23/98

(Date)

*David J. Clark*

(Chief Cadastral Surveyor, Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 17 N., R. 30 E., M.D.M., Nevada, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor, Nevada)~~