

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

A PORTION OF THE SUBDIVISIONAL LINES,

THE SUBDIVISION OF SECTION 6

AND

A METES-AND-BOUNDS SURVEY IN SECTION 6,

TOWNSHIP 18 NORTH, RANGE 29 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

EXECUTED BY

Craig L. Wanless, Cadastral Surveyor

Under Special Instructions dated June 12, 2003,
and approved June 12, 2003,
which provided for the surveys included under Group No. 813,
and Assignment Instructions dated June 12, 2003

Survey commenced June 12, 2003

Survey completed June 19, 2003

INDEX DIAGRAM

TOWNSHIP 18 NORTH, RANGE 29 EAST

6 5 ²	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Subdivision of Section 6 Pages 6-12
 Metes-and-Bounds Survey in Section 6 Pages 12-13

TOWNSHIP 18 NORTH, RANGE 29 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines, the subdivision of section 6 and a metes-and-bounds survey in section 6, Township 18 North, Range 29 East, Mount Diablo Meridian, Nevada.

The south, east, north and west boundaries were surveyed by U.S. Deputy Surveyor E.B. Monroe, in 1868, under Contract No's. 10 and 19. A portion of the east boundary and portions of sections 1, 4 and 9, were surveyed and subdivided by U.S. Bureau of Reclamation Surveyor J.J. Walsh, in 1912, under Departmental Instructions dated October 24, 1906.

Before restoring the corners, the lines of the original surveys were retraced and a diligent search made for any evidence of the original corners and other calls of the original field note record.

In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 813 dated June 12, 2003.

The direction and distances of the lines of this survey were obtained by Trimble 5700 Global Positioning System (GPS) receivers using the real time kinematic method and refer to the true meridian, based on geodetic methods.

The mean bearings of the lines and horizontal equivalents of ground distances only are entered in the field notes.

The geographic position NAD 83 (1999) of the corner of sections 5, 6, 7 and 8, as determined by survey grade GPS receivers, in 2003, from National Geodetic Survey control station "C 446" located in section 33, T. 19 N., R. 29 E., is as follows:

Latitude: 39°26'44.433" N. Longitude: 118°45'46.724" W.

The 1980 mean magnetic declination is 16°30' East, as shown on U.S.G.S. quadrangle map "FALLON, NEV." provisional edition dated 1985.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 18 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">Reestablishment of a Portion of the Survey Executed by E.B. Monroe, U.S. Deputy Surveyor, in 1868</p> <hr/> <p>From the cor. of secs. 5, 6, 7 and 8, determined by person(s) unknown, monumented with an iron pipe, 1 in. diam., firmly set, 6 ins. below the asphalt surface of the intersection of Harrigan Road and Drumm Lane. This position has been adopted and recorded by various professional land surveyors, as indicated on survey records recorded in Churchill County, Nevada, and is accepted as the best available evidence of the position of the original corner.</p> <p>from which accessories established by Barry A. Fitzpatrick, Nevada Professional Land Surveyor No. 7809, in 1993, as recorded in Churchill County, Nevada, Document No. 274237, Corner Record:</p> <p style="padding-left: 40px;">A rebar, 5/8 in. diam., firmly set in a concrete post, 6 ins. diam., projecting 8 ins. above the ground, bears N. 49°50'50" E., 78.8 lks. dist.</p> <p style="padding-left: 40px;">A rebar, 5/8 in. diam., firmly set in a concrete post, 6 ins. diam., projecting 8 ins. above the ground, bears S. 72°23'20" W., 104.6 lks. dist.</p> <p>The corner is located at the eastern side of Harrigan Road, asphalt surface, 60 lks. wide, bears N. and S., and S., 5 lks. dist., from the centerline of Drumm Lane, asphalt surface, 30 lks. wide, extending E.</p> <p>From this point, National Geodetic Survey control station "C 446" monumented with a brass tablet, 3 ins. diam., firmly set in concrete, flush with the surface of the ground, with top mkd. U.S. NAVY GEOTHERMAL BENCHMARK NO. C 446 1991 SURVEY, bears N. 35°22'00" E., (mean bearing), 145.623 chs. dist.</p> <p>N. 0°35'30" E., bet. secs. 5 and 6.</p>
20.091	<p>The S 1/16 sec. cor. of secs. 5 and 6, monumented with a steel nail and metal washer, firmly set at the eastern edge of asphalt surface of Harrigan Road, 60 lks. wide, bears N. and S. This position was determined by Wallace A. Cooper, Nevada Professional Land Surveyor No. 749, in 1955, as recorded in Churchill County, Nevada, Book 1, Page 11, of subdivisions, was subsequently redetermined by person(s) unknown and has been adopted and recorded by various professional land surveyors, as indicated on land survey records recorded in Churchill County, Nevada. This is accepted as a careful and faithful determination of the position of the corner.</p>

273

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 18 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS					
	<p>from which</p> <p>A brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, set in a drill hole of concrete bridge abutment, for a reference monument, bears N. 52°27'00" E., 58.6 lks. dist., with the top mkd. RM S 1/16 S5 38.7 FT TO COR 2003 and an arrow pointing to the corner.</p> <p>A brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, set in a drill hole in the right abutment of Check Structure No. L4-1, for a reference monument, bears S. 37°15'00" E., 74.1 lks. dist., with the top mkd. RM S 1/16 S5 48.9 FT TO COR 2003 and an arrow pointing to the corner.</p> <hr/>				
5.530	<p>N. 0°33'10" E., beginning new measurement.</p> <p>Point for Angle Point No. 3, of a metes-and-bounds survey in sec. 6.</p>				
	<p>Set a copper-coated steel stake, 24 ins. long, 24 ins. in the ground, with top mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: center;">S 6</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;">S 5</td> </tr> <tr> <td style="text-align: center;">AP 3</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;">2003</td> </tr> </table>	S 6	S 5	AP 3	2003
S 6	S 5				
AP 3	2003				
	<p>from which</p> <p>A magnetic steel nail and metal washer, driven into concrete bridge abutment, for a reference monument, bears N. 48°33'00" E., 76.8 lks. dist., with washer mkd. RM1 2003.</p> <p>A bolt in a metal washer on a concrete structure, bears S. 59°52'00" E., 92.6 lks. dist. Add the marks RM2 2003 to the washer.</p>				
20.073	<p>The 1/4 sec. cor. of secs. 5 and 6, monumented with a rebar, 5/8 in. diam., firmly set, 4 ins. below the asphalt surface of Harrigan Road. This position was determined by Wallace A. Cooper, Nevada Professional Land Surveyor No. 749, in 1955, as recorded in Churchill County, Nevada, Book 1, Page 11, of subdivisions, and was subsequently perpetuated, adopted and recorded by various professional land surveyors, as indicated on survey records recorded in Churchill County, Nevada. This position is accepted as the best available evidence of the position of the original corner.</p>				

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 18 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

from which an accessory established by Barry A. Fitzpatrick, Nevada Professional Land Surveyor No. 7809, in 1993, as recorded in Churchill County, Nevada, Document No. 274238, Corner Record:

A rebar, 5/8 in. diam., firmly set in a concrete post, 4 ins. diam., projecting 6 ins. above the ground, bears S. 73°44'30" W., 168.9 lks. dist.

and from which

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 28 ins. in the ground, for a reference monument, bears N. 42°53'10" E., 46.2 lks. dist., with brass cap mkd. RM 1/4 S5 T18N R29E 30.5 FT TO COR 2003 and an arrow pointing to the cor.

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 42°52'50" E., 44.5 lks. dist., with brass cap mkd. RM 1/4 S5 T18N R29E 29.4 FT TO COR 2003 and an arrow pointing to the cor.

Deposit a magnet in a white plastic case at the base of each stainless steel post.

Both reference monuments fall in fence line, bears N. and S.

The corner is located at the eastern edge of the asphalt surface of Harrigan Road, 60 lks. wide, bears N. and S.

From this corner, the N 1/16 sec. cor. of secs. 5 and 6, monumented with a steel nail, firmly set, in the asphalt surface of Harrigan Road, bears N. 0°32'20" E., 20.329 chs. dist. This position was determined by Roger D. Glidden, Nevada Professional Land Surveyor No. 3202, in 1974, as recorded in Churchill County, Nevada, Document No. 136900, Book 1, Page 43, of records of surveys, and was subsequently redetermined, adopted and recorded by various professional land surveyors, as indicated on survey records recorded in Churchill County, Nevada. This is accepted as a careful and faithful determination of the position of the corner.

The cor. is located W., 2 lks. dist., from the eastern edge of asphalt surface of Harrigan Road, 60 lks. wide, bears N. and S.

From this corner, the cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., bears N. 0°33'00" E., 20.444 chs. dist., set by Barry A. Fitzpatrick, Nevada Professional Land Surveyor No. 7809, in 1992, monumented with a steel nail and metal washer mkd. 7809, firmly set in the asphalt surface of Harrigan Road as recorded in Churchill County, Nevada, Document No. 271234, Book 18, Page 47, of parcel maps. This position has been adopted and recorded by various professional

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 18 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p>	<p>land surveyors, as indicated on survey records recorded in Churchill County, Nevada, and is accepted as the best available evidence of the position of the original corner.</p> <p>The cor. is located on the eastern side of a concrete bridge on Harrigan Road, 60 lks. wide, bears N. and S., and over the centerline of canal, bears E. and W.</p> <hr/> <p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 89°42'10" W., bet. secs. 6 and 7.</p> <p>Over nearly level land, along Drumm Lane.</p> <p>20.019 The E 1/16 sec. cor. of secs. 6 and 7, determined by person(s) unknown, monumented with a steel nail and metal washer, firmly set in Drumm Lane. This position has been adopted and recorded by various professional land surveyors, as indicated on survey records recorded in Churchill County, Nevada, and is accepted as a careful and faithful determination of the position of the corner.</p> <p>The cor. is located in centerline of Drumm Lane, asphalt surface, 30 lks. wide, bears E. and W.</p> <hr/> <p>N. 89°42'30" W., beginning new measurement.</p> <p>20.014 The 1/4 sec. cor. of secs. 6 and 7, determined by person(s) unknown, monumented with a steel nail and metal washer set in Drumm Lane. This position has been adopted and recorded by various professional land surveyors, as indicated on survey records recorded in Churchill County, Nevada, and is accepted as the best available evidence of the position of the original corner.</p> <p>from which accessories established by Barry A. Fitzpatrick, Nevada Professional Land Surveyor No. 7809, in 1993, as recorded in Churchill County, Nevada, Document No. 274236, Corner Record:</p> <p style="padding-left: 40px;">A rebar, 5/8 in. diam., firmly set in a concrete post, 4 ins. diam., projecting 6 ins. above the ground, bears S. 43°33'00" W., 52.4 lks. dist.</p> <p style="padding-left: 40px;">A rebar, 5/8 in. diam., firmly set in a concrete post, 4 ins. diam., projecting 6 ins. above the ground, bears N. 48°23'50" W., 58.4 lks. dist.</p> <p>The corner is located N., 8 lks. dist., from the southern edge of asphalt surface of Drumm Lane, 30 lks. wide, bears E. and W.</p>
---------------	---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 18 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From this corner, the cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., reestablished by Barry A. Fitzpatrick, Nevada Professional Land Surveyor No. 7809, in 1997, monumented with a railroad spike, firmly set, flush with the asphalt surface of the intersection of U.S. Highway No. 95 and Drumm Lane, the top mkd. 7809, as recorded in Churchill County, Nevada, Document No. 310762, Book 10, Page 2, of records of survey, bears N. 89°50'50" W., 39.483 chs. dist. This position has been adopted and recorded by various professional land surveyors, as indicated on survey records recorded in Churchill County, Nevada, and is accepted as a careful and faithful reestablishment of the position of the corner.</p>
	<p>The corner is located at intersection of the eastern side of U.S. Highway No. 95, asphalt surface, 60 lks. wide, bears N. and S., and S., 5 lks. dist., from the centerline of Drumm Lane, asphalt surface, 30 lks. wide, extending E.</p>
	<hr/> <p>SUBDIVISION OF SECTION 6, T. 18 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 6 and 7.</p> <p>N. 0°09'20" W., on the N. and S. center line of sec. 6.</p> <p>Over nearly level land along dirt road.</p>
20.021	<p>The center S 1/16 sec. cor. of sec. 6, determined by person(s) unknown monumented with a rebar, 5/8 in. diam., firmly set, 2 ins. below the surface of dirt road, 15 lks. wide, bears N. and S. This position has been adopted and recorded by various professional land surveyors, as indicated on survey records recorded in Churchill County, Nevada, and is accepted as a careful and faithful determination of the position of the corner.</p>
	<p>N. 0°08'50" W., beginning new measurement.</p>
20.018	<p>The center 1/4 sec. cor. of sec. 6, determined by person(s) unknown, monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of dirt road, 15 lks. wide, bears N. and S., with brass cap mkd. C 1/4 S6 1960 PLS 1251 as recorded in Churchill County, Nevada, Document No. 241572, Book 6, Page 37, of records of surveys. This position has been adopted and recorded by various professional land surveyors, as indicated on survey records recorded in Churchill County, Nevada, and is accepted as a careful and faithful determination of the position of the corner.</p>

SUBDIVISION OF SECTION 6,
T. 18 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	N. 0°09'30" W., beginning new measurement.
20.369	<p>The center N 1/16 sec. cor. of sec. 6, determined by Lowell D. Emery, Nevada Professional Land Surveyor No. 1251, in 1988, monumented with a rebar, 5/8 in. diam., firmly set, projecting 1 in. above the surface of dirt road, 15 lks. wide, bears N. and S., as recorded in Churchill County, Nevada, Document No. 241572, Book 6, Page 37, of records of survey. This position is accepted as a careful and faithful determination of the position of the corner.</p> <hr/>
	N. 0°09'00" W., beginning new measurement.
19.705	<p>A witness corner to the 1/4 sec. cor. of secs. 6 and 31, on the N. bdy. of the Tp., established by person(s) unknown, adopted by Lowell D. Emery, Nevada Professional Land Surveyor No. 1251, in 1983, monumented with a rebar, 1/2 in. diam., firmly set, 1 in. below the asphalt surface of Wildes Road, 40 lks. wide, bears E. and W., as recorded in Churchill County, Nevada, Document No. 194109, Book 4, Page 23, of records of survey.</p> <hr/>
	N. 0°09'00" W., beginning new measurement.
0.727	<p>Point for the 1/4 sec. cor. of secs. 6 and 31, on the N. bdy. of the Tp., determined at record distance from the witness corner and projected bearing from the center N 1/16 sec. cor. of sec. 6, through the witness corner, as recorded in Churchill County, Nevada, Document No. 241572, Book 6, Page 37, of records of survey. This position has been adopted and recorded by various professional land surveyors, as indicated on survey records recorded in Churchill County, Nevada, and is accepted as the best available evidence of the position of the original corner.</p> <p>The corner is located in canal, bears E. and W., where it is impractical to establish a permanent monument.</p> <p>From this point, the cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., bears S. 89°50'40" E., 41.029 chs. dist., hereinbefore described.</p> <p>From this same point, the cor. of Tps. 18 and 19 N., Rs. 28 and 29 E., determined by person(s) unknown, bears N. 89°53'40" W., 39.158 chs. dist., monumented with a railroad spike, firmly set, 2 ins. below the asphalt surface of U.S. Highway No. 95. This position has been adopted and recorded by various professional land surveyors, as indicated on survey records recorded in Churchill County, Nevada, and is accepted as the best available evidence of the position of the original corner.</p>

SUBDIVISION OF SECTION 6,
T. 18 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>N. 89°53'00" W., beginning new measurement.</p>
20.267	<p>The center 1/4 sec. cor. of sec. 6.</p> <hr/>
	<p>N. 89°57'20" W., beginning new measurement.</p>
39.352	<p>The 1/4 sec. cor. of secs. 1 and 6, on the W. bdy. of the Tp., determined by person(s) unknown, monumented with a rebar, 5/8 in. diam., firmly set, 3 ins. below the graveled surface of the eastern shoulder of U.S. Highway No. 95. This position has been adopted and recorded by various professional land surveyors, as indicated on survey records recorded in Churchill County, Nevada, and is accepted as the best available evidence of the position of the original corner.</p> <p>The corner is located E., 14 lks. dist., from the eastern edge of asphalt surface of U.S. Highway No. 95, 60 lks. wide, bears N. and S.</p> <p>From this corner, the cor. of Tps. 18 and 19 N., Rs. 28 and 29 E., bears N. 0°06'50" E., 40.843 chs. dist., hereinbefore described.</p> <p>From this same corner, the cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., bears S. 0°01'50" W., 39.964 chs. dist., hereinbefore described.</p> <hr/>
	<p>From the E 1/16 sec. cor. of secs. 6 and 7.</p> <p>N. 0°14'20" E., on the N. and S. center line of the SE1/4 of sec. 6.</p>
20.057	<p>Continue over nearly level land, through residential area.</p> <p>The SE 1/16 sec. cor. of sec. 6, determined by person(s) unknown, monumented with a rebar, 5/8 in. diam., firmly set in concrete post, 6 ins. diam., 4 ins. below the surface of the ground. This position has been adopted and recorded by various professional land surveyors, as indicated on survey records recorded in Churchill County, Nevada, and is accepted as a careful and faithful determination of the position of the corner.</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 28 ins. in the ground, for a reference monument, bears S. 41°36'50" E., 9.4 lks. dist., with brass cap mkd. RM SE 1/16 S6 6.2 FT TO COR 2003 and an arrow pointing to the corner.</p>

SUBDIVISION OF SECTION 6,
T. 18 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 88°44'40" W., 9.7 lks. dist., with brass cap mkd. RM SE 1/16 S6 6.4 FT TO COR 2003 and an arrow pointing to the corner.</p> <p>Deposit a magnet in a white plastic case at the base of each of the stainless steel posts.</p> <p>The corner is located at intersection of fence lines, extending E., W. and S.</p> <hr/> <p>N. 0°11'10" E., beginning new measurement.</p> <p>Ascend over S. slope.</p>
0.15	Top of southern bank of "Ld" drain; over drain.
0.90	Top of northern bank of "Ld" drain; continue over nearly level land, along eastern edge of residential area.
1.00	Intersection of fence lines, extending N. and W.
2.208	A property corner, established by Lowell D. Emery, Nevada Professional Land Surveyor No. 1251, in 1980, monumented with a rebar, 5/8 in. diam., firmly set, 2 ins. below the surface of the ground, as recorded in Churchill County, Nevada, Document No. 171318, Book 6, Page 24, of parcel maps.
6.252	A property corner, established by Lowell D. Emery, Nevada Professional Land Surveyor No. 1251, in 1980, monumented with a rebar, 5/8 in. diam., firmly set, 4 ins. below the surface of the ground, as recorded in Churchill County, Nevada, Document No. 172672, Book 6, Page 43, of parcel maps.
8.528	A property corner, established by Lowell D. Emery, Nevada Professional Land Surveyor No. 1251, in 1980, monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, as recorded in Churchill County, Nevada, Document No. 172672, Book 6, Page 43, of parcel maps.
10.742	A property corner, established by Lowell D. Emery, Nevada Professional Land Surveyor No. 1251, in 1980, monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, as recorded in Churchill County, Nevada, Document No. 172672, Book 6, Page 43, of parcel maps.
12.952	A property corner, established by Lowell D. Emery, Nevada Professional Land Surveyor No. 1251, in 1980, monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, as recorded in Churchill County, Nevada, Document No. 173684, Book 7, Page 13, of parcel maps.

SUBDIVISION OF SECTION 6,
T. 18 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 15.160</p>	<p>A property corner, established by Lowell D. Emery, Nevada Professional Land Surveyor No. 1251, in 1980, monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, as recorded in Churchill County, Nevada, Document No. 173684, Book 7, Page 13, of parcel maps.</p>
<p>19.587</p>	<p>A property corner, established by Lowell D. Emery, Nevada Professional Land Surveyor No. 1251, in 1980, monumented with a rebar, 5/8 in. diam., firmly set, projecting 4 ins. above the ground, as recorded in Churchill County, Nevada, Document No. 171318, Book 6, Page 24, of parcel maps.</p>
<p>20.043</p>	<p>The center E 1/16 sec. cor. of sec. 6.</p> <hr/> <p>From the S 1/16 sec. cor. of secs. 5 and 6.</p> <p>N. 89°48'00" W., on the E. and W. center line of the SE1/4 of sec. 6.</p> <p>Continue over nearly level land.</p>
<p>6.330</p>	<p>Point for Angle Point No. 1, of a metes-and-bounds survey in sec. 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a magnet in a white plastic case, with brass cap mkd.</p> <div style="text-align: center;"> <p style="margin-left: 100px;">2003</p> </div> <p>from which</p> <p style="margin-left: 40px;">A copper-coated steel stake, 24 ins. long, set 24 ins. in the ground, for a reference monument, bears N. 54°54'50" E., 17.5 lks. dist., with top mkd. RM AP1 S6 2003 and an arrow pointing to the corner.</p> <p style="margin-left: 40px;">A copper-coated steel stake, 24 ins. long, set 24 ins. in the ground, for a reference monument, bears N. 56°28'10" W., 17.7 lks. dist., with top mkd. RM AP1 S6 2003 and an arrow pointing to the corner.</p>
<p>8.50</p>	<p>Top of northeastern bank of "Ld" drain; over drain.</p>
<p>9.70</p>	<p>Top of southwestern bank of "Ld" drain; continue over nearly level land.</p>

SUBDIVISION OF SECTION 6,
T. 18 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
10.464	<p>A property corner, established by Barry A. Fitzpatrick, Nevada Professional Land Surveyor No. 7809, in 1992, monumented with a rebar, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with plastic cap mkd. PLS 7809, as recorded in Churchill County, Nevada, Document No. 272074, Book 19, Page 13, of parcel maps.</p> <p>The corner is located at intersection of fence lines, extending E., W. and S.</p>
14.176	<p>A property corner, established by Barry A. Fitzpatrick, Nevada Professional Land Surveyor No. 7809, in 1992, monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, as recorded in Churchill County, Nevada, Document No. 272074, Book 19, Page 13, of parcel maps.</p> <p>The corner is located at intersection of fence lines, extending E., W. and S.</p>
16.805	<p>From this point, a property corner, established by Lowell D. Emery, Nevada Professional Land Surveyor No. 1251, in 1991, bears S., 2.3 lks. dist., monumented with a rebar, 5/8 in. diam., firmly set, 2 ins. below the surface of the ground, as recorded in Churchill County, Nevada, Document No. 262236, Book 8, Page 3, of records of survey.</p> <p>The corner is located in a fence line, bears E. and W.</p>
20.142	<p>The SE 1/16 sec. cor. of sec. 6.</p> <hr/> <p>N. 89°48'50" W., beginning new measurement.</p>
20.151	<p>The center S 1/16 sec. cor. of sec. 6.</p> <hr/> <p style="text-align: center;">A METES-AND-BOUNDS SURVEY IN SECTION 6, T. 18 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From Angle Point No. 1, on the E. and W. center line of the SE1/4 of sec. 6, hereinbefore described.</p> <p>N. 0°33'10" E., on line 1-2.</p>
5.530	<p>Point for Angle Point No. 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 30 ins. in the ground, with brass cap mkd.</p>

A METES-AND-BOUNDS SURVEY IN SECTION 6,
T. 18 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

S 6

AP 2

2003

from which

A copper-coated steel stake, 24 ins. long, set 22 ins. in the ground, for a reference monument, bears N. $72^{\circ}58'10''$ E., 136.7 lks. dist., with top mkd. RM AP2 S6 2003 and an arrow pointing to the corner.

A copper-coated steel stake, 24 ins. long, set 22 ins. in the ground, for a reference monument, bears S. $46^{\circ}46'40''$ E., 107.7 lks. dist., with top mkd. RM AP2 S6 2003 and an arrow pointing to the corner.

Thence S. $89^{\circ}48'00''$ E., on line 2-3.

6.330

Angle Point No. 3, on the line bet. secs. 5 and 6, hereinbefore described.

GENERAL DESCRIPTION

The lands included in this survey are located in the city of Fallon, Churchill County, Nevada. The area can be accessed by way of U.S. Highway No. 95 and several asphalt surfaced roads.

The area is mainly residential. The average elevation is 3950 feet above sea level.

No mining activities of any consequence were noted during the course of the survey.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANT

Clay W. Morrow

Surveying Technician

CERTIFICATE OF SURVEY

I, Craig L. Wanless, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 12th day of June, 2003, I have dependently resurveyed a portion of the subdivisional lines, subdivided section 6 and executed a metes-and-bounds survey in section 6, Township 18 North, Range 29 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

September 3, 2003

(Date)

Craig Wanless
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of the dependent resurvey of a portion of the subdivisional lines, the subdivision of section 6 and a metes-and-bounds survey in section 6, Township 18 North, Range 29 East, Mount Diablo Meridian, Nevada, executed by Craig L. Wanless, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

September 4, 2003

(Date)

David J. Clark
Acting (Chief Cadastral Surveyor, Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 18 N., R. 29 E., Mount Diablo Meridian, Nevada, is a true copy of the original field notes.~~

~~_____
(Date)~~

~~_____
(Chief Cadastral Surveyor, Nevada)~~