

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF A PORTION OF THE SUBDIVISIONAL LINES,

THE SUBDIVISION OF SECTION 16,

AND

METES-AND-BOUNDS SURVEYS IN SECTION 16,

TOWNSHIP 35 NORTH, RANGE 37 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

EXECUTED BY

Lance A. Barney, Cadastral Surveyor

Mark G. Petrosine, Surveying Technician

Under Special Instructions dated April 11, 2006,

and approved April 11, 2006,

which provided for the surveys included under Group No. 835,

and Assignment Instructions dated July 12, 2006.

Survey commenced July 13, 2006

Survey completed July 28, 2006

INDEX DIAGRAM

TOWNSHIP 35 NORTH, RANGE 37 EAST, MOUNT DIABLO MERIDIAN, NEVADA

6	5	4	3	2	1
7	8	9 4	10	11	12
18	17	3 16	2 15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Subdivision of Section 16 pp. 6 - 8.
 Metes-and-Bounds Survey of the Southerly Right-of-Way Line
 of the Union Pacific Railroad through Section 16 pp. 8 - 9.
 Metes-and-Bounds Survey of the Northerly Right-of-Way Line
 of the Union Pacific Railroad through Section 16 pp. 9 - 10.
 Metes-and-Bounds Survey of Old U.S. Highway No. 40, through
 the NE1/4 of the NW1/4 of Section 16 pp. 10 - 11.

TOWNSHIP 35 NORTH, RANGE 37 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines, the subdivision of section 16, and metes-and-bounds surveys in section 16, Township 35 North, Range 37 East, Mount Diablo Meridian, Nevada.

The north (Seventh Standard Parallel North), east, south, and west boundaries were surveyed by U.S. Deputy Surveyor W. Epler in 1867 under Contract No. 5. The subdivisional lines were surveyed by U.S. Deputy Surveyor A.J. Hatch in 1868 under Contract No. 14. The west boundary of section 6 was dependently resurveyed by U.S. Deputy Surveyor H.B. Maxon in 1888 under Contract No. 189. The north boundary (Seventh Standard Parallel North), the south and west boundaries and the north five miles of the east boundary and a portion of the subdivisional lines were dependently resurveyed by Cadastral Surveyor J.R. Munson in 1965 under Group No. 427.

Before restoring the corners, the lines of the original surveys were retraced and a diligent search made for any evidence of the original corners and other calls of the original field note record.

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 835, dated April 11, 2006.

Measurements were made with Trimble 5800 Global Positioning System (GPS) receivers using the real-time kinematics' method and refer to the true meridian based on geodetic methods. The mean bearings of the lines and horizontal equivalents of ground distances only are entered in the field notes.

The NAD 83 geographic position of the 1/4 section corner of section 15 and 16, determined from Global Positioning system (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) "GARLIC CORS ARP", "SHELDON REFUGE CORS ARP" and "TUNGSTEN CORS ARP" in 2006, is as follows:

Latitude: 40°54'30.639" N. Longitude: 117°48'49.809" W.

The mean magnetic declination is 17° E, as shown on U.S.G.S. quadrangle map "WINNEMUCCA WEST, NEVADA", dated 1982.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 35 N., R. 37 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor A.J. Hatch in 1868 and a Portion of the Dependent Resurvey Executed by Cadastral Surveyor J.R. Munson in 1965</p> <hr/>
	<p>Beginning at the 1/4 sec. cor. of secs. 15 and 16, monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone, 2 1/2 ft. base, 4 ins. high, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 35 N., R. 37 E., executed under Group No. 427.</p>
	<p>N. 0°45'30" W., bet. secs. 15 and 16.</p>
	<p>Over nearly level land through scattered sagebrush.</p>
5.00	<p>From this point, a corner of barbed wire fences extending S. and S. 63° W., bears W., 0.15 chs. dist.</p>
5.20	<p>Graded dirt road, 10 lks. wide, bears N. 63° E. and S. 63° W.</p>
12.00	<p>Corner of barbed wire fences extending N. and E.</p>
21.076	<p>The N 1/16 sec. cor. of secs. 15 and 16, determined by John H. Milton, Nevada Professional Land Surveyor No. 5271, monumented with a rebar, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with plastic cap mkd. J.H. Milton, PLS 5271, as recorded in Humboldt County, Nevada, Document No. 2001 3312. This is accepted as a careful and faithful determination of the position of the corner.</p>
	<p>At the corner point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">N 1/16 S16 S15</p>
	<p style="text-align: center;">2006</p>
	<p>Deposit rebar inside stainless steel post.</p>
	<p>Corner is located on W. side of corner of barbwire fences extending S. and E.</p> <hr/>
	<p>N. 0°45'40" W., beginning new measurement.</p>
	<p>Over nearly level land through scattered sage.</p>
0.20	<p>Powerline, bears N. 59° W. and S. 59° E.</p>
7.239	<p>Point for the witness point at intersection with the southerly right-of-way line of Union Pacific Railroad, hereinafter described.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 35 N., R. 37 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
7.24	Barbed wire fence, wooden posts, bears N. 66° E., and S. 66° W.
10.535	Center of railroad tracks, bears N. 66°04'00" E., and S. 66°04'00" W.
13.83	Barbed wire fence, wooden posts, bears N. 66° E., and S. 66° W.
13.831	Point for the witness point at intersection with the northerly right-of-way line of Union Pacific Railroad, hereinafter described.
21.076	The cor. of secs. 9, 10, 15 and 16, monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone, 2 1/2 ft. base, 6 ins. high, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 35 N., R. 37 E., executed under Group No. 427.
	From the cor. of secs. 16, 17, 20 and 21, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 35 N., R. 37 W., executed under Group No. 427. Mound of stone 3 ft. base, 2 ft. high, W. of iron post.
	N. 0°16'40" W., bet. secs. 16 and 17.
	Over nearly level land through scattered sagebrush.
1.90	Graded dirt road, 10 lks. wide, bears N. 63° E., S. 63° W. Powerline along N. side dirt road.
30.82	Barbed wire fence, wooden posts, bears N. 66° E., and S. 66° W.
30.826	Point for the witness point at intersection with the southerly right-of-way line of Union Pacific Railroad, hereinafter described.
34.135	Center of railroad tracks, bears N. 66°04'00" E., and S. 66°04'00" W.
37.43	Barbed wire fence, wooden posts, bears N. 66° E., and S. 66° W.
37.443	Point for the witness point at intersection with the northerly right-of-way line of Union Pacific Railroad, hereinafter described.
40.585	The 1/4 sec. cor. of secs. 16 and 17, monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone, 2 1/2 ft. base, 4 ins. high, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 35 N., R. 37 E., executed under Group No. 427.
	N. 0°17'20" W., beginning new measurement.
	Over nearly level land through scattered sage.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 35 N., R. 37 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.320	<p>The N 1/16 sec. cor. of secs. 16 and 17, determined by Robert N. Caldwell, Nevada Professional Land Surveyor No. 4233, monumented with a rebar, 5/8 in. diam., flush with the ground, with 2 in. diam. aluminum cap mkd. ROBERT N. CALDWELL, PLS 4233, as recorded in Humboldt County, Nevada, File 182552. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S17 S16</p> <p style="text-align: center;">2006</p> <p>Deposit rebar inside stainless steel post.</p> <p>Corner is located at corner of fences extending N. and E.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°17'20" W., beginning new measurement.</p> <p>Over nearly level land.</p>
6.09	<p>Center of Old U.S. Highway No. 40, bears N. 67°29' E. and S. 67°29' W.</p>
20.319	<p>The cor. of secs. 8, 9, 16 and 17, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, at corner of fences extending N., E., S., and W., with brass cap mkd. as described in the field notes of the dependent resurvey of T. 35 N., R. 37 E., executed under Group No. 427.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>N. 88°58'10" W., bet. secs. 9 and 16.</p> <p>Over nearly level land through scattered sagebrush.</p>
39.593	<p>The 1/4 sec. cor. of secs. 9 and 16, determined by John H. Milton, Nevada Professional Land Surveyor No. 5271, monumented with a rebar, 5/8 in. diam., firmly set, projecting 2 ins. above a mound of stone, 2 1/2 ft. base, 1 ft. high, with plastic cap mkd. J.H. Milton, PLS 5271, as recorded in Humboldt County, Nevada, Document No. 1997 8272. This is accepted as a careful and faithful reestablishment of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a mound of stone, 2 1/2 ft. base, to top, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 35 N., R. 37 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p> <p>14.324</p> <p>19.791</p> <p>39.582</p>	<p style="text-align: center;">T35N R37E S 9 1/4 $\frac{\quad}{\quad}$ S16</p> <p style="text-align: center;">2006</p> <p>Deposit rebar inside stainless steel post.</p> <hr style="width: 30%; margin: auto;"/> <p>N. 88°55'50" W., beginning new measurement.</p> <p>Over nearly level land through scattered sagebrush.</p> <p>Point for the witness point at intersection with the centerline of Old U.S. Highway No. 40, hereinafter described.</p> <p>Point for the W 1/16 sec. cor. of secs. 9 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">W 1/16 $\frac{\quad}{\quad}$ S 9 S16</p> <p style="text-align: center;">2006</p> <p>The cor. of secs. 8, 9, 16 and 17.</p>
<p>SUBDIVISION OF SECTION 16, T. 35 N., R. 37 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>	
<p>26.70</p> <p>26.80</p> <p>44.060</p>	<p>From the 1/4 sec. cor. of secs. 16 and 21, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 35 N., R. 37 E., executed under Group No. 427. Mound of stone 2 ft. base, 12 ins. high, N. of iron post.</p> <p>N. 0°29'00" E., on the N-S center line of sec. 16.</p> <p>Over nearly level land through scattered sagebrush.</p> <p>Powerline bears N. 63° E., S. 63° W.</p> <p>Graded dirt road, 10 lks. wide, bears N. 63° E., S. 63° W. Road parallels powerline.</p> <p>The center 1/4 sec. cor. of sec. 16, determined by John H. Milton, Nevada Professional Land Surveyor No. 5271, monumented with a rebar, 5/8 in. diam., flush with ground, with plastic cap mkd. J.H. Milton, PLS 5271, as recorded in Humboldt County, Nevada, Document No. 1997 8272. This is accepted as a careful and faithful determination of the position of the corner.</p>

SUBDIVISION OF SECTION 16,
T. 35 N., R. 37 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T35N R37E C 1/4 S16</p> <p style="text-align: center;">2006</p> <p>Deposit rebar inside stainless steel post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°26'30" E., beginning new measurement.</p> <p>Over nearly level land through scattered sagebrush.</p> <p>7.754 The C-N-S-S-N 1/1024 sec. cor. of sec. 16, determined by John H. Milton, Nevada Professional Land Surveyor No. 5271, monumented with a rebar, 5/8 in. diam., flush with ground, with plastic cap mkd. J.H. Milton, PLS 5271, as recorded in Humboldt County, Nevada, Document No. 1997 8272. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">1/1024</p> <p style="text-align: center;">2006</p> <p>Deposit rebar inside stainless steel post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°28'40" E., beginning new measurement.</p> <p>Over nearly level land through scattered sagebrush.</p> <p>1.279 Intersect the southerly right-of-way line of Union Pacific Railroad.</p> <p>1.28 Barbed wire fence, wooden posts, bears N. 66° E., and S. 66° W.</p> <p>4.607 Center of railroad tracks, bears N. 66°04'00" E., and S. 66°04'00" W.</p> <p>7.93 Barbed wire fence, wooden posts, bears N. 66° E., and S. 66° W.</p> <p>7.935 Intersect the northerly right-of-way line of Union Pacific Railroad.</p> <p>12.923 Point for the C-N 1/16 sec. cor. of sec. 16, determined at proportionate distance utilizing the record of John H. Milton, Nevada Professional Land Surveyor No. 5271, as recorded in Humboldt County, Nevada, Document No. 1997 8272.</p>
--------	---

SUBDIVISION OF SECTION 16,
T. 35 N., R. 37 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;"> $\begin{array}{c} C \\ N\ 1/16 \quad \quad S16 \\ C \end{array}$ </p> <p style="text-align: center;">2006</p>
33.599	<p>The 1/4 sec. cor. of secs. 9 and 16.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 15 and 16.</p> <p>N. 87°52'00" W., on the E-W center line of sec. 16.</p> <p>Over nearly level land through scattered sagebrush.</p>
9.10	Barbed wire fence, steel posts, bears N. 63° E., and S. 63° W.
9.30	Graded dirt road, 10 lks. wide, bears N. 63° E., and S. 63° W.
20.00	Overhead powerline, bears N. 26° W. and S. 26° E.
40.518	<p>The center 1/4 sec. cor. of sec. 16.</p> <hr/> <p>N. 87°52'00" W., beginning new measurement.</p> <p>Over nearly level land through scattered sage.</p>
18.720	Intersect the southerly right-of-way line of Union Pacific Railroad.
18.77	Barbed wire fence, wooden posts, bears N. 66° E., and S. 66° W.
19.531	Point for the C-W 1/16 sec. cor. of sec. 16, not monumented.
25.616	Center of railroad tracks, bears N. 66°04'00" E., and S. 66°04'00" W.
32.50	Barbed wire fence, wooden posts, bears N. 66° E., and S. 66° W.
32.512	Intersect the northerly right-of-way line of Union Pacific Railroad.
39.062	<p>The 1/4 sec. cor. of secs. 16 and 17.</p> <hr/> <p>From the point for the C-W 1/16 sec. cor. of sec. 16.</p> <p>N. 0°05'50" E., on the N-S center line of the NW1/4 of sec. 16.</p> <p>Over nearly level land through scattered sagebrush.</p>
2.928	Center of railroad tracks, bears N. 66°04'00" E., and S. 66°04'00" W.
6.22	Barbed wire fence, wooden posts, bears N. 66° E., and S. 66° W.

SUBDIVISION OF SECTION 16,
T. 35 N., R. 37 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
6.246	Intersect the northerly right-of-way line of Union Pacific Railroad.
20.496	<p>The NW 1/16 sec. cor. of sec. 16, determined by Robert N. Caldwell, Nevada Professional Land Surveyor No. 4233, monumented with a rebar, 5/8 in. diam., flush with the ground, with 2 in. diam. aluminum cap mkd. ROBERT N. CALDWELL, PLS 4233, as recorded in Humboldt County, Nevada, File 182552. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S16</p> <p style="text-align: center;">2006</p> <p>Deposit rebar inside stainless steel post.</p> <p>Corner is located at corner of fences extending N. and W.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°05'40" E., beginning new measurement.</p> <p>Over nearly level land through scattered sagebrush.</p>
16.830	Point for the witness point at intersection with the centerline of Old U.S. Highway No. 40, hereinafter described.
20.498	<p>The W 1/16 sec. cor. of secs. 9 and 16.</p> <hr/> <p>From for the C-N 1/16 sec. cor. of sec. 16.</p> <p>N. 88°24'20" W., on the E-W center line of the NW1/4 of sec. 16.</p> <p>Over nearly level land through scattered sagebrush.</p>
19.657	<p>The NW 1/16 sec. cor. of sec. 16.</p> <hr/> <p>N. 88°24'00" W., beginning new measurement.</p> <p>Over nearly level land through scattered sagebrush.</p>
19.660	<p>The N 1/16 sec. cor. of secs. 16 and 17.</p> <hr/> <p style="text-align: center;">METES-AND-BOUNDS SURVEY OF THE SOUTHERLY RIGHT-OF-WAY LINE OF THE UNION PACIFIC RAILROAD THROUGH SECTION 16, T. 35 N., R. 37 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the witness point, at the intersection of the line bet. secs. 15 and 16 and the southerly right-of-way line of Union Pacific Railroad, determined at 200 ft. right angle measurement from the center of tracks.</p>

175

METES-AND-BOUNDS SURVEY OF THE SOUTHERLY RIGHT-OF-WAY LINE
OF THE UNION PACIFIC RAILROAD THROUGH SECTION 16,
T. 35 N., R. 37 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T35N R37E WP S16 S15 2006</p> <p>S. 66°04'00" W, on the southerly right-of-way line of Union Pacific Railroad.</p> <p>Over nearly level land through scattered sage.</p>
43.808	Intersect the N-S center line of sec. 16.
64.353	Intersect the E-W center line of sec. 16.
86.541	<p>The witness point, at the intersection of the line bet. secs. 16 and 17 and the southerly right-of-way of Union Pacific Railroad, determined at 200 ft. right angle measurement from the center of tracks.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T35N R37E WP S17 S16 2006</p> <hr/> <p style="text-align: center;">METES-AND-BOUNDS SURVEY OF THE NORTHERLY RIGHT-OF-WAY LINE OF THE UNION PACIFIC RAILROAD THROUGH SECTION 16, T. 35 N., R. 37 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the witness point, at the intersection of the line bet. secs. 15 and 16 and the northerly right-of-way line of Union Pacific Railroad, determined at 200 ft. right angle measurement from the center of tracks.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T35N R37E WP S16 S15 2006</p> <p>S. 66°04'00" W, on the northerly right-of-way line of Union Pacific Railroad.</p> <p>Over nearly level land through scattered sagebrush.</p>

176

METES-AND-BOUNDS SURVEY OF THE NORTHERLY RIGHT-OF-WAY LINE
OF THE UNION PACIFIC RAILROAD THROUGH SECTION 16,
T. 35 N., R. 37 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
43.651	Intersect the N-S center line of sec. 16.
65.130	Intersect the N-S center line of the NW1/4 of sec. 16.
79.334	Intersect the E-W center line of sec. 16.
86.479	<p>The witness point, at the intersection of the line bet. secs. 16 and 17 and the southerly right-of-way line of Union Pacific Railroad, determined at 200 ft. right angle measurement from the center of tracks.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<div style="text-align: center;"> <p>T35N R37E WP S17 S16  2006</p> </div>
	<hr/> <p style="text-align: center;">METES-AND-BOUNDS SURVEY OF THE CENTERLINE OF OLD U.S. HIGHWAY NO. 40, THROUGH THE NE1/4 OF THE NW1/4 OF SECTION 16, T. 35 N., R. 37 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>
	<p>From the witness point, at the intersection of the line bet. secs. 9 and 16 and the centerline of Old U.S. Highway No. 40.</p>
	<p>Set a PK nail flush with the asphalt surface.</p>
	<p>from which</p>
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, over a plastic-encased magnet, bears N. 21°43' E., 2.654 chs. dist., with brass cap mkd. T35N R37E S16 RM WP 175.2 FT and an arrow pointing to the cor.</p>
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, over a plastic-encased magnet, bears N. 64°16' W., 1.785 chs. dist., with brass cap mkd. T35N R37E S16 RM WP 117.8 FT and an arrow pointing to the cor.</p>
	<p>From this point, a Nevada State Highway monument, 6 in. square concrete block, firmly set, projecting 6 ins. above the ground with copper wire in top center, bears N. 55°35'00" E., 65.312 chs. dist.</p>
	<p>S. 56°54'40" W., on the centerline of Old U.S. Highway No. 40.</p>
	<p>Over nearly level land.</p>
1.447	<p>From this point, a Nevada State Highway monument, 6 in. square concrete block, firmly set, projecting 6 ins. above the ground with copper wire in top center, bears N. 33°05'20" W., 1.515 chs. dist.</p>

METES-AND-BOUNDS SURVEY OF THE CENTERLINE OF OLD U.S.
HIGHWAY NO. 40, THROUGH THE NE1/4 OF THE NW1/4 OF SECTION 16,
T. 35 N., R. 37 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p> <p>6.531</p>	<p>The witness point, at the intersection of the N-S center line of the NW1/4 of sec. 16 and the centerline of Old U.S Highway No. 40.</p> <p>Set a PK nail flush with the asphalt surface.</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, over a plastic-encased magnet, bears S. 7°48' E., 1.772 chs. dist., with brass cap mkd. T35N R37E S16 RM WP 117.0 FT and an arrow pointing to the cor.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, over a plastic-encased magnet, bears S. 80°04' E., 2.250 chs. dist., with brass cap mkd. T35N R37E S16 RM WP 148.5 FT and an arrow pointing to the cor.</p> <p>From this point, a Nevada State Highway monument, 6 in. square concrete block, firmly set, projecting 6 ins. above the ground with copper wire in top center, bears S. 77°12'30" W., 3.275 chs. dist.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The lands included in the survey are located in Humboldt County, Nevada, about 5 miles southwest of Winnemucca, Nevada along Old U.S. Highway No. 40. The area is nearly level but slopes gradually to the northwest with no drains. The area is covered with scattered sagebrush. The Humboldt River is approximately one mile north. The elevation of the area is approximately 4295 feet above sea level. Elevation taken from U.S.G.S. quadrangle map "WINNEMUCCA WEST, NEVADA", dated 1982.</p> <hr/>
----------------------------	--

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANT

De' Vonte Whitmore

Survey Aid

CERTIFICATE OF SURVEY

We, Lance A. Barney, Cadastral Surveyor, and Mark G. Petrosine, Surveying Technician, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 11th day of April, 2006, we have dependently resurveyed a portion of the subdivisional lines, subdivided section 16, and executed metes-and-bounds surveys in section 16, Township 35 North, Range 37 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

December 6, 2006

(Date)

Lance A. Barney

(Cadastral Surveyor)

December 6, 2006

(Date)

Mark G. Petrosine

(Surveying Technician)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of the dependent resurvey of a portion of the subdivisional lines, the subdivision of section 16, and metes-and-bounds surveys in section 16, Township 35 North, Range 37 East, Mount Diablo Meridian, Nevada, executed by Lance A. Barney, Cadastral Surveyor, and Mark G. Petrosine, Surveying Technician, having been critically examined and found correct, are hereby approved.

December 8, 2006

(Date)

Daniel Clark

(Acting Chief Cadastral Surveyor, Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 35 N., R. 37 E., Mount Diablo Meridian, Nevada, is a true copy of the original field notes.~~

~~(Date)~~

~~(Acting Chief Cadastral Surveyor, Nevada)~~