

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF A PORTION OF THE SUBDIVISIONAL LINES,

THE SUBDIVISION OF SECTIONS 3 AND 10,

AND

METES-AND-BOUNDS SURVEYS IN SECTIONS 3 AND 10,

TOWNSHIP 4 NORTH, RANGE 69 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

EXECUTED BY

Craig L. Wanless, Cadastral Surveyor

Mark G. Petrosine, Surveying Technician

Under Special Instructions dated October 24, 2003,

and approved October 24, 2003,

which provided for the surveys included under Group No. 815,

and Assignment Instructions dated November 6, 2003.

Survey commenced November 13, 2003

Survey completed December 7, 2003

INDEX DIAGRAM

TOWNSHIP 4 NORTH, RANGE 69 EAST

6	5	4	5 3 3	2 2	1
7	8	9	3 10	2 11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Subdivision of Section 3 . . . . . Pgs. 6 - 12  
 Subdivision of Section 10 . . . . . Pgs. 12 - 17  
 Metes-and-Bounds Surveys in Section 3 . . . . . Pgs. 17 - 21  
 Metes-and-Bounds Survey on Section 10 . . . . . Pgs. 22 - 23

## 223

TOWNSHIP 4 NORTH, RANGE 69 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines, the subdivision of sections 3 and 10, and metes-and-bounds surveys in sections 3 and 10, Township 4 North, Range 69 East, Mount Diablo Meridian, Nevada.

The north boundary and subdivisional lines were surveyed by W.A. Pray in 1913, under Group No. 23. The history of exterior boundaries remote to the area surveyed are not included.

Before restoring the corners, the lines of the original surveys were retraced and diligent search made for any evidence of the original corners and other calls of the original field note record.

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated October 24, 2003, for Group No. 815, Nevada.

Measurements were made using Trimble 4700 and 5800 GPS receivers. Only the mean bearings of the lines based on the true meridian and horizontal equivalents of ground distances are entered in the field notes.

The distance to each new bearing tree was measured to a 2 ½ x ¼ inch magnetic nail driven at the base on right-side center.

The geographic position (NAD 1983) of the one-quarter section corner of sections 10 and 11, as determined by survey grade GPS receivers, in 2003, from National Geodetic Survey control (formerly U.S. Coast and Geodetic Survey triangulation) stations "LAKE" and "DRYLAKE", is as follows:

Latitude: 38°13'18.436" N. Longitude: 114°13'40.136" W.

The mean magnetic declination is 15 1/2° E., as shown on U.S.G.S. quadrangle map "BUCK WASH WELL, NEV.", dated 1972.

---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 4 N., R. 69 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Reestablishment of the Survey Executed by W.A. Pray in 1913</p> <hr/> <p>Beginning at the 1/4 sec. cor. of secs. 10 and 11, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above the ground, with brass cap mkd. as described in the field notes of the original survey, and a mound of stone, 2 ft. base, 6 ins. high, W. of the cor.</p> <p>Add the marks T4N R69E 2003 to the brass cap.</p> <p>Cor. is located at S. edge of a wash, 7 chs. wide, drains SE.</p> <p>N. 0°04'30" W., bet. secs. 10 and 11.</p>
20.038	Point for the N 1/16 sec. cor. of secs. 10 and 11, not monumented.
40.076	<p>The cor. of secs. 2, 3, 10, and 11, monumented with an iron post, 2 ins. diam., firmly set, projecting 15 ins. above the ground, and in a scattered mound of stone, 3 ft. base, 8 ins. high, with brass cap mkd. as described in the field notes of the original survey, from which the original bearing trees</p> <p>A juniper, 30 ins. diam., bears N. 45° E., 61 lks. dist., with scribe marks R69E S2 T4N BT visible on partially healed blaze. (Record, N. 40° E.)</p> <p>A juniper, 17 ins. diam., bears S. 20 1/2° W., 32 lks. dist., with scribe marks T4N R69E S10 BT visible on partially healed blaze. (Record, S. 29° 15' W.)</p> <p>A pinion pine, 12 ins. diam., bears N. 85° W., 21 lks. dist., with scribe marks T4N R69E S3 BT visible on partially healed blaze.</p>
	<p>Rebuild the mound of stone, 4 ft. base, to top of iron post.</p> <hr/>
	<p>N. 0°00'10" W., bet. secs. 2 and 3.</p>
20.011	Point for the S 1/16 sec. cor. of secs. 2 and 3, not monumented.
40.022	<p>The 1/4 sec. cor. of secs. 2 and 3, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. as described in the field notes of the original survey, and a mound of stone, 2 ft. base, 6 ins. high, W. of the cor., from which the original bearing trees</p> <p>A pinion pine, 15 ins. diam., bears N. 26°45' E., 29 lks. dist., with scribe marks 1/4 S2 BT visible on partially healed blaze.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 4 N., R. 69 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>A pinion pine, 11 ins. diam., bears S. 69° W., 34 1/2 lks. dist., with scribe marks 1/4 S3 BT visible on partially healed blaze. (Record, 39 lks.)</p> <p>Add the marks T4N R69E 2003 to the brass cap.</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 9 and 10, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above the ground, with brass cap mkd. as described in the field notes of the original survey, and a mound of stone, 2 ft. base, 6 ins. high, W. of the cor., from which the original bearing trees</p>
	<p>A juniper, 8 ins. diam., bears N. 49°15' E., 24 lks. dist., with the scribe marks 1/4 S10 BT visible on partially healed blaze.</p>
	<p>A pinion pine, 9 ins. diam., bears S. 21 1/2° W., 31 lks. dist., with the scribe marks S9 BT visible on partially healed blaze. (Record, S. 24°10' W.)</p>
	<p>Add the marks T4N R69E 2003 to the brass cap.</p>
	<p>N. 0°00'20" W., bet. secs. 9 and 10.</p>
20.023	<p>Point for the N 1/16 sec. cor. of secs. 9 and 10, not monumented.</p>
40.046	<p>The cor. of secs. 3, 4, 9, and 10, monumented with an iron post, 2 ins. diam., firmly set, projecting 16 ins. above the ground, in a scattered mound of stone, 2 1/2 ft. base, 16 ins. high, with brass cap mkd. as described in the field notes of the original survey.</p> <p>from which</p>
	<p>A chiseled X followed by the letters BO, bears N. 0°25' E., 22.9 lks. dist., mkd. on the top of an igneous boulder, 24X18X8 ins.</p>
	<p>A pinion pine, 6 ins. diam., bears S. 51 1/2° E., 36.8 lks. dist., mkd. X on upper blaze and BT on lower blaze.</p>
	<p>A chiseled X followed by the letters BO, bears S. 28°30' W., 58.0 lks. dist., mkd. 9 ins. above ground on the N face of an igneous boulder, 36X30X18 ins.,</p>
	<p>A pinion pine, 7 ins. diam., bears N. 69 3/4° W., 33.8 lks. dist., mkd. X on upper blaze and BT on lower blaze.</p>
	<p>Rebuild the mound of stone, 4 ft. base, to top of iron post.</p> <hr/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 4 N., R. 69 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From the cor. of secs. 2, 3, 10, and 11.</p> <p>S. 89°58'00" W., bet. secs. 3 and 10.</p>
19.966	<p>Point for the E 1/16 sec. cor. of secs. 3 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S 3 E 1/16 — S10  2003</p> <p>from which</p> <p style="padding-left: 40px;">A pinion pine, 7 ins. diam., bears S. 67 3/4° W., 37.0 lks. dist., mkd. E 1/16 S10 BT.</p> <p style="padding-left: 40px;">A chiseled X followed by the letters B0, bears N. 19°16' W., 55.7 lks. dist., mkd. on the top of an igneous boulder, 24X24X6 ins.</p>
20.72	<p>Spur, slopes S. 30° W.</p>
33.58	<p>Center of graded dirt road, 20 lks. wide, bears N. 10° W. and S. 10° E.</p>
39.932	<p>Point for the 1/4 sec. cor. of secs. 3 and 10, at proportionate dist.; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 40 ins. in the ground, with the top 12 ins. below the surface, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T4N R69E S 3 1/4 — S10  2003</p> <p>Cor. is located in open pasture.</p>
49.55	<p>Ditch, 15 lks. wide, 3 ft. deep, drains S. 30° E.</p>
49.915	<p>Point for the E-W 1/64 sec. cor. of secs. 3 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 4 N., R. 69 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	S 3 E-W 1/64 S10  2003
50.00	Barbed wire fence, T-bar posts, bears N. 30° W. and S. 30° E.
50.27	Center of Camp Valley Road, a graded dirt road, 25 lks. wide, bears N. 30° W. and S. 30° E.
59.898	Point for the W 1/16 sec. cor. of secs. 3 and 10.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	S 3 W 1/16 — S10  2003
	from which  A juniper, 9 ins. diam., bears S. 4 1/4° W., 13.2 lks. dist., mkd. W 1/16 S10 BT.  A pinion pine, 11 ins. diam., bears N. 76° W., 15.5 lks. dist., mkd. W 1/16 S3 BT.
79.864	The cor. of secs. 3, 4, 9, and 10. <hr/>
	N. 0°02'10" E., bet. secs. 3 and 4.
20.016	Point for the S 1/16 sec. cor. of secs. 3 and 4, not monumented.
28.92	Buckhorn Springs Ranch Road, a graded dirt road, 25 lks. wide, bears N. 60° E. and S. 60° W.
40.032	Point for the 1/4 sec. cor. of secs. 3 and 4, at proportionate dist., there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.
	T4N R69E 1/4 S 4   S 3  2003

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 4 N., R. 69 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, for a reference monument, bears S. 0°30' E., 153.3 lks. dist., with brass cap mkd. RM 1/4 S3 101.2 FT TO COR and an arrow pointing to the cor.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, for a reference monument, bears S. 78°54' W., 81.0 lks. dist., with brass cap mkd. RM 1/4 S4 53.5 FT TO COR and an arrow pointing to the cor.</p> <p>Cor. is located on E. shoulder of Camp Valley Road, graded dirt surface, 25 lks. wide., bears N. 45° W. and S. 45° E.</p>
44.73	Camp Creek, 25 lks. wide, course S. 65° E.
79.824	<p>The cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. as described in the field notes of the original survey, from which the remains of the original bearing trees</p> <p>A dead and standing pinion pine, 14 ins. diam., bears S. 5° W., 6 lks. dist., with illegible scribe marks visible on partially healed blaze.</p> <p>A root hole, bears N. 39° W., 110 lks. dist., alongside of which is lying a pinion pine, 11 ins. diam., with scribe marks T5N R69E S33 BT visible on partially healed blaze.</p> <p>and a new bearing tree</p> <p>A pinion pine, 12 ins. diam., bears N. 5° W., 25.5 lks. dist., mkd. T5N R69E S33 BT.</p>
	<hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 3, T. 4 N., R. 69 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 3 and 10.</p> <p>N. 0°03'40" E., on the N-S center line of sec. 3.</p> <p>8.83 Center of graded dirt road, 20 lks. wide, bears N. 50° W. and S. 50° E.</p>

SUBDIVISION OF SECTION 3,  
T. 4 N., R. 69 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.014	<p>Point for the C-S 1/16 sec. cor. of sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <math display="block">\begin{array}{c} C \\ S\ 1/16 \quad   \quad S\ 3 \\ C \end{array}</math> <p>2003</p> </div> <p>from which</p> <p style="padding-left: 40px;">A pinion pine, 7 ins. diam., bears S. 20 1/2° E., 47.4 lks. dist., mkd. CS 1/16 S3 BT.</p> <p style="padding-left: 40px;">A pinion pine, 8 ins. diam., bears S. 32 1/2° W., 34.9 lks. dist., mkd. X on upper blaze and BT on lower blaze.</p>
39.03	Ravine, drains S. 70° W.
40.028	<p>Point for the center 1/4 sec. cor. of sec. 3, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T4N R69E C 1/4 S 3</p> <p>2003</p> </div> <p>from which</p> <p style="padding-left: 40px;">A pinion pine, 8 ins. diam., bears S. 60° W., 146.5 lks. dist., mkd. C 1/4 S3 BT.</p> <p style="padding-left: 40px;">A chiseled X followed by the letters BO, bears N. 43°53' W. 141.6 lks. dist., mkd on the top of an igneous boulder, 36X36X24 ins.</p>
79.819	<p>The 1/4 sec. cor. of secs. 3 and 34, on the N. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd. as described in the field notes of the original survey, and a mound of stone, 2 ft. base, 6 ins. high, N. of the cor.</p> <p>Add the marks T5N R69E T4N 2003 to the brass cap.</p> <hr/>

SUBDIVISION OF SECTION 3,  
T. 4 N., R. 69 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	From the 1/4 sec. cor. of secs. 2 and 3.
	S. 89°58'20" W., on the E-W center line of sec. 3.
19.942	Point for the C-E 1/16 sec. cor. of sec. 3, not monumented.
39.884	The center 1/4 sec. cor. of sec. 3.
59.856	Point for the C-W 1/16 sec. cor. of sec. 3, not monumented.
74.70	Camp Creek, 25 lks. wide, drains S. 5° W.
79.828	The 1/4 sec. cor. of secs. 3 and 4.
<hr/>	
	From the E 1/16 sec. cor. of secs. 3 and 10.
	N. 0°01'40" E., on the N-S center line of the SE1/4 of sec. 3.
20.013	Point for the SE 1/16 sec. cor. of sec. 3, at intersection with the E-W center line of the SE1/4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.
	SE 1/16 S 3
	2003
	from which
	A chiseled X followed by the letters BO, bears N. 9°49' E., 89.6 lks. dist., mkd. 2 1/2 ft. above ground on the SW face of an igneous outcrop, 10X8X6 ft.
	A pinion pine, 11 ins. diam., bears S. 62 1/4° E., 66.5 lks. dist., mkd. SE 1/16 S3 BT.
40.025	The point for the C-E 1/16 sec. cor. of sec. 3.
<hr/>	
	From the point for the S 1/16 sec. cor. of secs. 2 and 3.
	S. 89°58'10" W., on the E-W center line of the SE1/4 of sec. 3.
19.954	The SE 1/16 sec. cor. of sec. 3.
39.908	The C-S 1/16 sec. cor. of sec. 3.
<hr/>	


SUBDIVISION OF SECTION 3,  
T. 4 N., R. 69 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From the W 1/16 sec. cor. of secs. 3 and 10.</p> <p>N. 0°02'50" E., on the N-S center line of the SW1/4 of sec. 3.</p>
13.82	<p>Camp Valley Road, a graded dirt road, 25 lks. wide, bears N. 60° W. and S. 50° E in curve.</p>
14.412	<p>Point for Angle Point No. 1, of a metes-and-bounds survey in sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <div data-bbox="738 703 933 913" style="text-align: center;"> </div>
15.97	<p>Ditch, 15 lks. wide, 3 ft. deep, drains S. 35° E.</p>
20.016	<p>Point for the SW 1/16 sec. cor. of sec. 3, at intersection with the E-W center line of the SW1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 40 ins. in the ground, the top 12 ins. below the surface, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SW 1/16 S 3</p> <p style="text-align: center;">2003</p>
20.53	<p>Barbed wire fence, T-bar posts, bears N. 45° E. and S. 45° W.</p>
30.023	<p>Point for the C-N-SW 1/64 sec. cor. of sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S 3 C-N-SW 1/64</p> <p style="text-align: center;">2003</p>
33.08	<p>Center of graded dirt road, 20 lks. wide, bears N. 35° W. and S. 35° E.</p>


SUBDIVISION OF SECTION 3,  
T. 4 N., R. 69 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
34.345	Intersect line 7-8, of a metes-and-bounds survey in sec. 3.
40.030	The point for the C-W 1/16 sec. cor. of secs. 3.
	<hr/> <p>From the C-S 1/16 sec. cor. of sec. 3.</p> <p>S. 89°58'00" W., on the E-W center line of the SW1/4 of sec. 3.</p>
6.585	Point for Angle Point No. 13, of a metes-and-bounds survey in sec. 3.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p style="margin: 0;">T4N R69E AP13 \ S ————— 3 2003</p> </div> <p>Cor. is located in open pasture, 1 ch. S. of tree line, bears N. 60° W. and S. 60° E.</p>
10.40	Center of graded dirt road, 20 lks. wide, bears N. 45° W. and S. 45° E.
14.976	Point for the C-W-E-SW 1/256 sec. cor. of sec. 3.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 40 ins. in the ground, the top 12 ins. below the surface, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 3 C-W-E-SW 1/256 2003</p> </div> <p>Cor. is located in open pasture.</p>
19.968	The SW 1/16 sec. cor. of sec. 3.
20.45	Barbed wire fence, T-bar posts, bears N. 45° E. and S. 45° W.
22.25	Ditch, 15 lks. wide, 3 ft. deep, drains S. 10° E.
23.749	Intersect line 2-3, of a metes-and-bounds survey in sec. 3.
24.86	Center of Camp Valley Road, graded dirt surface, 25 lks. wide, bears N. 20° W. and S. 20° E.

SUBDIVISION OF SECTION 3,  
T. 4 N., R. 69 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.937	<p>The point for the S 1/16 sec. cor. of secs. 3 and 4.</p> <hr/>
	<p>From the C-W-E-SW 1/256 sec. cor. of sec. 3.</p>
	<p>N. 0°03'00" E., on the computed N-S center line of the SW1/4NE1/4SW1/4 of sec. 3.</p>
3.86	<p>Center of graded dirt road, 20 lks. wide, bears N. 50° W. and S. 50° E.</p>
5.44	<p>Barbed wire fence, T-bar and juniper posts, bears N. 50° W. and S. 50° E. From this point, an angle point in fences, extending S. 50° E. and S. 50° W., bears N. 50° W., 14 lks. dist.</p>
5.602	<p>Point for Angle Point No. 10, of a metes-and-bounds survey in sec. 3.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p>
	
	<p>2003</p>
10.007	<p>Point for the C-W-NE-SW 1/256 sec. cor. of sec. 3, at its computed position.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p>
	<p>S 3</p>
	<p>C-W-NE-SW</p>
	<p>1/256</p>
	<p>2003</p>
	<hr/> <p>S. 89°58'10" W., on a portion of the computed E-W center line of the NE1/4SW1/4 of sec. 3.</p>
2.713	<p>Point for Angle Point No. 9, of a metes-and-bounds survey in sec. 3.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

SUBDIVISION OF SECTION 3,  
T. 4 N., R. 69 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<div style="text-align: center;">  <p>T4N R69E AP9 \ S ----- 3</p> </div> <p style="text-align: center;">2003</p> <p>3.05 Center of graded dirt road, 20 lks. wide, bears N. 5° W. and S. 5° E.</p> <p>4.993 The C-N-SW 1/64 sec. cor. of sec. 3.</p>
	<hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 10, T. 4 N., R. 69 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 10 and 15, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above the ground, with brass cap mkd. as described in the field notes of the original survey, and a mound of stone, 2 ft. base, 6 ins. high, W. of the cor., from which the original bearing trees</p> <p style="padding-left: 40px;">A pinion pine, 10 ins. diam., bears S. 9°30' W., 30 lks. dist., with scribe marks 1/4 S15 BT visible on partially healed blaze.</p> <p style="padding-left: 40px;">A juniper, 12 ins. diam., bears N. 57 1/2° W., 62 lks. dist., with scribe marks 1/4 S10 BT visible on exposed wood surface. (Record, N. 59° W., 55 lks.)</p> <p>N. 0°01'00" E., on the N-S center line of sec. 10.</p> <p>40.000 Point for the center 1/4 sec. cor. of sec. 10, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, over a plastic-encased magnet, in a 3/4 in. wide, 3/4 in. deep hole chiseled square in the nose of a large subsurface boulder, and in a mound of stone, 4 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T4N R69E C 1/4 S10</p> <p>2003</p> </div> <p>from which</p> <p style="padding-left: 40px;">A chiseled X followed by the letters B0, bears S. 50°43' E., 44.9 lks. dist., mkd. on the top of an igneous boulder, 36X20X6 ins.</p>

SUBDIVISION OF SECTION 10,  
T. 4 N., R. 69 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	A juniper, 8 ins. diam., bears S. 51 1/4° W., 34.0 lks. dist., mkd. C 1/4 S10 BT.
60.029	Point for the C-N 1/16 sec. cor. of sec. 10.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.  <div style="text-align: center;">           C            N 1/16   S10            C             2003         </div> Cor. is located 5 lks. SE. of a well embedded mound of stone of unknown origin, 2 1/2 ft. base, 6 ins. high.
65.036	Point for the C-S-N-N 1/256 sec. cor. of sec. 10.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.  <div style="text-align: center;">           S10            C-S-N-N            1/256             2003         </div> Cor. is located 10 lks. W. of the SW edge of a graded dirt road, 25 lks. wide, bears N. 35° W. and S. 35° E.
65.290	Center of Camp Valley Road, graded dirt surface, 25 lks. wide, bears N. 35° W. and S. 35° E.
66.49	Ditch, 25 lks. wide, 3 ft. deep, course S. 40° E.
80.058	The 1/4 sec. cor. of secs. 3 and 10. <hr/>
	From the 1/4 sec. cor. of secs. 10 and 11.  S. 89°59'10" W., on the E-W center line of sec. 10.
3.02	Center of graded dirt road, 20 lks. wide, bears N. 40° W. and S. 40° E.
16.06	Camp Creek, 15 lks. wide, course S. 60° E.
18.85	Center of Camp Valley Road, graded dirt surface, 25 lks. wide, bears N. 20° W. and S. 20° E.
20.000	Point for the C-E 1/16 sec. cor. of sec. 10, not monumented.

SUBDIVISION OF SECTION 10,  
T. 4 N., R. 69 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.000	The center 1/4 sec. cor. of sec. 10.
59.960	Point for the C-W 1/16 sec. cor. of sec. 10, not monumented.
79.920	The 1/4 sec. cor. of secs. 9 and 10.
	<hr/>
	From the point for the C-E 1/16 sec. cor. of sec. 10.
	N. 0°01'40" W., on the N-S center line of the NE1/4 of sec. 10.
3.75	Center of Camp Valley road, graded dirt surface, 25 lks. wide, bears N. 15° W. and S. 15° E.
6.74	End of ditch, begin Camp Creek, 25 lks. wide, course S. 40° E.
9.55	Barbed wire fence, T-bar posts, bears N. 40° E. and S. 40° W.
9.559	Intersect line 2-3, of a metes-and-bounds survey in sec. 10.
15.95	Center of graded dirt road, 20 lks. wide, bears N. 45° W. and S. 45° E.
16.655	Intersect line 1-2, of a metes-and-bounds survey in sec. 10.
20.034	Point for the NE 1/16 sec. cor. of sec. 10, at intersection with the E-W center line of the NE1/4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	NE 1/16 S10
	2003
	from which
	A pinion pine, 7 ins. diam., bears N. 13 3/4° E., 25.3 lks. dist., mkd. X on upper blaze and BT on lower blaze.
	A pinion pine, 7 ins. diam., bears N. 85 1/2° W., 19.7 lks. dist., mkd. NE 1/16 S10 BT.
35.99	Center of graded dirt road, 20 lks. wide, bears N. 50° W and S. 50° E.
40.067	The E 1/16 sec. cor. of secs. 3 and 10.
	<hr/>

SUBDIVISION OF SECTION 10,  
T. 4 N., R. 69 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From the point for the N 1/16 sec. cor. of secs. 10 and 11. S. 89°58'40" W., on the E-W center line of the NE1/4 of sec. 10.</p>
19.983	The NE 1/16 sec. cor. of sec. 10.
23.586	<p>Point for Angle Point No. 1, of a metes-and-bounds survey in sec. 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T4N R69E</p> <p>S</p> <p>N ————— N</p> <p>AP1 \ 10</p> <p>2003</p> </div>
24.13	Center of graded dirt road, 20 lks. wide, bears N. 45° W and S. 45° E.
34.703	<p>Point for Angle Point No. 4, of a metes-and-bounds survey in sec. 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T4N R69E</p> <p>S</p> <p>N ————— N</p> <p>10 \ AP4</p> <p>2003</p> </div>
	<p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, for a reference monument, bears S. 11°54' W., 180.5 lks. dist., with brass cap mkd. RM AP4 119.1 FT TO COR and an arrow pointing to the cor.</p>

SUBDIVISION OF SECTION 10,  
T. 4 N., R. 69 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, for a reference monument, bears S. 75°43' W., 157.3 lks. dist., with brass cap mkd. RM AP4 103.8 FT TO COR and an arrow pointing to the cor.</p>
34.93	Ditch, 15 lks. wide, 3 ft. deep, drains S. 35° E.
35.88	Center of Camp Valley road, graded dirt surface, 26 lks. wide, bears N. 35° W. and S. 35° E.
39.965	The C-N 1/16 sec. cor. of sec. 10.
	<hr/> <p>From the point for the C-W 1/16 sec. cor. of sec. 10. N. 0°00'20" E., on the N-S center line of the NW1/4 of sec. 10.</p>
20.026	Point for the NW 1/16 sec. cor. of sec. 10, at intersection with the E-W center line of the NW1/4, not monumented.
40.051	The W 1/16 sec. cor. of secs. 3 and 10.
	<hr/> <p>From the C-N 1/16 sec. cor. of sec. 10. S. 89°58'30" W., on the E-W center line of the NW1/4 of sec. 10.</p>
19.963	The point for the NW 1/16 sec. cor. of sec. 10.
39.926	The point for the N 1/16 sec. cor. of secs. 9 and 10.
	<hr/> <p>From the C-S-N-N 1/256 sec. cor. of sec. 10. S. 89°58'30" W., on a portion of the computed E-W center line of the SE1/4NE1/4NW1/4 of sec. 10.</p>
4.991	Point for the SE-NE-NW 1/256 sec. cor. of sec. 10, at its computed position.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S10 SE-NE-NW 1/256  2003</p> <hr/>

SUBDIVISION OF SECTION 10,  
T. 4 N., R. 69 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
5.007	<p>N. 0°00'50" E., on a portion of the computed N-S center line of the SE1/4NE1/4NW1/4 of sec. 10.</p> <p>Point for the C-E-NE-NW 1/256 sec. cor. of sec. 10, at its computed position.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S10 C-E-NE-NW 1/256</p> <p style="text-align: center;">2003</p> <p>Cor. is located 1.38 chs. W. and 1.77 chs. S. of the center of Camp Valley Road, graded dirt surface, 26 lks. wide, bears N. 40° W. and S. 40° E.</p> <hr/> <p>S. 89°58'20" W., on a portion of the computed E-W center line of the NE1/4NW1/4 of sec. 10.</p> <p>Point for the NE-NW 1/64 sec. cor. of sec. 10, at its computed position.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S10 NE-NW 1/64</p> <p style="text-align: center;">2003</p> <hr/> <p>N. 0°00'40" E., on a portion of the computed N-S center line of the NE1/4NW1/4 of sec. 10.</p> <p>Center of Camp Valley Road, graded dirt surface, 25 lks. wide, bears N. 30° W. and S. 30° E.</p>
4.991	
9.23	
10.014	<p>The E-W 1/64 sec. cor. of secs. 3 and 10.</p> <hr/> <p style="text-align: center;">METES-AND-BOUNDS SURVEYS IN SECTION 3, T. 4 N., R. 69 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From Angle Point No. 1, sec. 3, on the N-S center line of the SW1/4 of sec. 3, hereinbefore described.</p> <p>N. 43°22'20" W., on line 1-2.</p>

METES-AND-BOUNDS SURVEYS IN SECTION 3,  
T. 4 N., R. 69 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
4.898	<p>Point for Angle Point No. 2, sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <div data-bbox="795 441 998 651" style="text-align: center;"> <p>T4N R69E S 3      AP2</p> <p>2003</p> </div> <p>Cor. is located 62 lks. E. of the center of Camp Valley Road, graded dirt surface, 25 lks. wide, bears N. 20° W. and S. 30° E. in curve.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 11°25'20" W., on line 2-3.</p>
2.083	<p>Intersect the E-W center line of the SW1/4 of sec. 3, at a point from which from the SW 1/16 sec. cor. of sec. 3, bears N. 89°58'00" E., 3.781 chs. dist., hereinbefore described.</p>
9.379	<p>Point for Angle Point No. 3, sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <div data-bbox="779 1186 982 1417" style="text-align: center;"> <p>T4N R69E S 3      AP3</p> <p>2003</p> </div> <p>Cor. is located 68 lks. E. of the center of Camp Valley Road, graded dirt surface, 25 lks. wide, bears N. 20° W. and S. 10° E., in curve.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 29°43'10" W., on line 3-4.</p>
6.659	<p>Point for Angle Point No. 4, sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p>

METES-AND-BOUNDS SURVEYS IN SECTION 3,  
T. 4 N., R. 69 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

T4N  
R69E  
S 3      AP4

2003

Cor. is located 1.03 chs. E. of the center of Camp Valley Road, graded dirt surface, 25 lks. wide, bears N. 50° W. and S. 35° E., in curve.

---

N. 55°02'30" W., on line 4-5.

3.483

Point for Angle Point No. 5, sec. 3.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.

T4N  
R69E  
S 3      AP5

2003

Cor. is located 27 lks. E. of the E. edge of the intersection of Buckhorn Springs Ranch and Camp Valley Roads.

---

N. 38°00'20" E., on line 5-6.

3.50

Camp Creek, 2 lks. wide, course S. 60° E.

5.923

Point for Angle Point No. 6, sec. 3.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.

T4N R69E  
S 3      AP6

2003

Cor. is located 18 lks. S. of the S. edge and 27 lks. W. of the W. edge of a graded dirt road, 20 lks. wide, bears S. 60° E. and W., in curve.

---



METES-AND-BOUNDS SURVEYS IN SECTION 3,  
T. 4 N., R. 69 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
3.384	<p>S. 74°38'40" E., on line 6-7.</p> <p>Point for Angle Point No. 7, sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <div data-bbox="824 527 998 730" style="text-align: center;"> <p>T4N R69E S 3 AP7 2003</p> </div> <p>Cor. is located 88 lks. E. and 62 lks. N. of the center of graded dirt road, 20 lks. wide, bears N. 50° W. and S. 50° E.</p> <hr style="width: 20%; margin: 10px auto;"/>
6.260	<p>S. 45°44'30" E., on line 7-8.</p> <p>Intersect the N-S center line of the SW1/4 of sec. 3, at a point from which the C-N-SW 1/64 sec. cor. of sec. 3, bears S. 0°02'50" W., 4.322 chs. dist., hereinbefore described.</p>
7.454	<p>Point for Angle Point No. 8, sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div data-bbox="836 1245 998 1449" style="text-align: center;"> <p>T4N R69E S 3 AP8 2003</p> </div> <p>Cor. is located 56 lks. E. of the center of a graded dirt road, 25 lks. wide, bears N. 40° W. and S. 30° E., in curve.</p> <hr style="width: 20%; margin: 10px auto;"/>
3.766	<p>S. 22°10'30" E., on line 8-9.</p> <p>Angle Point No. 9, sec. 3, on the E-W center line of the NE1/4SW1/4 of sec. 3, hereinbefore described.</p> <hr style="width: 20%; margin: 10px auto;"/>

METES-AND-BOUNDS SURVEYS IN SECTION 3,  
T. 4 N., R. 69 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From Angle Point No. 10, sec. 3, on the N-S center line of the SW1/4NE1/4SW1/4 of sec. 3.</p> <p>S. 50°03'00" E., on line 10-11.</p> <p>3.679 Point for Angle Point No. 11, sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <div data-bbox="844 609 1023 819" style="text-align: center;"> <p>T4N R69E S 3 AP11 2003</p> </div> <p>Cor. is located 14 lks. N. of a juniper tree used as a fence corner post from which barbed wire fences, T-bar and juniper posts, extend N. 85° W. and S. 40° E.</p> <hr style="width: 30%; margin: auto;"/> <p>N. 86°04'40" E., on line 11-12.</p>
	<p>3.431 Point for Angle Point No. 12, sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <div data-bbox="795 1239 990 1449" style="text-align: center;"> <p>T4N R69E S 3 AP12 2003</p> </div> <hr style="width: 30%; margin: auto;"/>
	<p>S. 31°43'20" E., on line 12-13.</p>
0.05	<p>Barbed wire fence, T-bar and juniper posts, bears N. 85° W. and S. 85° E.</p>
4.079	<p>Angle Point No. 13, sec. 3, on the E-W center line of the SW1/4 of sec. 3, hereinbefore described.</p> <hr style="width: 60%; margin: auto;"/>

METES-AND-BOUNDS SURVEY IN SECTION 10,  
T. 4 N., R. 69 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From Angle Point No. 1, sec. 10, on the E-W center line of the NE1/4 of sec. 10, hereinbefore described.</p>
	<p>S. 46°52'00" E., on line 1-2.</p>
4.939	<p>Intersect the N-S center line of the NE1/4 of sec. 10, at a point from which the NE 1/16 sec. cor. of sec. 10, bears N. 0°01'40" W., 3.379 chs. dist., hereinbefore described.</p>
9.444	<p>Point for Angle Point No. 2, sec. 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p>
	<div style="text-align: center;">  <p>2003</p> </div> <p>Cor. is located 1 lk. S. of barbed wire fence, T-bar and juniper posts, bears N. 40° E. and S. 40° W., and 1 ch. SW. of petroglyphs at the southerly end of rock faces, extending N. 45° W.</p>
	<hr style="width: 20%; margin: auto;"/> <p>S. 39°16'20" W., on line 2-3, along barbed wire fence, T-bar posts.</p>
1.45	<p>Center of graded dirt road, 20 lks. wide, bears N. 20° W. and S. 50° E., in curve.</p>
5.188	<p>Intersect the N-S center line of the NE1/4 of sec. 10, at a point from which the NE 1/16 sec. cor. of sec. 3, bears N. 0°01'40" W., 10.475 chs. dist., hereinbefore described.</p>
6.637	<p>Point for Angle Point No. 3, sec. 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p>
	<div style="text-align: center;">  <p>2003</p> </div>

METES-AND-BOUNDS SURVEY IN SECTION 10,  
T. 4 N., R. 69 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

from which

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, for a reference monument, bears N. 81°55' E., 99.0 lks. dist., with brass cap mkd. RM AP3 65.3 FT TO COR and an arrow pointing to the cor.

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, for a reference monument, bears S. 3°49' W., 284.6 lks. dist., with brass cap mkd. RM AP3 187.8 FT TO COR and an arrow pointing to the cor.

Cor. is located at SE. end of dirt embankment, 7 lks. wide, 1 ft. high, bears N. 50° W., and 23 lks. E. of a ditch, 15 lks. wide, 3 ft. deep, drains S. 50° E.

---

N. 49°59'20" W. on line 3-4, along dirt embankment, 7 lks. wide, 1 ft. high, dividing open pasture from ditch.

18.028

Angle Point No. 4, sec. 10, on the E-W center line of the NE1/4 of sec. 10, hereinbefore described.

---

## TOWNSHIP 4 NORTH, RANGE 69 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

## GENERAL DESCRIPTION

The land encompassed in this survey is located on the Mount Wilson National Back Country Byway on the east side of the Wilson Creek Range. The area is approximately 20 miles north of Eagle Valley Reservoir in Nevada's Spring Valley State Park at Ursine, Nevada.

The vegetation in the area is rolling hills covered with pinion pine, western juniper and sagebrush. The area drains into Camp Valley which drains southeasterly from the west boundary of section 3 to the east boundary of section 10. Camp Valley varies in size from 5 to 20 chains wide, with elevations ranging from about 6200 feet above sea level on the east boundary of section 10 up to about 6800 feet at the upper rims of Camp Valley.

The floor of Camp Valley in the southwest one-quarter of section 3, northeast one-quarter of the northwest one-quarter and the northeast one-quarter of section 10, has been developed into a small ranch and from sage covered land to pasture for cattle grazing. Camp Creek, a small intermittent stream, was diverted into a flood control ditch near the C-N-SW 1/64 section corner of section 3, which runs along the easterly side of Camp Valley Road and the southwest edge of Camp Valley. The ditch drains into unimproved lands in the southeast one-quarter of section 10, where Camp Creek returns to its natural course.

---

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Jeremiah J. Lee	Surveying Technician
Clive M. Staple	Surveying Technician
Michael Derby	Survey Aid
Michelle E. Martin	Survey Aid

CERTIFICATE OF SURVEY

We, Craig L. Wanless, Cadastral Surveyor, and Mark G. Petrosine, Surveying Technician, HEREBY CERTIFY upon honor, that in pursuance of Special Instructions bearing date of the 24th day of October, 2003, we have dependently resurveyed a portion of the subdivisional lines, subdivided sections 3 and 10, and executed metes-and-bounds surveys in sections 3 and 10, in Township 4 North, Range 69 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

January 10, 2005  
(Date)

Craig L. Wanless  
(Cadastral Surveyor)

January 10, 2005  
(Date)

Mark Petrosine  
(Surveying Technician)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Reno, Nevada

The foregoing field notes of the dependent resurvey of a portion of the subdivisional lines, the subdivision of sections 3 and 10, and metes-and-bounds surveys in sections 3 and 10, Township 4 North, Range 69 East, Mount Diablo Meridian, Nevada, executed by Craig L. Wanless, Cadastral Surveyor, and Mark G. Petrosine, Surveying Technician, having been critically examined and found correct, are hereby approved.

January 25, 2005  
(Date)

David D. Morlan  
(Chief Cadastral Surveyor, Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 4 N., R. 69 E., Mount Diablo Meridian, Nevada, is a true copy of the original field notes.~~

~~\_\_\_\_\_  
(Date)~~

~~\_\_\_\_\_  
(Chief Cadastral Surveyor, Nevada)~~