

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

A PORTION OF THE SOUTH BOUNDARY (FIRST STANDARD PARALLEL SOUTH),

THE EAST, WEST AND NORTH BOUNDARIES

AND

A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF CERTAIN SECTIONS,

TOWNSHIP 4 SOUTH, RANGE 66 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

EXECUTED BY

Brock R. Clifford, Cadastral Surveyor

Under Special Instructions dated October 19, 1992,  
approved October 19, 1992, and Amended Special Instructions  
dated September 18, 2001, approved September 18, 2001,  
which provided for the surveys included under Group No. 729,  
and Assignment Instructions dated October 20, 1992.

Survey commenced December 1, 1992

Survey completed October 4, 1997

# INDEX DIAGRAM

TOWNSHIP 4 SOUTH, RANGE 66 EAST

20	19	18	17	17	16
15 6	5	4	3	2	29 1 9
					28
14 7	8	9	10	11	27 12 8
					27
13 18	17	16	15	14	26 13 7
					26
13 19	20	21	22	23	25 24 6
				32	24
12 30	29	28	27	31 26	23 25 5
				30	22
11 31	32	33	34	29 35	20 36 4
				3	2

Subdivision of Section 1 . . . . . pp. 33-34  
 Subdivision of Section 12 . . . . . pp. 34-35  
 Subdivision of Section 13 . . . . . pp. 35-36  
 Subdivision of Section 24 . . . . . pp. 36-39  
 Subdivision of Section 25 . . . . . pp. 40-42  
 Subdivision of Section 26 . . . . . pp. 42-43  
 Subdivision of Section 35 . . . . . pp. 43-45

## TOWNSHIP 4 SOUTH, RANGE 66 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The following field notes are those of the dependent resurvey of a portion of the south boundary (First Standard Parallel South), the east, west and north boundaries and a portion of the subdivisional lines, and the subdivision of certain sections, Township 4 South, Range 66 East, Mount Diablo Meridian, Nevada.

The west four miles of the south boundary (First Standard Parallel South) were surveyed by U.S. Deputy Surveyor E.B. Monroe in 1869 under Contract No. 31. The north three and one-half miles of the east boundary and a portion of the subdivisional lines were surveyed and a traverse was run between certain corners from the standard cor. of secs. 34 and 35, to the  $\frac{1}{4}$  sec. cor. of secs. 19 and 24, T. 4 S., Rs. 66 and 67 E. by U.S. Deputy Surveyor E.B. Monroe in 1872 under Contract No. 53. The east two miles of the south boundary (First Standard Parallel South), the south two and one-half miles of the east boundary, the north and west boundaries and the subdivisional lines were surveyed by U.S. Deputy Surveyor R.H. Woods in 1881 under Contract No. 121. The south boundaries of secs. 34 and 35, and the east one-half mile of the south boundary of sec. 33 (First Standard Parallel South) were retraced and resurveyed by U.S. Transitman E.R. Bunbury in 1916 under Group No. 34. The cor. of Tps. 3 and 4 S., Rs. 66 and 67 E., was remonumented by Cadastral Surveyor N.R. Forsyth during the dependent resurvey of T. 3 S., R. 67 E. in 1971 under Group No. 477.

Before restoring the corners, the lines of the original surveys were retraced and diligent search made for any evidence of the original corners and other calls of the original field note record.

During the course of this resurvey, the record of the traverse run by E.B. Monroe for the subdivisional lines for T. 4 S., R. 66 E. in 1872 under Contract No. 53, was retraced with no evidence of the intervening corners being found, due to flooding and fires. For simplification, this traverse is omitted from the body of these field notes.

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated October 19, 1992, and Amended Special Instructions dated September 18, 2001.

The direction of the lines of this survey were determined by azimuth taken from National Geodetic Survey control, (formerly U.S.C. & G.S. triangulation) stations "GREY DOME" and "ELLA MOUNTAIN", located in sec. 26, T. 3 S., R. 65 E., and unsurveyed T. 5 S., R. 67 E., respectively and carried forward by sustained angulation, and were checked by numerous Polaris and Solar observations throughout the progress of the survey.

The vertical angles of measurements made on the slope were ascertained with a theodolite in good adjustment; the horizontal equivalents only are entered in the field notes.

## TOWNSHIP 4 SOUTH, RANGE 66 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The geographic position of the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., determined from National Geodetic Survey control (formerly U.S.C. & G.S. triangulation) stations "CALIENTE" and "ECOLAH", located in unsurveyed T. 4 S., R. 65 E. and sec. 31, T. 4 S., R. 68 E., respectively, using survey grade GPS receivers, is at latitude 37°36'26.55" N. and longitude 114°32'04.55" W., (NAD 27).

The mean magnetic declination is 15<sup>1</sup>/<sub>2</sub>° E., as shown on U.S. Geological Survey 7<sup>1</sup>/<sub>2</sub> minute quadrangle map "CALIENTE", dated 1970.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY  
(FIRST STANDARD PARALLEL SOUTH),  
T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by  
U.S. Deputy Surveyor R.H. Woods in 1881,  
and the Dependent Resurvey by U.S. Transitman  
E.R. Bunbury in 1916

From the point for the standard cor. of Tps. 4 S., Rs. 66 and 67 E., at proportionate distance, falls on steep rocky bluff where it is impracticable to establish a permanent monument; there is no remaining evidence of the original corner.

From this point the point selected for an off-line witness cor. to the standard cor. of Tps. 4 S., Rs. 66 and 67 E., bears N. 46°43'00" E., 3.863 chs. dist.

Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 6 ins. in the ground to bedrock, over a magnetic marker, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

WC  
SC  
T4S  
R66E R67E  
S 36 | S 31

↙  
1993

From this same point the cor. of Tps. 4 S., Rs. 67 and 68 E., bears N. 89°31'30" E., 481.260 chs. dist., monumented with an iron post, 2<sup>1</sup>/<sub>2</sub> ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the dependent resurvey of the First Standard Parallel South, through R. 68 E., executed by R.F. Wilson, Cadastral Engineer, in 1953 under Group No. 295.

This control line was fully retraced and careful search was made for evidence of intervening corners, none of which were recovered.

S. 89°31'30" W., on the S. bdy. of sec. 36.

Ascend over rocky bluffs on the W. side of Sawmill Canyon.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY  
 (FIRST STANDARD PARALLEL SOUTH),  
 T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.00	Top of ascent, continue over mountainous land, through scattered pinion pine and juniper.
24.00	Descend over W. slope.
38.705	<p>Point selected for the witness cor. to the standard 1/4 sec. cor. of sec. 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., over an "X" chiseled in bedrock, over a magnetic marker, and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC                      SC                      T4S R66E                      1/4 S36                      ←</p> <p>1993</p> </div>
	Descend sharply over rocky bluffs.
40.105	Point for the standard 1/4 sec. cor. of sec. 36, at proportionate distance, falls on steep W. facing rocky bluff where it is impracticable to establish a permanent monument; there is no remaining evidence of the original corner.
47.00	Ravine, drains NNE.; begin sharp ascent over E. facing rock bluffs.
54.00	Top of sharp ascent; continue over mountainous land, through pinion pine and juniper.
80.210	<p>The standard cor. of secs. 35 and 36, monumented with a sandstone, 8x7x6 ins., firmly set in a mound of stone, 3 ft. base, 1 ft. high, plainly mkd. with 5 notches on the W. edge and 1 notch on the E. edge as described in the field notes of T. 5 S., R. 66 E., executed under Group No. 34.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, over a magnetic marker, and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>SC                      T4S R66E                      S 35   S 36</p> <hr style="width: 10%; margin: auto;"/> <p>1993</p> </div> <p>Deposit the original cornerstone alongside the stainless steel post.</p> <hr style="width: 80%; margin: auto;"/> <p>S. 89°41'40" W., on the S. bdy. of sec. 35.</p> <p>Over mountainous land, descend gradually.</p>
19.934	Point for the standard E 1/16 sec. cor. of sec. 35.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY  
 (FIRST STANDARD PARALLEL SOUTH),  
 T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 12 ins. in the ground to bedrock, over a magnetic marker, and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">S 35                      E <sup>1</sup>/<sub>16</sub></p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">1993</p>
20.258	<p>From this point the original closing cor. of secs. 1 and 2, T. 5 S., R. 66 E., bears SOUTH, 0.040 chs. dist., monumented with an iron post, 2 ins. diam., firmly set projecting 18 ins. above a mound of stone, with brass cap mkd. as described in the field notes of T. 5 S., R. 66 E., executed under Group No. 34.</p>
38.00	<p>Begin sharp descent over W. facing rock bluffs through juniper.</p>
39.868	<p>The standard <sup>1</sup>/<sub>4</sub> sec. cor. of sec. 35, monumented with an iron post, 1 in. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of T. 5 S., R. 66 E., executed under Group No. 34. Add the marks 1993 to the brass cap.</p> <hr style="width: 50%; margin: auto;"/> <p style="text-align: center;">S. 89°37'40" W., beginning new measurement.</p>
29.50	<p>Wash, drains NNW.</p>
39.572	<p>The standard cor. of secs. 34 and 35, monumented with an iron post, 2 ins. diam., firmly set projecting 18 ins. above a mound of stone, with brass cap mkd. as described in the field notes of T. 5 S., R. 66 E., executed under Group No. 34. Add the marks 1993 to the brass cap.</p> <p>The cor. is located at the base of a shear rock face, 30 ft. high.</p> <hr style="width: 80%; margin: auto;"/> <p style="text-align: center;">DEPENDENT RESURVEY OF THE EAST BOUNDARY,                      T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr style="width: 80%; margin: auto;"/> <p style="text-align: center;">Reestablishment of the Surveys Executed by                      U.S. Deputy Surveyor E.B. Monroe in 1872 and                      U.S. Deputy Surveyor R.H. Woods in 1881</p> <hr style="width: 30%; margin: auto;"/> <p>From the true point for the standard cor. of Tps. 4 S., Rs. 66 and 67 E., hereinbefore described.</p> <p>N. 0°22'30" E., bet. secs. 31 and 36.</p> <p>Over rugged, rocky bluffs through pinion pine and juniper.</p>
4.00	<p>Sawmill Canyon, drains NNW.</p>
5.00	<p>Begin sharp ascent over SW. facing rock bluffs.</p>
33.00	<p>Top of ascent; begin descent over N. facing rock bluffs.</p>
40.164	<p>Point for the <sup>1</sup>/<sub>4</sub> sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p>

DEPENDENT RESURVEY OF THE EAST BOUNDARY,  
T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 18 ins. in the ground to bedrock, over a magnetic marker, and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T4S R66E R67E S 36   <sup>1</sup>/<sub>4</sub> S 31</p> <p style="text-align: center;">1993</p>
43.00	Ravine, drains WNW.; begin sharp ascent over SW. facing rock bluffs.
68.00	Ridge, bears ESE. and WNW.
80.328	<p>Point for the cor. of secs. 25, 30, 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 24 ins. in the ground, over a magnetic marker, and in a collar of stone, 2 ft. diam., with brass cap mkd.</p> <p style="text-align: center;">T4S R66E R67E S 25   S 30 ----- S 36   S 31</p> <p style="text-align: center;">1997</p>
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <hr/> <p>N. 0°22'30" E., bet. secs. 25 and 30.</p> <p>Over rugged, broken land, through pinion pine and juniper.</p>
10.50	Ravine, drains NW.
20.082	Point for the S <sup>1</sup> / <sub>16</sub> sec. cor. of secs. 25 and 30, falls on S. side of a steep rocky point, bears WNW. and ESE., where it is impracticable to establish a permanent monument.
24.479	<p>Point selected for the witness cor. to the S <sup>1</sup>/<sub>16</sub> sec. cor. of secs. 25 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 12 ins. in the ground to bedrock, over a magnetic marker, and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">WC S <sup>1</sup>/<sub>16</sub> S 25   S 30 ↓</p> <p style="text-align: center;">1997</p>
40.164	Point for the <sup>1</sup> / <sub>4</sub> sec. cor. of secs. 25 and 30, at proportionate distance; there is no remaining evidence of the original corner.

DEPENDENT RESURVEY OF THE EAST BOUNDARY,  
T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 18 ins. in the ground to bedrock, over a magnetic marker, and in a collar of stone, 3 ft. diam., with brass cap mkd.</p> <p style="text-align: center;">T4S R66E R67E S 25   <sup>1</sup>/<sub>4</sub> S 30</p> <p style="text-align: center;">1997</p> <p>Begin descent, over rugged, broken land.</p>
73.503	<p>Point selected for the witness cor. to the cor. of secs. 19, 24, 25 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 6 ins. in the ground to bedrock, over a magnetic marker, and in a mound of stone, 5 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">WC T4S R66E↑R67E S 24   S 19 ----- S 25   S 30</p> <p style="text-align: center;">1997</p>
80.328	<p>Point for the cor. of secs. 19, 24, 25 and 30, at proportionate distance, falls on steep rocky slide area where it is impracticable to establish a permanent monument; there is no remaining evidence of the original corner.</p> <hr/> <p>N. 0°22'30" E., bet. secs. 19 and 24.</p> <p>Over rugged, broken land.</p>
20.167	<p>Point for the S <sup>1</sup>/<sub>16</sub> sec. cor. of secs. 19 and 24, falls on steep rock projection, bears E. and W., where it is impracticable to establish a permanent monument.</p>
24.377	<p>Point selected for the witness cor. to the S <sup>1</sup>/<sub>16</sub> sec. cor. of secs. 19 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 26 ins. in the ground, over a magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">WC S <sup>1</sup>/<sub>16</sub> S 24   S 19 ↓</p> <p style="text-align: center;">1997</p>
27.00	<p>Set a 1x1 in. fiberglass fence post, 5 ft. long, alongside the stainless steel post.</p> <p>End descent; continue over level pasture land.</p>

202

DEPENDENT RESURVEY OF THE EAST BOUNDARY,  
T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.334	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 19 and 24, determined by the method of irregular boundary adjustment; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 26 ins. in the ground, over a magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T4S R66E R67E S 24   <math>\frac{1}{4}</math>S 19</p> <p style="text-align: center;">1997</p> <p>Set a 1x1 in. fiberglass fence post, 4 ft. long, alongside the stainless steel post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <hr/> <p>N. <math>0^{\circ}29'30''</math> E., beginning new measurement.</p>
7.00	State Route No. 317, 35 lks. wide, bears NNE. and SSW.
9.00	Meadow Valley Wash, drains SW.
15.50	Meadow Valley Wash, drains SE.
40.164	<p>Point for the cor. of secs. 13, 18, 19 and 24, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 26 ins. in the ground, over a magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T4S R66E R67E S 13   S 18</p> <hr/> <p style="text-align: center;">S 24   S 19</p> <p style="text-align: center;">1997</p> <p>Set a 1x1 in. fiberglass fence post, 4 ft. long, alongside the stainless steel post.</p> <hr/> <p>N. <math>0^{\circ}29'30''</math> E., bet. secs. 13 and 18.</p> <p>Over level pasture land.</p>
0.80	Meadow Valley Wash, drains SW.
9.20	Union Pacific Railroad, bears NNE. and SSW.
20.082	<p>Point for the S <math>\frac{1}{16}</math> sec. cor. of secs. 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a magnetic marker, with brass cap mkd.</p>

DEPENDENT RESURVEY OF THE EAST BOUNDARY,  
T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">S <math>\frac{1}{16}</math> S 13   S 18 1997</p>
40.164	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 13 and 18, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T4S R66E R67E S <math>\frac{1}{4}</math>   S 18 1997</p> <p>Set a steel fence post, 5 ft. long, alongside the stainless steel post.</p>
41.50	Begin sharp ascent over SE. facing rock bluffs.
54.00	Top of ascent; continue over rugged broken land.
61.50	Ravine, drains SE.
79.50	Spur, slopes SE.
80.328	<p>The cor. of secs. 7, 12, 13 and 18, perpetuated by Richard E. Fonger, Nevada Professional Land Surveyor No. 4235, monumented with an aluminum post, <math>2\frac{1}{2}</math> ins. diam., firmly set in a mound of stone, with aluminum cap mkd. T4S R66E R67E S7 S12 S13 S18 RLS4235 MDBM ELY NV 1989, with the original monument, a trapstone 18 X 12 X 6 ins. mkd. with 4 notches on an edge and 2 notches on the opposite edge set alongside. No plat of this survey is on record.</p> <p>Not remonumented.</p> <hr/> <p>N. <math>0^{\circ}41'00''</math> E., bet. secs. 7 and 12.</p> <p>Over rolling, nearly level land.</p>
20.065	<p>Point for the S <math>\frac{1}{16}</math> sec. cor. of secs. 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 12 ins. in the ground to bedrock, over a magnetic marker, and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">S <math>\frac{1}{16}</math> S 12   S 7 1993</p>

DEPENDENT RESURVEY OF THE EAST BOUNDARY,  
T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.130	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 7 and 12, reestablished by Richard E. Fonger, Nevada Professional Land Surveyor No. 4235, monumented with an aluminum post, <math>2\frac{1}{2}</math> ins. diam., firmly set in a collar of stone, with aluminum cap mkd. T4S R66E R67E S7 S12 RLS 4235 ELY NV 1989 and is accepted as a careful and faithful reestablishment of the position of the original corner. No plat of this survey is on record.</p>
	<p>Not remonumented.</p>
	<hr/> <p>N. <math>0^{\circ}42'40''</math> E., beginning new measurement.</p>
	<p>Over nearly level, rolling land, through sagebrush.</p>
1.10	<p>Power line, bears NW. and SE.</p>
6.00	<p>Newman Canyon, drains SE.</p>
8.30	<p>U.S. Highway No. 93, 50 lks. wide, bears NW. and SE.</p>
20.069	<p>The N <math>\frac{1}{16}</math> sec. cor. of secs. 7 and 12, determined by person(s) unknown, monumented with an iron "T post", 1x1 in., 4 ft. long, firmly set projecting 3 ins. above the ground and is accepted as a careful and faithful determination of the position of the corner.</p>
	<p>At the corner point</p>
	<p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 22 ins. in the ground, over a magnetic marker, with brass cap mkd.</p>
	<p style="text-align: center;">N <math>\frac{1}{16}</math> S 12   S 7 1993</p>
	<p>Reset the iron "T post", inverted alongside the stainless steel post.</p>
	<hr/> <p>N. <math>0^{\circ}42'40''</math> E., beginning new measurement.</p>
20.069	<p>The cor. of secs. 1, 6, 7 and 12, reestablished by Richard E. Fonger, Nevada Professional Land Surveyor No. 4235, monumented with an aluminum post, <math>2\frac{1}{2}</math> ins. diam., firmly set in a collar of stone, with aluminum cap mkd. T4S R66E R67E S1 S6 S7 S12 RLS4235 ELY NV 1989 and is accepted as a careful and faithful reestablishment of the position of the original corner. No plat of this survey is on record.</p>
	<p>Not remonumented.</p>
	<hr/> <p>N. <math>0^{\circ}39'30''</math> E., bet. secs. 1 and 6.</p>
	<p>Over broken, rolling land, through sagebrush, with scattered pinion pine and juniper.</p>
20.063	<p>Point for the S <math>\frac{1}{16}</math> sec. cor. of secs. 1 and 6.</p>

DEPENDENT RESURVEY OF THE EAST BOUNDARY,  
T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 14 ins. in the ground to bedrock, over a magnetic marker, and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">S 1<sup>1</sup>/<sub>16</sub></p> <p style="text-align: center;">S 1   S 6</p> <p style="text-align: center;">1993</p>
34.00	Top of ascent.
40.126	<p>The <sup>1</sup>/<sub>4</sub> sec. cor. of secs. 1 and 6, monumented with a quartzite stone, 12x10x6 ins., firmly set in a mound of stone, 3 ft. base, 1 ft. high, mkd. <sup>1</sup>/<sub>4</sub> on the W. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 16 ins. in the ground to bedrock, over a magnetic marker, and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T4S R66E R67E S 1<sup>1</sup>/<sub>4</sub>   S 6</p> <p style="text-align: center;">1993</p> <p>Bury the original cornerstone and set a steel fence post, 6 ft. long, alongside the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°54'10" W., beginning new measurement.</p>
36.910	<p>The cor. of Tps. 3 and 4 S., Rs. 66 and 67 E., monumented with an iron post, 2<sup>1</sup>/<sub>2</sub> ins. diam., firmly set in a mound of stone, with brass cap erroneously mkd. for R. 67 E. only in the 1971 resurvey, executed under Group No. 477. Add mks. for R. 66 E.; the cap is now marked.</p> <p style="text-align: center;">T3S R66E R67E S 36   S 31</p> <hr style="width: 20%; margin: auto;"/> <p style="text-align: center;">S 1   S 6 T4S</p> <p style="text-align: center;">1971 1993</p> <p>The corner is located on the S. side of Antelope Canyon, drains SE.</p> <hr style="width: 20%; margin: auto;"/>

DEPENDENT RESURVEY OF THE WEST BOUNDARY,  
T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

Reestablishment of the Survey Executed by  
U.S. Deputy Surveyor R.H. Woods in 1881

From the standard cor. of Tps. 4 S., Rs. 65 and 66 E., monumented with a trachyte stone, 10x10x8 ins., firmly set in a mound of stone, 2 ft. base, 1 ft. high, plainly mkd. with 6 notches on the E. edge and 6 notches on the W. edge.

At the corner point

Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 16 ins. in the ground to bedrock, over a magnetic marker, and in a mound of stone, 3 ft. base to top, with brass cap mkd.

SC  
T4S  
R65E R66E  
S 36 | S 31

1993

N. 0°31'40" E., bet. secs. 31 and 36.

Over mountaineous land, through sagebrush, with dense pinion pine and juniper.

5.50 Ravine, drains ENE.

37.50 Colburn Canyon, drains SE.

40.232 Point for the <sup>1</sup>/<sub>4</sub> sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 6 ins. in the ground to bedrock, over a magnetic marker, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T4S  
R65E R66E  
<sup>1</sup>/<sub>4</sub>  
S 36 | S 31

1993

Set a 1x1 in. fiberglass fence post, 4 ft. long, alongside the stainless steel post.

80.464 Point for the cor. of secs. 25, 30, 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 12 ins. in the ground to bedrock, over a magnetic marker, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

DEPENDENT RESURVEY OF THE WEST BOUNDARY,  
T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS											
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T4S</td></tr> <tr><td style="text-align: center;">R65E</td><td style="text-align: center;">R66E</td></tr> <tr><td style="text-align: center;">S 25</td><td style="text-align: center;">S 30</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S 36</td><td style="text-align: center;">S 31</td></tr> </table> <p style="text-align: center;">1993</p> <p>Set a 1x1 in. fiberglass fence post, 4 ft. long, alongside the stainless steel post.</p> <hr/> <p>N. 0°31'40" E., bet. secs. 25 and 30.</p> <p>Over mountaineous land, through sagebrush, with dense pinion pine and juniper.</p>	T4S		R65E	R66E	S 25	S 30	-----		S 36	S 31
T4S											
R65E	R66E										
S 25	S 30										
-----											
S 36	S 31										
40.232	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 25 and 30, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 6 ins. in the ground to bedrock, over a magnetic marker, and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p>										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T4S</td></tr> <tr><td style="text-align: center;">R65E</td><td style="text-align: center;">R66E</td></tr> <tr><td style="text-align: center;">S 25</td><td style="text-align: center;">S 30</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S 25</td><td style="text-align: center;">S 30</td></tr> </table> <p style="text-align: center;">1993</p> <p>Set a 1x1 in. fiberglass fence post, 4 ft. long, alongside the stainless steel post.</p>	T4S		R65E	R66E	S 25	S 30	-----		S 25	S 30
T4S											
R65E	R66E										
S 25	S 30										
-----											
S 25	S 30										
53.00	Hardy Canyon, drains ENE.										
67.80	Trail road, 15 lks. wide, bears NE. and SW.										
77.50	Ravine, drains ENE.										
80.464	<p>Point for the cor. of secs. 19, 24, 25 and 30, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 4 ins. in the ground to bedrock, over a magnetic marker, and in a mound of stone, 5 ft. base to top, with brass cap mkd.</p>										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T4S</td></tr> <tr><td style="text-align: center;">R65E</td><td style="text-align: center;">R66E</td></tr> <tr><td style="text-align: center;">S 24</td><td style="text-align: center;">S 19</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S 25</td><td style="text-align: center;">S 30</td></tr> </table> <p style="text-align: center;">1993</p> <p>from which</p> <p style="text-align: center;">A pinion pine, 6 ins. diam., bears N. <math>52\frac{1}{2}</math>°E., 22.5 lks. dist., mkd. T4S R66E S19 BT.</p>	T4S		R65E	R66E	S 24	S 19	-----		S 25	S 30
T4S											
R65E	R66E										
S 24	S 19										
-----											
S 25	S 30										

DEPENDENT RESURVEY OF THE WEST BOUNDARY,  
T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>A pinion pine, 4 ins. diam., bears S. <math>15\frac{1}{4}^{\circ}</math> E., 37 lks. dist., mkd. X BT.</p> <hr/> <p>N. <math>0^{\circ}31'40''</math> E., bet. secs. 19 and 24.</p> <p>Over mountaineous land, through sagebrush, with dense pinion pine and juniper.</p>
31.50	Buckboard Canyon, drains ESE.
40.232	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 19 and 24, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 10 ins. in the ground to bedrock, over a magnetic marker, and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T4S R65E R66E <math>\frac{1}{4}</math> S 24   S 19</p> <p>1993</p> </div> <p>Set a 1x1 in. fiberglass fence post, 4 ft. long, alongside the stainless steel post.</p>
52.00	Ravine, drains E.
80.464	<p>Point for the cor. of secs. 13, 18, 19 and 24, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a brass tablet, <math>3\frac{1}{4}</math> ins. diam., <math>3\frac{1}{2}</math>-in. stem, in drill hole in granite outcrop, with top mkd.</p> <div style="text-align: center;"> <p>T4S R65E R66E S 13   S 18 <hr/>S 24   S 19</p> <p>1993</p> </div> <p>from which</p> <p>A juniper, 10 ins. diam., bears S. <math>50\frac{3}{4}^{\circ}</math> E., 87 lks. dist., mkd. T4S R66E S19 BT.</p> <hr/> <p>N. <math>0^{\circ}31'40''</math> E., bet. secs. 13 and 18.</p> <p>Over mountaineous land, through sagebrush, with dense pinion pine and juniper.</p>
0.70	Ravine, drains ESE.
21.00	Spur, slopes SE.

DEPENDENT RESURVEY OF THE WEST BOUNDARY,  
T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.232	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 13 and 18, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 10 ins. in the ground to bedrock, over a magnetic marker, and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T4S R65E R66E S 13   <math>\frac{1}{4}</math> S 18</p> <p style="text-align: center;">1993</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 6 ins. diam., bears N. <math>72\frac{3}{4}^{\circ}</math> E., 44 lks. dist., mkd. <math>\frac{1}{4}</math> S18 BT.</p> <p style="padding-left: 40px;">A pinion pine, 8 ins. diam., bears S. <math>6^{\circ}</math> W., 59 lks. dist., mkd. <math>\frac{1}{4}</math> S13 BT.</p>
48.00	Spur, slopes NE.
63.50	U.S. Highway No. 93, 50 lks. wide, bears ESE. and WNW.
77.20	Ravine, drains NE.
80.464	<p>Point for the cor. of secs. 7, 12, 13 and 18, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 10 ins. in the ground to bedrock, over a magnetic marker, and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T4S R65E R66E S 12   S 7 <hr style="width: 50%; margin: auto;"/>S 13   S 18</p> <p style="text-align: center;">1993</p> <p>Set a 1x1 in. fiberglass fence post, 5 ft. long, alongside the stainless steel post.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>N. <math>0^{\circ}31'40''</math> E., bet. secs. 7 and 12.</p> <p>Over mountaineous land, through sagebrush, with dense pinion pine and juniper.</p>
40.232	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 10 ins. in the ground to bedrock, over a magnetic marker, and in a mound of stone, 5 ft. base to top, with brass cap mkd.</p>

DEPENDENT RESURVEY OF THE WEST BOUNDARY,  
T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T4S R65E R66E <math>\frac{1}{4}</math> S 12   S 7  1993</p>
60.50	Ravine, drains SE.
80.464	<p>Point for the cor. of secs. 1, 6, 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 18 ins. in the ground to bedrock, over a magnetic marker, and in a collar of stone, 2 ft. diam., with brass cap mkd.</p> <p style="text-align: center;">T4S R65E R66E S 1   S 6 <hr style="width: 50%; margin: auto;"/>S 12   S 7  1993</p> <p>from which</p> <p style="padding-left: 40px;">A pinion pine, 10 ins. diam., bears N. 45<math>\frac{3}{4}</math>° E., 31 lks. dist., mkd. T4S R66E S6 BT.</p> <p style="padding-left: 40px;">A pinion pine, 8 ins. diam., bears S. 29<math>\frac{1}{2}</math>° E., 29 lks. dist., mkd. T4S R66E S7 BT.</p>
	<p>N. 0°31'40" E., bet. secs. 1 and 6.</p>
	<p>Over mountaineous land, through sagebrush, with dense pinion pine and juniper.</p>
34.00	Ravine, drains SE.
40.232	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 10 ins. in the ground to bedrock, over a magnetic marker, and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T4S R65E R66E <math>\frac{1}{4}</math> S 1   S 6  1993</p>
52.00	Ravine, drains NE.
80.464	<p>The cor. of Tps. 3 and 4 S., Rs. 65 and 66 E., monumented with a limestone, 8x8x6 ins., firmly set in a mound of stone, 3 ft. diam., plainly mkd. with 6 notches on the N., E. and W. edges and dimly mkd. on the S. edge.</p>

DEPENDENT RESURVEY OF THE WEST BOUNDARY,  
T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

At the corner point

Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 16 ins. in the ground to bedrock, over a magnetic marker, and in a mound of stone, 3 ft. base to top, with brass cap mkd.

T3S	
R65E	R66E
S 36	S 31
-----	
S 1	S 6
T4S	

1993

Bury the original cornerstone and set a steel fence post, 5 ft. long, alongside the stainless steel post.

---

DEPENDENT RESURVEY OF THE NORTH BOUNDARY  
T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

---

Reestablishment of the Survey Executed by  
U.S. Deputy Surveyor R.H. Woods in 1881

---

From the cor. of Tps. 3 and 4 S., Rs. 66 and 67 E., hereinbefore described.

N. 89°38'20" W., bet. secs. 1 and 36.

Over rolling land, covered with scattered creosote brush, Yuccas, cacti and native grass.

39.050 Point for the <sup>1</sup>/<sub>4</sub> sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 18 ins. in the ground to bedrock, over a magnetic marker, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T3S R66E	
S 36	
<sup>1</sup> / <sub>4</sub>	-----
S 1	
T4S	

1993

44.00 Top of ascent; continue over rolling land, through sagebrush, with scattered pinion pine and juniper.

74.00 Ravine, drains SE.

78.100 Point for the cor. of secs. 1, 2, 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 22 ins. in the ground, over a magnetic marker, with brass cap mkd.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS								
	<div style="text-align: center;"> <table border="1"> <tr><td>T3S R66E</td></tr> <tr><td>S 35   S 36</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 2   S 1</td></tr> <tr><td colspan="2">T4S</td></tr> </table> <p>1993</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>The corner is located on a spur, slopes SSE.</p> <hr/> <p>N. 89°38'20" W., bet. secs. 2 and 35.</p> <p>Over mountaineous land, through sagebrush, with scattered pinion pine and juniper.</p> </div>	T3S R66E	S 35   S 36	<hr/>		S 2   S 1	T4S	
T3S R66E								
S 35   S 36								
<hr/>								
S 2   S 1								
T4S								
38.50	Ravine, drains SE.							
39.050	<p>Point for <math>\frac{1}{4}</math> sec. cor. of secs. 2 and 35, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 26 ins. in the ground, over a magnetic marker, with brass cap mkd.</p>							
61.50	<div style="text-align: center;"> <table border="1"> <tr><td>T3S R66E</td></tr> <tr><td>S 35</td></tr> <tr><td><math>\frac{1}{4}</math> ———</td></tr> <tr><td>S 2</td></tr> <tr><td colspan="2">T4S</td></tr> </table> <p>1993</p> <p>Set a 1x1 in. fiberglass fence post, 5 ft. long, alongside the stainless steel post.</p> </div>	T3S R66E	S 35	$\frac{1}{4}$ ———	S 2	T4S		
T3S R66E								
S 35								
$\frac{1}{4}$ ———								
S 2								
T4S								
78.100	<p>Ravine, drains SE.</p> <p>Point for the cor. of secs. 2, 3, 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 10 ins. in the ground to bedrock, over a magnetic marker, and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p>							
24.00	<div style="text-align: center;"> <table border="1"> <tr><td>T3S R66E</td></tr> <tr><td>S 34   S 35</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 3   S 2</td></tr> <tr><td colspan="2">T4S</td></tr> </table> <p>1993</p> <hr/> <p>N. 89°38'20" W., bet. secs. 3 and 34.</p> <p>Over mountaineous land, through sagebrush, with pinion pine and juniper.</p> </div> <p>Ravine, drains S.</p>	T3S R66E	S 34   S 35	<hr/>		S 3   S 2	T4S	
T3S R66E								
S 34   S 35								
<hr/>								
S 3   S 2								
T4S								

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.050	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 3 and 34, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 26 ins. in the ground, over a magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <p>T3S R66E S 34 <math>\frac{1}{4}</math> ——— S 3 T4S</p> <p>1993</p> </div> <p>Set a 1x1 in. fiberglass fence post, 5 ft. long, alongside the stainless steel post.</p>
78.100	<p>Point for the cor. of secs. 3, 4, 33 and 34, at proportionate distance, falls on steep E. facing bluff where it is impracticable to establish a permanent monument; there is no remaining evidence of the original corner.</p> <hr/> <p>N. <math>89^{\circ}38'20''</math> W., bet. secs. 4 and 33.</p> <p>Over mountaineous land, through sagebrush, with pinion pine and juniper.</p>
6.250	<p>Point selected for the witness cor. to the cor. of secs. 3, 4, 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 26 ins. in the ground, over a magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC T3S R66E S 33   S 34 —————&gt;  S 4   S 3 T4S</p> <p>1993</p> </div> <p>Set a 1x1 in. fiberglass fence post, 5 ft. long, alongside the stainless steel post.</p> <p>The witness cor. is located at the top of a 200 ft. high, E. facing rock bluff, bears N. and S.</p>
7.20	<p>Trailroad, 15 lks. wide, bears ENE. and WSW.</p>
39.050	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 4 and 33, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 26 ins. in the ground, over a magnetic marker, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T3S R66E S 33 <math>\frac{1}{4}</math> ——— S 4 T4S</p> <p style="text-align: center;">1993</p> <p>from which</p> <p style="padding-left: 40px;">A pinion pine, 10 ins. diam., bears S. <math>18\frac{1}{2}^\circ</math> E., 210 lks. dist., mkd. <math>\frac{1}{4}</math> S4 BT.</p> <p>Set a 1x1 in. fiberglass fence post, 5 ft. long, alongside the stainless steel post.</p>
50.50	Wash, 2 chs. wide, drains NE.
78.100	<p>Point for the cor. of secs. 4, 5, 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 18 ins. in the ground to bedrock, over a magnetic marker, and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p>
	<p style="text-align: center;">T3S R66E S 32   S 33 ——— ——— S 5   S 4 T4S</p> <p style="text-align: center;">1993</p> <p>Set a 1x1 in. fiberglass fence post, 4 ft. long, alongside the stainless steel post.</p> <hr/> <p>N. <math>89^\circ 38' 20''</math> W., bet. secs. 5 and 32.</p> <p>Over mountaineous land, through sagebrush, with dense pinion pine and juniper.</p>
39.050	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 5 and 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 26 ins. in the ground, over a magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T3S R66E S 32 <math>\frac{1}{4}</math> ——— S 5 T4S</p> <p style="text-align: center;">1993</p> <p>Set a 1x1 in. fiberglass fence post, 4 ft. long, alongside the stainless steel post.</p>

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS											
78.100	<p>Point for the cor. of secs. 5, 6, 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 26 ins. in the ground, over a magnetic marker, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T3S R66E</td></tr> <tr><td>S 31</td><td>S 32</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 6</td><td>S 5</td></tr> <tr><td colspan="2">T4S</td></tr> </table> <p style="text-align: center;">1993</p> <p>Set a 1x1 in. fiberglass fence post, 4 ft. long, alongside the stainless steel post.</p> <hr/> <p>N. 89°38'20" W., bet. secs. 6 and 31.</p> <p>Over mountaineous land, through sagebrush, with dense pinion pine and juniper.</p>	T3S R66E		S 31	S 32	<hr/>		S 6	S 5	T4S	
T3S R66E											
S 31	S 32										
<hr/>											
S 6	S 5										
T4S											
39.050	<p>Point for the <sup>1</sup>/<sub>4</sub> sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 24 ins. in the ground, over a magnetic marker, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T3S R66E</td></tr> <tr><td>S 31</td><td></td></tr> <tr><td><sup>1</sup>/<sub>4</sub></td><td><hr/></td></tr> <tr><td>S 6</td><td></td></tr> <tr><td colspan="2">T4S</td></tr> </table> <p style="text-align: center;">1993</p> <p>Set a 1x1 in. fiberglass fence post, 4 ft. long, alongside the stainless steel post.</p>	T3S R66E		S 31		<sup>1</sup> / <sub>4</sub>	<hr/>	S 6		T4S	
T3S R66E											
S 31											
<sup>1</sup> / <sub>4</sub>	<hr/>										
S 6											
T4S											
48.00	Trail road, 20 lks. wide, bears irregularly E. and W.										
77.944	The cor. of Tps. 3 and 4 S., Rs. 65 and 66 E., hereinbefore described.										
<p>DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>											
<p>Reestablishment of the Survey Executed by U.S. Deputy Surveyor R.H. Woods in 1881</p> <hr/>											
<p>From the standard cor. of secs. 35 and 36, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 1°48'00" E., bet. secs. 35 and 36.</p> <p>Over mountaineous land, through dense pinion pine and juniper, descend gradually.</p>											

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.014	<p>Point for the S <math>\frac{1}{16}</math> sec. cor. of secs. 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 20 ins. in the ground, over a magnetic marker, and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">S <math>\frac{1}{16}</math> S 35   S 36 1993</p>
26.00	<p>Begin sharp descent over W. facing rock bluffs.</p>
40.028	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., over an "X" chiseled in bedrock, over a magnetic marker, and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T4S R66E S 35   <math>\frac{1}{4}</math> S 36 1993</p>
60.042	<p>Point for the N <math>\frac{1}{16}</math> sec. cor. of secs. 35 and 36, falls on steep N. facing rock bluff where it is impracticable to establish a permanent monument.</p>
62.492	<p>Point selected for the witness cor. to the N <math>\frac{1}{16}</math> sec. cor. of secs. 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 26 ins. in the ground, over a magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">WC N <math>\frac{1}{16}</math> S 35   S 36 ↓ 1997</p> <p>The witness cor. is located at the base of a 200 ft. high rock bluff, bears E. and W.</p>
65.00	<p>End of descent, continue over nearly level land.</p>
80.056	<p>Point for the cor. of secs. 25, 26, 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 26 ins. in the ground, over a magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T4S R66E S 26   S 25 ----- S 35   S 36 1997</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a steel water pipe, 2<math>\frac{1}{2}</math> ins. diam., 7 ft. long, alongside the stainless steel post.</p>
	<p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°17'20" W., bet. secs. 25 and 36.</p> <p>Over rugged, broken land, through sagebrush, with dense pinion pine and juniper.</p>
18.893	<p>Point selected for the witness cor. to the E <math>\frac{1}{16}</math> sec. cor. of secs. 25 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 26 ins. in the ground, over a magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC S 25 ← E <math>\frac{1}{16}</math> S 36</p> <p>1997</p> </div> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of witness cor.</p> <p>The witness cor. is located at the top of a 30 ft. high rock bluff, bears N. and S.</p>
19.553	<p>Point for the E <math>\frac{1}{16}</math> sec. cor. of secs. 25 and 36, falls on W. facing rock bluff where it is impracticable to establish a permanent monument.</p>
39.106	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <p>T4S R66E S 25 — <math>\frac{1}{4}</math> S 36</p> <p>1997</p> </div> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
44.00	<p>Spur, slopes NW.</p>
58.659	<p>Point for the W <math>\frac{1}{16}</math> sec. cor. of secs. 25 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 25 — W <math>\frac{1}{16}</math> S 36</p> <p>1997</p> </div>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
60.50	Sawmill Canyon, drains NW.
78.212	The cor. of secs. 25, 26, 35 and 36.
	<hr/>
	N. 0°25'50" E., bet. secs. 25 and 26.
	Over nearly level land.
13.00	Meadow Valley Wash, drains SW.
18.60	State Route No. 317, 35 lks. wide, bears NE. and SW.
24.25	Union Pacific Railroad, bears NNE. and SSW.
35.009	Point selected for the witness cor. to the $\frac{1}{4}$ sec. cor. of secs. 25 and 26.
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, over a magnetic marker, with brass cap mkd.
	<div style="text-align: center;">           WC            T4S R66E  <math>\frac{1}{4}</math>            ↑            S 26   S 25         </div>
	1997
	Set a 1x1 in. fiberglass fence post, 5 ft. long, alongside the stainless steel post.
	The witness cor. is located at the base of a 150 ft. high rock bluff, bears NE. and SW.
	Over rugged broken land.
40.009	Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 26, at proportionate distance, falls on steep SE. facing bluff where it is impracticable to establish a permanent monument; there is no remaining evidence of the original corner.
58.00	Buckboard Canyon, drains SE.
80.018	Point for the cor. of secs. 23, 24, 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground to bedrock, over a magnetic marker, and in a mound of stone, 5 ft. base to top, with brass cap mkd.
	<div style="text-align: center;">           T4S R66E            S 23   S 24            -----            S 26   S 25         </div>
	1997
	<hr/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From the true point for the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°03'30" W., bet. secs. 24 and 25.</p> <p>Over rugged, broken land, through sagebrush, with scattered pinion pine and juniper.</p>
19.532	<p>Point for the E <math>\frac{1}{16}</math> sec. cor. of secs. 24 and 25.</p> <p>Set a brass tablet, <math>3\frac{1}{4}</math> ins. diam., <math>3\frac{1}{2}</math>-in. stem, in drill hole in granite bedrock, with top mkd.</p> <div style="text-align: center;"> <p>S 24 E <math>\frac{1}{16}</math> ——— S 25</p> <p>1997</p> </div> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
37.00	Enter nearly level land.
37.60	State Route No. 317, 35 lks. wide, on curve, bears NNE. and SSW.
39.063	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 26 ins. in the ground, over a magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <p>T4S R66E S 24 <math>\frac{1}{4}</math> ——— S 25</p> <p>1997</p> </div> <p>Set a 1x1 in. fiberglass fence post, 5 ft. long, alongside the stainless steel post.</p>
43.50	Meadow Valley Wash, drains S.
45.70	Union Pacific Railroad, bears NNE. and SSW.
58.595	<p>Point for the W <math>\frac{1}{16}</math> sec. cor. of secs. 24 and 25.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 24 W <math>\frac{1}{16}</math> ——— S 25</p> <p>1997</p> </div> <p>Set a 1x1 in. fiberglass fence post, 5 ft. long, alongside the stainless steel post.</p> <p>Ascend sharply over rugged, broken land.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
78.126	The cor. of secs. 23, 24, 25 and 26.
	<hr/> <p>N. 0°13'40" E., bet. secs. 23 and 24.</p> <p>Over rugged, broken land, through sagebrush, with scattered pinion pine and juniper.</p>
20.004	<p>Point for the S <math>\frac{1}{16}</math> sec. cor. of secs. 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 22 ins. in the ground, over a magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">S <math>\frac{1}{16}</math> S 23   S 24 1997</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>
40.008	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 23 and 24, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 12 ins. in the ground to bedrock, over a magnetic marker, and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T4S R66E S 23   <math>\frac{1}{4}</math> S 24 1997</p>
80.016	<p>Point for the cor. of secs. 13, 14, 23 and 24, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 25 ins. in the ground, over a magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T4S R66E S 14   S 13 S 23   S 24 1997</p> <p>Raise a mound of stone, 4 ft. base, 2 ft. high, W. of cor.</p> <p>From this corner the cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., bears N. 89°51'50" W., 391.003 chs. dist., hereinbefore described.</p> <p>This control line was fully retraced and careful search was made for evidence of intervening corner, none of which were recovered.</p> <hr/> <p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., hereinbefore described.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	S. 88°42'40" W., bet. secs. 13 and 24.
	Over nearly level land.
0.80	Meadow Valley Wash, drains SW.
4.00	Union Pacific Railroad, bears NNE. and SSW.
19.603	Point for the E $\frac{1}{16}$ sec. cor. of secs. 13 and 24.
	Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 26 ins. in the ground, over a magnetic marker, with brass cap mkd.
	$E \frac{1}{16} \frac{S \ 13}{S \ 24}$
	1997
	Set a 1x1 in. fiberglass fence post, 5 ft. long, alongside the stainless steel post.
27.00	Begin ascent over rugged, broken land.
39.206	Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 18 ins. in the ground to bedrock, over a magnetic marker, and in a mound of stone, 4 ft. base to top, with brass cap mkd.
	$T4S \ R66E$
	$\frac{1}{4} \frac{S \ 13}{S \ 24}$
	1997
	Set a 1x1 in. fiberglass fence post, 5 ft. long, alongside the stainless steel post.
44.50	Little Kershaw Canyon, drains SSE.
78.412	The cor. of secs. 13, 14, 23 and 24.
	<hr/>
	N. 0°28'00" E., bet. secs. 13 and 14.
	Over rolling land, through sagebrush.
21.50	Little Kershaw Canyon, drains SSE.
40.009	Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 26 ins. in the ground, over a magnetic marker, with brass cap mkd.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T4S R66E S 14 <sup>1/4</sup>   S 13 1997</p> <p>Set a 1x1 in. fiberglass fence post, 5 ft. long, alongside the stainless steel post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
80.018	<p>Point for the cor. of secs. 11, 12, 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1/2</sup> ins. diam., 10 ins. in the ground to bedrock, over a magnetic marker, and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T4S R66E S 11   S 12 S 14   S 13 1993</p> <p>From this corner the cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., bears N. 89°47'50" W., 390.834 chs. dist., hereinbefore described.</p> <p>This control line was fully retraced and careful search was made for evidence of intervening corners, none of which were recovered.</p>
31.00	<p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 88°29'00" W., bet. secs. 12 and 13.</p> <p>Over rolling land, through sagebrush.</p> <p>Ravine, drains SSE.</p>
39.222	<p>Point for the <sup>1/4</sup> sec. cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1/2</sup> ins. diam., 12 ins. in the ground to bedrock, over a magnetic marker, and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p>
78.444	<p style="text-align: center;">T4S R66E S 12 <sup>1/4</sup> ——— S 13 1993</p> <p>The cor. of secs. 11, 12, 13 and 14.</p> <hr/> <p>N. 0°50'50" E., bet. secs. 11 and 12.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	Over rolling land, through sagebrush, with scattered pinion pine and juniper.
40.012	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 11 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 14 ins. in the ground to bedrock, over a magnetic marker, and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T4S R66E <math>\frac{1}{4}</math> S 11   S 12</p> <p style="text-align: center;">1993</p>
	Set a 1x1 in. fiberglass fence post, 3 ft. long, alongside the stainless steel post.
80.024	<p>Point for the cor. of secs. 1, 2, 11 and 12, at proportionate distance falls in Newman Canyon, drains irregularly E.; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 26 ins. in the ground, over a magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T4S R66E S 2   S 1 ----- S 11   S 12</p> <p style="text-align: center;">1993</p>
	<p>from which</p> <p style="padding-left: 40px;">A juniper, 4 ins. diam., bears S. <math>50\frac{3}{4}^{\circ}</math> E., 103 lks. dist., mkd. X BT.</p> <p>From this corner the cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., bears N. <math>89^{\circ}44'00''</math> W., 391.200 chs. dist., hereinbefore described.</p> <p>This control line was fully retraced and careful search was made for evidence of intervening corners, none of which were recovered.</p>
	<p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. <math>88^{\circ}18'10''</math> W., bet. secs. 1 and 12.</p>
	Over rolling land, through sagebrush, with scattered pinion pine and juniper.
29.00	Ravine, drains SSW.
39.115	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 1 and 12, at proportionate distance, falls on the northerly shoulder of U.S. Highway No. 93; there is no remaining evidence of the original corner.</p> <p>Drive a PK nail, <math>1\frac{1}{2}</math> ins. long, flush with the asphalt surface</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>from which</p> <p>A Nevada Highway Department, brass tablet, 3<math>\frac{1}{2}</math> ins. diam., cemented in concrete, flush with the ground, bears N. 67°55' E., 173.1 lks. dist., mkd. DIST 96.42 STA F537+84.85</p> <p>A stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., set 25 ins. in the ground for a reference monument, bears N. 22°05' W., 160.9 lks. dist, with brass cap mkd. RM T4S R66E 1/4 S1 106.2 FT 1993 and an arrow pointing to the cor.</p>
39.60	U.S. Highway No. 93, 50 lks. wide, on a curve, bears W. and ESE.
50.40	Newman Canyon, drains ESE.
60.55	Newman Canyon, drains ENE.
66.70	Wash, drains SE.
78.230	The cor. of secs. 1, 2, 11 and 12.
	<hr/> <p>N. 0°01'40" W., bet. secs. 1 and 2.</p> <p>Over rolling land, through sagebrush, with scattered pinion pine and juniper.</p>
2.20	U.S. Highway No. 93, 50 lks. wide, on a curve, bears W. and ENE.
25.00	Ravine, drains SE.
40.008	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 16 ins. in the ground to bedrock, over a magnetic marker, and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T4S R66E S 2<math>\frac{1}{4}</math>S 1 1993</p>
	<p>Set a 1x1 in. fiberglass fence post, 4 ft. long, alongside the stainless steel post.</p>
79.836	The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., hereinbefore described.
	<hr/> <p>From the standard cor. of secs. 34 and 35, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 2°36'10" E., bet. secs. 34 and 35.</p> <p>Over nearly level land.</p>
18.00	Wash, drains NW.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
18.70	State Route No. 317, 35 lks. wide, bears NNE. and SSW.
27.00	Meadow Valley Wash, drains SSW.
30.50	Union Pacific Railroad, bears NNE. and SSW.
32.00	Begin ascent over rugged, broken land, through sagebrush, with scattered pinion pine and juniper.
40.132	Point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, over a magnetic marker, with brass cap mkd.  <div style="text-align: center;">           T4S R66E  <math>\frac{1}{4}</math>            S 34   S 35            1997         </div>
78.764	Set a 1x1 in. fiberglass fence post, 5 ft. long, alongside the stainless steel post.  Point selected for the witness cor. to the cor. of secs. 26, 27, 34 and 35.  Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to bedrock, over a magnetic marker and in a mound of stone, 3 ft. base to top, with brass cap mkd.  <div style="text-align: center;">           WC            T4S R66E            ↑            S 27   S 26            ————            S 34   S 35            1997         </div>
80.264	Point for the cor. of secs. 26, 27, 34 and 35, at proportionate distance, falls on steep rock bluff where it is impracticable to establish a permanent monument; there is no remaining evidence of the original corner.  From this point the cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., bears N. $89^{\circ}56'10''$ W., 313.420 chs. dist., hereinbefore described.  This control line was fully retraced and careful search was made for evidence of intervening corners, none of which were recovered.  <hr/> From the cor. of secs. 25, 26, 35 and 36.  S. $89^{\circ}46'40''$ W., bet. secs. 26 and 35.  Over nearly level land.
11.00	Meadow Valley Wash, drains S.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
13.00	State Route No. 317, 35 lks. wide, bears NNE. and SSW.
15.00	Union Pacific Railroad, bears NNE. and SSW.
19.574	<p>Point for the E <math>\frac{1}{16}</math> sec. cor. of secs. 26 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 22 ins. in the ground, over a magnetic marker, and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> $\begin{array}{r} \text{S } 26 \\ \text{E } \frac{1}{16} \text{ ---} \\ \text{S } 35 \\ 1997 \end{array}$
	Set a 1x1 in. fiberglass fence post, 5 ft. long, alongside the stainless steel post.
22.00	Begin ascent, over rugged broken land, through sagebrush, with scattered pinion pine and juniper.
36.00	Top of ascent, begin descent over rugged broken land, through sagebrush, with scattered pinion pine and juniper.
39.147	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 26 and 35, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 10 ins. in the ground to bedrock, over a magnetic marker, and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> $\begin{array}{r} \text{T4S R66E} \\ \text{S } 26 \\ \frac{1}{4} \text{ ---} \\ \text{S } 35 \\ 1997 \end{array}$
58.70	Ravine, drains SSW.
65.00	Ravine, drains SE.; begin ascent over rugged broken land.
78.294	The true point for the cor. of secs. 26, 27, 34 and 35.
	<hr/> <p>N. 0°11'40" E., bet. secs. 26 and 27.</p> <p>Over rugged, broken land, through sagebrush, with scattered pinion pine and juniper.</p>
12.00	Ravine, drains SE.
40.091	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 26 and 27, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 6 ins. in the ground to bedrock, over a magnetic marker, and in a mound of stone, 6 ft. base to top, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T4S R66E  <math>\frac{1}{4}</math>  S 27   S 26    1997</p>
80.182	<p>Point for the cor. of secs. 22, 23, 26 and 27, at proportionate distance, falls on steep rock pinnacle where it is impracticable to establish a permanent monument; there is no remaining evidence of the original corner. The witness cor. to the cor. of secs. 22, 23, 26 and 27, is hereinafter described.</p> <p>From this point the cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., bears N. 89°53'00" W., 312.895 chs. dist., hereinbefore described.</p> <p>From this same point the cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., bears N. 0°27'30" E., 320.528 chs. dist., hereinbefore described.</p> <p>These control lines were fully retraced and careful search was made for evidence of intervening corners, none of which were recovered.</p> <hr/> <p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>S. 89°54'00" W., bet. secs. 23 and 26.</p> <p>Over rugged, broken land, through sagebrush, with scattered pinion pine and juniper.</p>
39.303	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 23 and 26, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 26 ins. in the ground, over a magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T4S R66E  S 23  <math>\frac{1}{4}</math> ———  S 26    1997</p> <p>Set a 1x1 in. fiberglass fence post, 5 ft. long, alongside the stainless steel post.</p>
42.50	Buckboard Canyon, drains SSE.
78.524	<p>Point selected for the witness cor. to the cor. of secs. 22, 23, 26 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., over a "X" chiseled in bedrock, over a magnetic marker, and in a mound of stone, 6 ft. base to top, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">WC T4S R66E S 22   S 23 ←   S 27   S 26</p> <p style="text-align: center;">1997</p>
78.606	<p>The true point for the cor. of secs. 22, 23, 26 and 27.</p> <hr/>
	<p style="text-align: center;">SUBDIVISION OF SECTION 1, T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>
	<p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 1 and 12. N. <math>0^{\circ}03'30''</math> W., on the N. and S. center line of sec. 1. Over rolling land, through sagebrush, with scattered pinion pine and juniper.</p>
20.030	<p>Point for the C-S <math>\frac{1}{16}</math> sec. cor. of sec. 1. Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 28 ins. in the ground, over a magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">C S <math>\frac{1}{16}</math>   S 1 C</p> <p style="text-align: center;">1993</p> <p>Set a 1x1 in. fiberglass fence post, 4 ft. long, alongside the stainless steel post.</p>
22.00	<p>Ravine, drains SSE.</p>
40.060	<p>Point for the center <math>\frac{1}{4}</math> sec. cor. of sec. 1, at intersection with the E. and W. center line. Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 28 ins. in the ground, over a magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T4S R66E C <math>\frac{1}{4}</math> S 1</p> <p style="text-align: center;">1993</p> <p>Set a 1x1 in. fiberglass fence post, 4 ft. long, alongside the stainless steel post.</p>
78.434	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 1 and 36, on the N. bdy. of the Tp.</p> <hr/> <p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 1 and 6, on the E. bdy. of the Tp. S. <math>88^{\circ}13'40''</math> W., on the E. and W. center line of sec. 1. Over rolling land, through sagebrush, with scattered pinion pine and juniper.</p>

SUBDIVISION OF SECTION 1,  
T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.615	The center $\frac{1}{4}$ sec. cor. of sec. 1.
43.00	Ravine, drains S.
78.706	The $\frac{1}{4}$ sec. cor. of secs. 1 and 2.
<hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 12, T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>	
	From the $\frac{1}{4}$ sec. cor. of secs. 12 and 13.
	N. $0^{\circ}46'20''$ E., on the N. and S. center line of sec. 12.
	Over rolling land, through sagebrush, with scattered pinion pine and juniper.
4.50	Ravine, drains ESE.
40.074	Point for the center $\frac{1}{4}$ sec. cor. of sec. 12, at intersection with the E. and W. center line.
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground to bedrock, over a magnetic marker, and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T4S R66E C $\frac{1}{4}$ S 12 1993
	Set a 1x1 in. fiberglass fence post, 4 ft. long, alongside the stainless steel post.
60.110	Point for the C-N $\frac{1}{16}$ sec. cor. of sec. 12.
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground to bedrock, over a magnetic marker, and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	C N $\frac{1}{16}$   S 12 C
	1993
	Set a 1x1 in. fiberglass fence post, 4 ft. long, alongside the stainless steel post.
77.00	Newman Canyon, drains ESE.
79.85	U.S. Highway No. 93, 50 lks. wide, on a shallow curve, bears WNW. and ESE.
80.146	The $\frac{1}{4}$ sec. cor. of secs. 1 and 12.
	From the $\frac{1}{4}$ sec. cor. of secs. 7 and 12, on the E. bdy. of the Tp. S. $88^{\circ}23'40''$ W., on the E. and W. center line of sec. 12.

SUBDIVISION OF SECTION 12,  
T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	Over rolling land, through sagebrush, with scattered pinion pine and juniper.
39.159	The center $\frac{1}{4}$ sec. cor. of sec. 12.
78.327	The $\frac{1}{4}$ sec. cor. of secs. 11 and 12.
<hr/> SUBDIVISION OF SECTION 13, T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA <hr/>	
	From the $\frac{1}{4}$ sec. cor. of secs. 13 and 24.
	N. $0^{\circ}28'40''$ E., on the N. and S. center line of sec. 13.
	Over rugged, broken land, through sagebrush.
20.044	Point for the C-S $\frac{1}{16}$ sec. cor. of sec. 13.
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, over a magnetic marker, with brass cap mkd.
	$  \begin{array}{c}  C \\  S \frac{1}{16} \left  S \ 13 \right. \\  C  \end{array}  $ 1997
	Set a 1x1 in. fiberglass fence post, 5 ft. long, alongside the stainless steel post.
40.088	Point for the center $\frac{1}{4}$ sec. cor. of sec. 13, at intersection with the E. and W. center line.
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground to bedrock, over a magnetic marker, and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T4S R66E C $\frac{1}{4}$ S 13 1997
	Set a 1x1 in. fiberglass fence post, 5 ft. long, alongside the stainless steel post.
80.174	The $\frac{1}{4}$ sec. cor. of secs. 12 and 13.
	From the $\frac{1}{4}$ sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp.
	S. $88^{\circ}35'50''$ W., on the E. and W. center line of sec. 13.
	Over rugged, broken land, through sagebrush.
19.607	Point for the C-E $\frac{1}{16}$ sec. cor. of sec. 13.
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a magnetic marker, with brass cap mkd.

SUBDIVISION OF SECTION 13,  
T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	$C \frac{E \frac{1}{16}}{S \ 13} C$ <p style="text-align: center;">1997</p> <p>Set a 1x1 in. fiberglass fence post, 5 ft. long, alongside the stainless steel post and raise a mound of stone, 5 ft. base, 2 ft. high, N. of cor.</p>
39.214	The center $\frac{1}{4}$ sec. cor. of sec. 13.
78.427	The $\frac{1}{4}$ sec. cor. of secs. 13 and 14.
	<hr/> <p>From the E <math>\frac{1}{16}</math> sec. cor. of secs. 13 and 24.</p> <p>N. <math>0^{\circ}29'10''</math> E., on the N. and S. center line of the SE<math>\frac{1}{4}</math> of sec. 13.</p> <p>Over nearly level pasture land.</p>
20.063	<p>Point for the SE <math>\frac{1}{16}</math> sec. cor. of sec. 13, at intersection with the E. and W. center line of the SE<math>\frac{1}{4}</math>.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 26 ins. in the ground over a magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">SE <math>\frac{1}{16}</math> S 13</p> <p style="text-align: center;">1997</p> <p>Set a 1x1 in. fiberglass fence post, 5 ft. long, alongside the stainless steel post.</p>
40.126	The C-E $\frac{1}{16}$ sec. cor. of sec. 13.
	<hr/> <p>From the S <math>\frac{1}{16}</math> sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp.</p> <p>S. <math>88^{\circ}39'20''</math> W., on the E. and W. center line of the SE<math>\frac{1}{4}</math> of sec. 13.</p> <p>Over nearly level pasture land.</p>
19.605	The SE $\frac{1}{16}$ sec. cor. of sec. 13.
27.00	Begin ascent over rolling land, through sagebrush.
39.210	The C-S $\frac{1}{16}$ sec. cor. of sec. 13.
	<hr/> <p>SUBDIVISION OF SECTION 24, T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 24 and 25.</p> <p>N. <math>0^{\circ}20'00''</math> E., on the N. and S. center line of sec. 24.</p>

SUBDIVISION OF SECTION 24,  
T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	Over nearly level pasture land.
6.00	Meadow Valley Wash, drains SW.
11.50	Union Pacific Railroad, bears NNE. and SSW.
20.087	Point for the C-S $\frac{1}{16}$ sec. cor. of sec. 24.
	Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 26 ins. in the ground, over a magnetic marker, with brass cap mkd.
	$  \begin{array}{c}  C \\  S \frac{1}{16} \left  S 24 \right. \\  C  \end{array}  $ <p style="text-align: center;">1997</p>
	Set a 1x1 in. fiberglass fence post, 5 ft. long, alongside the stainless steel post.
26.00	Begin ascent, over rugged, broken land, through sagebrush.
40.174	Point for the center $\frac{1}{4}$ sec. cor. of sec. 24, at intersection with the E. and W. center line.
	Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 26 ins. in the ground, over a magnetic marker, with brass cap mkd.
	$  \begin{array}{c}  T4S R66E \\  C \frac{1}{4} S 24  \end{array}  $ <p style="text-align: center;">1997</p>
	Set a 1x1 in. fiberglass fence post, 5 ft. long, alongside the stainless steel post.
72.50	Little Kershaw Canyon, drains SE.
80.259	The $\frac{1}{4}$ sec. cor. of secs. 13 and 24.
	<hr/> <p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 19 and 24, on the E. bdy. of the Tp. S. 88°49'20" W., on the E. and W. center line of sec. 24.</p>
	Over nearly level pasture land.
5.10	State Route No. 317, 35 lks. wide, bears NE. and SW.
7.00	Meadow Valley Wash, drains SSW.
19.547	Point for the C-E $\frac{1}{16}$ sec. cor. of sec. 24.
	Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 26 ins. in the ground, over a magnetic marker, with brass cap mkd.

SUBDIVISION OF SECTION 24,  
T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	$\begin{array}{c} E \frac{1}{16} \\ C \xrightarrow{\quad} C \\ S \ 24 \\ \\ 1997 \end{array}$
	Set a 1x1 in. fiberglass fence post, 5 ft. long, alongside the stainless steel post.
22.75	Union Pacific Railroad, bears NNE. and SSW.
25.50	Begin ascent over rugged, broken land, through sagebrush.
39.094	The center $\frac{1}{4}$ sec. cor. of sec. 24.
58.661	Point for the C-W $\frac{1}{16}$ sec. cor. of sec. 24, falls on steep rock bluff where it is impracticable to establish a permanent monument.
63.661	Point selected for the witness cor. to the C-W $\frac{1}{16}$ sec. cor. of sec. 24.
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to bedrock, over a magnetic marker, and in a mound of stone, 4 ft. base to top, with brass cap mkd.
	$\begin{array}{c} WC \\ W \frac{1}{16} \\ C \xrightarrow{\quad} C \\ S \ 24 \\ \\ 1997 \end{array}$
78.228	The $\frac{1}{4}$ sec. cor. of secs. 23 and 24.
	From the E $\frac{1}{16}$ sec. cor. of secs. 24 and 25.
	N. $0^{\circ}21'20''$ E., on the N. and S. center line of the SE $\frac{1}{4}$ of sec. 24.
	Descend over a rocky NW. facing slope, through sagebrush.
15.00	End of descent, continue over nearly level pasture land.
16.00	State Route No. 317, 35 lks. wide, bears NE and SW.
17.00	Meadow Valley Wash, drains WSW.
20.127	Point for the SE $\frac{1}{16}$ sec. cor. of sec. 24, at intersection with the E. and W. center line of the SE $\frac{1}{4}$ .
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, over a magnetic marker, with brass cap mkd.
	$\begin{array}{c} SE \frac{1}{16} \ S \ 24 \\ \\ 1997 \end{array}$

SUBDIVISION OF SECTION 24,  
T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	Set a 1x1 in. fiberglass fence post, 5 ft. long, alongside the stainless steel post.
40.254	The C-E $\frac{1}{16}$ sec. cor. of sec. 24.
	From the true point for the S $\frac{1}{16}$ sec. cor. of secs. 19 and 24, on the E. bdy. of the Tp.
	S. 88°56'30" W., on the E. and W. center line of the SE $\frac{1}{4}$ of sec. 24.
	Descend sharply over rocky W. facing bluffs.
3.00	End descent, continue over nearly level pasture land.
14.55	State Route No. 317, 35 lks. wide, bears NE. and SW.
16.60	Meadow Valley Wash, drains SW.
19.539	The SE $\frac{1}{16}$ sec. cor. of sec. 24.
34.10	Union Pacific Railroad, bears NNE. and SSW.
39.078	The C-S $\frac{1}{16}$ sec. cor. of sec. 24.
	From the W $\frac{1}{16}$ sec. cor. of secs. 24 and 25.
	N. 0°16'50" E., on the N. and S. center line of the SW $\frac{1}{4}$ of sec. 24.
	Over rugged, broken land, through sagebrush.
20.046	Point for the SW $\frac{1}{16}$ sec. cor. of sec. 24, at intersection with the E. and W. center line of the SW $\frac{1}{4}$ , not monumented, falls on inaccessible cliffs.
40.092	The true point for the C-W $\frac{1}{16}$ sec. cor. of sec. 24.
	From the C-S $\frac{1}{16}$ sec. cor. of sec. 24.
	S. 88°56'20" W., on the E. and W. center line of the SW $\frac{1}{4}$ of sec. 24.
	Over nearly level land.
10.00	Begin sharp ascent over rocky bluffs.
19.549	The true point for the SW $\frac{1}{16}$ sec. cor. of sec. 24.
39.098	The S $\frac{1}{16}$ sec. cor. of secs. 23 and 24.

SUBDIVISION OF SECTION 25,  
T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 25 and 36.</p> <p>N. <math>0^{\circ}24'10''</math> E., on the N. and S. center line of sec. 25.</p> <p>Descend over broken land, through sagebrush, with scattered pinion pine and juniper.</p>
20.044	Point for the C-S $\frac{1}{16}$ sec. cor. of sec. 25, falls on steep rock bluff where it is impracticable to establish a permanent monument.
27.138	<p>Point selected for the witness cor. to the C-S <math>\frac{1}{16}</math> sec. cor. of sec. 25.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 26 ins. in the ground, over a magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC C S <math>\frac{1}{16}</math>   S 25 ↓ C</p> <p>1997</p> </div> <p>Set a 1x1 in. fiberglass fence post, 5 ft. long, alongside the stainless steel post.</p> <p>Continue over nearly level pasture land.</p>
32.00	Wash, drains NW.
34.50	Meadow Valley Wash, drains WSW.
40.088	<p>Point for the center <math>\frac{1}{4}</math> sec. cor. of sec. 25, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 28 ins. in the ground, over a magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <p>T4S R66E C <math>\frac{1}{4}</math> S 25</p> <p>1997</p> </div> <p>Set a 1x1 in. fiberglass fence post, 4 ft. long, alongside the stainless steel post.</p>
68.75	Meadow Valley Wash, drains SSE.
69.75	State Route No. 317, 35 lks. wide, bears NNE. and SSW.
80.172	The $\frac{1}{4}$ sec. cor. of secs. 24 and 25.
	<hr/> <p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp.</p> <p>S. <math>89^{\circ}10'10''</math> W., on the E. and W. center line of sec. 25.</p> <p>Descend over rugged W. facing slope, through sagebrush, with scattered pinion pine and juniper.</p>

SUBDIVISION OF SECTION 25,  
T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
19.542	Point for the C-E $\frac{1}{16}$ sec. cor. of sec. 25, falls on steep rock bluff where it is impracticable to establish a permanent monument.
22.963	Point selected for the witness cor. to the C-E $\frac{1}{16}$ sec. cor. of sec. 25.  Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock, over a magnetic marker, and in a mound of stone, 4 ft. base to top, with brass cap mkd.  $\begin{array}{c} \text{WC} \\ \text{E } \frac{1}{16} \\ \text{C} \xrightarrow{\quad} \text{C} \\ \text{S } 25 \end{array}$ <p style="text-align: center;">1997</p> Set a 1x1 in. fiberglass fence post, 5 ft. long, alongside the stainless steel post.
24.00	End of descent, continue over nearly level pasture land.
31.00	Meadow Valley Wash, drains, SSW.
39.084	The center $\frac{1}{4}$ sec. cor. of sec. 25.
46.80	State Route No. 317, 35 lks. wide, bears NE. and SW.
58.626	Point for the C-W $\frac{1}{16}$ sec. cor. of sec. 25.  Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, over a magnetic marker, and in a collar of stone, 2 ft. diam., with brass cap mkd.  $\begin{array}{c} \text{W } \frac{1}{16} \\ \text{C} \xrightarrow{\quad} \text{C} \\ \text{S } 25 \end{array}$ <p style="text-align: center;">1997</p> Set a 1x1 in. fiberglass fence post, 5 ft. long, alongside the stainless steel post.
68.30	Union Pacific Railroad, bears NNE. and SSW.
78.168	The true point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 26. <hr/> From the true point for the E $\frac{1}{16}$ sec. cor. of secs. 25 and 36.  N. $0^{\circ}23'10''$ E., on the N. and S. center line of the SE $\frac{1}{4}$ of sec. 25.  Over rugged, broken land, through sagebrush, with scattered pinion pine and juniper.
17.00	Ravine, drains WNW.
20.063	Point for the SE $\frac{1}{16}$ sec. cor. of sec. 25, at intersection with the E. and W. center line of the SE $\frac{1}{4}$ , not monumented, falls on inaccessible cliffs.

SUBDIVISION OF SECTION 25,  
T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.126	<p>The true point for the C-E <math>\frac{1}{16}</math> sec. cor. of sec. 25.</p> <hr/> <p>From the true point for the S <math>\frac{1}{16}</math> sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp.</p> <p>S. 89°13'50" W., on the E. and W. center line of the SE<math>\frac{1}{4}</math> of sec. 25.</p> <p>Over rugged, broken land, through sagebrush with scattered pinion pine and juniper.</p>
19.547	The true point for the SE $\frac{1}{16}$ sec. cor. of sec. 25.
25.50	Ravine, drains NW.
39.094	The true point for the C-S $\frac{1}{16}$ sec. cor. of sec. 25.
	<p>SUBDIVISION OF SECTION 26, T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>
	<p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 26 and 35.</p> <p>N. 0°18'50" E., on the N. and S. center line of sec. 26.</p> <p>Over rolling land, through sagebrush.</p>
40.051	<p>Point for the center <math>\frac{1}{4}</math> sec. cor. of sec. 26, at the intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 14 ins. in the ground to bedrock, over a magnetic marker, and in a mound of stone, 5 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T4S R66E C <math>\frac{1}{4}</math> S 26  1997</p>
61.00	Begin sharp descent over rocky NE. facing bluffs.
76.50	Buckboard Canyon, drains SE.
80.099	The $\frac{1}{4}$ sec. cor. of secs. 23 and 26.
	<hr/>
	<p>From the true point for the <math>\frac{1}{4}</math> sec. cor. of secs. 25 and 26.</p> <p>S. 89°50'10" W., on the E. and W. center line of sec. 26.</p> <p>Over rugged, rocky bluffs.</p>
19.612	<p>Point for the C-E <math>\frac{1}{16}</math> sec. cor. of sec. 26.</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 22 ins. in the ground, over a magnetic marker, and in a collar of stone, 3 ft. diam., with brass cap mkd.</p>

SUBDIVISION OF SECTION 26,  
T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	$C \frac{E \frac{1}{16}}{S \ 26} C$ <p style="text-align: center;">1997</p>
	Continue over rolling land, through sagebrush.
39.224	The center $\frac{1}{4}$ sec. cor. of sec. 26.
78.448	The $\frac{1}{4}$ sec. cor. of secs. 26 and 27.
<hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 35, T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>	
	From the standard $\frac{1}{4}$ sec. cor. of sec. 35, on the S. bdy. of the Tp.
	N. $2^{\circ}18'30''$ E., on the N. and S. center line of sec. 35.
	Over rugged, broken land, through sagebrush, with scattered piñon pine and juniper.
20.031	Point for the C-S $\frac{1}{16}$ sec. cor. of sec. 35, not monumented, falls on steep rock bluffs.
40.062	Point for the center $\frac{1}{4}$ sec. cor. of sec. 35, at intersection with the E. and W. center line, falls on steep rock bluff where it is impracticable to establish a permanent monument.
48.372	Point selected for the witness cor. to the center $\frac{1}{4}$ sec. cor. of sec. 35.
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground to bedrock, over a magnetic marker, and in a mound of stone, 5 ft. base to top, with brass cap mkd.
	<p style="text-align: center;">WC T4S R66E C <math>\frac{1}{4}</math> S 35 ↓</p> <p style="text-align: center;">1997</p>
51.50	Meadow Valley Wash, drains W.
55.70	State Route No. 317, 35 lks. wide, bears ENE. and WSW.
58.00	Union Pacific Railroad, bears ENE. and WSW.
60.103	Point for the C-N $\frac{1}{16}$ sec. cor. of sec. 35.
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock, over a magnetic marker, and in a mound of stone, 5 ft. base to top, with brass cap mkd.

SUBDIVISION OF SECTION 35,  
T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	$\begin{array}{c} C \\ N \frac{1}{16}   S \ 35 \\ C \end{array}$
	1997
80.144	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 26 and 35.</p> <hr/> <p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 35 and 36. S. <math>89^{\circ}43'10''</math> W., on the E. and W. center line of sec. 35. Over rugged, broken land.</p>
19.754	Point for the C-E $\frac{1}{16}$ sec. cor. of sec. 35, not monumented, falls on inaccessible cliffs.
39.508	The true point for the center $\frac{1}{4}$ sec. cor. of sec. 35.
68.50	Meadow Valley Wash, drains S.
71.90	State Route No. 317, 35 lks. wide, bears NNE. and SSW.
73.50	Union Pacific Railroad, bears NNE. and SSW.
78.866	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 34 and 35.</p> <hr/> <p>From the true point for the C-E <math>\frac{1}{16}</math> sec. cor. of sec. 35. N. <math>2^{\circ}03'20''</math> E., on the N. and S. center line of the NE<math>\frac{1}{4}</math> of sec. 35. Descend over a broken N. slope.</p>
17.10	Meadow Valley Wash, drains SSW.
20.028	<p>Point for the NE <math>\frac{1}{16}</math> sec. cor. of sec. 35, at intersection with the E. and W. center line of the NE<math>\frac{1}{4}</math>.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 27 ins. in the ground, over a magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">NE <math>\frac{1}{16}</math> S 35</p> <p style="text-align: center;">1997</p> <p>Set a steel fence post, 5 ft. long, alongside the stainless steel post.</p>
28.30	State Route No. 317, 35 lks. wide, bears NE. and SW.
33.00	Union Pacific Railroad, bears NNE. and SSW.
40.056	<p>The E <math>\frac{1}{16}</math> sec. cor. of secs. 26 and 35.</p> <hr/> <p>From the true point for the N <math>\frac{1}{16}</math> sec. cor. of secs. 35 and 36.</p>

SUBDIVISION OF SECTION 35,  
T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	S. 89°45'00" W., on the E. and W. center line of the NE <sup>1</sup> / <sub>4</sub> of sec. 35.
	Over rolling, nearly level land.
18.50	Meadow Valley Wash, drains SSW.
19.664	The NE <sup>1</sup> / <sub>16</sub> sec. cor. of sec. 35.
30.40	State Route No. 317, 35 lks. wide, bears NE. and SW.
32.00	Union Pacific Railroad, bears NE. and SW.
39.328	The C-N <sup>1</sup> / <sub>16</sub> sec. cor. of sec. 35.
	<hr/>
	From the standard E <sup>1</sup> / <sub>16</sub> sec. cor. of sec. 35, on the S. bdy. of the Tp.
	N. 2°03'20" E., on the N. and S. center line of the SE <sup>1</sup> / <sub>4</sub> of sec. 35.
	Over mountainous land, through sagebrush, with scattered piñon pine and juniper.
20.023	Point for the SE <sup>1</sup> / <sub>16</sub> sec. cor. of sec. 35, at intersection with the E. and W. center line of the SE <sup>1</sup> / <sub>4</sub> .
	Set a stainless steel post, 28 ins. long, 2 <sup>1</sup> / <sub>2</sub> ins. diam., 12 ins. in the ground to bedrock, over a magnetic marker, and in a mound of stone, 4 ft. base to top, with brass cap mkd.
	SE <sup>1</sup> / <sub>16</sub> S 35
	1993
23.00	Begin sharp descent over N. facing rocky bluffs.
40.046	The true point for the C-E <sup>1</sup> / <sub>16</sub> sec. cor. of sec. 35.
	<hr/>
	From the S <sup>1</sup> / <sub>16</sub> sec. cor. of secs. 35 and 36.
	S. 89°42'30" W., on the E. and W. center line of the SE <sup>1</sup> / <sub>4</sub> of sec. 35.
	Over mountainous land, through sagebrush, with scattered piñon pine and juniper.
19.844	The SE <sup>1</sup> / <sub>16</sub> sec. cor. of sec. 35.
39.688	The true point for the C-S <sup>1</sup> / <sub>16</sub> sec. cor. of sec. 35.
	<hr/>

## TOWNSHIP 4 SOUTH, RANGE 66 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

## GENERAL DESCRIPTION

The area surveyed within Township 4 South, Range 66 East is rugged and rocky hills and canyons, the soil is a sandy loam. The vegetation consists of sagebrush and rabbit brush, with pinion pine and juniper trees in the higher elevations.

There are few roads within the greater part of the township, providing limited access by motor vehicles.

---

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

David D. Morlan	Cadastral Surveyor
Nicholas E. Solokowski	Land Surveyor (Trainee)
Robert W. Crouch	Surveying Technician
Daryl K. Moistner	Surveying Technician
Clay W. Morrow	Surveying Technician
Peter F. Perazzo	Surveying Technician
Teri J. Thompson	Survey Aid
Roger Kennedy	Survey Aid

CERTIFICATE OF SURVEY

I, Brock R. Clifford, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of Special Instructions bearing date of the 19th day of October, 1992, and Amended Special Instructions bearing date of the 18th day of September, 2001, I have dependently resurveyed a portion of the south boundary (First Standard Parallel South), the east, west and north boundaries and a portion of the subdivisional lines, and subdivided certain sections, Township 4 South, Range 66 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

9-25-2001

(Date)



/For Brock R. Clifford

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Reno, Nevada

The foregoing field notes of the dependent resurvey of a portion of the south boundary (First Standard Parallel South), the east, west and north boundaries and a portion of the subdivisional lines, and the subdivision of certain sections, Township 4 South, Range 66 East, Mount Diablo Meridian, Nevada, executed by Brock R. Clifford, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

9-25-2001

(Date)



(Chief Cadastral Surveyor, Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 4 S., R. 66 E., M.D.M., Nevada, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor, Nevada)~~