

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

A PORTION OF THE NORTH BOUNDARY,

A PORTION OF THE SUBDIVISIONAL LINES

AND

MINERAL SURVEY NO. 2114,

AND THE SUBDIVISION

OF

SECTIONS 5, 7 and 8,

TOWNSHIP 4 SOUTH, RANGE 67 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

EXECUTED BY

Richard A. Zaninovich, Cadastral Surveyor

Under Special Instructions dated October 23, 1992,
approved October 23, 1992, and Amended Special Instructions
dated September 18, 2001, approved September 18, 2001,
which provided for the surveys included under Group No. 730,
and Assignment Instructions dated April 21, 1994.

Survey commenced June 15, 1994

Survey completed October 10, 1994

INDEX DIAGRAM

TOWNSHIP 4 SOUTH, RANGE 67 EAST

	2				
6	11 5	6 4	3	2	1
11	9				
7	8 8	3 9	10	11	12
7	6				
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Mineral Survey No 2114. pp. 13-14
 Subdivision of Section 5. pp. 14-17
 Subdivision of Section 7. pp. 18-20
 Subdivision of Section 8. page 20

TOWNSHIP 4 SOUTH, RANGE 67 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The following field notes describe the dependent resurvey of a portion of the north boundary, a portion of the subdivisional lines and Mineral Survey No. 2114, and the subdivision of sections 5, 7 and 8, Township 4 South, Range 67 East, Mount Diablo Meridian, Nevada.

The north boundary, a portion of the west boundary, and a portion of the subdivisional lines were surveyed by U.S. Deputy Surveyor E.B. Monroe in 1872 under joint Contract No. 53 with A.G. Bateman. The south boundary (First Standard Parallel South), the east boundary, a portion of the west boundary, and a portion of the subdivisional lines were surveyed by U.S. Deputy Surveyor R.H. Woods in 1881 under Contract No. 121. The east boundary was resurveyed by U. S. Deputy Surveyor H.B. Maxson in 1901 under Contract No. 227. The north boundary was resurveyed by Cadastral Surveyor N.R. Forsyth in 1971 under Group No. 477. The standard cor. of Tps. 4 S., Rs. 67 and 68 E., was remonumented by Cadastral Engineer R.F. Wilson in 1953 under Group No. 295. The west boundary was resurveyed by Cadastral Surveyor B.R. Clifford in 1992-1997 under Group No. 729. Mineral Survey No. 2114, Sunset lode was surveyed by U.S. Deputy Mineral Surveyor W.H. Blackburn in 1903.

Before restoring the corners, the lines of the original surveys were retraced and diligent search made for any evidence of the original corners and other calls of the original field note record.

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated October 23, 1992, and Amended Special Instructions dated September 18, 2001, for Group No. 730,

The directions of the lines of this survey were determined by hour angle observations of Polaris and carried forward by sustained angulation; only the mean bearings of lines are entered in the field notes.

The vertical angles of measurements made on the slope were ascertained with a theodolite in good adjustment; only the horizontal equivalents are entered in the field notes.

The geographic position of the corner of sections 7, 12, 13 and 18, on the west boundary of the Tp., as determined from National Geodetic Survey Control (formerly U.S.C. & G.S. triangulation) stations "CALIENTE" and "ECOLAH" located in unsurveyed T. 4 S., R. 65 E., and sec. 31, T. 4 S., R. 68 E., respectively, using survey grade GPS receivers, is at latitude 37°36'26.55" N. and longitude 114°32'04.55" W., (NAD 27).

The mean magnetic declination is 15¹/₂° E., as shown on U.S. Geological Survey 7¹/₂ minute quadrangle map "CALIENTE" dated 1970.

247

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 4 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Reestablishment of the Survey Executed by E.B. Monroe in 1872 and the Dependent Resurvey Executed by N.R. Forsyth in 1971</p> <hr/>
	<p>Beginning at the cor. of secs. 4, 5, 32 and 33, on the north boundary of the Tp., monumented with an iron post, 2¹/₂ ins. diam., projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the 1971 resurvey, and a mound of stone west of the cor.; add the date 1994 to the cap.</p>
	<p>S. 89°22'40" W., bet. secs. 5 and 32.</p>
20.039	<p>Point for the E ¹/₁₆ sec. cor. of secs. 5 and 32.</p>
	<p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 20 ins. in the ground, over a magnetic marker, and in a collar of stone, with brass cap mkd.</p>
	$\begin{array}{r} \text{S } 32 \\ \text{E } \frac{1}{16} \text{ ---} \\ \text{S } 5 \\ 1994 \end{array}$
	<p>Corner is located in a steep ravine which drains NW.</p>
24.30	<p>Base of steep ledges.</p>
36.70	<p>U.S. Highway No. 93, bears NNE-SSW.</p>
40.078	<p>The ¹/₄ sec. cor. of secs. 5 and 32, monumented with an iron post, 2¹/₂ ins. diam., projecting 8 ins. above the ground, with brass cap mkd. as described in the field notes of the 1971 resurvey; add the date 1994 to the cap.</p> <hr/>
	<p>S. 89°28'00" W., beginning new measurement.</p>
20.046	<p>Point for the W ¹/₁₆ sec. cor. of secs. 5 and 32.</p>
	<p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 24 ins. in the ground, over a magnetic marker, and in a collar of stone, with brass cap mkd.</p>
	$\begin{array}{r} \text{S } 32 \\ \text{W } \frac{1}{16} \text{ ---} \\ \text{S } 5 \\ 1994 \end{array}$
40.092	<p>The cor. of secs. 5, 6, 31 and 32, monumented with an iron post, 2¹/₂ ins. diam., set in a mound of stone, with brass cap mkd. as described in the field notes of the 1971 resurvey; add the date 1994 to the cap.</p> <hr/>

248

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 4 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">Reestablishment of the Survey Executed by R.H. Woods in 1881</p> <hr/> <p>From the cor. of secs. 8, 9, 16 and 17, monumented with an aluminum rod, $\frac{3}{4}$ in. diam., set in a mound of stone, with an aluminum cap, 3 ins. diam., mkd.</p> <p style="text-align: center;">CALIENTE SURVEY MONUMENT 1992 SURVEY JAMES J OWENS T4S R67E S 8 S 9 <hr/>S 17 S 16</p> <p style="text-align: center;">1992 PLS 2884</p> <p>No map record of this monument was found; it is accepted as a careful and faithful remonumentation of the corner position remonumented by Richard E. Fonger, Professional Land Surveyor No. 4235, in 1989, and shown on an unrecorded Record of Survey map dated July 6, 1990, and as the best available evidence of the position of the original corner; the Fonger monument, an aluminum post and cap, was found lying on the ground a short distance downslope.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, over a magnetic marker, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T4S R67E S 8 S 9 <hr/>S 17 S 16</p> <p style="text-align: center;">1994</p> <p>Deposit the aluminum rod inside and the aluminum post alongside the stainless steel post.</p> <p>N. $0^{\circ}25'00''$ W., bet. secs. 8 and 9.</p> <p>6.50 Draw, drains NW.</p> <p>18.00 Ridge, bears NW-SE.</p> <p>19.903 Point for the S $\frac{1}{16}$ sec. cor. of secs. 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a magnetic marker, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">S $\frac{1}{16}$ S 8 S 9</p> <p style="text-align: center;">1994</p>
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 4 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS 33.70	Spur, projects NW.
38.10	Spur, projects NW.
39.806	<p>The $\frac{1}{4}$ sec. cor. of secs. 8 and 9, monumented with an aluminum rod, $\frac{3}{4}$ in. diam., set alongside a wooden post, 6 ins. square, mkd. RR PROPERTY, in a mound of stone, with an aluminum cap, 3 ins. diam., mkd.</p> <p style="text-align: center;">CALIENTE SURVEY MONUMENT 1992 SURVEY JAMES J OWENS $\frac{1}{4}$ T4S R67E S 8 S 9</p> <p style="text-align: center;">1992 PLS 2884</p> <p>No map record of this monument was found; it is accepted as a careful and faithful remonumentation of the corner position remonumented by Richard E. Fonger, Professional Land Surveyor No. 4235, in 1989, and shown on an unrecorded Record of Survey map dated July 6, 1990, and as the best available evidence of the position of the original corner; the Fonger monument, an aluminum post and cap, was found lying on the ground a short distance downslope.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a magnetic marker, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T4S R67E $\frac{1}{4}$ S 8 S 9</p> <p style="text-align: center;">1994</p> <p>Deposit the aluminum rod inside and the aluminum post alongside the stainless steel post.</p> <hr/> <p>N. $0^{\circ}31'50''$ W., beginning new measurement.</p>
9.60	Base of steep north slope.
12.95	Railroad track, bears E-W.
13.20	Railroad siding, bears E-W.
14.40	Graded road, bears E-W.
15.75	Clover Creek, drains W.
20.260	The N $\frac{1}{16}$ sec. cor. of secs. 8 and 9, monumented with a brass tablet, $2\frac{1}{2}$ ins. diam., set in concrete, mkd.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 4 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

STATE OF NEV
PROP COR
N $\frac{1}{16}$
S 8 | S 9
RE 305

This monument was set by Jack Asher, Professional Land Surveyor and Engineer No. 305, in 1960, as shown on a Record of Survey map recorded in Official Records Book A (Plats), Page 70, in the office of the Lincoln County Recorder, and is accepted as a careful and faithful determination of the corner position.

Corner is located under a power transmission line which bears E-W and at the corner of fences projecting S and E.

N. 0°40'10" W., beginning new measurement.

19.875

The cor. of secs. 4, 5, 8 and 9, monumented with an aluminum rod, $\frac{3}{4}$ in. diam., set alongside a steel fence post in a mound of stone, with an aluminum cap, 3 ins. diam., mkd.

CALIENTE SURVEY MONUMENT
1992 SURVEY
JAMES J OWENS
T4N R67E
S 5 | S 4

S 8 | S 9

1992
PLS 2884

No map record of this monument was found; it is accepted as a careful and faithful remonumentation of the corner position remonumented by Richard E. Fonger, Professional Land Surveyor No. 4235, in 1989, and shown on an unrecorded Record of Survey map dated July 6, 1990, and as the best available evidence of the position of the original corner; the Fonger monument, an aluminum post and cap, was found lying on the ground a short distance downslope.

At the corner point

Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 14 ins. in the ground, over a magnetic marker, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

T4S R67E
S 5 | S 4

S 8 | S 9

1994

Deposit the aluminum rod inside and the aluminum post alongside the stainless steel post.

Corner is located 2.50 chs. west of a ridge which bears N-S.


DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 4 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Reestablishment of the Survey Executed by E.B. Monroe in 1872</p> <hr/>
	<p>N. 1°44'20" E., bet. secs. 4 and 5.</p>
19.868	<p>Point for the S ¹/₁₆ sec. cor. of secs. 4 and 5.</p> <p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 14 ins. in the ground, over a magnetic marker, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S ¹/₁₆ S 5 S 4</p> <p style="text-align: center;">1994</p>
39.736	<p>The ¹/₄ sec. cor. of secs. 4 and 5, monumented with a trachyte stone, 16x12x10 ins., mkd. ¹/₄ on the east face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 24 ins. in the ground, over a magnetic marker, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T4S R67E ¹/₄ S 5 S 4</p> <p style="text-align: center;">1994</p> <p>Deposit the original cornerstone alongside the stainless steel post.</p> <hr/>
40.056	<p>N. 0°30'10" W., beginning new measurement.</p> <p>The cor. of secs. 4, 5, 32 and 33, on the north boundary of the Tp., hereinbefore described.</p> <hr/>
	<p>Reestablishment of the Survey Executed by R.H. Woods in 1881</p> <hr/>
	<p>From the cor. of secs. 8, 9, 16 and 17, hereinbefore described.</p>
	<p>S. 89°29'00" W., bet. secs. 8 and 17.</p>
1.00	<p>Ridge, bears NW-SE.</p>
39.70	<p>Graded road in bottom of draw which drains NW.</p>
40.114	<p>The ¹/₄ sec. cor. of secs. 8 and 17, monumented with an aluminum rod, ³/₄ in. diam., set in a mound of stone, with an aluminum cap, 3 ins. diam., mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 4 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

CALIENTE SURVEY MONUMENT
1992 SURVEY
JAMES J OWENS



No map record of this monument was found; it is accepted as a careful and faithful remonumentation of the corner position reestablished by Richard E. Fonger, Professional Land Surveyor No. 4235, in 1989, and shown on an unrecorded Record of Survey map dated July 6, 1990.

At the corner point

Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a magnetic marker, and in a collar of stone, with brass cap mkd.

T4S R67E
S 8
 $\frac{1}{4}$ ———
S 17
1994

Deposit the aluminum rod inside the stainless steel post.

Reestablishment of the Survey Executed by
E.B. Monroe in 1872

From the cor. of secs. 7, 8, 17 and 18, monumented with an iron post, 2 $\frac{1}{2}$ ins. diam., projecting 30 ins. above the ground, set in a small mound of stone, capped with a brass plate mkd.

T4S R67E
S 7 | S 8
—————
S 18 | S 17
11-20-63
RLS 1795
FWM+SON

No map record of this monument was found; it is accepted as a careful and faithful remonumentation of the position of the original corner; a trachyte stone, 18x10x10 ins., mkd. with notches, 5 on one edge and 4 on another, was found lying on the ground a short distance away.

Deposit the original cornerstone alongside the iron post and rebuild the mound of stone.

N. 88°52'20" W., bet. secs. 7 and 18.

19.782

Intersect a rebar, $\frac{1}{2}$ in. diam., no cap, projecting 4 ins. above the ground.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 4 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 39.564</p>	<p>The $\frac{1}{4}$ sec. cor. of secs. 7 and 18, monumented with an aluminum post, $2\frac{1}{2}$ ins. diam., projecting 12 ins. above the ground, with aluminum cap mkd.</p> <p style="text-align: center;">FONGER SURVEYING T4S R67E S 7 $\frac{1}{4}$ ——— S 18 1989 ELY NV</p> <p>This monument was set by Richard E. Fonger, Professional Land Surveyor No. 4235, in 1989, as shown on an unrecorded Record of Survey map dated July 6, 1990, and is accepted as a careful and faithful reestablishment of the original corner position.</p> <hr/> <p>N. $88^{\circ}52'20''$ W., beginning new measurement.</p>
<p>1.70</p>	Railroad track, bears NE-SW.
<p>2.30</p>	Railroad siding, bears NE-SW.
<p>4.90</p>	Nevada State Route No. 317, bears NE-SW.
<p>14.85</p>	Graded road, bears N-S.
<p>19.782</p>	Point for the W $\frac{1}{16}$ sec. cor. of secs. 7 and 18.
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a magnetic marker, with brass cap mkd.
	<p>S 7 W $\frac{1}{16}$ ——— S 18 1994</p>
<p>37.00</p>	Spur, projects NE.
<p>39.564</p>	The cor. of secs. 7, 12, 13 and 18, on the west boundary of the Tp., monumented with an aluminum post, $2\frac{1}{2}$ ins. diam., set in a mound of stone, with aluminum cap mkd. as described in the field notes of the dependent resurvey of the west boundary executed by B.R. Clifford in 1992-97.
	<hr/> <p>From the cor. of secs. 7, 8, 17 and 18, hereinbefore described.</p> <p>N. $0^{\circ}18'20''$ E., bet. secs. 7 and 8.</p>
<p>24.35</p>	Railroad track, bears NE-SW.
<p>24.60</p>	Railroad siding, bears NE-SW.
<p>25.25</p>	Railroad siding, bears NE-SW.
<p>28.25</p>	U.S. Highway No. 93, bears NE-SW.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 4 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 40.178</p>	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 8, at proportionate distance, falls inside a house; there is no remaining evidence of the original corner.</p> <p>Not monumented.</p>
<p>60.267</p>	<p>Point for the N $\frac{1}{16}$ sec. cor. of secs. 7 and 8.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a magnetic marker, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;"> $\begin{array}{c} \text{N } \frac{1}{16} \\ \text{S } 7 \mid \text{S } 8 \end{array}$ 1994 </p>
<p>80.356</p>	<p>From this corner a rebar, $\frac{5}{8}$ in. diam., no cap, projecting 6 ins. above the ground, bears N. $64^{\circ}39'00''$ W., 0.355 chs. dist.</p> <p>The cor. of secs. 5, 6, 7 and 8, monumented with a trachyte stone, 12x8x6 ins., set in a mound of stone and mkd. with 5 notches on the south and east edges.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a magnetic marker, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;"> $\begin{array}{c} \text{T4S R67E} \\ \text{S } 6 \mid \text{S } 5 \\ \hline \text{S } 7 \mid \text{S } 8 \end{array}$ 1994 </p> <p>Deposit the original cornerstone alongside the stainless steel post.</p>
<p>19.706</p>	<p>From the cor. of secs. 4, 5, 8 and 9, hereinbefore described.</p> <p>N. $89^{\circ}56'30''$ W., bet. secs. 5 and 8.</p> <p>Point for the E $\frac{1}{16}$ sec. cor. of secs. 5 and 8.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a magnetic marker, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;"> $\begin{array}{c} \text{S } 5 \\ \text{E } \frac{1}{16} \text{ ---} \\ \text{S } 8 \end{array}$ 1994 </p> <p>From this corner a brass tablet, $2\frac{1}{2}$ ins. diam., set in concrete, mkd. STATE OF NEV PROP COR E1/16 S5 S8 RE 305, bears S. $3^{\circ}05'30''$ E., 0.500 chs. dist.; this monument was set by Jack Asher, Professional Land Surveyor and Engineer No. 305, in 1960,</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 4 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>as shown on a Record of Survey map recorded in Official Records Book A (Plats), Page 70, in the office of the Lincoln County Recorder. This point was established using incorrect control and is not utilized in this survey.</p> <p>39.412 The $\frac{1}{4}$ sec. cor. of secs. 5 and 8, monumented with a trachyte stone, 14x12x6 ins., mkd. $\frac{1}{4}$.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, over a magnetic marker, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T4S R67E</p> <p>S 5</p> <p>$\frac{1}{4}$ ———</p> <p>S 8</p> <p>1994</p> </div> <p>Deposit the original cornerstone alongside the stainless steel post.</p> <p>From this corner an aluminum rod, $\frac{3}{4}$ in. diam., set in a mound of stone, with an aluminum cap, 3 ins. diam., mkd. CALIENTE SURVEY MONUMENT 1992 SURVEY JAMES J OWENS T4S R67E $\frac{1}{4}$ S5 S8 1992 PLS 2884, bears S. $44^{\circ}15'50''$ W., 0.485 chs. dist.; no map record of this monument was found.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. $89^{\circ}29'40''$ W., beginning new measurement.</p> <p>1.00 Rocky spur, projects SW.</p> <p>11.00 Base of steep west slope.</p> <p>13.60 Meadow Valley Wash, drains SE.</p> <p>15.00 U.S. Highway No. 93, bears NW-SE.</p> <p>19.840 Point for the W $\frac{1}{16}$ sec. cor. of secs. 5 and 8.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 5</p> <p>W $\frac{1}{16}$ ———</p> <p>S 8</p> <p>1994</p> </div> <p>Corner is located in a fence which bears E-W.</p> <p>From this corner a brass tablet, $2\frac{1}{2}$ ins. diam., set in concrete flush with the paved surface of Ryan street, mkd. 18 FONGER SURVEY ELY NEVADA RLS 4235, bears S. $17^{\circ}33'20''$ E., 0.335 chs. dist.; this point was remonumented by Richard E. Fonger, Professional Land Surveyor No. 4235, in 1989, as shown on an unrecorded Record of Survey map dated July 6, 1990. This point was established using incorrect control and is not utilized in this survey.</p>
--------	--



DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 4 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS 29.70	Ascend steep east slope.
39.680	The cor. of secs. 5, 6, 7 and 8, hereinbefore described.
	N. 88°56'10" W., bet. secs. 6 and 7.
39.174	Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 7, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a magnetic marker, and in a collar of stone, with brass cap mkd.
	T4S R67E S 6 $\frac{1}{4}$ ——— S 7 1994
	From this corner an aluminum post, $2\frac{1}{2}$ ins. diam., set in a mound of stone, with an aluminum cap mkd. FONGER SURVEYING ELY NV T4S R67E $\frac{1}{4}$ S6 S7 1989, bears S. 56°01'00" W., 0.267 chs. dist.; this monument was set by Richard E. Fonger, Professional Land Surveyor No. 4235, in 1989, as shown on an unrecorded Record of Survey map dated July 6, 1990. This point was established using incorrect control and is not utilized in this survey.
58.761	Point for the W $\frac{1}{16}$ sec. cor. of secs. 6 and 7. Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, over a magnetic marker, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	S 6 W $\frac{1}{16}$ ——— S 7 1994
78.563	The cor. of secs. 1, 6, 7 and 12, on the west boundary of the Tp., monumented with an aluminum post, $2\frac{1}{2}$ ins. diam., set in a collar of stone, with aluminum cap mkd. as described in the field notes of the dependent resurvey of the west boundary executed by B.R. Clifford in 1992-97.
	From the cor. of secs. 5, 6, 7 and 8, hereinbefore described. N. 0°10'10" W., bet. secs. 5 and 6.
19.794	Point for the S $\frac{1}{16}$ sec. cor. of secs. 5 and 6. Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground, over a magnetic marker, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.



DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 4 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">S $\frac{1}{16}$ S 6 S 5 1994</p>
	<p>Corner is located on a steep east slope, on the north side of a small rock outcrop.</p> <p>From this corner a rebar, $\frac{1}{2}$ in. diam., with plastic cap mkd. PLS 6204, projecting 8 ins. above the ground, bears S. $54^{\circ}54'40''$ W., 0.395 chs. dist.; this monument was set by Carl D. Peterson, Professional Land Surveyor No. 6204, in 1990, as shown on a Parcel Map recorded in Official Records Book A (Plats), Page 330, in the office of the Lincoln County Recorder. This point was established using incorrect control and is not utilized in this survey.</p>
39.588	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, over a magnetic marker, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T4S R67E $\frac{1}{4}$ S 6 S 5 1994</p>
50.10	Enter gravel pit.
58.60	Power transmission line, bears NW-SE.
59.382	<p>Point for the N $\frac{1}{16}$ sec. cor. of secs. 5 and 6.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a magnetic marker, with brass cap mkd.</p>
	<p style="text-align: center;">N $\frac{1}{16}$ S 6 S 5 1994</p>
	<p>From this corner</p> <p style="padding-left: 40px;">A well, bears S. $45^{\circ}35'$ E., 13.05 chs. dist.</p> <p style="padding-left: 40px;">The north corner of an office building, 30x40 ft., bears S. $47^{\circ}20'$ E., 14.10 chs. dist.</p> <p style="padding-left: 40px;">The north corner of a shop building, 40x50 ft., bears S. $36^{\circ}50'$ E., 12.50 chs. dist.</p>
62.70	Unimproved road, bears NW-SE at base of steep SW slope, leave gravel pit.
76.70	Top of ledges, bears NW-SE.
79.275	The cor. of secs. 5, 6, 31 and 32, on the north boundary of the Tp., hereinbefore described.

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 2114,
T. 4 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">Reestablishment of the Survey Executed by W.H. Blackburn in 1903</p>
	<p>From the point for Corner No. 1, M.S. No. 2114, Sunset lode, determined at record bearing and distance from the witness corner to Corner No. 4, M.S. No. 2114, Sunset lode; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., flush with the surface of the ground inside a corral, over a magnetic marker, with brass cap mkd.</p> <div style="text-align: center;">  </div> <p>From this corner the cor. of secs. 7, 8, 17 and 18, hereinbefore described, bears S. 15°50'30" E., 47.758 chs. dist. (Record, S. 15°52'30" E., 47.648 chs.)</p> <p>N. 56°06'00" E., on line 1-2, M.S. No. 2114, Sunset lode.</p>
8.815	<p>Point for Corner No. 2, M.S. No. 2114, Sunset lode, determined at record bearing and distance from Corner No. 3, M.S. No. 2114, Sunset lode; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 24 ins. in the ground, over a magnetic marker, with brass cap mkd.</p> <div style="text-align: center;">  </div> <p>N. 26°42'00" W., on line 2-3, M.S. No. 2114, Sunset lode.</p>
10.757	<p>Intersect the E-W center line of the NE¹/₄ of sec. 7, hereinafter described.</p>
21.658	<p>Corner No. 3, M.S. No. 2114, Sunset lode, monumented with a mound of stone, no wood post found. This point is at record position in relation to the true point for Corner No. 4 and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point at the center of the mound of stone</p> <p>Set a stainless steel post, 28 ins. long 2¹/₂ ins. diam., 14 ins. in the ground, over a magnetic marker, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 2114,
T. 4 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<div style="text-align: center;">  <p>T4S R67E S7 3 S-2114 1994</p> </div>
	<p>S. 56°06'00" W., on line 3-4, M.S. No. 2114, Sunset lode.</p>
8.815	<p>The true point for Corner No. 4, M.S. No. 2114, Sunset lode, determined at record bearing and distance from the witness corner to Corner No. 4, M.S. No. 2114, Sunset lode.</p>
	<p>S. 26°42'00" E., on line 4-1, M.S. No. 2114, Sunset lode.</p>
0.682	<p>The witness corner to Corner No. 4, M.S. No. 2114, Sunset lode, monumented with a mound of stone, no wood post found. This point is at near record position in relation to the cor. of secs. 7, 8, 17 and 18 and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point at the center of the mound of stone</p> <p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 24 ins. in the ground, over a magnetic marker, with brass cap mkd.</p> <div style="text-align: center;">  <p>T4S R67E S7 WC S-2114 4 1994</p> </div>
	<p>Raise a mound of stone west of the corner.</p>
	<p>S. 26°42'00" E., beginning new measurement.</p>
4.505	<p>Intersect the E-W center line of the NE¹/₄ of sec. 7, hereinafter described.</p>
20.976	<p>Corner No. 1, M.S. No. 2114, Sunset lode, and point of beginning.</p>
	<p style="text-align: center;">SUBDIVISION OF SECTION 5, T. 4 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA</p>
	<p>From the ¹/₄ sec. cor. of secs. 5 and 8.</p> <p>N. 0°08'00" E., on the N-S center line of sec. 5.</p>
19.730	<p>Point for the center S ¹/₁₆ sec. cor. of sec. 5.</p> <p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 4 ins. in the ground, over a magnetic marker, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p>

SUBDIVISION OF SECTION 5,
T. 4 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	$S \frac{1}{16} \begin{array}{c} C \\ \\ S \ 5 \\ \\ C \end{array}$
	1994
	From this corner a rebar, $\frac{1}{2}$ in. diam., no cap, projecting 4 ins. above the ground, bears S. $49^{\circ}22'30''$ W., 0.325 chs. dist.
29.50	Meadow Valley Wash, drains SW.
39.460	Point for the center $\frac{1}{4}$ sec. cor. of sec. 5, at intersection with the E-W center line.
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a magnetic marker, with brass cap mkd.
	$T4S \ R67E$ $C \ \frac{1}{4} \ S \ 5$
	1994
	From this corner the corner of fences projecting south and west, bears S. $61^{\circ}10'$ W., 0.20 chs. dist.
50.30	Meadow Valley Wash, drains SE.
56.65	U.S. Highway No. 93, bears NE-SW.
79.300	The $\frac{1}{4}$ sec. cor. of secs. 5 and 32, on the north boundary of the Tp., hereinbefore described.
	From the $\frac{1}{4}$ sec. cor. of secs. 4 and 5.
	S. $89^{\circ}41'10''$ W., on the E-W center line of sec. 5.
19.460	Point selected for a witness corner to the center E $\frac{1}{16}$ sec. cor. of sec. 5.
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground, over a magnetic marker, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	WC $E \ \frac{1}{16}$ $C \ \leftarrow \frac{\quad}{\quad} \ C$ $S \ 5$
	1994
	Corner is located on top of a ridge, bears N-S.
20.260	Point for the center E $\frac{1}{16}$ sec. cor. of sec. 5, falls in inaccessible ledges on a steep west slope where it is impracticable to establish a permanent monument.
39.70	Meadow Valley Wash, drains S.
40.520	The center $\frac{1}{4}$ sec. cor.

SUBDIVISION OF SECTION 5,
T. 4 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS 43.45	U.S. Highway No. 93, bears NNE-SSW.
57.70	Paved road, bears NW-SE.
60.464	Point for the center W $\frac{1}{16}$ sec. cor. of sec. 5. Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a magnetic marker, with brass cap mkd. $\begin{array}{c} W \frac{1}{16} \\ C \text{ --- } C \\ S \ 5 \\ 1994 \end{array}$
	Corner is located under a power transmission line which bears E-W. From this corner The south corner of a power substation, 100x300 ft. bears N. 31°40' W., 5.60 chs. dist. The south corner of a building, 35x45 ft., bears N. 71°00' W., 3.10 chs. dist. The south corner of a building, 35x50 ft., bears N. 68°20' W., 4.30 chs. dist.
60.80	Power transmission line, at angle point, bears E. and NW.
64.60	Power transmission line, bears NW and SE.
80.408	The $\frac{1}{4}$ sec. cor. of secs. 5 and 6. <hr/>
	From the true point for the center E $\frac{1}{16}$ sec. cor. N. 0°11'00" W., on the N-S center line of the NE $\frac{1}{4}$ of sec. 5.
39.948	The E $\frac{1}{16}$ sec. cor. of secs. 5 and 32, on the north boundary of the Tp., hereinbefore described. <hr/>
	From the E $\frac{1}{16}$ sec. cor. of secs. 5 and 8. N. 0°56'20" E., on the N-S center line of the SE $\frac{1}{4}$ of sec. 5.
19.796	Point for the SE $\frac{1}{16}$ sec. cor. of sec. 5, at intersection with the E-W center line of the SE $\frac{1}{4}$. Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a magnetic marker, with brass cap mkd. $\begin{array}{c} SE \frac{1}{16} \ S \ 5 \\ 1994 \end{array}$
39.592	The true point for the center E $\frac{1}{16}$ sec. cor. <hr/>



SUBDIVISION OF SECTION 5,
T. 4 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	From the S $\frac{1}{16}$ sec. cor. of secs. 4 and 5. S. 89°52'10" W., on the E-W center line of the SE $\frac{1}{4}$ of sec. 5.
19.983	The SE $\frac{1}{16}$ sec. cor.
39.966	The center S $\frac{1}{16}$ sec. cor.
<hr/>	
	From the W $\frac{1}{16}$ sec. cor. of secs. 5 and 8. N. 0°01'10" W., on the N-S center line of the SW $\frac{1}{4}$ of sec. 5.
19.761	Point for the SW $\frac{1}{16}$ sec. cor. of sec. 5, at intersection with the E-W center line of the SW $\frac{1}{4}$. Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a magnetic marker, with brass cap mkd. SW $\frac{1}{16}$ S 5 1994
19.95	Power transmission line, bears NW-SE.
23.20	Intersect the southwest wall of a house trailer, 4.3 ft. southeast of its west corner.
23.90	Power transmission line, bears NE-SW.
33.95	Power transmission line, bears NW-SE.
37.75	Power transmission line which bears E-W.
39.522	The center W $\frac{1}{16}$ sec. cor.
<hr/>	
	From the center S $\frac{1}{16}$ sec. cor. S. 89°35'30" W., on the E-W center line of the SW $\frac{1}{4}$ of sec. 5.
5.50	Meadow Valley Wash, drains SW.
11.45	U.S. Highway No. 93, bears NE-SW.
19.892	The SW $\frac{1}{16}$ sec. cor.
39.784	The S $\frac{1}{16}$ sec. cor. of secs. 5 and 6.
<hr/>	
	From the center W $\frac{1}{16}$ sec. cor. N. 0°01'10" W., on the N-S center line of the NW $\frac{1}{4}$ of sec. 5.
1.95	Paved road, bears NW-SE.
39.764	The W $\frac{1}{16}$ sec. cor. of secs. 5 and 32, on the north boundary of the Tp., hereinbefore described.
<hr/>	

SUBDIVISION OF SECTION 7,
T. 4 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	From the $\frac{1}{4}$ sec. cor. of secs. 7 and 18. N. $0^{\circ}34'40''$ E., on the N-S center line of sec. 7.
1.15	Railroad track, bears NE-SW.
1.50	Railroad siding, bears NE-SW.
3.05	Nevada State Route No. 317, bears NE-SW.
14.40	U.S. Highway No. 93, bears NW-SE.
40.152	Point for the center $\frac{1}{4}$ sec. cor. of sec. 7, at intersection with the E-W center line. Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., flush with the surface of the ground in the Caliente City Cemetery, over a magnetic marker, with brass cap mkd. T4S R67E C $\frac{1}{4}$ S 7 1994
57.80	Spur, projects SE.
60.230	Point for the center N $\frac{1}{16}$ sec. cor. of sec. 7. Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a magnetic marker, and in a collar of stone, with brass cap mkd. N $\frac{1}{16}$ $\begin{array}{c} C \\ \\ S \\ C \end{array}$ 7 1994
80.308	The $\frac{1}{4}$ sec. cor. of secs. 6 and 7. <hr/> From the point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 8. N. $88^{\circ}54'20''$ W., on the E-W center line of sec. 7.
39.370	The center $\frac{1}{4}$ sec. cor.
59.059	Point for the center W $\frac{1}{16}$ sec. cor. of sec. 7. Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground, over a magnetic marker, and in a mound of stone, 4 ft. base, to top, with brass cap mkd. C $\frac{W \frac{1}{16}}{S 7}$ C 1994
73.60	Underground telephone cable, bears NW-SE.

SUBDIVISION OF SECTION 7,
T. 4 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS 74.20	U.S. Highway No. 93, bears NW-SE.
77.90	Power transmission line, bears NW-SE.
78.856	The $\frac{1}{4}$ sec. cor. of secs. 7 and 12, on the west boundary of the Tp., monumented with an aluminum post, $2\frac{1}{2}$ ins. diam., set in a collar of stone, with aluminum cap mkd. as described in the field notes of the dependent resurvey of the west boundary executed by B.R. Clifford in 1992-97.
	<hr/> <p>From the N $\frac{1}{16}$ sec. cor. of secs. 7 and 8.</p> <p>N. $88^{\circ}55'10''$ W., on the E-W center line of the NE$\frac{1}{4}$ of sec. 7.</p>
10.877	Intersect line 2-3, M.S. No. 2114, Sunset lode. Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground, over a magnetic marker, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	 <p style="text-align: center;">1994</p>
20.762	Intersect line 4-1, M.S. No. 2114, Sunset lode. Set a stainless post, 28 ins. lone, $2\frac{1}{2}$ ins. diam., 24 ins in the ground, over a magnetic marker, with brass cap mkd.
	 <p style="text-align: center;">1994</p>
39.272	The center N $\frac{1}{16}$ sec. cor.
	<hr/> <p>From the W $\frac{1}{16}$ sec. cor. of secs. 7 and 18.</p> <p>N. $0^{\circ}42'20''$ E., on the N-S center line of the SW$\frac{1}{4}$ of sec. 7.</p>
17.30	Graded road, bears NW-SE.
19.30	Power transmission line, bears NW-SE.
26.85	U.S. Highway No. 93, bears NW-SE.
27.45	Underground telephone cable, bears NW-SE.
40.138	The center W $\frac{1}{16}$ sec. cor.
	<hr/> <p>N. $0^{\circ}43'20''$ E., on the N-S center line of the NW$\frac{1}{4}$ of sec. 7.</p>
20.072	Point for the NW $\frac{1}{16}$ sec. cor. of sec. 7, at intersection with the E-W center line of the NW $\frac{1}{4}$.

SUBDIVISION OF SECTION 7,
T. 4 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 24 ins. in the ground, over a magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">NW ¹/₁₆ S 7</p> <p style="text-align: center;">1994</p>
40.144	<p>The W ¹/₁₆ sec. cor. of secs. 6 and 7.</p> <hr/> <p>From the center N ¹/₁₆ sec. cor.</p> <p>N. 88°55'40" W., on the E-W center line of the NW¹/₄ of sec. 7.</p>
19.638	<p>The NW ¹/₁₆ sec. cor.</p>
39.437	<p>The N ¹/₁₆ sec. cor. of secs. 7 and 12, on the west boundary of the Tp., monumented with a stainless steel post, 2¹/₂ ins. diam., projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the west boundary executed by B.R. Clifford in 1992-97.</p> <hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 8, T. 4 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the ¹/₄ sec. cor. of secs. 8 and 17.</p> <p>N. 0°09'30" W., on the N-S center line of sec. 8.</p>
2.70	<p>Graded road in bottom of draw which drains NW.</p>
19.866	<p>Point for the center S ¹/₁₆ sec. cor. of sec. 8.</p> <p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 12 ins. in the ground, over a magnetic marker, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;"> $\begin{array}{c} C \\ S \frac{1}{16} \left S \ 8 \\ C \end{array}$ </p> <p style="text-align: center;">1994</p>
39.732	<p>The center ¹/₄ sec. cor. of sec. 8, monumented with a rebar, ¹/₂ in. diam., cemented inside an iron post, 3 ins. diam., projecting 18 ins. above the ground.</p> <p>This monument is of unknown origin; it is shown as a found corner on a number of recorded and unrecorded plats; this is accepted as the best available evidence of the position of the original corner.</p> <hr/> <p>From the S ¹/₁₆ sec. cor. of secs. 8 and 9.</p> <p>S. 89°25'40" W., on the E-W center line of the SE¹/₄ of sec. 8.</p>
40.022	<p>The center S ¹/₁₆ sec. cor.</p> <hr/>

T. 4 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

GENERAL DESCRIPTION

The City of Caliente Nevada is located in portions of sections 5, 7 and 8, T. 4 S., R. 67 E. The average elevation of the area surveyed is about 4700 feet. Clover Creek drains west through section 8 to its confluence with Meadow Valley Wash which drains southwest through sections 5, 7 and 8. Terrain and vegetation vary from steep hills covered with sage and scattered juniper to the lush gardens of the "Rose City of the Silver State" in the level bottomland of Meadow Valley Wash. U.S. Highway No. 93, Nevada State Highway No. 317 and the Union Pacific Railroad provide access to the area. There is an active gravel pit in sections 5 and 6 and an abandoned gold mine in section 7. The mean magnetic declination was determined by reference to U.S. Geological Survey quadrangle map "CALIENTE" dated 1970.

267

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Peter F. Perazzo Surveying Technician
Clay W. Morrow Surveying Technician

268

CERTIFICATE OF SURVEY

I, Richard A. Zaninovich, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 23rd day of October, 1992, and Amended Special Instructions bearing date of the 18th day of September, 2001, I have dependently resurveyed a portion of the north boundary, a portion of the subdivisional lines and Mineral Survey No. 2114, and subdivided sections 5, 7 and 8, Township 4 South, Range 67 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

9-27-01

(Date)

Richard A. Zaninovich

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of dependent resurvey of a portion of the north boundary, a portion of the subdivisional lines and Mineral Survey No. 2114, and the subdivision of sections 5, 7 and 8, Township 4 South, Range 67 East, Mount Diablo Meridian, Nevada, executed by Richard A. Zaninovich, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

10-2-2001

(Date)

Richard A. Zaninovich

(Chief Cadastral Surveyor, Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 4 S., R. 67 E., M.D.M., Nevada, is a true copy of the original field notes.~~

~~_____~~
~~(Date)~~

~~_____~~
~~(Chief Cadastral Surveyor, Nevada)~~