

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF PORTIONS OF THE
NORTH AND WEST BOUNDARIES
AND A PORTION OF THE SUBDIVISIONAL LINES,
THE SUBDIVISION OF SECTIONS 6 AND 7,
AND A METES-AND-BOUNDS SURVEY IN SECTION 6,
TOWNSHIP 6 SOUTH, RANGE 61 EAST,
OF THE MOUNT DIABLO MERIDIAN,
IN THE STATE OF NEVADA

EXECUTED BY

Richard A. Zaninovich, Cadastral Surveyor

Under Special Instructions dated September 28, 1998,
and approved September 28, 1998,
which provided for the surveys included under Group No. 776,
and Assignment Instructions dated September 28, 1998.

Survey commenced September 28, 1998

Survey completed October 6, 1998

INDEX DIAGRAM

TOWNSHIP 6 SOUTH, RANGE 61 EAST

| | | | | | | |
|-----|------|----|----|----|----|--|
| 4 | | | | | | |
| 3 6 | 8 5 | 4 | 3 | 2 | 1 | |
| 7 | | | | | | |
| 2 7 | 7 8 | 9 | 10 | 11 | 12 | |
| 6 | | | | | | |
| 18 | 5 17 | 16 | 15 | 14 | 13 | |
| | | | | | | |
| 19 | 20 | 21 | 22 | 23 | 24 | |
| | | | | | | |
| 30 | 29 | 28 | 27 | 26 | 25 | |
| | | | | | | |
| 31 | 32 | 33 | 34 | 35 | 36 | |

Subdivision of Section 6 pp. 8-10
 Subdivision of Section 7 pp. 10-12
 Metes-and-Bounds Survey in Section 6 pp. 12-13

TOWNSHIP 6 SOUTH, RANGE 61 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The following field notes are those of the dependent resurvey of portions of the north and west boundaries and a portion of the subdivisional lines, the subdivision of sections 6 and 7, and a metes-and-bounds survey in section 6, Township 6 South, Range 61 East, Mount Diablo Meridian, Nevada.

The township boundaries and a portion of the subdivisional lines were surveyed by E.B. Monroe in 1870 under Contracts No. 34 and 35. A portion of the south boundary was dependently resurveyed and the east boundary and a portion of the north boundary were independently resurveyed by D.R. Averill and R.F. Wilson in 1953 under Group No. 355. A portion of the north boundary was dependently resurveyed by E.W. Sibley in 1964 under Group No. 422.

Before restoring the corners, the lines of the original surveys were retraced and diligent search made for any evidence of the original corners and other calls of the original field note record.

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and Special Instructions for Group No. 776, dated September 28, 1998.

Measurements were made with Trimble 4400 GPS receivers. The mean bearings of the lines and horizontal equivalents of ground distances only are entered in the field notes.

The geographic position, NAD 83(1994), of the corner of sections 17, 18, 19, and 20, as determined by ties made to U.S. Geological Survey stations "ASH ET" and "CORRAL" is as follows:

Latitude 37°25'14.23" N. Longitude 115°10'25.90" W.

The mean magnetic declination is 15¹/₂° E., as shown on U.S.G.S. quadrangle map "ASH SPRINGS" dated 1969.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 6 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

| CHAINS | | | | | | | | | | |
|-----------|---|-----|-----------|-----------|-------|-----------|-----|-----------|-----|-----------|
| | <p style="text-align: center;">Reestablishment of the Survey Executed by E.B. Monroe in 1870</p> <hr style="width: 20%; margin: auto;"/> <p>Beginning at the corner of sections 7, 12, 13, and 18, monumented with a small mound of stone and fragments of a cottonwood post on which scribe marks are visible.</p> <p>At the corner point at the center of the mound of stone</p> <p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 24 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T6S</td></tr> <tr><td>R60E R61E</td></tr> <tr><td>S12 S 7</td></tr> <tr><td>-----</td></tr> <tr><td>S13 S18</td></tr> </table> <p>1998</p> </div> <p>Deposit the fragments of original cottonwood post alongside the stainless steel post.</p> <p>Corner is located in a fence which bears N-S.</p> <p>N. 0°44'00" W., bet. secs. 7 and 12.</p> <p>40.514 Point for the ¹/₄ sec. cor. of secs. 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T6S</td></tr> <tr><td>R60E R61E</td></tr> <tr><td>1/4</td></tr> <tr><td>S12 S 7</td></tr> </table> <p>1998</p> </div> <p>60.771 Point for the N ¹/₁₆ sec. cor. of secs. 7 and 12; not monumented.</p> <p>81.028 The cor. of secs. 1, 6, 7, and 12, monumented with a small mound of stone as described in the field notes of the resurvey executed by E.W. Sibley in 1964; this is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point at the center of the mound of stone</p> <p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 24 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd.</p> | T6S | R60E R61E | S12 S 7 | ----- | S13 S18 | T6S | R60E R61E | 1/4 | S12 S 7 |
| T6S | | | | | | | | | | |
| R60E R61E | | | | | | | | | | |
| S12 S 7 | | | | | | | | | | |
| ----- | | | | | | | | | | |
| S13 S18 | | | | | | | | | | |
| T6S | | | | | | | | | | |
| R60E R61E | | | | | | | | | | |
| 1/4 | | | | | | | | | | |
| S12 S 7 | | | | | | | | | | |

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 6 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

| CHAINS | |
|--------|--|
| | T6S R60E R61E S 1 S 6 <hr style="width: 50%; margin: auto;"/> S12 S 7 1998 |
| | N. 0°03'20" E., bet. secs. 1 and 6. |
| 32.30 | Pole line, NW-SE. |
| 34.90 | U.S. Highway No. 93, NW-SE. |
| 39.886 | <p>The $\frac{1}{4}$ sec. cor. of secs. 1 and 6, monumented with an iron rod, 4 ft. long and $\frac{1}{2}$ in. square, wired to which is a fragment of an ash post, 18 ins. long and 3 ins. square, no scribe marks visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> |
| | T6S R60E R61E $\frac{1}{4}$ S 1 S 6 1998 |
| | <p>Deposit the iron rod and original ash post alongside the stainless steel post.</p> <p>From this corner U.S. Geological Survey station "ASH ET" monumented with a standard brass tablet, marked ASH ET 1969, bears S. 75°14'40" E., 15.765 chs. dist.</p> |
| | N. 1°19'00" W., beginning new measurement. |
| 14.451 | Point for Angle Point No. 1 of the metes-and-bounds survey in section 6, hereinafter described. |
| 20.046 | Point for the N $\frac{1}{16}$ sec. cor. of secs. 1 and 6; not monumented. |
| 25.057 | <p>Point for the S-N-N $\frac{1}{256}$ sec. cor. of secs. 1 and 6.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> |
| | $\frac{1}{256}$ S-N-N S 1 S 6 1998 |
| 40.092 | The cor. of secs. 1, 6, 31, and 36, Tps. 5 and 6 S., Rs. 60 and 61 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., projecting |

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 6 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

6 ins. above the ground with brass cap marked as described in the field notes of the dependent resurvey of a portion of the north boundary executed by E.W. Sibley in 1964.

Corner is located in a fence which bears N-S.

From this corner Ash Spring bears S. 30° E., 4¹/₂ chs. dist.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 6 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
E.B. Monroe in 1870 and the Resurvey Executed by
E.W. Sibley in 1964

From the cor. of secs. 5, 6, 31, and 32, monumented with an iron post, 2¹/₂ ins. diam., projecting 4 ins. above the ground with brass cap marked as described in the field notes of the 1964 resurvey.

N. 89°45'20" W., bet. secs. 6 and 31.

39.907 The ¹/₄ sec. cor. of secs. 6 and 31, determined at the center of a large mound of stone; the iron post set in 1964 has been removed.

At the corner point

Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 6 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 5 ft. base, to top, with brass cap mkd.

T5S R61E
S31
1/4 ———
S 6
T6S

1998

N. 89°45'20" W., beginning new measurement.

19.985 Point for the W ¹/₁₆ sec. cor. of secs. 6 and 31; not monumented.

38.421 The cor. of secs. 1, 6, 31, and 36, Tps. 5 and 6 S., Rs. 60 and 61 E., hereinbefore described.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 6 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
E.B. Monroe in 1870

From the cor. of secs. 17, 18, 19, and 20, monumented with a trachyte stone, 16x8x6 ins., marked with notches, 3 on the south and 5 on the east edges, set in a small mound of stone.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 6 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

| CHAINS | | | | | | | | | |
|--------|--|-----|------|-----|-----|-------|-----|-----|-----|
| | <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T6S</td><td>R61E</td></tr> <tr><td>S18</td><td>S17</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S19</td><td>S20</td></tr> </table> <p style="text-align: center;">1998</p> <p>Deposit the original marked stone alongside the stainless steel post.</p> <p>Raise a mound of stone west of the corner.</p> <p>From this corner U.S. Geological Survey station "CORRAL", monumented with a standard aluminum tablet, marked CORRAL 1969, bears S. 3°50'00" E., 82.751 chs. dist.</p> <p>N. 1°27'40" W., bet. secs. 17 and 18.</p> | T6S | R61E | S18 | S17 | <hr/> | | S19 | S20 |
| T6S | R61E | | | | | | | | |
| S18 | S17 | | | | | | | | |
| <hr/> | | | | | | | | | |
| S19 | S20 | | | | | | | | |
| 40.026 | <p>Point for the ¹/₄ sec. cor. of secs. 17 and 18, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T6S</td><td>R61E</td></tr> <tr><td>1/4</td><td></td></tr> <tr><td>S18</td><td>S17</td></tr> </table> <p style="text-align: center;">1998</p> <p>Raise a mound of stone west of the corner.</p> | T6S | R61E | 1/4 | | S18 | S17 | | |
| T6S | R61E | | | | | | | | |
| 1/4 | | | | | | | | | |
| S18 | S17 | | | | | | | | |
| 80.052 | <p>Point for the cor. of secs. 7, 8, 17, and 18, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T6S</td><td>R61E</td></tr> <tr><td>S 7</td><td>S 8</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S18</td><td>S17</td></tr> </table> <p style="text-align: center;">1998</p> <p>From this corner a rebar, 24 ins. long and ³/₄ in. diam., no cap, lying on the ground alongside a trachyte stone, 10x8x4 ins., no marks, bears N. 5°40' E., 3.20 chs. dist.; this point is not utilized in the course of this resurvey.</p> <p>Also, from this corner the cor. of secs. 9, 10, 15, and 16, monumented with a juniper post, 36 ins. long and 3 ins. square, no</p> | T6S | R61E | S 7 | S 8 | <hr/> | | S18 | S17 |
| T6S | R61E | | | | | | | | |
| S 7 | S 8 | | | | | | | | |
| <hr/> | | | | | | | | | |
| S18 | S17 | | | | | | | | |

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 6 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

| CHAINS | | | | | | | | | |
|--------|---|--------|------|-----|-------|-------|-------|-----|-----|
| | <p>marks visible, set in a small mound of stone, bears N. 89°59'20" E., 160.467 chs. dist.; this is accepted as the best available evidence of the position of the original corner. This control line was fully retraced and a careful search was made for intervening corners, none of which were found.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T6S</td><td>R61E</td></tr> <tr><td>S 9</td><td>S10</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S16</td><td>S15</td></tr> </table> <p style="text-align: center;">1998</p> <p>Deposit the juniper post alongside the stainless steel post.</p> <p>Raise a mound of stone west of the corner.</p> <hr/> | T6S | R61E | S 9 | S10 | <hr/> | | S16 | S15 |
| T6S | R61E | | | | | | | | |
| S 9 | S10 | | | | | | | | |
| <hr/> | | | | | | | | | |
| S16 | S15 | | | | | | | | |
| 20.011 | <p>S. 89°05'40" W., bet. secs. 7 and 18.</p> <p>Point for the E ¹/₁₆ sec. cor. of secs. 7 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td>E 1/16</td><td>S 7</td></tr> <tr><td></td><td><hr/></td></tr> <tr><td></td><td>S18</td></tr> </table> <p style="text-align: center;">1998</p> | E 1/16 | S 7 | | <hr/> | | S18 | | |
| E 1/16 | S 7 | | | | | | | | |
| | <hr/> | | | | | | | | |
| | S18 | | | | | | | | |
| 26.60 | U.S. Highway No. 93, NW-SE. | | | | | | | | |
| 31.30 | Pole line, NW-SE. | | | | | | | | |
| 40.022 | <p>Point for the ¹/₄ sec. cor. of secs. 7 and 18, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T6S</td><td>R61E</td></tr> <tr><td>S 7</td><td></td></tr> <tr><td>1/4</td><td><hr/></td></tr> <tr><td></td><td>S18</td></tr> </table> <p style="text-align: center;">1998</p> | T6S | R61E | S 7 | | 1/4 | <hr/> | | S18 |
| T6S | R61E | | | | | | | | |
| S 7 | | | | | | | | | |
| 1/4 | <hr/> | | | | | | | | |
| | S18 | | | | | | | | |
| 78.873 | <p>The cor. of secs. 7, 12, 13, and 18, on the west boundary of the Tp., hereinbefore described.</p> <hr/> | | | | | | | | |

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 6 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

| CHAINS | |
|--------|--|
| 40.014 | <p>From the cor. of secs. 7, 8, 17, and 18.</p> <p>N. 0°24'00" E., bet. secs. 7 and 8.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 8, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T6S R61E $\frac{1}{4}$ S 7 S 8 1998</p> |
| 60.021 | <p>Point for the N $\frac{1}{16}$ sec. cor. of secs. 7 and 8.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">N $\frac{1}{16}$ S 7 S 8 1998</p> |
| 80.028 | <p>The cor. of secs. 5, 6, 7, and 8, monumented with an ash post, 3 ft. long and 3 ins. square, with notches visible on 2 edges.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T6S R61E S 6 S 5 ----- S 7 S 8 1998</p> <p>Deposit the original ash post alongside the stainless steel post.</p> |
| 40.930 | <p>S. 89°49'20" W., bet. secs. 6 and 7.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 7, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> |

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 6 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

| CHAINS | |
|--------|--|
| | <p style="text-align: center;">T6S R61E S 6 1/4 $\frac{\quad}{\quad}$ S 7 1998</p> |
| 61.395 | <p>Point for the W $\frac{1}{16}$ sec. cor. of secs. 6 and 7.</p> <p>Set a stainless steel post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 6 W 1/16 $\frac{\quad}{\quad}$ S 7 1998</p> |
| 65.90 | U.S. Highway No. 93, NW-SE. |
| 67.30 | Pole line, NW-SE. |
| 80.447 | The cor. of secs. 1, 6, 7, and 12, on the west boundary of the Tp., hereinbefore described. |
| | <hr/> <p>From the cor. of secs. 5, 6, 7, and 8.</p> <p>N. 2°09'20" W., bet. secs. 5 and 6.</p> |
| 39.502 | <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T6S R61E 1/4 S 6 S 5 1998</p> |
| 79.438 | The cor. of secs. 5, 6, 31, and 32, on the north boundary of the Tp., hereinbefore described. |
| | <hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 6, T. 6 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the $\frac{1}{4}$ sec. cor. of secs. 6 and 7.</p> <p>N. 1°25'00" W., on the N-S center line of section 6.</p> |
| 39.696 | <p>Point for the center $\frac{1}{4}$ sec. cor., at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> |

SUBDIVISION OF SECTION 6,
T. 6 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

| CHAINS | T6S R61E C 1/4 S 6 1998 |
|--------|---|
| 59.593 | Point for the C-N $\frac{1}{16}$ sec. cor.; not monumented. |
| 79.704 | The $\frac{1}{4}$ sec. cor. of secs. 6 and 31, on the north boundary of the Tp., hereinbefore described. |
| | <hr/> From the $\frac{1}{4}$ sec. cor. of secs. 5 and 6. N. $89^{\circ}53'00''$ W., on the E-W center line of section 6. |
| 40.422 | The center $\frac{1}{4}$ sec. cor. |
| 60.400 | Point for the C-W $\frac{1}{16}$ sec. cor.; not monumented. |
| 78.914 | The $\frac{1}{4}$ sec. cor. of secs. 1 and 6, on the west boundary of the Tp., hereinbefore described. |
| | <hr/> From the point for the C-W $\frac{1}{16}$ sec. cor. of sec. 6. N. $1^{\circ}25'40''$ W., on the N-S center line of the NW $\frac{1}{4}$. |
| 19.975 | Point for the NW $\frac{1}{16}$ sec. cor., at intersection with the E-W center line of the NW $\frac{1}{4}$; not monumented. |
| 40.052 | The point for the W $\frac{1}{16}$ sec. cor. of secs. 6 and 31, on the north boundary of the Tp., hereinbefore described. |
| | <hr/> From the point for the C-N $\frac{1}{16}$ sec. cor. of sec. 6. N. $89^{\circ}39'30''$ W., on the E-W center line of the NW $\frac{1}{4}$. |
| 19.983 | The point for the NW $\frac{1}{16}$ sec. cor. |
| 24.979 | Point for the C-E-W-NW $\frac{1}{256}$ sec. cor., and will now also function as Angle Point No. 3 of the metes-and-bounds survey in section 6. Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd. |
| | S 6 C-E-W-NW 1/256 1998 |
| 29.975 | Point for the C-W-NW $\frac{1}{64}$ sec. cor. Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd. |

SUBDIVISION OF SECTION 6,
T. 6 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

| CHAINS | |
|--------|---|
| | <p style="text-align: center;">S 6 C-W-NW 1/64 1998</p> |
| 38.459 | <p>The point for the N ¹/₁₆ sec. cor. of secs. 1 and 6, on the west boundary of the Tp., hereinbefore described.</p> |
| | <hr/> <p>From the C-W-NW ¹/₆₄ sec. cor., hereinbefore described. N. 1°25'50" W., on the computed N-S center line of the NW¹/₄ NW¹/₄ of sec. 6</p> |
| 5.003 | <p>True point for the C-S-NW-NW ¹/₂₅₆ sec. cor., falls on a limestone ledge where it is impractical to set a permanent monument.</p> |
| | <hr/> <p>N. 89°35'50" W., on the computed E-W center line of the SW¹/₄ NW¹/₄ NW¹/₄ of sec. 6.</p> |
| 0.100 | <p>Point selected for the witness corner to the C-S-NW-NW ¹/₂₅₆ sec. cor.</p> |
| | <p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 18 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">WC S 6 → C-S-NW-NW 1/256 1998</p> |
| 8.474 | <p>The S-N-N ¹/₂₅₆ sec. cor. of secs. 1 and 6, on the west boundary of the Tp., hereinbefore described.</p> |
| | <hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 7, T. 6 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA</p> |
| | <hr/> <p>From the ¹/₄ sec. cor. of secs. 7 and 18.</p> |
| | <p>N. 0°15'20" W., on the N-S center line of section 7.</p> |
| 22.70 | <p>Pole line, NW-SE.</p> |
| 34.10 | <p>U.S. Highway No. 93, NW-SE.</p> |
| 40.266 | <p>Point for the center ¹/₄ sec. cor., at intersection with the E-W center line.</p> |

SUBDIVISION OF SECTION 7,
T. 6 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

| CHAINS | |
|--------|--|
| | <p>Set a stainless steel post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T6S R61E C 1/4 S 7</p> <p style="text-align: center;">1998</p> |
| 60.399 | <p>Point for the C-N $\frac{1}{16}$ sec. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">N $\frac{1}{16}$ S 7 C</p> <p style="text-align: center;">1998</p> |
| 80.532 | <p>The $\frac{1}{4}$ sec. cor. of secs. 6 and 7.</p> <hr/> <p>From the $\frac{1}{4}$ sec. cor. of secs. 7 and 8.</p> <p>S. 89°27'40" W., on the E-W center line of section 7.</p> |
| 40.475 | The center $\frac{1}{4}$ sec. cor. |
| 43.20 | U.S. Highway No. 93, NW-SE. |
| 47.40 | Pole line, NW-SE. |
| 60.712 | Point for the C-W $\frac{1}{16}$ sec. cor.; not monumented. |
| 79.658 | <p>The $\frac{1}{4}$ sec. cor. of secs. 7 and 12, on the west boundary of the Tp., hereinbefore described.</p> <hr/> <p>From the N $\frac{1}{16}$ sec. cor. of secs. 7 and 8.</p> <p>S. 89°38'30" W., on the E-W center line of the NE$\frac{1}{4}$ of sec. 7.</p> |
| 40.702 | <p>The C-N $\frac{1}{16}$ sec. cor.</p> <hr/> <p>From the point for the C-W $\frac{1}{16}$ sec. cor. of sec. 7.</p> <p>N. 0°35'00" W., on the N-S center line of the NW$\frac{1}{4}$.</p> |
| 20.197 | <p>Point for the NW $\frac{1}{16}$ sec. cor., at intersection with the E-W center line of the NW$\frac{1}{4}$.</p> <p>Set a stainless steel post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S 7</p> <p style="text-align: center;">1998</p> |
| 29.20 | Pole line, NW-SE. |

METES-AND-BOUNDS SURVEY IN SECTION 6,
T. 6 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

| | |
|---------------------|---|
| CHAINS 5.610 | <p>N. 1°26'00" W., on line 2-3.</p> <p>Angle Point No. 3, identical with the C-E-W-NW $\frac{1}{256}$ sec. cor., hereinbefore described.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The average elevation of the area surveyed is about 3700 feet. General drainage is to the southwest. Vegetation consists of creosote and cacti.</p> <hr/> |
|---------------------|---|

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Clay W. Morrow

Surveying Technician

Dylan S. Hansen

Survey Aid

CERTIFICATE OF SURVEY

I, Richard A. Zaninovich, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 28th day of September, 1998, I have dependently resurveyed portions of the north and west boundaries and a portion of the subdivisional lines, subdivided sections 6 and 7, and executed a metes-and-bounds survey in section 6, Township 6 South, Range 61 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

5-11-99

(Date)

Richard A. Zaninovich
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of the dependent resurvey of portions of the north and west boundaries and a portion of the subdivisional lines, the subdivision of sections 6 and 7, and a metes-and-bounds survey in section 6, Township 6 South, Range 61 East, Mount Diablo Meridian, Nevada, executed by Richard A. Zaninovich, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

5-18-99

(Date)

David L. Clark
(Chief Cadastral Surveyor, Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 6 S., R. 61 E., M.D.M., Nevada, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor, Nevada)~~