Resurvey of a Portion of the Subdivisions of

Fractional T. 29 S., R. 61 E.

Chains.	
	sec. 4 only, with brass cap mkd. ¼ S 4 1933
40.50	Enter wash, course SW.
42.20	Leave wash, course SW.; asc. 280 ft. over SE. slope.
68.00	Ridge, bears NE. and SW.; asc. 60 ft. on SW. slope.
73.70	Spur, slopes W.; desc. 180 ft. over NW. slope.
80.71	The original closing cor. of secs. 4 and 5, which is a granite stone, 20x14x8 ins., set in a mound of stone, 3 ft. base, 1 ft. high, marked C C on S. side. As this cor. now becomes a witness point, I add the marks WP on S. side.
80.87	Intersect the 7th Standard Parallel South. Set an iron post, 3 ft. long, 2 ins. diam., 15 ins. in the ground to bedrock, with a stone mkd. X, deposited at the base, and in a mound of stone to top, for closing cor. of secs. 4 and 5, with brass cap mkd. T 28 S R 61 E S 32 S 5 | S 4 T 29 S | R 61 E C C 1933 From point of intersection the standard cor. of secs. 32, and 33, T. 28 S., R. 61 E., bears S.89°56'E., 12.13 chs. dist.; and iron post, 2 ins. diam., 20 ins. above ground firmly set in a mound of stone, marked and witnessed as described in the official record. From the same point the standard ¼ sec. cor. S. bdy. sec. 32, T. 28 S., R. 61 E., bears N.89°56'W., 27.29 chs. dist.: an iron post, 1 in. diam., 20 ins. above ground, firmly set in a mound of stone, marked and witnessed as described in the official record. Land rolling, and rolling hills. Soil, gravelly, 3rd rate; and rocky, 4th rate. No timber. Undergrowth, scattered jushua, cactus, yucca and sage.

	From the cor. of secs. 4,5,8 and 9. West, on a random line bet. secs. 5 and 8.
40.00	Find no trace of the original ¼ sec. cor. Set temp. cor.
81.12	Intersect the original cor. of secs. 5,6,7 and 8. Continue line and measurement west bet. secs. 6 and 7.
121.12	Find no trace of the original ¼ sec. cor.
128.44	Find no trace of the original closing corner of frac. secs. 6 and 7.