Chains.	
	malpais stone,12x10x8 ins., set in a mound of stone 3 ft. base, 1 ft. high, marked ¼ on W. side.
	The true course and distance for S½ mile bet. secs. 7 and 12,is therefore N.0°10'W.,40.37 chs. dist.

	Thence from cor.
	North on a random line bet. secs. 7 and 12.
40.29	A point 40 lks. W. of the original cor. of secs. 1,6,7 and 12, which is a catclaw post, 2 ins. sq., 36 ins. long, set in a mound of earth 3 ft. base, 1 ft. high, marks illegible.
	At point for cor., with old post alongside,
	Set an iron post, 3 ft. long, 2 ins. diam., 14 ins. in the ground to bedrock, with a stone mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 1,6,7 and 12, with brass cap mkd.
	T30S R62E R63E S 1 | S 6 S12 | S 7 1933
	The true course and distance for N½ mile bet. secs. 7 and 12,is therefore N.0°34'E., 40.29 chs. dist.

	Resurvey of a Portion of the Subdivisions of Fractional T.30 S., R. 63 E.

	From the cor. of secs. 5,6,31, and 32,on S. bdy. of Tp., hereinbefore described.
	North on a random line bet. secs. 31 and 32.
40.72	A point 22 lks. E. of the original ¼ sec. cor.
	Thence from cor.
	North on a random line bet. secs. 31 and 32.
39.93	A point 5 lks. E. of the original cor. of secs. 29,30,31, and 32.
	Return to the cor. of secs. 5,6,31, and 32.
	Thence
	N.0°19'W., on a true line bet. secs. 31 and 32.
	Over rolling land, through scattered undergrowth.
	Ascend 44 ft. over SW. slope.
8.70	Spur, slopes NW.; desc. 280 ft. over NE. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a stone mkd. X, deposited at the base, and in a mound of stone to top, for ¼ sec. cor. of sec. 31 only, with brass cap mkd.