

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
TOWNSHIP 30 SOUTH, RANGE 63 EAST, MDM, NEVADA

CHAINS 8.30	Trail road, bears N. and S.
37.00	Wash, 30 lks. wide, 2 ft. deep, drains SSE.
40.33	<p>The $\frac{1}{4}$ sec. cor. of secs. 3 and 34, monumented with a volcanic stone, 12X12X8 ins., (record: wooden post), plainly mkd. $\frac{1}{4}$ on N. face, firmly set in a mound of earth.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30S R63E S 34 $\frac{1}{4}$ $\frac{5}{3}$ T31S</p> <p style="text-align: center;">1989</p> <p>Deposit the original cornerstone alongside the stainless steel post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
	<p style="text-align: center;">_____</p> <p>N. $89^{\circ} 26'$ W., beginning new measurement.</p> <p>Over gently rolling land.</p>
14.00	Wash, 30 lks. wide, 2 ft. deep, drains SSE.
40.37	<p>The cor. of secs. 3, 4, 33 and 34, monumented with an iron post, 2 ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 31 S., R. 63 E., executed under Group 204, California.</p>
<p>DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 30 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA</p>	
<p>Reestablishment of the Survey Executed by W. H. Myrick, U.S. Deputy Surveyor, in 1883.</p>	
	<p style="text-align: center;">_____</p> <p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp.</p> <p>N. $0^{\circ} 32'$ E., bet. secs. 35 and 36.</p> <p>Over gently rolling land, covered with creosote, greasewood, and scattered cacti.</p>
33.30	Wash, 40 lks. wide, 1 ft. deep, drains SSE.
35.60	Trail road, bears E. and W.