

DEPENDENT RESURVEY OF THE WEST BOUNDARY,
T. 32 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">Reestablishment of the Survey Executed by T.A. Magee in 1883</p> <hr/>
	<p>Beginning at the standard cor. of Tps. 32 S., Rs. 65 and 66 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the 1932 dependent resurvey of a portion of the Eighth Standard Parallel South executed by C.S. Swanholm under Group No. 157, and a mound of stone N. of the cor.</p>
	<p>N. 0°29'10" W., bet. secs. 31 and 36.</p>
13.80	<p>Power transmission line, NE-SW.</p>
39.288	<p>The 1/4 sec. cor. of secs. 31 and 36, recovered by C.S. Swanholm in 1932, and unofficially remonumented by J.W. Hardison in 1947, from original evidence no longer in existence, monumented with an iron post, 1 in. diam., firmly set in a mound of stone, with brass cap mkd.</p>
	<p style="text-align: center;">1/4 S36 1947</p>
	<p>Remark the brass cap to read as follows:</p>
	<p style="text-align: center;">T32S R65E R66E 1/4 S36 S31</p>
	<p style="text-align: center;">1947 1997</p> <hr/>
	<p>N. 0°53'50" W., beginning new measurement.</p>
5.814	<p>A point unofficially established as the 1/4 sec. cor. of sec. 31 only, by J.W. Hardison in 1947, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, with a mound of stone E. of cor., with brass cap mkd.</p>
	<p style="text-align: center;"> T32S 1/4 S31 R66E 1947</p>
	<p>This will now function as a control monument; remark the brass cap to read as follows:</p>
	<p style="text-align: center;">CM 1997 1947</p>