

H.E.S. No.37.

Chains

Beginning at Cor.No.1 on rocky side hill 1 ch. west of Bruneau River Bottom, I set a granite stone 6x8x24 ins. set 1 ft. in the ground chiseled H-1-37 and raise a mound of stone 2 ft. base 1½ ft. high 8 lks. south. Whence the Standard Tp. cor. on 9th Standard Parallel North, common to Tp.46 N., Rgs.56 and 57 E., M.D.B. and M. bears N.4.09 chs. This cor. consists of a granite stone 4x7x22 ins. set in a substantial mound of stone chiseled 6 bars 57 on East face. T 46 and 6 bars on North face, 56 E and 6 Bars on West face. No marks on south face, situated on steep rocky hillside. F.S.M. No.1 bears N.1.06 chs. a cross and B.R. chiseled on the face of a prominent bluff bears S.89°W.68 lks.

Thence south.

along the base of Main Mountains on west side of Bruneau River over rolling land.

27.58 Clump of willows on line.

47.65 Clump of willows on line.

80.00 To Cor. No.2. I set a granite stone 4x8x24 ins. set 1 ft. in the ground chiseled H-2-37 and raise a mound of stone 2 ft. high 2½ ft. base 6 lks. N.E.F.S.M.No.2 bears South 3.80 chs. A cross and B.R. chiseled on the face of a rock in place bears N.59°W. 2.23 chs.

Thence East.

4.40 Top of bench.

6.50 Foot of bench along river bottom in thicket.

9.00 Left bank of Bruneau River 65 lks. wide course near N. and S.

13.06 S.E. Cor. of Log Stable 16x100 ft. bears N.8½°W. 1.82 chs. long side bears N.35°W. N.W. Cor. Prunty's House bears N.10°W. 4.55 chs. long side of House bears N.59°E. 25x60 feet.

14.78 Foot of bench and east side of thicket. Ascend.

30.00 To Cor. No.3 on east side bench land. I set a granite stone 6x10x24 ins. set 1 ft. in the ground chiseled H-3-37 and raise a mound of stone 2 ft. base, 1½ ft. high 8 lks. N.W. F.S.M. No.3 bears S.14°03'E. 3.47 chs. A cross and B. R. chiseled on the face of a rock in place bears N.45°45'E. 40 lks.

Thence N.14°03'W.

Ascending.

6.10 To notch on prominent bluff, descending.

12.65 Enter Miller Creek thicket.

13.60 Miller Creek 12 lks. wide flowing southwesterly.

16.00 Out of thicket to foot of bluff on line 300 ft. long. At this point offset at right angles to line 1.44 chs. westerly, ascend.

23.80 At this point offset at right angles to line 1.44 chs. easterly.

25.78 Top of bench.

30.36 North side of bench. Descending.

48.50 On rocky bluff gorge at foot of same on north side.

56.37 Top of a ridge.

63.20 Top of a bluff, descending to a flat.

73.25 South end of a rocky ledge that continues to Cor.No.4 Not possible to measure on this ledge therefore offset at right angles to line westerly 1.30 chs. and continue on same course at the foot of rocky ledge.

82.46 Intersect east line from Cor.No.1. At this point I set a granite stone 6x10x48 ins. 1 ft. in the ground, chiseled H-4-37, W.C. and raise a substantial mound of earth and stone around it 5 ft. base, 2 ft. high. F.S.M. No.4 bears N.78°35'E. 2.70 chs. A cross and B.R. chiseled on the face of bluff bears S.34°E. 21 lks. A cross and B.R. chiseled on the face of bluff bears N.41°W. 35 lks. This cor. stands at the foot of an inaccessible bluff 1.34 chs. west of actual position.

Thence West from Witness Cor.

Descending.

2.42 Right bank of Bruneau River 60 lks.wide, course near N. and S.