

HUMBOLDT NATIONAL FOREST

14.

STATE OF NEVADA

Chains		Chains
	Along edge brush side of ditch	
	N. 39° 51' W. Ditch 8 ins. wide	0.58
	Over rolling sagebrush land	0.80
	Ascend.	4.87
0.42	Fence bears NE. and SW. W. edge of ditch	00.8
2.04	Road bears NE. and SW. To Cor. No. 15	18.31
20.04	To Cor. No. 15, about 40 ft. above Cor. No. 14, identical to each with Cor. H-1 of the listing survey, and Forest Service Monument, which is quartzite stone, firmly set, mkd. as described by the Surveyor General, in place of which I set a lava stone, 24 x 10 x 10 ins., 14 ins. in the ground, over broken glass, for Cor. 15 of this survey, mkd. 15-HES-63 on the side facing the claim, and a cross (x) on the top; no bearings, therefore, dig pits, 24 x 24 x 12 ins., crosswise on this and the succeeding course, 7 ft. dist. and raise a mound of earth, 4 ft. base, 2 ft. high, 3 1/2 ft. dist. within the claim.	
	Cor. 4 of H. E. S. No. 76 (survey unapproved), an aspen post, 4 ins. square, showing 12 ins. above ground, mkd. 4-HES-76 on the NW. face with a tack in the top, bears N. 1° 59' W., 22.92 chs. dist. By To Cor. No. 14, identical with Cor. H-2 of the listing survey, which is a quartzite stone, firmly set, the bearing and distance was found to be, S. 1° 59' E., 23.02 chs.	
	place of which I set a quartzite stone, 24 x 10 x 10 ins., 14 ins. in the ground, over a lava stone, and 15 ins. The fence bears NE. and SW. To Cor. No. 14 of this survey; mkd. 14-HES-62 on the side facing the claim and a cross (x) on the top; no bearings, therefore, dig pits, 24 x 24 x 12 ins. crosswise on this and the succeeding course, 7 ft. dist. and raise a mound of earth, 4 ft. base, 2 ft. high, 3 1/2 ft. dist. within the claim.	