

Chains

- described by the Surveyor General, bears N. 54° 29' W., 90 lks. dist. I destroy this cor. and its witness.
- Thence
S. 35° 24' E.
- 0.23 Fence bears N. and S.
- 13.40 Strike road, and follow, bears N. and S. 35° 24' E.
- 16.35 Leave road, which bears S. and N. 35° 24' W.
- 19.65 Fence bears NW. and SE.
- 20.85 Corral fence bears NE. and SW.
- 21.65 Corral fence bears NE. and SW.
- 23.21 Ditch, 2 lks. wide, 6 ins. deep, flows E.
- 23.73 Same ditch, flows SW.
- 27.21 Fence bears NE. and SW.
- 30.59 Ditch, 2 lks. wide, 6 ins. deep, flows SE.
- 32.20 Ditch, 2 lks. wide, 6 ins. deep, flows S.
- 54.82 To Cor. No. 5, previously mkd. by a temp. stake, in place of which I set a granite stone, 30 x 12 x 8 ins., 15 ins. in the ground to bedrock, in a mound of stone, over a cross (x), mkd. on the face of the bedrock, on line bet. Secs. 1 and 6, T. 2 N., Rs. 56 and 57 E., for closing cor. and Cor. No. 5 of this survey, mkd. 5-HES-117 on the side facing the claim, CC on the NW. face, and a cross (x) on top. No bearings. Pits impracticable. Raise a mound of stone, 5 ft. base, 2½ ft. high, 4 ft. dist. on the closing line, N. 35° 24' W., 3½ ft. dist.
- The cor. of Secs. 1, 6, 7 and 12, T. 2 N., Rs. 56 and 57 E., heretofore described, bears S. 10° 08' W., 35.20 chs. dist.
- The ¼ cor. bet. Secs. 1 and 6, T. 2 N., Rs. 56 and 57