

Chains
19.98

To Cor. No. 3, about 73 ft. below Cor. No. 2, identical with Cor. No. 3 of the listing survey, which is a pinon pine stake, showing 28 ins. above ground, firmly set, mkd. as described by the Surveyor General, in place of which I set a blue limestone, 26 x 14 x 6 ins., 16 ins. in the ground, over broken glass, for Cor. No. 3 of this survey, mkd. 3-HES-192 on the side facing the claim, and a cross (x) on top. No bearings, therefore dig pits, 24 x 24 x 12 ins., crosswise on this and the succeeding course, 7 ft. dist., and raise a mound of earth, 4 ft. base, 2 ft. high, 3½ ft. dist., within the claim.

September 20, 1917.

Thence

S. 0° 38' E.

Over level land, through sagebrush.

8.70 Road bears E. and W.

10.41 Ascend.

20.66 To Cor. No. 4, about 34 ft. above point of ascent,

identical with Cor. No. 3 of H. E. Survey No. 191,

which is a blue limestone, showing 10 ins. above

ground, firmly set, mkd. 3-HES-191 on the SW. face,

and a cross (x) on top, and properly witnessed by

pits and a mound of earth. I mk. this same stone,

4-HES-192 on the NW. face, for Cor. No. 4 of this

survey. Dig a pit, 24 x 24 x 12 ins., crosswise

on line, N. 0° 38' E., 7 ft. dist., and raise a

mound of earth, 4 ft. base, 2 ft. high, 3½ ft. dist.,

within the claim.