

Chains

Chains

Dig a pit, 24 x 24 x 12 ins., crosswise on line
S. 0° 10' E., 7 ft. dist., and raise a mound of
earth 4 ft. base, 2 ft. high, 3 1/2 ft. dist., within
the claim.

No bearing objects available.
The Cor. of Secs. 5, 6, 31 and 32, Tps. 28 and 29 N.,
R. 57 E., (survey accepted), which is a granite stone,
firmly set, mkd. 5 notches on the E. edge and 1
notch on the W. edge and witnessed by a mound of
stone to the W., being in sight, bears N. 0° 10'
W., 17.00 chs. dist.

Thence

N. 89° 51' E.

Ascend over rolling sagebrush land along line 4-3 of
H. E. S. No. 229 (survey unapproved).
30.00 To Cor. No. 2, about 150 ft. above Cor. No. 1,
identical with Cor. No. 3 of H. E. S. No. 229
(survey unapproved), which is a quartzite stone,
firmly set, 16 x 6 ins., showing 10 ins above
ground, mkd. 3-HES-229 on the N. face, and a cross
(x) on top, and witnessed by pits and a mound of
earth. I mark this stone 2-HES-228 on the S.
face for Cor. No. 2 of this survey. No bearing
objects available. Dig a pit, 24 x 24 x 12 ins.,
crosswise on line S. 52° 24' E., 7 ft. dist., and
raise a mound of earth 4 ft. base, 2 ft. high, 3 1/2
ft. dist., within the claim.

June 27, 1918.

Thence to Cor. No. 3 below Cor. No. 2 for which

S. 52° 24' E. 33 x 12 x 7 ins.