

U. S. Survey No. 2209, Hot Springs Borax Placer.

Feet.	<p>Beginning at Cor. No. 1, identical with a cor. of the loc., a sandstone 24 x 10 x 5 ins. set 12 ins. in the ground and chiseled "1-2209", with a X at cor. point, raise a mound of earth alongside; whence the cor. to sec.s 34 and 35, South boundary T. 33 N., R. 23 E., M.D.B. and M., bears N. 16° 25' 50" E. 9905.8 ft., a granite rock 18, x 12 x 8 ins. above ground, properly marked, with a mound of earth North.</p>
	<p>Thence West</p>
1980.00	<p>To cor. No. 2, a sandstone 36 x 18 x 6 ins set 12 ins. in the ground and chiseled "2-2209" with a X at cor. point raise a mound of earth alongside; whence a cor. of the loc. bears N. 1.8 ft.</p>
	<p>Thence South.</p>
655.00	<p>Cross road N.W. and S.E.</p>
1980.00	<p>To cor. No. 3, a sandstone 40 x 20 x 8 ins. set 12 ins. in the ground and chiseled "3-2209" with a X at cor. point, raise a mound of earth alongside; whence a cor. of the loc. bears S. 45° 40' W. 2.9 ft., and U.S. Loc. Mon. No. 164 bears S. 57° 8' W. 2810.7 ft.</p>
	<p>Thence East</p>
385.00	<p>Cross road S.W. and N.E.</p>
660.00	<p>To cor. No. 4, a sandstone 30 x 15 x 8 ins. set 12 ins. in the ground and chiseled "4-2209" with a X at cor. point raise a mound of earth alongside; whence a cor. of the loc. bears S. 45° 00' W. 2.8 ft.</p>
	<p>Thence South</p>
660.00	<p>To cor. No. 5, a sandstone 32 x 20 x 6 ins. set 12 ins. in the ground and chiseled "5-2209" with a X at cor. point raise a mound of earth alongside; whence a cor. of the loc. bears S. 25° 00' W. 3.4 ft.</p>
	<p>Thence East</p>
20.00	<p>Cross road N. and S.</p>
1980.00	<p>To cor. No. 6, a sandstone 24 x 14 x 6 ins. set 12 ins.</p>

W. H. ...
U.S. Survey Mineral Surveyor.