development of these two locations through one system of workings. It is situated at practically the lowest point of surface elevation on the claim. It is the intention of the claimant to crosscut to the S.W. until the veins of its two locations are encountered and then to drift on the same, thus opening up its ore bodies at great depth.

An undivided 1/2 interest in this improvement is applied upon each location of this survey.

The remaining improvements are accredited to the location upon which they are situated.

OTHER IMPROVEMENTS

1 An open cut 8 ft. face, 12 ft. wide, and 60 ft. long, with wagon road leading to same, the center of cut bears from Cor. No. 5, Crocker Lode, N.74° 53'E. 454.2 ft.

Leona Placer Quarry Claimant.

INSTRUMENTS

This survey was made with an A. Lietz Co. Transit No. 0523.

The courses were deflected by plate angles from the true meridian as established by the U.S. Coast and Geodetic Survey, and markde by stone piers set about one mile apart.

The distances were measured with a 650 ft. standard steel tape.

REPORT

The S.W. Cor. Sec. 35, T.3 N., R.42 E., Mount Diablo Base and Meridian, is a rhyolite stone 12 x 4 x 16 ins., set in mound of stone, chiseled with 2 notches on E. and 4 notches on W. edges.

Cor. No. 1, Sur. No. 2042 Curtis Lode, is a pine post 4 ins. square, 2-1/2 ft. above ground, in mound