

SURVEY NO. 2401.

Amended Sterling lodes, an undivided one-half interest in said last 100 feet being credited to each lode.

Said drift is run on the vein which passes through the Amended Sterling and Amended Resurrection lodes, and develops the same at great depth, and furnishes the most economical method of working this vein.

The last 75 feet of drift No. 2, (Improvement No.8), is applied upon the Amended Boston lode, and by drifting in a southerly direction on an incline the vein of said lode is developed most economically and with one system of workings.

Improvement No. 4, (An open cut), is credited to the Amended Rebellion lode.

OTHER IMPROVEMENTS.

A sawed lumber blacksmith shop and equipments, the S. E. corner of which bears from corner No. 1 Amended Resurrection lode N. 62° 30' W. 210 ft., 20x15 ft., course of long sides is N. 60° W.

A boarding house 40x18 ft., the N. E. corner of which bears from corner No. 1 Amended Boston lode S. 42° 30' W. 252 ft. The course of the long sides is east.

Said buildings belong to the claimants herein.

INSTRUMENT

This survey was made with a Berger & Sons No. 4 Mining Transit. The courses were deflected from the true meridian as determined by direct solar observations. The distances were measured with a 300 ft. steel tape.

REPORT

The W. 1/4 corner Sec. 36, Tp. 31 N. R. 43 E. is an andesitic lava rock 12x8x12 inches above ground, marked 1/4 on the west face.

Survey No. 2202 End Line lode

Corners Nos. 1 and 5 are sawed pine posts 4 inches square, 2 1/2 feet above ground and mound of stones, scribed 1-2202 and 1-5-2202, respectively.