

A frame building the S.W. Cor. of which bears from Cor. No. 2 N. $31^{\circ}01'E.$ - 171 ft. 20 x 40 ft. course of long side N.E. Claimant unknown.

Instrument.

This survey was made with a Lietz transit. The courses were deflected from the true meridian as determined by direct solar observations. The distances were measured with steel tapes.

Report.

The lines of this survey and connections to the corner of the public survey were run upon the ground and found to be as given herein.

The S.E. Cor. Sec. 7 T. 16 N. R. 63 E. M. D. B. and M. is a lime rock showing 12 ins. above the ground with four grooves on the South side and five grooves on the East side.

The S. $1/4$ Cor. Sec. 7 T. 16 N. R. 63 E. M. D. B. and M. could not be found.

The N.W. Cor. Sec. 7 T. 16 N. R. 63 E. M. D. B. and M. is a lime rock showing 12 ins. above the ground with five grooves on the South and one groove on the North face.

The original S.W. Cor. Sec. 7 T. 16 N. R. 63 E. M. D. B. and M. is missing, its original position being marked by Cor. No. 6 Sur. No. 2680 Maud S. Placer, which is a pine post 4 ins. square 4.5 ft. long set 2 ft. in the ground, scribed 6-2600

Whence the N.W. Cor. Sec. 7 T. 16 N. R. 63 E. M. D. B. and M. bears N. $2^{\circ}05'E.$ 5282.9 ft. The S.E. Cor. Sec. 7 T. 16 N. R. 63 E. M. D. B. and M. bears N. $89^{\circ}34'E.$ - 5297.45 ft. The S.W. Cor. Sec. 18 T. 16 N. R. 63 E. M. D. B. and M. bears S. $2^{\circ}05'W.$ - 5282.9 ft.

The S.W. Cor. Sec. 18 T. 16 N. R. 63 E. M. D. B. and M. is a lime rock showing 14 ins. above the ground with three grooves on the South and three grooves on the North side. The S.E. Cor. Sec. 18 T. 16 N. R. 63 E. M. D. B. and M. could not be found.

Cors. Nos. 4 and 5 Sur. No. 2680 Maud S. Placer are pine posts