

Survey No. 2900.

5.

distances were measured with 100 and 500 ft. steel tapes.

NOTE: The disagreements between these field notes and the location notices are due to errors in the latter.

✓ REPORT.

The Cor. common to Secs. 31 and 32 T. 44 N., R. 52 E. M.D.B. and M. and Secs. 5 and 6 T. 43 N., R. 52 E. is a mound of rock with no marked stone or post. This corner was identified by retracing the lines North, South, East and West. The distances and alignment agree with notes on file in the U.S. Surveyor General's Office. A juniper tree 16 ins. in diameter bears S. 53 W. 23 ft., which I blazed and scribed B.T.S. 6, 43-52.

This survey was tied to the N.W. Cor. of Sec. 5, T. 43 N., R. 52 E. because it was the nearest corner of the public survey that could be identified.

---

do solemnly swear that we assisted

United States Deputy Mineral Surveyor, in marking the corners and surveying

the boundaries of the mining claim of

known as the

represented in the foregoing field notes as having been surveyed by said deputy mineral surveyor and under his

direction, and that said survey has been in all respects, to the best of our knowledge and belief, faithfully and

correctly executed, and the corner and boundary monuments established according to law and the instructions

published by the United States Surveyor-General for

*Regada*  
*W. E. Bligerson* Chairman  
*H. J. In Japan* Chairman  
*Fred Linder* Assn.

Flagman.

Subscribed and sworn to by the above-named persons before me this

day of

*July*

1907

*H. T. Baer*

*Notary Public*

Recorded in

*My commission expires*  
*July 23 1909*