

SURVEY NO. 3054.

✓ OTHER IMPROVEMENTS.

A galvanized iron engine house 24 x 36 ft., course of long sides N. 83° W., N.E. Cor. of which bears from Cor. No. 3, ^{Dewdrop lode} S. 64° W. 295 ft. Said engine house belongs to claimant herein.

A frame pump house 20 x 21^{ft}, course of long sides N. 83° W., N.E. Cor. of which bears from Cor. No. 3, ^{Dew drop lode} S. 59° W. 310 ft. Said Pump house belongs to claimant herein.

✓ INSTRUMENT.

This survey was made with a Brandis Sons and Co. Light Mountain Transit.

The courses were deflected from the true meridian as determined by direct observations upon the sun.

The distances were measured with 600 ft. and 100 ft. steel tapes.

✓ REPORT.

The N. E. Cor. of Sec. 20, T. 2 S. R 43 E., M.D. Base and Meridian, to which connection was made, consists of a stone 8 x 10 inches, showing 12 ins. above ground, with earth mound, marked 4 notches on East Side 3 notches on South side and cross on top.

Cor. No. 2, Sur. No. 2535 Buffalo lode is a pine post 4 x 4 ins. 2½ ft. above ground, in mound of stone, scribed 2-2535.

Cor. No. 1, Sur. No. 2298 Midnight Fraction lode, is a pine post 4 x 4 ins., 2½ ft. above ground, in mound of earth and stone, scribed 1-2298.

N.E. Cor. Last Chance lode (unsurveyed) is a pine