

SURVEY NO. 3116.

FEET. that said improvements consist of,:

A shaft 8x6 ft. 50 ft. deep in earth and rock;
timbered, bears S. 9° W. 106 ft. from Cor. No. 2-3116.

Value of shaft,.....\$500.00 ✓

OTHER IMPROVEMENTS

None.

INSTRUMENT.

This survey was made with a Buff and Berger Light mountain transit. The courses of which were deflected from a true meridian as determined from a direct solar observation.

The distances were measured with a 500 ft. steel tape.

Note:....The disagreement between these field notes and the location certificates in regard to the position of the Discovery Monument and the courses and distances of the boundary lines are due to errors in the latter.

REPORT.

All lines of this survey of the Gold Bug lode, and the section tie to the quarter section Cor. between Secs. 27 and 34 T. 13 N. R. 24 E. M. D. B. and M., were made direct upon the ground.

The quarter section Cor. between secs. 27 and 34 T. 13 N. R. 24 E., M. D. B. and M., is a granite rock 12x10x18 ins., marked with a (x) on top and $\frac{1}{4}$ on W. face, standing in a mound of rock.

I find the course and distance of the section line from the quarter section Cor. between secs. 27 and 34 T. 13 N. R. 24 E., M. D. B. and M. to be S. 88° 13' W. 2663.08 ft. instead of N. 89° 54' W. 2636.37 ft., to the S. W. Cor. of Sec. 27, T. 13 N. R. 24 E., M. D. B. and M.