

No other improvements.

INSTRUMENT.

This survey was made with a W. & L. E. Gurley Light Mountain Transit. The courses were deflected from a true meridian determined by an observation on Polaris on October 7th 1907. The distances were measured with a 300 feet steel tape.

REPORT.

The corner of sections 25, 30, 31 and 36, Township 13 North, Ranges 24 and 25 East of Mount Diablo Base and Meridian is an eruptive stone 18 inches long, 8 by 10 inches diameter in mound of stones, chiseled with one groove on the south and five grooves on the north.

Corner No. 2 Survey No. 3044 North Excelsior lode is a fir post $2\frac{1}{2}$ feet above the surface of the ground 4 inches square set in mound of earth and stone, scribed
2-3044

Corner No. 4 Survey No. 3044 Excelsior No. 3 lode is a fir post $2\frac{1}{2}$ feet above the surface of the ground 4 inches square set in mound of earth and stone, scribed
4-3044

Corner No. 3 Survey No. 2913 July lode is a fir post $2\frac{1}{2}$ feet high 4 by 6 inches with sides at right angles?
scribed 3-2913

Corner No. 6 Survey No. 3157 Copper Age lode, also

Corner No. 2 Survey No. 2913 July lode is a fir post $2\frac{1}{2}$ feet above the ground 4 by 6 inches square in mound of earth, scribed 6-3157 and 2-2913.

Corner No. 1 Survey No. 3157 Copper Ridge lode is a fir post $2\frac{1}{2}$ feet high 4 inches square, set in mound of earth and stone, scribed 1-3157 (North Excelsior Fraction Lode)

The SW corner of location is a fir post 4 feet high 4 inches square set firmly in the ground.

Corner No. 4 Survey No. 3157 Copper Ridge lode is a fir post $2\frac{1}{2}$ feet high 4 inches square set in mound of earth and stone, scribed 4-3157.