

-4-

Survey No. 3395.

Widows Mine Lode.

A shaft 4 by 6 ft. 27 ft. deep in solid rock which bears from Cor. No. 5 $N. 80^{\circ} 35' W.$ 219.95 ft.

Value

\$202.50

Other improvements.

A frame blacksmith shop, the north-east corner of which bears from Cor. No. 5 of this survey $S. 49^{\circ} 26' W.$ 162.71 ft. 12 by 16 ft. Course of long sides $N. 28^{\circ} 0' W.$ Said shop belongs to claimant herein.

Instrument.

This survey was made with a Gurley Engineer's transit, the courses were deflected from the true meridian as determined by direct solar observation. The distances were measured with a 500 foot steel tape graduated to feet and with a 25 foot steel tape graduated to hundredths of a foot.

Report.

The sec. cor. common to secs, 3, 4, 9 and 10, to which connection is given in these notes, consists of a granite boulder 10 by 9 by 8 ins, marked with 3 notches on the East side and 5 notches on the south side, and is set 5 ins. in the ground with badly weathered mound alongside.

Cor. No. 1 of Survey No. 3227, X Ray Lode consists of a pine post, 4 ins. square, 3 ft. above ground, in mound of earth and stone, scribed 1-3227.
Cor. No. 2 of Survey No. 3227, X Ray Lode consists of a pine post, 4 ins. square, 3 ft. above ground, in mound of earth and stone, scribed 2-3227.