

FINAL SURVEY  
Survey No. 3629.

## ✓ Other Improvements.

1. Office building 14 x 12 ft. the N.W.Cor. of which bears S 82°-51'E, 489.0 ft. from Cor.No.2 Windy Ridge Lode - short side running N 73°-25'E.
2. Cabin 9 x 12 ft. the S.W.Cor. of which bears S 83°-05'E 510.0 ft. from Cor.No.2 Windy Ridge Lode - the short side running N 73°-25'E.
3. Mess house 12 x 42 ft. the S.W.Cor. of which bears S 84°-21'E, 544.0 ft. from Cor.No.2 Windy Ridge Lode - the long side running N 73°-25'E.
4. Bunk house 14 x 24 ft. the S.W.Cor. of which bears S 87°-23'E, 629 ft. from Cor.No.2 Windy Ridge Lode - the long side running N 73°-25'E.
5. Engine house 14 x 20 ft. the S.E.Cor. of which bears N 79°-42'W, 392.1 ft. from Cor.No.4 Humboldt Lode - the long side running S 55° W.

## INSTRUMENTS.

This survey was made with a Keuffel and Esser Light Mountain Transit. The courses were deflected from the true meridian as determined by direct observation upon Polaris. The distances were measured with 50 and 500 ft. steel tapes.

The N.E.Cor. of Sec.25, T 4 N, R 35 E, Mt.D.B. and M. is a hard dark stone 12x10x12 inches with 2 marks on the South side and 4 marks on the North.

Any disagreement between these notes and the location certificates <sup>amended</sup> due to errors in the latter.

*Walter G. Hunter*

U.S.Deputy Mineral Surveyor.

Subscribed and sworn to by the above-named person before me this

day of January 1898.