

Survey No. 3660

Feet

Expenditure of Five Hundred Dollars/
Improvements not returned herewith.

Other Improvements.

There are no other improvements.

Instrument.

This survey was made with a Berger No. 4 Transit.
The courses were deflected from the true Meridian as
determined by a direct Solar observation.

The distances were measured with a 500 ft. steel tape

Report.

The Cor. to Secs. 12, 13, 7 and 18, T. 13 N., Rgs. 23 and
24 E., Mt. Diablo B. and M., is a porphyry stone 5x6x6 ins.
above ground in mound of Gypsum stones, marked with 2
notches on the N. edge and 4 notches on the S. edge.

The Cor. to Secs. 13, 24, 18 and 19, T. 13 N., Rgs. 23 and
24 E., Mt. Diablo B. and M., is a lava stone 5x5x10 ins.
above ground, marked with 3 notches on the N. edge and
3 notches on the S. edge.

Did not find the 1/4 Cor. between Secs. 13 and 18, T.
13 N., Rgs. 23 and 24 E., Mt. D. B. and M.

The N.E. and S.E. Cors. of Iron Mountain lode (Unsurvey-
ed) are pine posts 4 ins. square, 2 1/2 ft. above ground in
mounds of stone marked N. E. Cor. Iron Mt. and S. E. Cor. Iron
Mt., respectively.

Errors

I find the line between Secs. 13 and 18, T. 13 N., Rgs.
23 and 24 E., Mt. D. B. and M., to be North 5322.3 ft.

Witnessed and sworn to by the above-named persons before me this
June 1904