

Survey No. 3721 A and B

is S 48°13'W, 560.2 feet,
 from Cor No. 3 to Cor. No. 9 is N 44°29'W, 1480.3 feet
 from Cor. No. 9 to Cor. No. 11 is N 48°13'E, 588 feet
 and from Cor. No. 11 to Cor. No. 1, is S 43°25'E, 1479.2 ft.
 instead of the courses and distances given in the
 approved field notes thereof.

Sur. No. 134 Brennan lode.

Cor. No. 2 is a mound of stone, identified by the Deputy
 who made the survey, Mr. J.H. Trolson, as being the posi-
 tion of the original corner. The post is gone.

All the other corners are gone.

The courses and distances as given in the approved
 field notes thereof were used.

Sur. No. 1810. Woodbridge lode.

Cor. No. 1 is a pine post, 4/4 ins. by 3 feet above
 ground. Scribed 1-1810.

Sur. No. 1883. Mill Site No. 2.

Cor. No. 1 is a pine post, 7 ins. in diameter by 4
 feet above ground. Scribed 1-1-1883. All the other cor-
 ners are gone. From Cor. No. 1 to the East $\frac{1}{4}$ Cor. Sec. 24,
 T19N, R43E, Mt. Diablo B. and M. is S 69°54'W, 737.1 ft. in-
 stead of the course and distance given in the approved
 field notes thereof. The courses and distances of lines
 3-4 and 4-1 as given in the approved field notes there-
 of were used.

Sur. No. 3715, Brannan lode.

All the corners are pine posts, 4/4 ins. by 2 feet above
 ground. Properly set and scribed with the correct corner
 and survey number.

3rd. The East $\frac{1}{4}$ Cor. Sec. 24, T 19 N, R 43 E, Mt. Diablo
 B. and M. is a granite stone, 12/12 ins. by 10 ins above
 ground. Chiseled 1-3721 B and $\frac{1}{4}$ on the West face.

The N.E. Cor. Sec. 25, T 19 N, R 43 E, Mt. Diablo B. and
 M. is a granite stone, 12/14 ins. by 8 ins. above ground.
 Chiseled with 4 grooves on the North face and 2 grooves
 on the South face.

The course and distance between the East $\frac{1}{4}$ Cor. Sec.