

Survey No. 3754.

INSTRUMENT.

This survey was made with a C. L. Berger mining transit No. 6253. The courses were deflected from the true meridian as determined by direct solar observations. The distances were measured with 6 ft. and 500 ft. steel tapes.

REPORT.

The Corner of Sections 7, 8, 17 and 18, T.16 N., R.63 E., Mount Diablo Base and Meridian is a limestone with five marks on the east and four marks on the south faces. This is the nearest standing corner of the public land survey that can be found and identified.

Sur. No. 37 A, Aultman lode.

Cor. No. 2 is a pine post, properly set but not marked. Cor. No. 3 is a pine post, properly set and scribed with the number of the corner and survey.

Line 2-3 is S. 32° 30' W., 243 ft. instead of S. 34° 15' W., 250 ft. as given in the approved field notes.

Sur. No. 64, Southern Cross lode.

Cor's No. 2, 3 and 4, are pine posts, properly set and scribed with the number of the corner and survey.

Line 2-3 is S. 29° 28' W., 346.31 ft. instead of S. 30° W., 350 ft. as given in the approved field notes.

Line 3-4 is S. 40° 41' E. instead of S. 40° 11' E. as given in the approved field notes.

Note. Tunnel No. 11 is being driven to develop the Golden Fleece lode of this survey and the Golden Fleece Fraction lode, unsurveyed, and 1/2 of the value of said tunnel is credited to this claim.