

meridian as determined by direct solar observations.

The distances were measured with a 500 and 100 foot steel tape.

Report.

All lines and ties of this survey were run direct on the ground.

The S.W. Cor. Sec. 16, T. 16 N. R. 62 E. M. D. B. and M. to which connection is given herein is a lime rock showing 4 x 6 x 6 ins. above a mound of rock with 3 notches on the S. side and 4 notches on the E. side.

The S.E. Cor. Sec. 16 T. 16 N. R. 62 E. M. D. B. and M. to which connection is also given is a lime rock showing 6 x 6 x 8 ins. above a mound of rock with 3 notches on the S. and E. sides.

The above are the nearest corners of the public survey that can be found and identified.

Sur. No. 49 El Dorado Lode.

All corners are pine posts properly set and scribed with number of corner and survey.

Sur. No. 2474 Sibley, Aldebaron and Aucu Lodes.

All corners are pine posts properly set and scribed with number of corner and survey.

All corners of Sur. No. 3445 Badger lode are pine posts properly set and scribed with number of corner and survey.

All corners of Sur. No. 3811 Ely National No. 2 lode are pine posts properly set and scribed with name of claim and number of corner and survey.

All corners of Herstelle No. 1 lode, unsurveyed, are pine posts properly set and marked with name of claim.

All corners of Herstelle No. 2 lode, unsurveyed, are pine posts properly set and marked with name of claim.