It is contemplated to use both as working shafts, the first for the Golden Lance No. 1 lode to be carried back south through the Betsy lode for its development and in order to obtain a tunnel opening to the ~~the~~ very deep canyon on its south; the other will be used for the development of the Golden Lance No. 2 and the Betsey Fraction lodes, the vein being been located as continuing directly on into the said Fraction. Such a system of workings will inure to the common benefit of the said locations in a most advantageous manner.

Betsy

The other improvements described above are credited to their respective locations on which they are located.

OTHER IMPROVEMENTS.

There are no other improvements on the claim.

INSTRUMENT.

This survey was made with a Gurley Light Mountain transit; the courses were deflected from the meridian as determined by observation on Polaris. The distances were measured by 100 ft. and 500 ft. steel tapes.

REPORT.

The E. 1/4 Cor. of Sec. 21, T. 23.N., R. 35 E., M. D. B. & M., is a post showing 2-1/2 ft. above ground, 3 ins. in diameter. Marked stone could not be found and pits are practically obliterated.

The N. E. Cor. of said Sec. 21 is a post 4 ins. square showing 3 ft. above ground, marked T. 23 N., S. 15 on N. E. face, R. 35 E., S. 22 on S. E. face, S. 21 on S. W. face and S. 16 on N. W. face with three notches on South edge and three notches on East edge. Pits and mounds are