

long sides S.87°13'E. Contains an 18 H. P. Western gasoline hoisting engine.

A frame blacksmith shop, the S. W. Cor. of which bears from Cor. No. 4, Prairie Flower lode, N.50°08'E. 436.55 ft., 10x12 ft. Course of long sides N.5°E. All of these buildings belong to claimant herein.

INSTRUMENT.

This survey was made with a Gurley light mountain transit, style No. 27. The courses were deflected from the true meridian as determined by direct solar observations. The distances were measured with 100-ft. and 500-ft. steel tapes.

REPORT.

The lode line of each location of this claim was run directly upon the ground, and the several corners established by means of offsets from the lode lines. All tie lines were run either directly upon the ground or by traverses, run upon the ground and submitted in a separate report herewith.

The S.E. Cor. Sec. 17, T. 24 S., R. 58 E., M.D.M., is a limestone rock, 5x8 ins., showing 18 ins. above a mound of rock and earth, chiseled with four notches on the East face and three notches on the South face. This is the nearest standing corner of the public survey that can be found and identified. The S. and E. $\frac{1}{4}$ Cors. to Sec. 17 cannot be found.

Sur. No. 1855, Green Copper lode;--

Cors. Nos. 4 and 1 are pine posts, properly set and scribed with the number of the corner and survey. I find line 4-1 and the tie from Cor. No. 1 to S. E. Cor. Sec. 17 to be N.81°02'E. 600.18 ft. and N.6°29'30"W. 544.86 ft., respectively, instead of N.81°30'E. 600 ft. and N.6°00"W. 540 ft., respectively, as approved.

Como, Radio, Scorpion, Pocahontas, and Pocahontas No. 2 lodes, unsurveyed;--

All corners mentioned herein are pine posts, properly set and marked with a description of the corner and the name of the claim.

NOTE;-- The discrepancies between these field notes and the several amended certificates of location are due to errors in the latter. The entire description of the Yellow Pine Extension lode, as given in the amended certificate of location, is in error 30'.