

Distances were measured with 100 ft. and 500 ft. steel tapes.

REPORT.

The lode line of each location of this claim was run directly upon the ground, and the several corners established by means of offsets from the lode lines. All tie lines were run either directly upon the ground or by traverses, run upon the ground and submitted in a separate report herewith.

The S. E. Cor. Sec. 12, T. 30 S., R. 64 E., M.D.M., is a rock about 12x12x18 ins., set in a mound of stone, chiseled with four notches on the south face and two notches on the north face. This is the nearest standing corner of the public survey that can be found and identified.

Bellevue lode, unsurveyed;-- The N. E. Cor. is a pine post, properly set and marked with a description of the corner and the name of the claim.

NOTE;-- The discrepancies between these field notes and the several certificates of location are due to errors in the latter.

The main incline working shaft, improvement No. 1, Golden Rod lode, is a common improvement made for the benefit of the entire claim, all parts of which can be easily prospected and worked from its several levels. An undivided one sixth interest in said improvement is, therefore, credited to each of the locations embraced in this survey. All other improvements are credited to the respective locations on which they are situated.

#### OTHER IMPROVEMENTS.

A one stamp Kasaan Mill, situated on the lode line, Golden Rod lode, is a common improvement made for the benefit of the entire claim, all parts of which can be easily prospected and worked from its several levels. An undivided one sixth interest in said improvement is, therefore, credited to each of the locations embraced in this survey. All other improvements are credited to the respective locations on which they are situated.

#### TESTIMONY.

This survey was made with a Bull and Bull mining transit No. 4004. The courses were deflected from the true meridian as determined by observation on Polaris at western elongation. The dis-