

SURVEY No. 3937.

INSTRUMENT.

This survey was made a C. L. Berger & Sons mining transit No. 16253. The courses were deflected from the true meridian as determined by direct solar observations. The distances were measured with a 650 ft. steel tape.

REPORT.

The lines of this survey and the connection to the corner of the public land survey were run upon the ground.

The South $\frac{1}{4}$ Corner of Section 12, T.16 N., R.62 E., Mt. Diablo Base and Meridian is a limestone marked $\frac{1}{4}$ on the North face and set in a mound of stone. This is the nearest standing corner of the public land survey that can be found and identified.

Sur. No. 44, Isaacs lode.

All of the corners are pine posts properly set and scribed with the number of the corner and survey. I find all courses and distances to be correct as approved.

Sur. No. 55, Hicks lode.

Corners 1, 5 and 8 are pine posts properly set but not scribed. I find lines 5-8 and 8-1 to be correct as approved.

Sur. No. 2679, Scorpion Placer.

Corners 2, 3 and 4 are pine posts properly set and scribed with the number of corner and survey. I find lines 2-3 and 3-4 to be correct as approved.

Sur. No. 2789, Yolo Nevada lode.

Corners 1, 2 and 3 are pine posts properly set and scribed with the number of corner and survey. I find lines 1-2 and 2-3 to be correct as approved.

Sur. No. 2791, Ralston No. 2 lode.

Corners 2, 3 and 4 are pine posts properly set and scribed with the number of corner and survey. I find lines 2-3 and 3-4 to be correct as approved.